

# Programming Languages Recitation

Ada - procedures, packages and tasks

Arpit Jain

Computer Science Department  
Courant Institute of Mathematical Sciences  
New York University

*arpit.jain@cs.nyu.edu*

September 11, 2014

# Overview

- 1 What is Ada and Motivation
- 2 Basics
- 3 Subprograms
  - Procedures
  - Functions
- 4 Packages
- 5 Tasks

# What is Ada

## Features

- Structured
- Statically Typed
- Object-oriented high level programming language

## Users/Uses

- U.S. Department of Defense (DoD) for real-time embedded systems
- Large-scale information systems
- Distributed systems
- Scientific computation
- Safety-critical systems

# Ada and NYU Courant

- Jack Schwartz (founder of CS dept.) developed SETL (High level based on mathematical theory of sets ). SETL was then used for the first valid implementation of Ada called NYU Ada/ED

# Ada and NYU Courant

- Jack Schwartz (founder of CS dept.) developed SETL (High level based on mathematical theory of sets ). SETL was then used for the first valid implementation of Ada called NYU Ada/ED
- Adacore Executive Team
  - Robert Dewar (President Adacore, Emeritus Professor CS dept. NYU)
  - Edmond Schonberg ( Professor CS dept. NYU )
  - Richard Kenner ( Researcher CS dept. NYU )
  - Franco Gasperoni ( PhD from CS dept. NYU )

# Compilation Units

An Ada program is composed of one or more units of

- Subprograms - Procedures or Functions
- Packages

Additionally there are other units like

- Task
- Protected
- Generic

# Procedures

- A procedure call is a statement and does not return any value
- Subprogram parameters modes:
  - 'in' - value may be used but not changed (Default mode)
  - 'out' - value may be changed but not used
  - 'in out' - value may be changed and/or used
  - 'access'
- procedure Average(A, B : in Integer; Result : out Integer);

```
with Ada.Text_IO ;  
procedure Hello is  
begin  
  Ada.Text_IO.Put_Line(" Hello , _world!" );  
end Hello ;
```

# Functions

- Unlike procedure a Function returns value
- Parameters mode remain same as procedures
- `function Average_Two(A, B : in Integer) return Integer;`

```
function Sum(A, B : in Integer) return Integer is  
    Total : Integer := A;  
begin  
    Total := Total + B;  
    return Total;  
end Sum;
```



# Packages

Each Program unit consists of two parts :

- Declaration/Specification - interface of the unit. Analogous to '.h' file in C
- Body - Implementation details of the unit. Analogous to '.c' file in C

What is a Package :

Collection of logically related entities

# Package Declaration/Specification

- Package Specification go in the .ads file

```
package stack is  
  procedure push(x:integer);  
  function pop return integer;  
end stack;
```

- Package body go in .abd file

```
package body stack is  
  procedure push(x:integer) is  
    begin  
      — Do something here  
    end;  
  function pop return integer is  
    begin  
      — Do something here  
    end;  
end stack;
```

# Tasks

- An independent execution of the same static code, having a stack, program counter and local environment but shared memory
- Ada task communicated through
  - Rendezvous - message passing
  - Shared Variables
  - Protected objects

```
with text_io;  
use text_io;  
  
procedure hello is  
    task Foo;  
    task body Foo is  
        begin  
            Put(" In _foo" );  
            New_Line;  
        end Foo;  
begin  
    Put(" Hello _World" ); New_Line;  
end Hello;
```