



**George Herbert Walker School of
Business & Technology**

DATA ANALYTICS

TERM PROJECT

R CODES

FALL 2021

CSDA 6010 DATA ANALYTICS PRACTICUM

Case 1: Predicting Corporate Bankruptcy

Case 2: Classifying Book Sales Market

Case 3: Classifying Home Equity Loan Applicants

Developed by: Chau Hai Phuong Nguyen

Instructor: Dr. Ali Ovlia

CONTENTS

CASE 1 Predicting Corporate Bankruptcy	1
1. Set Environments	1
1.1. Load Mandy Nguyen's Customed Functions	1
1.2. Load Required Packages.....	1
1.3. Set fonts	1
1.4. Create Customed Color Scheme	1
2. Collect Data	1
3. Pre-process Data	1
3.1. Create Variable Objects and Data Set	1
3.2. Check for Missing and Null Values	2
3.2.1. Check Missing Values	2
3.2.2. Check Null Values	2
4. Attributes Analysis	2
4.1. Statistical Measures	2
4.2. "D" Target Attribute	2
4.3. "Year" Attribute	3
4.4. Ratios	3
4.5. Correlation Matrix.....	3
4.6. Plot Box	3
5. Partition	4
5.1. Original Dataset.....	4
5.2. Normalized Dataset.....	4
5.3. Reduced Dataset	4

5.4. Summary of Data sets	4
6. Prediction.....	5
6.1. Logistic Regression	5
6.1.1. Logistic Regression Generic Functions	5
6.1.2. Original Dataset.....	6
6.1.3. Original Training Dataset.....	6
6.1.4. Normalized Dataset.....	6
6.1.5. Normalized Training Dataset.....	6
6.1.6. Reduced Dataset	6
6.1.7. Reduced Training Dataset	7
6.2. Neural Networks	7
6.2.1. Neural Networks Generic Functions	7
6.2.2. Original Dataset.....	7
6.2.3. Original Training Dataset.....	7
6.2.4. Normalized Dataset.....	7
6.2.5. Normalized Training Dataset.....	8
6.2.6. Reduced Dataset	8
6.2.7. Reduced Training Dataset	8
6.3. k-Nearest Neighbor	8
6.3.1. Calculate best k	8
6.3.2. k-Nearest Neighbor Generic Functions	8
6.3.3. Original Dataset.....	9
6.3.4. Original Training Dataset.....	9
6.3.5. Normalized Dataset.....	9
6.3.6. Normalized Training Dataset.....	9

6.3.7. Reduced Dataset	9
6.3.8. Reduced Training Dataset	9
7. Clean Environment	10
CASE 2 Classifying Book Sales Market	11
RFM Analysis.....	11
1. Set Environments	11
1.1. Load Mandy's Functions.....	11
1.2. Load Packages	11
1.3. Set fonts	11
2. Collect Data	12
3. Pre-Process Data	12
3.1. Create Main Working Data Frame	12
3.2. Compute RFM_score.....	12
3.3. Factor Categorical Attributes	12
4. Partition.....	12
5. RFM Analysis	12
5.1. Compute Response Rate	12
5.1.1. Plot Class Distribution of Target Variable	12
5.1.2. Plot Class Distribution	12
5.1.3. Response rate of Whole Data Set	13
5.1.4. Response Rate of Training	13
5.1.5. Response Rate of Validation	13
5.2. Evaluate with different cut-offs	13
5.2.1. Generic Functions	13
5.2.3. Compute Mean of Response Rates.....	14
5.2.4. Compute More Comparison	14
5.2.5. Compute Less Comparison.....	14

5.2.6. Confusion Matrix Results	14
5.2.7. Plot Confusion Matrices	14
6. Clean Environment	15
MACHINE LEARNING	16
1. Set Environments	16
1.1. Load Mandy's Functions	16
1.2. Load Packages	16
1.3. Set fonts	16
1.4. Color Scheme	16
2. Collect Data	16
3. Pre-Process Data	16
3.1. Variables	16
3.2. Normalize Data	16
4. Explore Variables	16
4.1. Target Variable	17
4.2. Attributes Summaries	17
4.3. Stepwise Regression	17
5. Partition	17
5.1. Raw Data	17
5.2. Balance with ROSE	17
6. Analysis	18
6.1. Logistic Regression (LR)	18
6.1.1. LR Data Sets	18
6.1.2. Generic Function for LR Fitting and Confusion Matrices Computing	18
6.1.3. Imbalanced Full	18
6.1.4. Balanced Full	18
6.1.5. Imbalanced Set 1	19

6.1.6. Balanced Set 1	19
6.1.7. Imbalanced Set 2.....	19
6.1.8. Balanced Set 2	19
6.1.9. LR Confusion Matrices	19
6.1.10. LR CM Plot.....	19
6.2. k-Nearest Neighbors	19
6.2.1. k-Nearest Neighbors (KNN) Data Sets.....	19
6.2.2. Optimal K.....	19
6.2.3. k's Accuracies	20
6.2.4. Plot k's Accuracies.....	20
6.2.5. KNN Confusion Matrices	20
6.2.6. KNN Confusion Matrices Plot.....	21
7. Clean Environment.....	21

CASE 3 Classifying Home Equity Loan Applicants22

1. Set Environments	22
1.1. Load Mandy Nguyen's Customized Functions	22
1.2. Load Required Packages.....	22
1.3. Set fonts	22
1.4. Create Customized Color Scheme	22
2. Collect Data.....	22
2.1. Load Data Set Stored Online in My Github Repository	22
2.2. Overview Data.....	22
2.3. Export Detailed Statistic Summary to .CSV File	22
3. Data Cleaning and Harmonization	23
3.1. Create Working Data Frame and Character Version of Target Attribute	23
3.2. Check Missing Values	23
3.3. Check Typographical Errors.....	23

3.4. Check Outliers	24
3.5. Clean Data Set	26
4. Attribute Exploration	27
4.1. Target Attribute	27
4.2. Predictor Attributes	27
4.2.1. Target against Categorical Attributes.....	27
4.2.2. Target against Numerical Attributes	28
4.3. Select Variables	28
4.3.1. Correlation Matrix.....	28
4.3.2. Stepwise Regression.....	29
4.3.3. Information Value	29
4.3.4. Variables in Use.....	29
5. Partition	29
5.1. Training and Validation	29
5.2. Balance Training with ROSE	29
5.3. Plot STATUS distribution of 3 sets.....	30
6. Classifications.....	30
6.1. Logistic Regression	30
6.1.1. Logistic Regression (lr) Data Sets	30
6.1.2. Generic Function	30
6.1.3. Imbalanced All.....	31
6.1.4. Balanced All.....	31
6.1.5. Imbalanced Set 1.....	31
6.1.6. Balanced Set 1.....	31
6.1.7. Imbalanced Set 2.....	31

6.1.8. Balanced Set 2	31
6.1.9. Four Fold Plots of Confusion Matrix.....	31
6.2. k-Nearest Neighbors	31
6.2.1. k-Nearest Neighbors (knn) Data Sets	31
6.2.2. Optimal K.....	31
6.2.3. Generic Functions	32
6.2.4. Imbalanced All.....	33
6.2.5. Balanced All.....	33
6.2.6. Imbalanced Set 1	33
6.2.7. Balanced Set 1	33
6.2.8. Imbalanced Set 2	33
6.2.9. Balanced Set 2	33
6.2.10. Four Fold Plots of Confusion Matrix.....	33
6.3. Neural Networks	34
6.3.1. Neural Networks (nn) Data sets	34
6.3.2. Generic Function	34
6.3.3. Imbalanced All.....	34
6.3.4. Balanced All.....	34
6.3.5. Imbalanced Set 1	35
6.3.6. Balanced Set 1	35
6.3.7. Imbalanced Set 2	36
6.3.8. Balanced Set 2	36
6.3.9. Four Fold Plots of Confusion Matrix.....	37
7. Clean Environment	37

CASE 1

PREDICTING CORPORATE BANKRUPTCY

1. SET ENVIRONMENTS

1.1. Load Mandy Nguyen's Customized Functions

```
source("https://raw.githubusercontent.com/mandyhpnguyen/Mandy-Functions/main/M.R-Funcs/general.R")
```

1.2. Load Required Packages

```
pkgs <- c(
  "beepR",
  # General pkgs:
  "tidyverse", "dplyr", "summarytools", "reshape2", "pastecs", "ROSE",
  # Analytics pkgs:
  "forecast", "zoo", "scorecard",
  # Evaluation pkgs:
  "caret", "DT", "lift", "gains", "gt", "cvms", "tibble", "fourfoldplot",
  # Visualization pkgs:
  "RColorBrewer", "hrbrthemes", "knitr", "showtext", "sysfonts",
  "ggfortify", "ggplot2", "corrplot", "GGally", "viridis",
  "lattice", "grid", "cowplot", "Amelia"
)
suppressMessages(suppressWarnings(loadpkg(pkgs)))
```

1.3. Set fonts

```
# Load the main font used in the paper to plot charts for standardization

windowsFonts(cambria = windowsFont("Cambria"))
my.par <- function() {
  options(scipen = 999)
  par(mfrow = c(1, 1),
      family = "cambria",
      cex.main = 1.25, cex.lab = 1.25, cex.axis = 1.25)
}
```

1.4. Create Customized Color Scheme

```
pal <- c("cornflowerblue", "orange", "red2", "forestgreen", "mediumorchid1", "tomato3", "cadetblue1")
```

2. COLLECT DATA

```
bankruptcy <- read.csv("https://raw.githubusercontent.com/mandyhpnguyen/MS-Data-Analytics-Datasets/main/Practicum/Bankruptcy.csv")
data <- bankruptcy
```

3. PRE-PROCESS DATA

3.1. Create Variable Objects and Data Set

```
cols <-
c('D', 'R1', 'R2', 'R3', 'R4', 'R5', 'R6', 'R7', 'R8', 'R9', 'R10', 'R11', 'R12', 'R13', 'R14', 'R15', 'R16', 'R17',
  'R18', 'R19', 'R20', 'R21', 'R22', 'R23', 'R24')
vars <-
c('R1', 'R2', 'R3', 'R4', 'R5', 'R6', 'R7', 'R8', 'R9', 'R10', 'R11', 'R12', 'R13', 'R14', 'R15', 'R16', 'R17', 'R18',
  'R19', 'R20', 'R21', 'R22', 'R23', 'R24')
```

```
data2 <- data
data2$STATUS <- factor(ifelse(data$D == 0, "bankrupt", "healthy"),
  levels = c("bankrupt", "healthy"))
```

3.2. Check for Missing and Null Values

3.2.1. Check Missing Values

```
sum(is.na(data))
sum(data[, 4:27] == 0) # 50
```

3.2.2. Check Null Values

```
zeroset <- data[data[, 4] == 0 |
  data[, 5] == 0 |
  data[, 6] == 0 |
  data[, 7] == 0 |
  data[, 8] == 0 |
  data[, 9] == 0 |
  data[, 10] == 0 |
  data[, 11] == 0 |
  data[, 12] == 0 |
  data[, 13] == 0 |
  data[, 14] == 0 |
  data[, 15] == 0 |
  data[, 16] == 0 |
  data[, 17] == 0 |
  data[, 18] == 0 |
  data[, 19] == 0 |
  data[, 20] == 0 |
  data[, 21] == 0 |
  data[, 22] == 0 |
  data[, 23] == 0 |
  data[, 24] == 0 |
  data[, 25] == 0 |
  data[, 26] == 0 |
  data[, 27] == 0,
]
```

```
View(zeroset)
```

```
# Check number of rows with Null values
zeroset %>%
  group_by(YR) %>%
  filter(D == 1) %>%
  nrow()
```

4. ATTRIBUTES ANALYSIS

4.1. Statistical Measures

```
summary(data)
```

4.2. "D" Target Attribute

```
# Distribution of the data indicator in the data set
my.par() %>% par(mfrow = c(1, 1),
  mai = par("mai") * 1,
  oma = c(0,0,0,0) + 0.1,
  mar = c(4,2,2,0) + 0.1
)
D_p <- plot(as.factor(data$D), ylim = c(1, 75),
  xlab = "0: Bankrupt - 1: Healthy",
  col = c("cornflowerblue", "red2"))
text(D_p, y = table(data$D),
  labels = table(data$D),
  pos = 3, cex = 1)
```

4.3. "Year" Attribute

```
# Year Distribution
yr <- data[, 2:3]
table(yr$YR)

yrs <- function(i, j){
  for (i in i:j) {
    print(table(yr[yr$YR == i,]$D))
    i = i + 1
  }
}
yrs(70, 82)

# Plot Year Distribution
my.par() %>% par(mfrow = c(1, 1),
               mai = par("mai") * 1,
               oma = c(0,0,0,0) + 0.1,
               mar = c(4,2,2,0) + 0.1
               )
yr_p <- plot(as.factor(data$YR), ylim = c(0, 30),
            xlab = "Year (YY)",
            col = pal)
text(yr_p, y = table(data$YR),
     labels = table(data$YR),
     pos = 3, cex = 1)
```

4.4. Ratios

```
# Generic Function to Create Box Plot

out.bp <- function(dataset) {
  my.par() %>% par(mfrow = c(2, 12),
                 mai = par("mai") * 1,
                 oma = c(0,0,0,0) + 0.1,
                 mar = c(0.5,2.5,5,0) + 0.1
                 )

  i = 2
  for (i in 2:length(colnames(dataset))) {
    boxplot(dataset[, i],
            main = colnames(dataset)[i],
            cex.main = 2, cex.axis = 2,
            col = "red2")
    i = i + 1
  }
}

# Plot All Ratio Attributes
out.bp(data[, -c(1:2)])
```

4.5. Correlation Matrix

```
# Compute Correlation

corr.df <- data[, cols]
corr.mat <- round(corr(corr.df),2)
testRes = cor.mtest(corr.mat, conf.level = 0.95)

# Plot Correlation Matrix
my.par()
corrplot(corr.mat, method = "color",
         type = "full", tl.col = "black")$corrPos -> corrp
text(corrp$x, corrp$y, round(corrp$corr, 2))
```

4.6. Plot Box

```
# Generic Function for Box Plot
bp <- function(i, ylab) {
  ggplot(data = data2, aes(fill = STATUS, y = data2[, i], x = STATUS)) +
    geom_boxplot(alpha = .5, notch = TRUE, notchwidth = .95) +
```

```

    geom_jitter(alpha = .25) +
    theme_classic() + labs(y = ylab) +
    scale_fill_manual(values = c("red2", "cornflowerblue")) +
    theme(text = element_text(size = 12, family = "cambria")) +
    theme(axis.ticks.y = element_blank(),
          axis.title.x = element_blank(),
          legend.position = "none")
}

# Box plot for R9, R10, R17, R20
bpR9 <- bp(12, "R9 (CURASS / CURDEBT)")
bpR10 <- bp(13, "R10 (CURASS / SALES)")
bpR17 <- bp(20, "R17 (INCDEP / ASSETS)")
bpR20 <- bp(21, "R20 (SALES / ASSETS)")
my.par()
cowplot::plot_grid(bpR9, bpR10, bpR17, bpR20, labels = "AUTO", nrow = 1, ncol = 4)

```

5. PARTITION

5.1. Original Dataset

```

# Randomize Data set
set.seed(2021)
index_ran <- sample(seq_len(nrow(data)), size = 1*nrow(data))
data_s <- data[index_ran,]

set.seed(2021)
index_s <- sample(seq_len(nrow(data_s)), size = 0.6*nrow(data_s))
train_s <- data_s[index_s, cols]
test_s <- data_s[-index_s, cols]

# summary(as.factor(train_s$D))
# summary(as.factor(test_s$D))

```

5.2. Normalized Dataset

```

# Normalize Function using Min-max
normalize <- function(x) {
  return((x - min(x)) / (max(x) - min(x)))
}

# Create Normalized Dataset
data_n <- data
data_n[, 4:27] <- as.data.frame(lapply(data[, 4:27], normalize))

set.seed(2021)
index_n <- sample(seq_len(nrow(data_n)), size = 0.6*nrow(data_n))
train_n <- data_n[index_n, cols]
test_n <- data_n[-index_n, cols]

# summary(as.factor(train_n$D))
# summary(as.factor(test_n$D))

```

5.3. Reduced Dataset

```

data_r <- data[, c("D", "R9", "R10", "R17", "R20")]
str(data_r)
set.seed(2021)
index_r <- sample(seq_len(nrow(data_r)), size = 0.6*nrow(data_r))
train_r <- data_r[index_r, ]
test_r <- data_r[-index_r, ]

# summary(as.factor(train_r$D))
# summary(as.factor(test_r$D))

```

5.4. Summary of Data sets

```

# summary(as.factor(train_r$D))

```

```
# summary(as.factor(test_r$D))

## Set 1: Original Dataset & Testing Set
# data_r
# test_r

## Set 2: Original Training Dataset & Testing Set
# train_r
# test_r

## Set 3: Normalized Dataset & Normalized Testing Set
# data_r
# test_r

## Set 4: Normalized Training Dataset & Normalized Testing Set
# data_r
# test_r

## Set 5: Original Training Dataset & Testing Set
# train_r
# test_r

## Set 6: Reduced Training Dataset & Testing Set
# train_r
# test_r
```

6. PREDICTION

6.1. Logistic Regression

6.1.1. Logistic Regression Generic Functions

```
### Model + Evaluation

loreg_m <- function(X, Y){
  # Model
  if (!require("lattice")) install.packages("lattice")
  lg.reg <- glm(D ~ ., data = X, family = "binomial")
  print(summary(lg.reg))
  # Predict
  lg.reg.pred <- predict(lg.reg, Y)
  # Evaluate
  if (!require("caret")) install.packages("caret")
  library(caret)
  confusionMatrix(factor(ifelse(lg.reg.pred > 0.5, 1, 0)), factor(Y$D), positive = '0')
  # plot(lg.reg, which = 1:2)
}

### Stepwise Function

loreg_m_ic <- function(X, Z){
  lg.reg <- glm(D ~ ., data = X, family = "binomial")
  # step(lg.reg, direction = Z)
  summary(step(lg.reg, direction = Z))
}

# New Attributes Sets' Prediction & Evaluation
loreg_m_i <- function(X, Y, a, b, c){
  # 3 new models
  lg.reg_2 <- glm(D ~ ., data = X[, a], family = "binomial")
  lg.reg_3 <- glm(D ~ ., data = X[, b], family = "binomial")
  lg.reg_4 <- glm(D ~ ., data = X[, c], family = "binomial")
  summary(lg.reg_2)
  summary(lg.reg_3)
  summary(lg.reg_4)
  # Predict 3 new models
  lg.reg.pred_2 <- predict(lg.reg_2, Y)
  lg.reg.pred_3 <- predict(lg.reg_3, Y)
```

```

lg.reg.pred_4 <- predict(lg.reg_4, Y)
# Evaluate
library(caret)
print(confusionMatrix(factor(ifelse(lg.reg.pred_2 > 0.5, 1, 0)), factor(Y$D), positive = '0'))
# plot(lg.reg_2, which = 1:2)
print(confusionMatrix(factor(ifelse(lg.reg.pred_3 > 0.5, 1, 0)), factor(Y$D), positive = '0'))
# plot(lg.reg_3, which = 1:2)
print(confusionMatrix(factor(ifelse(lg.reg.pred_4 > 0.5, 1, 0)), factor(Y$D), positive = '0'))
# plot(lg.reg_4, which = 1:2)
}

```

6.1.2. Original Dataset

```

# Model + Evaluation
loreg_m(data_s[, cols], test_s) # 0.8491
# Improved Ratios
loreg_m_ic(data_s[, cols], "backward") # 0.8679
loreg_m_ic(data_s[, cols], "forward") # 0.8491
loreg_m_ic(data_s[, cols], "both") # 0.8679
a_s <- c("D", "R3", "R5", "R6", "R9", "R10", "R16", "R17", "R18", "R22", "R23", "R24")
b_s <- cols
c_s <- a_s
# Improved Performance with new ratios
loreg_m_i(data_s, test_s, a_s, b_s, c_s)

```

6.1.3. Original Training Dataset

```

# Model + Evaluation
loreg_m(train_s[, cols], test_s) # 0.6415
# Improved Ratios
loreg_m_ic(train_s[, cols], "backward") # 0.6604
loreg_m_ic(train_s[, cols], "forward") # 0.6415
loreg_m_ic(train_s[, cols], "both")
a_ts <- c("D", "R2", "R3", "R5", "R9", "R10", "R12", "R14", "R15", "R16", "R19", "R21")
b_ts <- cols
c_ts <- a_ts
# Improved Performance with new ratios
loreg_m_i(train_s, test_s, a_ts, b_ts, c_ts)

```

6.1.4. Normalized Dataset

```

# Model + Evaluation
loreg_m(data_n[, cols], test_n) # 0.9434
# Improved Ratios
loreg_m_ic(data_n[, cols], "backward")
loreg_m_ic(data_n[, cols], "forward")
loreg_m_ic(data_n[, cols], "both")
a_n <- c("D", "R3", "R5", "R6", "R9", "R10", "R16", "R17", "R18", "R22", "R23", "R24") # 0.9057
b_n <- cols
c_n <- a_n
# Improved Performance with new ratios
loreg_m_i(data_n, test_n, a_n, b_n, c_n)

```

6.1.5. Normalized Training Dataset

```

# Model + Evaluation
loreg_m(train_n[, cols], test_n) #0.6415
# Improved Ratios
loreg_m_ic(train_n[, cols], "backward")
loreg_m_ic(train_n[, cols], "forward")
loreg_m_ic(train_n[, cols], "both")
a_tn <- c("D", "R5", "R6", "R7", "R10", "R11", "R12", "R14", "R16", "R17", "R18", "R22", "R24") #
0.6415
b_tn <- cols
c_tn <- a_tn
# Improved Performance with new ratios
loreg_m_i(train_n, test_n, a_tn, b_tn, c_tn)

```

6.1.6. Reduced Dataset

```

loreg_m(data_r, test_r) # 0.9245
# Improved Ratios
loreg_m_ic(data_r, "backward")
loreg_m_ic(data_r, "forward")
loreg_m_ic(data_r, "both")
a_r <- c("D", "R9", "R10", "R17")
b_r <- c("D", "R9", "R10", "R17", "R20")
c_r <- a_r
# Improved Performance with new ratios
loreg_m_i(data_r, test_r, a_r, b_r, c_r) # 0.9245

```

6.1.7. Reduced Training Dataset

```

# Model + Evaluation
loreg_m(train_r, test_r) # 0.8868
# Improved Ratios
loreg_m_ic(train_r, "backward") # 0.9057
loreg_m_ic(train_r, "forward")
loreg_m_ic(train_r, "both")
a_tr <- c("D", "R9", "R10", "R17")
b_tr <- c("D", "R9", "R10", "R17", "R20")
c_tr <- a_r
# Improved Performance with new ratios
loreg_m_i(train_r, test_r, a_tr, b_tr, c_tr)

```

6.2. Neural Networks

6.2.1. Neural Networks Generic Functions

```

# Prediction & Plot Function
nn_f <- function(X, Y, i, j){
  if (!require("neuralnet")) install.packages("neuralnet")
  library(neuralnet)
  # Model
  nn <- neuralnet(D ~ .,
                  data = X,
                  hidden = i,
                  linear.output = FALSE)

  plot(nn)
  # Predict
  nn_pred <- compute(nn, Y[, -1])
  nn_pred_result <- nn_pred$net.result
  # Evaluate
  print(cor(nn_pred_result, Y$D))
  print(confusionMatrix(factor(ifelse(nn_pred_result > j, 1, 0)), factor(Y$D), positive = '0'))
}

```

6.2.2. Original Dataset

```

nn_f(data_s[, cols], test_s, 1, 0.5) # 0.9057
nn_f(data_s[, cols], test_s, 2, 0.5) # 0.8868
nn_f(data_s[, cols], test_s, 3, 0.5) # 0.9623
nn_f(data_s[, cols], test_s, c(1,2), 0.5) # 0.8868
nn_f(data_s[, cols], test_s, c(3,2), 0.5) # 0.9623

```

6.2.3. Original Training Dataset

```

nn_f(train_s[, cols], test_s, 1, 0.5) # 0.7547
nn_f(train_s[, cols], test_s, 2, 0.5) # 0.8113 (run twice)
nn_f(train_s[, cols], test_s, 3, 0.5) # 0.6981
nn_f(train_s[, cols], test_s, c(1,2), 0.5) # 0.6792
nn_f(train_s[, cols], test_s, c(3,2), 0.5) # 0.6415

```

6.2.4. Normalized Dataset

```

nn_f(data_n[, cols], test_n, 1, 0.5) # 0.9623
nn_f(data_n[, cols], test_n, 2, 0.5) # 0.9434
nn_f(data_n[, cols], test_n, 3, 0.5) # 0.9811

```

```
nn_f(data_n[, cols], test_n, c(1,2), 0.5) # 0.9623
nn_f(data_n[, cols], test_n, c(3,2), 0.5) # 0.9623
```

6.2.5. Normalized Training Dataset

```
nn_f(train_n[, cols], test_n, 1, 0.5) # 0.7736 (run 3 times)
nn_f(train_n[, cols], test_n, 2, 0.5) # 0.7358
nn_f(train_n[, cols], test_n, 3, 0.5) # 0.7358
nn_f(train_n[, cols], test_n, c(1,2), 0.5) # 0.7358
nn_f(train_n[, cols], test_n, c(3,2), 0.5) # 0.7547
```

6.2.6. Reduced Dataset

```
nn_f(data_r, test_r, 1, 0.5) # 0.9623
nn_f(data_r, test_r, 2, 0.5) # 0.9434
nn_f(data_r, test_r, 3, 0.5) # 0.9623
nn_f(data_r, test_r, c(1,2), 0.5) # 0.9623
nn_f(data_r, test_r, c(3,2), 0.5) # 0.9245
```

6.2.7. Reduced Training Dataset

```
nn_f(train_r, test_r, 1, 0.5) # 0.9245
nn_f(train_r, test_r, 2, 0.5) # 0.8679
nn_f(train_r, test_r, 3, 0.5) # 0.8113
nn_f(train_r, test_r, c(1,2), 0.5) # 0.9434
nn_f(train_r, test_r, c(3,2), 0.5) # 0.717
```

6.3. k-Nearest Neighbor

6.3.1. Calculate best k

```
numer_of_k <- sqrt(nrow(data_s))
numer_of_k # - 11.5
```

6.3.2. k-Nearest Neighbor Generic Functions

```
# Accuracy table and plot of k

knn_f <- function(X, Y, att, seq_i, seq_j, seq_step) {
  library(caret)
  library(FNN)
  library(class)
  library(gmodels)
  library(e1071)
  library(ggplot2)
  accuracy <- data.frame(k = seq(seq_i, seq_j, seq_step), accuracy = rep(0, 15))
  for(i in seq_i:seq_j) {
    knn.pred <- knn(X[, att],
                    Y[, att],
                    cl = X[, 'D'],
                    k = i)
    accuracy[i, 2] <- confusionMatrix(knn.pred, factor(Y[, 'D']), positive = '0')$overall[1]
  }
  print(accuracy)
  plot(accuracy$k, xlab = "Values of k",
       accuracy$accuracy,
       ylab = "Accuracies",
       main = "Values of k against their accuracies",
       type = 'l',
       cols = 'gray')
}

# Prediction and Evaluation of k = i

knn_e <- function(X, Y, att, i){
  library(caret)
  library(FNN)
```



```

library(class)
library(gmodels)
library(e1071)
library(ggplot2)
knn_pred <- knn(X[, att],
                Y[, att],
                cl = X[, 'D'],
                k = i)

# Evaluate
CrossTable(Y$D, knn_pred, prop.chisq = F)
confusionMatrix(factor(knn_pred), factor(Y$D))
}

```

6.3.3. Original Dataset

```

# k table
knn_f(data_s, test_s, vars, 1, 15)
# Model & Predict & Evaluate
knn_e(data_s, test_s, vars, 11)
# Improve
knn_e(data_s, test_s, vars, 1)
knn_e(data_s, test_s, vars, 3)

```

6.3.4. Original Training Dataset

```

# k table
knn_f(train_s, test_s, vars, 1, 15)
# Model & Predict & Evaluate
knn_e(train_s, test_s, vars, 11)
# Improve
knn_e(train_s, test_s, vars, 3)

```

6.3.5. Normalized Dataset

```

# k table
knn_f(data_n, test_n, vars, 1, 15)
# Model & Predict & Evaluate
knn_e(data_n, test_n, vars, 11)
# Improve
knn_e(data_n, test_n, vars, 1)
knn_e(data_n, test_n, vars, 2)

```

6.3.6. Normalized Training Dataset

```

# k table
knn_f(train_n, test_n, vars, 1, 15)
# Model & Predict & Evaluate
knn_e(train_n, test_n, vars, 11)
# Improve
knn_e(train_n, test_n, vars, 1)

```

6.3.7. Reduced Dataset

```

# k table
knn_f(data_r, test_r, -1, 1, 15)
# Model & Predict & Evaluate
knn_e(data_r, test_r, -1, 11)
# Improve
knn_e(data_r, test_r, -1, 1)
knn_e(data_r, test_r, -1, 3)

```

6.3.8. Reduced Training Dataset

```

knn_f(train_r, test_r, -1, 1, 15)
# Model & Predict & Evaluate
knn_e(train_r, test_r, -1, 11)
# Improve
knn_e(train_r, test_r, -1, 4)

```

7. CLEAN ENVIRONMENT

```
rm(list = ls())  
cat("\014")
```

CASE 2

CLASSIFYING BOOK SALES MARKET

The **Classifying Book Sales Market** with Charles Book Club data set requires two major classifications approaches including marketing expertise – RFM Analysis – and machine learning algorithms – Logistic Regression and K-Nearest Neighbor. For clarification and simplification, the analysis was written in one document with two separate R scripts for RFM Analysis and Machine Learning. Therefore, in this document, the R codes following for Case 2 are non-related despite similar naming methods. It is advised not to run the two sections at the same time in the same R environment.

RFM Analysis

1. SET ENVIRONMENTS

1.1. Load Mandy's Functions

```
source("https://raw.githubusercontent.com/mandyhpnguyen/Mandy-Functions/main/M.R-Funcs/general.R")
```

1.2. Load Packages

```
pkgs <- c(
  "beepR",
  # General pkgs:
  "tidyverse", "dplyr", "summarytools", "reshape2", "pastecs", "ROSE",
  # Analytics pkgs:
  "forecast", "zoo", "scorecard",
  # Evaluation pkgs:
  "caret", "DT", "lift", "gains", "gt", "cvms", "tibble", "fourfoldplot",
  # Visualization pkgs:
  "RColorBrewer", "hrbrthemes", "knitr", "showtext", "sysfonts",
  "ggfortify", "ggplot2", "corrplot", "GGally", "viridis",
  "lattice", "grid", "cowplot", "Amelia"
)
suppressMessages(suppressWarnings(loadpkg(pkgs)))
```

1.3. Set fonts

```
# Load the main font I used in my paper to plot charts for standardization
windowsFonts(cambria = windowsFont("Cambria"))
my.par <- function() {
  options(scipen = 999)
  par(mfrow = c(1, 1),
      family = "cambria",
      cex.main = 1.25, cex.lab = 1.25, cex.axis = 1.25)
}
```

2. COLLECT DATA

```
book <- read.csv("https://raw.githubusercontent.com/mandyhpnguyen/MS-Data-Analytics-Datasets/main/Data%20Mining/CharlesBookClub.csv")
```

3. PRE-PROCESS DATA

3.1. Create Main Working Data Frame

```
cbc <- book
```

3.2. Compute RFM_score

```
cbc$RFM_score <- paste(cbc$Rcode, cbc$Fcode, cbc$Mcode)
cbc$RFM_score <- gsub(" ", "", cbc$RFM_score)
cbc$RFM_score <- as.factor(cbc$RFM_score)
cbc[1:10, "RFM_score"]
```

3.3. Factor Categorical Attributes

```
cbc[, "Gender"] <- factor(cbc[, "Gender"])
cbc[, "Yes_Florence"] <- factor(cbc[, "Yes_Florence"], levels = c(1, 0))
cbc[, "No_Florence"] <- factor(cbc[, "No_Florence"], levels = c(0, 1))

cbc[, "Mcode"] <- factor(cbc[, "Mcode"])
cbc[, "Rcode"] <- factor(cbc[, "Rcode"])
cbc[, "Fcode"] <- factor(cbc[, "Fcode"])
```

4. PARTITION

```
set.seed(2021)
train.index <- sample(1:nrow(cbc), 0.7*nrow(cbc))
train <- cbc[train.index, ]
valid <- cbc[-train.index, ]
```

5. RFM ANALYSIS

5.1. Compute Response Rate

5.1.1. Plot Class Distribution of Target Variable

```
5.1.1.1. Generic Function to Create Bar Plot
# Fix height issue: https://stackoverflow.com/questions/16121903/r-barplot-y-axis-scale-too-short
rr_bar <- function(X, Z=""){
  barplot(height = X, space = .2,
    horiz = FALSE, density = 50, angle = 60,
    col = c("red2", "cornflowerblue"), border = NA,
    ylim = range(pretty(c(0, X))),
    xlab = 'Florence',
    ylab = 'Frequency of Response Rate',
    main = Z
  ) %>%
  text(0, y = X, labels = paste0(round(X*100,2), "%"),
    cex = 1, pos = 3)
}
```

5.1.2. Plot Class Distribution

```
my.par() %>% par(mfrow = c(1, 3))
rr_bar(prop.table(table(cbc$Florence)),
  "Raw Set")
rr_bar(prop.table(table(train$Florence)),
  "Training Set")
rr_bar(prop.table(table(valid$Florence)),
  "Validation Set")
```

5.1.3. Response rate of Whole Data Set

```
toprr_cbc <- cbc %>%
  group_by(RFM_score) %>%
  summarise(Yes = length(Yes_Florence[Yes_Florence == '1']),
            No = length(No_Florence[No_Florence == '1']),
            Response_Rate = round(Yes / (Yes + No), 3),
            Count = length(RFM_score))
  ) %>%
  arrange(desc(Response_Rate)) %>%
  as.data.frame()
toprr_cbc

# Export to .CSV File
setwd("C:/One Drives/OneDrive - Webster University/Webster Classes/21F_CSDA 6010_Practicum")
options(scipen = 0, digits = 2)
toprr_cbc %>% write.csv("toprr_cbc.csv", row.names = TRUE)
```

5.1.4. Response Rate of Training

```
toprr_train <- train %>%
  group_by(RFM_score) %>%
  summarise(Yes = length(Yes_Florence[Yes_Florence == '1']),
            No = length(No_Florence[No_Florence == '1']),
            Response_Rate = round(Yes / (Yes + No), 3),
            Count = length(RFM_score))
  ) %>%
  arrange(desc(Response_Rate)) %>%
  as.data.frame()

# Export to .CSV File
setwd("C:/One Drives/OneDrive - Webster University/Webster Classes/21F_CSDA 6010_Practicum")
options(scipen = 0, digits = 2)
toprr_train %>% write.csv("toprr_train.csv", row.names = TRUE)
```

5.1.5. Response Rate of Validation

```
toprr_valid <- valid %>%
  group_by(RFM_score) %>%
  summarise(Yes = length(Yes_Florence[Yes_Florence == '1']),
            No = length(No_Florence[No_Florence == '1']),
            Response_Rate = round(Yes / (Yes + No), 3),
            Count = length(RFM_score))
  ) %>%
  arrange(desc(Response_Rate)) %>%
  as.data.frame()

# Export to .CSV File
setwd("C:/One Drives/OneDrive - Webster University/Webster Classes/21F_CSDA 6010_Practicum")
options(scipen = 0, digits = 2)
toprr_valid %>% write.csv("toprr_valid.csv", row.names = TRUE)
```

5.2. Evaluate with different cut-offs

5.2.1. Generic Functions

```
# More Comparison
RFM_emore <- function(cut_off, equation="") {
  cat(">> Valid >= Cut-off =", cut_off, "\n",
      ifelse(equation == "", "", paste0("> Equation: ", equation)), "\n\n")
  train_c <- toprr_train
  train_c$Response <- factor(ifelse(train_c$Response_Rate >= cut_off, "Yes", "No"))
  valid_c <- toprr_valid
  valid_c$Response_V <- factor(ifelse(valid_c$Response_Rate >= cut_off, "Yes", "No"))
  index1 <- valid_c$RFM_score
  valid_c$Response_T <- train_c[index1, ]$Response
  valid_c <- valid_c[, c(1, 4:7)]
  confusionMatrix(valid_c$Response_T, valid_c$Response_V)
}
```

```
# Less Comparison
RFM_eless <- function(cut_off, equation="") {
  cat(">> Valid <= Cut-off =", cut_off, "\n",
      ifelse(equation == "", "", paste0("> Equation: ", equation))), "\n\n")
  train_c <- toprr_train
  train_c$Response <- factor(ifelse(train_c$Response_Rate <= cut_off, "Yes", "No"))
  valid_c <- toprr_valid
  valid_c$Response_V <- factor(ifelse(valid_c$Response_Rate <= cut_off, "Yes", "No"))
  index1 <- valid_c$RFM_score
  valid_c$Response_T <- train_c[index1, ]$Response
  valid_c <- valid_c[, c(1, 4:7)]
  confusionMatrix(valid_c$Response_T, valid_c$Response_V)
}
```

5.2.3. Compute Mean of Response Rates

```
mean(toprr_cbc$Response_Rate)
mean(toprr_train$Response_Rate)
```

5.2.4. Compute More Comparison

```
more1 <- RFM_emore(mean(toprr_train$Response_Rate), "mean(toprr_train$Response_Rate)")
more2 <- RFM_emore(mean(toprr_train$Response_Rate)*2, "mean(toprr_train$Response_Rate)*2")
more3 <- RFM_emore(mean(toprr_cbc$Response_Rate), "mean(toprr_cbc$Response_Rate)")
more4 <- RFM_emore(mean(toprr_cbc$Response_Rate)*2, "mean(toprr_cbc$Response_Rate)*2")
```

5.2.5. Compute Less Comparison

```
less1 <- RFM_eless(mean(toprr_train$Response_Rate), "mean(toprr_train$Response_Rate)")
less2 <- RFM_eless(mean(toprr_train$Response_Rate)*2, "mean(toprr_train$Response_Rate)*2")
less3 <- RFM_eless(mean(toprr_cbc$Response_Rate), "mean(toprr_cbc$Response_Rate)")
less4 <- RFM_eless(mean(toprr_cbc$Response_Rate)*2, "mean(toprr_cbc$Response_Rate)*2")
```

5.2.6. Confusion Matrix Results

```
more1
more2
more3
more4
less1
less2
less3
less4
```

5.2.7. Plot Confusion Matrices

```
# Generic Function to Plot Confusion Matrices
rfm_cmp <- function(cm, title) {
  fourfoldplot(cm, color = c("cornflowerblue", "red2"),
    margin = 1, space = 0.3,
    conf.level = 0, main = title)
}

# Plot Confusion Matrices
my.par() %>% par(mfrow = c(2, 4),
  mai = par("mai") * 1,
  oma = c(0,0,0,0) + 0.1,
  mar = c(2,4,2,0) + 0.1
)
rfm_cmp(more1$table, "A-1")
rfm_cmp(more2$table, "A-2")
rfm_cmp(more3$table, "A-3")
rfm_cmp(more4$table, "A-4")
rfm_cmp(less1$table, "A-5")
rfm_cmp(less2$table, "A-6")
rfm_cmp(less3$table, "A-7")
rfm_cmp(less4$table, "A-8")
```

6. CLEAN ENVIRONMENT

```
rm(list = ls())  
cat("\014")
```

MACHINE LEARNING

1. SET ENVIRONMENTS

1.1. Load Mandy's Functions

```
source("https://raw.githubusercontent.com/mandyhpnguyen/Mandy-Functions/main/M.R-Funcs/general.R")
```

1.2. Load Packages

```
pkgs <- c(
  "beepR",
  # General pkgs:
  "tidyverse", "dplyr", "summarytools", "reshape2", "pastecs", "ROSE",
  # Analytics pkgs:
  "forecast", "zoo", "scorecard",
  # Evaluation pkgs:
  "caret", "DT", "lift", "gains", "gt", "cvms", "tibble", "fourfoldplot",
  # Visualization pkgs:
  "RColorBrewer", "hrbrthemes", "knitr", "showtext", "sysfonts",
  "ggfortify", "ggplot2", "corrplot", "GGally", "viridis",
  "lattice", "grid", "cowplot", "Amelia"
)
suppressMessages(suppressWarnings(loadpkg(pkgs)))
```

1.3. Set fonts

```
# Load the main font I used in my paper to plot charts for standardization
windowsFonts(cambria = windowsFont("Cambria"))
my.par <- function() {
  options(scipen = 999)
  par(mfrow = c(1, 1),
      family = "cambria",
      cex.main = 1.25, cex.lab = 1.25, cex.axis = 1.25)
}
```

1.4. Color Scheme

```
pal <- c("cornflowerblue", "orange", "red2", "forestgreen", "mediumorchid1", "tomato3", "cadetblue1")
```

2. COLLECT DATA

```
book <- read.csv("https://raw.githubusercontent.com/mandyhpnguyen/MS-Data-Analytics-
Datasets/main/Data%20Mining/CharlesBookClub.csv")
```

3. Pre-Process Data

```
data <- book[, -c(1:2)]
```

3.1. Variables

```
var0 <- c(1:15, 17)
var1 <- c("Rcode", "Fcode", "Mcode", "FirstPurch", "Related.Purchase")
col0 <- c(1:17)
col1 <- c("Florence", "Rcode", "Fcode", "Mcode", "FirstPurch", "Related.Purchase")
```

3.2. Normalize Data

```
set.seed(2021)
options(scipen = 0)
normalize <- function(x) {
  return((x - min(x)) / (max(x) - min(x)))
}
data.n <- data
data.n[, c(2:15, 17)] <- as.data.frame(lapply(data.n[, c(2:15, 17)], normalize))
```

4. Explore Variables

4.1. Target Variable

```
# Plot Distribution
my.par() %>% par(mfrow = c(1, 1),
                 mai = par("mai") * 1,
                 oma = c(0,0,0,0) + 0.1,
                 mar = c(4,2,2,0) + 0.1
                 )
F_p <- plot(as.factor(book$Florence), ylim = c(0, 4000),
           xlab = "Florence", col = c("cornflowerblue", "red2"))
text(F_p, y = table(book$Florence),
     labels = table(book$Florence),
     pos = 3, cex = 1)
```

4.2. Attributes Summaries

```
# Export to .CSV File
setwd("C:/One Drives/OneDrive - Webster University/Webster Classes/21F_CSDA 6010_Practicum")
options(scipen = 0, digits = 2)
round(stat.desc(book), 0) %>% write.csv("book_descr.csv", row.names = TRUE)
```

4.3. Stepwise Regression

```
# Generic Function
loreg_m_ic <- function(X, Z){
  options(scipen = 0)
  set.seed(2021)
  lg.reg <- glm(Florence ~ ., data = X, family = "binomial")
  # step(lg.reg, direction = Z)
  summary(step(lg.reg, direction = Z))
}

# Fit Data
loreg_m_ic(data[, col0], "both")

# Set of Selected Variables
var2 <- c("Gender", "R", "F", "ChildBks", "YouthBks", "CookBks", "DoItYBks", "RefBks", "ArtBks",
          "GeogBks", "ItalArt")
col2 <- c("Florence", "Gender", "R", "F", "ChildBks", "YouthBks", "CookBks", "DoItYBks", "RefBks",
          "ArtBks", "GeogBks", "ItalArt")
```

5. Partition

5.1. Raw Data

```
set.seed(2021)
train.index <- sample(1:nrow(data), 0.7*nrow(data))
train <- data[train.index, ]
valid <- data[-train.index, ]

train.n <- data.n[train.index, ]
valid.n <- data.n[-train.index, ]
```

5.2. Balance with ROSE

```
train.rose <- ROSE(Florence ~ ., data = train)$data
train.n.rose <- ROSE(Florence ~ ., data = train.n)$data

table(train.rose$Florence)

# Plot New Distribution
my.par() %>% par(mfrow = c(1, 3),
                 mai = par("mai") * 1,
                 oma = c(0,0,0,0) + 0.1,
                 mar = c(4,4,2,0) + 0.1
                 )

plot(factor(train$Florence),
     ylim = c(0, 3000),
```

```

      xlab = "Florence",
      ylab = "Frequency",
      main = "ImBalanced Training Set",
      col = c("red2", "cornflowerblue")) %>%
text(0, y = table(train$Florence),
     labels = paste(table(train$Florence), "-",
                      round(prop.table(table(train$Florence))*100, 2), "%"),
     pos = 3, cex = 1)

plot(factor(train.rose$Florence),
     ylim = c(0, 3000),
     xlab = "Florence",
     ylab = "Frequency",
     main = "Balanced Training Set",
     col = c("red2", "cornflowerblue")) %>%
text(0, y = table(train.rose$Florence),
     labels = paste(table(train.rose$Florence), "-",
                      round(prop.table(table(train.rose$Florence))*100, 2), "%"),
     pos = 3, cex = 1)

plot(factor(valid$Florence),
     ylim = c(0, 3000),
     xlab = "Florence",
     ylab = "Frequency",
     main = "Validation Set",
     col = c("red2", "cornflowerblue")) %>%
text(0, y = table(valid$Florence),
     labels = paste(table(valid$Florence), "-",
                      round(prop.table(table(valid$Florence))*100, 2), "%"),
     pos = 3, cex = 1)

```

6. ANALYSIS

6.1. Logistic Regression (LR)

6.1.1. LR Data Sets

```

train.lr <- train
train.lr.rose <- train.rose
valid.lr <- valid

train.n.lr <- train.n
train.n.lr.rose <- train.n.rose
valid.n.lr <- valid.n

```

6.1.2. Generic Function for LR Fitting and Confusion Matrices Computing

```

loreg_m <- function(X, Y, cutoff){
  options(scipen = 0)
  set.seed(2021)
  # Model
  if (!require("lattice")) install.packages("lattice")
  lg.reg <- glm(Florence ~ ., data = X, family = "binomial")
  # print(summary(lg.reg))
  # Predict
  lg.reg.pred <- predict(lg.reg, Y)
  # Evaluate
  if (!require("caret")) install.packages("caret")
  library(caret)
  confusionMatrix(factor(ifelse(lg.reg.pred > cutoff, 1, 0)), factor(Y$Florence), positive = "0")
  # plot(lg.reg, which = 1:2)
}

```

6.1.3. Imbalanced Full

```
lr_cm_i0 <- loreg_m(train.n.lr[, col0], valid.n.lr[, col0], 0.5)
```

6.1.4. Balanced Full

```
lr_cm_b0 <- loreg_m(train.n.lr.rose[, col0], valid.n.lr[, col0], 0.5)
=> Two predictor variables are perfectly correlated.
```

6.1.5. Imbalanced Set 1

```
lr_cm_i1 <- loreg_m(train.n.lr[, col1], valid.n.lr[, col1], 0.5)
```

6.1.6. Balanced Set 1

```
lr_cm_b1 <- loreg_m(train.n.lr.rose[, col1], valid.n.lr[, col1], 0.5)
```

6.1.7. Imbalanced Set 2

```
lr_cm_i2 <- loreg_m(train.n.lr[, col2], valid.n.lr[, col2], 0.5)
```

6.1.8. Balanced Set 2

```
lr_cm_b2 <- loreg_m(train.n.lr.rose[, col2], valid.n.lr[, col2], 0.5)
```

6.1.9. LR Confusion Matrices

```
options(scipen = 0)
lr_cm_i0
lr_cm_i1
lr_cm_i2
lr_cm_b0
lr_cm_b1
lr_cm_b2
```

6.1.10. LR CM Plot

```
# Generic Function
lr_cmp <- function(cm, title) {
  fourfoldplot(cm, color = c("cornflowerblue", "red2"),
    margin = 1, space = 0.3,
    conf.level = 0, main = title)
}

# Plot
my.par() %>% par(mfrow = c(2, 3),
  mai = par("mai") * 1,
  oma = c(0,0,0,0) + 0.1,
  mar = c(2,4,2,0) + 0.1
)
lr_cmp(lr_cm_i0$table, "Model B")
lr_cmp(lr_cm_i1$table, "Model C")
lr_cmp(lr_cm_i2$table, "Model D")
lr_cmp(lr_cm_b0$table, "Model E")
lr_cmp(lr_cm_b1$table, "Model F")
lr_cmp(lr_cm_b2$table, "Model G")
```

6.2. k-Nearest Neighbors

6.2.1. k-Nearest Neighbors (KNN) Data Sets

```
train.knn <- train
train.knn.rose <- train.rose
valid.knn <- valid
```

6.2.2. Optimal K

```
# Compute Optimal K
k_opt <- sqrt(nrow(train.knn))/2
k_opt

# Generic Function to automatically compute k's
knn_ks <- function(X, Y, att, seq_i=1, seq_j=k_opt, seq_step=1) {
  library(caret); library(FNN); library(class)
```

```

library(gmodels); library(e1071); library(ggplot2)
options(scipen = 0)
set.seed(2021)
accuracy <- data.frame(k = seq(seq_i, seq_j, seq_step), accuracy = rep(0, k_opt))
for (i in seq_i:seq_j) {
  knn.pred <- knn(X[, att], Y[, att],
                  cl = X[, "Florence"], k = i)
  accuracy[i, 2] <- confusionMatrix(knn.pred,
                                   factor(Y[, "Florence"]),
                                   positive = '0')$overall[1]
}
accuracy
}

```

6.2.3. *k*'s Accuracies

```

knn_i0 <- knn_ks(train.knn, valid.knn, var0) #5
knn_b0 <- knn_ks(train.knn.rose, valid.knn[, -1], var0) #21
knn_i1 <- knn_ks(train.knn[, col1], valid.knn[, col1], var1) #3
knn_b1 <- knn_ks(train.knn.rose[, col1], valid.knn[, col1], var1) #13
knn_i2 <- knn_ks(train.knn[, col2], valid.knn[, col2], var2) #9
knn_b2 <- knn_ks(train.rose[, col2], valid[, col2], var2) #9

```

6.2.4. Plot *k*'s Accuracies

```

my.par() %>% par(mai = par("mai") * 1,
                 oma = c(0,0,0,0) + 0.1,
                 mar = c(4,4,0,0) + 0.1
                )
plot(knn_i0, bty = "n", type = "n",
      xlim = c(0, 30), ylim = c(0.5, 1.05),
      xlab = "k", ylab = "Accuracy",
      yaxt = "n")
axis(2, at = seq(0.5, 1.0, 0.1),
      labels = format(seq(0.5, 1.0, 0.1), digits = 2))
lines(knn_i0, type = "b", pch = 18, lwd = 2, col = pal[1])
lines(knn_i1, type = "b", pch = 18, lwd = 2, col = pal[2])
lines(knn_i2, type = "b", pch = 18, lwd = 2, col = pal[3])
lines(knn_b0, type = "b", pch = 18, lwd = 2, col = pal[4])
lines(knn_b1, type = "b", pch = 18, lwd = 2, col = pal[5])
lines(knn_b2, type = "b", pch = 18, lwd = 2, col = pal[6])
legend("top", bty = "n",
       legend = c("H", "I", "J", "K", "L", "M"),
       title = "MODELS", cex = 1.5,
       col = pal[1:6], horiz = TRUE,
       lty = 1, lwd = 2, pch = 18
       )

```

6.2.5. KNN Confusion Matrices

```

# Generic Function
knn_e <- function(X, Y, att, i){
  library(caret); library(FNN); library(class)
  library(gmodels); library(e1071); library(ggplot2)
  options(scipen = 0)
  set.seed(2021)
  knn_pred <- knn(X[, att], Y[, att], cl = X[, "Florence"], k = i)
  confusionMatrix(factor(knn_pred),
                  factor(Y$Florence),
                  positive = "0")
}

# Compute Confusion Matrices
knn_e_i0 <- knn_e(train.knn, valid.knn, col0, 5) #5
knn_e_b0 <- knn_e(train.knn.rose, valid.knn, col0, 21) #21
knn_e_i1 <- knn_e(train.knn[, col1], valid.knn[, col1], var1, 3) #3
knn_e_b1 <- knn_e(train.knn.rose[, col1], valid.knn[, col1], var1, 13) #13
knn_e_i2 <- knn_e(train.knn[, col2], valid.knn[, col2], var2, 9) #9
knn_e_b2 <- knn_e(train.rose[, col2], valid[, col2], var2, 9) #9

```

```
knn_e_i0
knn_e_i1
knn_e_i2
knn_e_b0
knn_e_b1
knn_e_b2
```

6.2.6. KNN Confusion Matrices Plot

```
# Generic Function
knn_cmp <- function(cm, title) {
  fourfoldplot(cm, color = c("cornflowerblue", "red2"),
    margin = 1, space = 0.3,
    conf.level = 0, main = title)
}

# Plot
my.par() %>% par(mfrow = c(2, 3),
  mai = par("mai") * 1,
  oma = c(0,0,0,0) + 0.1,
  mar = c(2,4,2,0) + 0.1
)
knn_cmp(knn_e_i0$table, "Model H: k = 5")
knn_cmp(knn_e_i1$table, "Model I: k = 21")
knn_cmp(knn_e_i2$table, "Model J: k = 3")
knn_cmp(knn_e_b0$table, "Model K: k = 13")
knn_cmp(knn_e_b1$table, "Model L: k = 9")
knn_cmp(knn_e_b2$table, "Model M: k = 9")
```

7. Clean Environment

```
rm(list = ls())
cat("\014")
```

CASE 3

CLASSIFYING HOME EQUITY LOAN APPLICANTS

1. SET ENVIRONMENTS

1.1. Load Mandy Nguyen's Customized Functions

```
source("https://raw.githubusercontent.com/mandyhpnguyen/Mandy-Functions/main/M.R-Funcs/general.R")
```

1.2. Load Required Packages

```
pkgs <- c(
  "beepR",
  # General pkgs:
  "tidyverse", "dplyr", "summarytools", "reshape2", "pastecs", "ROSE",
  # Analytics pkgs:
  "forecast", "zoo", "scorecard",
  # Evaluation pkgs:
  "caret", "DT", "lift", "gains", "gt", "cvms", "tibble", "fourfoldplot",
  # Visualization pkgs:
  "RColorBrewer", "hrbrthemes", "knitr", "showtext", "sysfonts",
  "ggfortify", "ggplot2", "corrplot", "GGally", "viridis",
  "lattice", "grid", "cowplot", "Amelia"
)
suppressMessages(suppressWarnings(loadpkg(pkgs)))
```

1.3. Set fonts

```
# Load the main font used in the paper to plot charts for standardization

windowsFonts(cambria = windowsFont("Cambria"))
my.par <- function() {
  options(scipen = 999)
  par(mfrow = c(1, 1),
      family = "cambria",
      cex.main = 1.25, cex.lab = 1.25, cex.axis = 1.25)
}
```

1.4. Create Customized Color Scheme

```
pal <- c("cornflowerblue", "orange", "red2", "forestgreen", "mediumorchid1", "tomato3", "cadetblue1")
```

2. COLLECT DATA

2.1. Load Data Set Stored Online in My Github Repository

```
hmeq <- read.csv("https://raw.githubusercontent.com/mandyhpnguyen/MS-Data-Analytics-Datasets/main/Practicum/hmeq.csv")
```

2.2. Overview Data

```
View(hmeq)
str(hmeq)
datatable(hmeq)
```

2.3. Export Detailed Statistic Summary to .CSV File

```
setwd("~/~/")
options(scipen = 0, digits = 2)
round(stat.desc(hmeq), 0) %>% write.csv("hmeq_descr.csv", row.names = TRUE)
```

3. DATA CLEANING AND HARMONIZATION

3.1. Create Working Data Frame and Character Version of Target Attribute

```
data <- hmeq
data$STATUS <- factor(ifelse(data$BAD == 1, "defaulted", "paid"),
                      levels = c("defaulted", "paid"),)
str(data)
View(data)
```

3.2. Check Missing Values

```
# Total Missing Values Cells
sum(is.na(data))
sum(apply(data, 1, anyNA))

# Missing Value Distribution
data.na <- data[apply(data, 1, anyNA), ]
table(data.na$BAD)

# Total number of Missing Values of Observations
count(data.na)

# Percentage of Missing Value
round((count(data.na)/count(data))*100, 2)

# Remaining Data
count(data) - count(data.na)
round(((count(data) - count(data.na))/count(data))*100, 2)

# Bar Plot of Missing Value Distribution
my.par()
na.aggr <- data.frame(sum = c("Defaulted", "Paid", "Total Rows", "Total Cells"),
                     count = c(880, 1565, 2445, 4740))

barplot(height = na.aggr$count,
        ylim = c(0, 5100), cex.lab = 0.75,
        names = na.aggr$sum,
        col = c("red2", "cornflowerblue", "forestgreen", "orange")) %>%
  text(0, y = na.aggr$count,
       labels = na.aggr$count,
       pos = 3, cex = 1)

# Heat Map of Missing Value
my.par()
missmap(data,
        col = c("red2", "cornflowerblue"),
        main = "",
        legend = FALSE,
        x.cex = 0.8, y.cex = 0.8,
        gap.xaxis = 1, x.las = 2
        )

# Preference for Reference: http://www.sthda.com/english/wiki/add-legends-to-plots-in-r-software-the-easiest-way

# Create new data frame without missing value

data.omit <- na.omit(data)
str(data.omit)

# Explort new data frame with no missing values to .CSV file
setwd("C:/One Drives/OneDrive - Webster University/Webster Classes/21F_CSDA 6010_Practicum")
options(scipen = 0, digits = 2)
data.omit %>% write.csv("hmeq.omit.csv", row.names = TRUE)
```

3.3. Check Typographical Errors

```
# Plot Categorical Attributes
my.par() %>% par(mfrow = c(1, 1),
```

```

        mai = par("mai") * 1,
        oma = c(0,0,0,0) + 0.1,
        mar = c(2,2,2,0) + 0.1
    )

## REASON Attribute
reason.bp <- plot(as.factor(data$REASON),
                 ylim = c(0, 4200),
                 main = "",
                 col = c("red2", "cornflowerblue", "forestgreen"))
text(x = reason.bp, y = table(as.factor(data$REASON)),
     labels = table(as.factor(data$REASON)),
     pos = 3, cex = 1)

my.par() %>% par(mfrow = c(1, 1),
                mai = par("mai") * 1,
                oma = c(0,0,0,0) + 0.1,
                mar = c(0,0,0,0) + 0.1
                )
pie(table(data$REASON),
    labels = paste(c("", "DebtCon", "HomeImp"),
                  round(prop.table(table(data$REASON)), 2)*100, "%"),
    col = c("red2", "cornflowerblue", "forestgreen")
)

## JOB Attribute
my.par() %>% par(mfrow = c(1, 1),
                mai = par("mai") * 1,
                oma = c(0,0,0,0) + 0.1,
                mar = c(2,5,2,0) + 0.1
                )
job.bp <- plot(as.factor(data$JOB),
               ylim = c(0, 2500),
               main = "",
               col = pal)
text(x = job.bp, y = table(as.factor(data$JOB)),
     labels = table(as.factor(data$JOB)),
     pos = 3, cex = 1)

my.par() %>% par(mfrow = c(1, 1),
                mai = par("mai") * 1,
                oma = c(0,0,0,0) + 0.1,
                mar = c(0,0,0,0) + 0.1
                )
pie(table(data$JOB),
    labels = paste(c("", "Mgr", "Office", "Other", "ProfExe", "Sales", "Self"),
                  round(prop.table(table(data$JOB)), 2)*100, "%"),
    col = pal
)

```

3.4. Check Outliers

```

# Generic Function for Combined Box Plot
out.bp <- function(dataset) {
  my.par() %>% par(mfrow = c(1, 10),
                  mai = par("mai") * 1,
                  oma = c(0,0,0,0) + 0.1,
                  mar = c(0.5,2.5,5,0) + 0.1
                  )

  i = 2
  for (i in 2:length(colnames(dataset))) {
    boxplot(dataset[, i],
            main = colnames(dataset)[i],
            cex.main = 2, cex.axis = 2,
            col = "red3")
    i = i + 1
  }
}

```



```

# Plot Raw Dataset
my.par()
out.bp(data[, -c(5, 6, 14)])

# Plot No Missing Value Set
my.par()
out.bp(data.omit[, -c(5, 6, 14)])

# Remove Outliers
## Generic Function to All Remove Outliers
outliers_removal <- function(a){
  df <- a
  aa <- c()
  count <- 1
  for (i in 1:ncol(df)) {
    if (is.numeric(df[,i])) {
      Q3 <- quantile(df[,i], 0.75, na.rm = TRUE)
      Q1 <- quantile(df[,i], 0.25, na.rm = TRUE)
      IQR <- Q3 - Q1 #IQR(df[,i])
      upper <- Q3 + 1.5 * IQR
      lower <- Q1 - 1.5 * IQR
      for (j in 1:nrow(df)) {
        if (is.na(df[j,i]) == TRUE) {
          next
        }
        else if (df[j,i] > upper | df[j,i] < lower) {
          aa[count] <- j
          count <- count + 1
        }
      }
    }
  }
  df <- df[-aa,]
}

## Remove Outliers in all Numeric Attributes
data.na.clean <- data
data.na.clean <- outliers_removal(data.na.clean)
data.clean <- data.omit
data.clean <- outliers_removal(data.clean)

## Check Variables
dim(data.na.clean)
dim(data.clean)

## Plot new data sets with no outliers
my.par()
out.bp(data.na.clean[, -c(5, 6, 14)])

out.bp(data.clean[, -c(5, 6, 14)])

# Clear Outliers Problem
dim(data.clean)

table(data.omit$DEROG)
table(data.clean$DEROG)
table(data.omit$DELINQ)
table(data.clean$DELINQ)
table(data.omit$NINQ)
table(data.clean$NINQ)
table(data.omit$CLNO)
table(data.clean$CLNO)
length(table(data.omit$CLNO))
length(table(data.clean$CLNO))

# Solution to Outliers
data.omit.group <- data.omit
data.omit.group$DEROG[data.omit.group$DEROG > 2] <- 2
data.omit.group$DELINQ[data.omit.group$DELINQ > 2] <- 2

```

```

data.omit.group$NINQ[data.omit.group$NINQ > 3] <- 3

table(data.omit.group$DEROG)
table(data.omit.group$DELINQ)
table(data.omit.group$NINQ)
data.omit.group.clean <- outliers_removal(data.omit.group)
str(data.omit.group.clean)

out.bp(data.omit.group.clean[, -c(5, 6, 14)])

table(data.omit.group.clean$DEROG)
table(data.omit.group.clean$DELINQ)
table(data.omit.group.clean$NINQ)

out.bp(data.omit.group[, -c(5, 6, 14)])

# Export new clean data set stats with no missing value and outliers
setwd("~/")
options(scipen = 0, digits = 2)
round(stat.desc(data.omit.group), 0) %>% write.csv("hmeq_omit_group_stats.csv", row.names = TRUE)

```

3.5. Clean Data Set

```

# Replace Empty Spaces

## Raw Data
data$REASON[data$REASON == ""] <- "Other"
data$REASON <- factor(data$REASON)
data$JOB[data$JOB == ""] <- "Other"
data$JOB <- factor(data$JOB)

data$.REASON <- ifelse(data$REASON == "DebtCon", 1,
                      ifelse(data$REASON == "HomeImp", 2, 3))

data$.JOB <- ifelse(data$JOB == "Other", 1,
                  ifelse(data$JOB == "ProfExe", 2,
                        ifelse(data$JOB == "Office", 3,
                              ifelse(data$JOB == "Mgr", 4,
                                    ifelse(data$JOB == "Self", 5, 6)
                                   )
                             )
                        )
                  )
)

## No Missing Value Data
data.omit$REASON[data.omit$REASON == ""] <- "Other"
data.omit$REASON <- factor(data.omit$REASON)
data.omit$JOB[data.omit$JOB == ""] <- "Other"
data.omit$JOB <- factor(data.omit$JOB)

data.omit$.REASON <- ifelse(data.omit$REASON == "DebtCon", 1,
                          ifelse(data.omit$REASON == "HomeImp", 2, 3))

data.omit$.JOB <- ifelse(data.omit$JOB == "Other", 1,
                      ifelse(data.omit$JOB == "ProfExe", 2,
                            ifelse(data.omit$JOB == "Office", 3,
                                  ifelse(data.omit$JOB == "Mgr", 4,
                                        ifelse(data.omit$JOB == "Self", 5, 6)
                                       )
                                )
                            )
                      )
)

## Grouped No Missing Value Data
data.omit.group$REASON[data.omit.group$REASON == ""] <- "Other"
data.omit.group$REASON <- factor(data.omit.group$REASON)
data.omit.group$JOB[data.omit.group$JOB == ""] <- "Other"
data.omit.group$JOB <- factor(data.omit.group$JOB)

data.omit.group$.REASON <- ifelse(data.omit.group$REASON == "DebtCon", 1,
                                ifelse(data.omit.group$REASON == "HomeImp", 2, 3))

data.omit.group$.JOB <- ifelse(data.omit.group$JOB == "Other", 1,

```

```

        ifelse(data.omit.group$JOB == "ProfExe", 2,
              ifelse(data.omit.group$JOB == "Office", 3,
                    ifelse(data.omit.group$JOB == "Mgr", 4,
                          ifelse(data.omit.group$JOB == "Self", 5, 6
                                ))))
    )))

# Export Final Data Set

## No Missing Data
setwd("~/")
options(scipen = 0, digits = 2)
data.omit %>% write.csv("hmeq_omit_final.csv", row.names = TRUE)

# Grouped No Missing Data
setwd("C:/One Drives/OneDrive - Webster University/Webster Classes/21F_CSDA 6010_Practicum")
options(scipen = 0, digits = 2)
data.omit.group %>% write.csv("hmeq_omit_group_final.csv", row.names = TRUE)

```

4. ATTRIBUTE EXPLORATION

```

df <- data.omit.group
str(df)
summary(df)

```

4.1. Target Attribute

```

my.par() %>% par(mfrow = c(1, 2),
               mai = par("mai") * 1,
               oma = c(0,0,0,0) + 0.1,
               mar = c(2,4,0,0) + 0.1
               )

stt.bp.raw <- plot(data$STATUS,
                  ylim = c(0, 5500),
                  ylab = "Frequency in Raw Dataset",
                  main = "",
                  col = c("red2", "cornflowerblue"))
text(x = stt.bp.raw, y = table(data$STATUS),
     labels = paste(table(data$STATUS), "-",
                     round(prop.table(table(data$STATUS))*100, 2), "%"),
     pos = 3, cex = 1)
# text(x = stt.bp.raw, y = c(1400, 4970),
#      labels = paste(round(prop.table(table(data$STATUS))*100, 2), "%"),
#      pos = 3, cex = 1)

stt.bp.clean <- plot(df$STATUS,
                    ylim = c(0, 5500),
                    ylab = "Frequency in Clean Dataset",
                    main = "",
                    col = c("red2", "cornflowerblue"))
text(x = stt.bp.clean, y = table(df$STATUS),
     labels = paste(table(df$STATUS), "-",
                     round(prop.table(table(df$STATUS))*100, 2), "%"),
     pos = 3, cex = 1)
# text(x = stt.bp.clean, y = c(300, 2400),
#      labels = paste(round(prop.table(table(df$STATUS))*100, 2), "%"),
#      pos = 3, cex = 1)

```

4.2. Predictor Attributes

4.2.1. Target against Categorical Attributes

```

# Function to Create Box Plot of Numeric Attributes
pred.box_f <- function(i) {
  explore.vars <- c(2:4, 15:16, 7:13)
  j = explore.vars[i]
  ggplot(df, aes(fill = STATUS,
                 y = df[, j],
                 x = STATUS)) +

```

```

ggtitle(paste(colnames(df)[j], "against STATUS")) +
geom_boxplot() + theme_minimal() +
scale_fill_manual(values = c("red2", "cornflowerblue")) +
theme(text = element_text(size = 12, family = "cambria")) +
theme(axis.title.y = element_blank(),
      axis.ticks.y = element_blank(),
      axis.title.x = element_blank(),
      legend.position = "none")
}

# Plot Attributes
box.LOAN <- pred.box_f(1)
box.MORTDUE <- pred.box_f(2)
box.VALUE <- pred.box_f(3)
box.REASON <- pred.box_f(4)
box.JOB <- pred.box_f(5)
box.YOJ <- pred.box_f(6)
box.DEROG <- pred.box_f(7)
box.DELINQ <- pred.box_f(8)
box.CLAGE <- pred.box_f(9)
box.NINQ <- pred.box_f(10)
box.CLNO <- pred.box_f(11)
box.DEBTINC <- pred.box_f(12)

# Combine Box Plots
my.par()
cowplot::plot_grid(box.LOAN, box.MORTDUE, box.VALUE, box.REASON,
                  box.JOB, box.YOJ, box.DEBTINC, box.DEROG,
                  box.DELINQ, box.CLAGE, box.NINQ, box.CLNO
                  )

```

4.2.2. Target against Numerical Attributes

```

# Function to Create Bar Plot of Numeric Categories
rm(i) %>% suppressWarning()
pred.bar_f <- function(df, i) {
  ggplot(df, aes(fill = STATUS, x = df[, i])) +
    labs(title = colnames(df)[i], y = "Percentage") +
    geom_bar(position = "fill") +
    theme_classic() +
    scale_fill_manual(values = c("red2", "cornflowerblue")) +
    theme(text = element_text(size = 12, family = "cambria")) +
    theme(axis.title.x = element_blank(),
          legend.position = "top")
}

# Plot Attributes
bar.REASON <- pred.bar_f(df, 5)
bar.JOB <- pred.bar_f(df, 6)
bar.DEROG <- pred.bar_f(df, 8)
bar.DELINQ <- pred.bar_f(df, 9)
bar.NINQ <- pred.bar_f(df, 11)

# Combine Bar Plots
cowplot::plot_grid(bar.DEROG, bar.DELINQ, bar.NINQ) %>% suppressWarnings()
cowplot::plot_grid(bar.REASON, bar.JOB) %>% suppressWarnings()

```

4.3. Select Variables

4.3.1. Correlation Matrix

```

# Calculate Correlation between Attributes
corr.var <- c(1:4, 7:13, 15, 16)
corr.df <- df[, corr.var]
corr.mat <- round(cor(corr.df), 2)
testRes = cor.mtest(corr.mat, conf.level = 0.95)

# Plot Correlation
my.par()

```

```
corrplot(corr.mat, method = "color",
         type = "full", tl.col = "black")$corrPos -> corrp
text(corrp$x, corrp$y, round(corrp$corr, 2))
```

4.3.2. Stepwise Regression

```
loreg_m_ic <- function(X, Z){
  options(scipen = 0)
  set.seed(2021)
  lg.reg <- glm(STATUS ~ ., data = X, family = "binomial")
  # step(lg.reg, direction = Z)
  summary(step(lg.reg, direction = Z))
}
```

```
options(scipen = 0)
loreg_m_ic(data.omit[, -c(1, 15, 16)], "both")
```

4.3.3. Information Value

```
# library(scorecard)
iv.df <- as.data.frame(iv(df[, -c(5:6, 14)],
                        y = "BAD", positive = "BAD|1")) %>% arrange()
print(iv.df)

my.par()
barplot(height = iv.df$info_value, names = iv.df$variable,
        ylim = c(0, 0.9), col = pal) %>%
  text(0, y = iv.df$info_value,
       labels = round(iv.df$info_value, 6),
       pos = 3, cex = 1) %>% suppressWarnings()
```

4.3.4. Variables in Use

```
var1 <- c("STATUS", "LOAN", "CLNO", "YOJ", "DELINQ", "DEROG", "NINQ")
col1 <- c("LOAN", "CLNO", "YOJ", "DELINQ", "DEROG", "NINQ")
var2 <- c("STATUS", "CLAGE", "DEBTINC", "DELINQ", "DEROG", "NINQ")
col2 <- c("CLAGE", "DEBTINC", "DELINQ", "DEROG", "NINQ")
var <- c(2:4, 7:16)
col <- c(2:4, 7:13, 15:16)

var.bad <- c(1:4, 7:13, 15:16)
col.bad <- c(2:4, 7:13, 15:16)

col.rose.k <- c(1:3, 6:12, 14:15)
```

5. PARTITION

5.1. Training and Validation

```
set.seed(2021)
index <- sample(c(1:dim(df)[1]), dim(df)[1]*0.7)
train <- df[index, ]
valid <- df[-index, ]

table(train$STATUS)
prop.table(table(train$STATUS))
table(valid$STATUS)
prop.table(table(valid$STATUS))
```

5.2. Balance Training with ROSE

```
train.rose <- ROSE(STATUS ~ ., data = train[, -1])$data
```

```
table(train.rose$STATUS)
prop.table(table(train.rose$STATUS))
```

5.3. Plot STATUS distribution of 3 sets

```
my.par() %>% par(mfrow = c(1, 3),
                mai = par("mai") * 1,
                oma = c(0,0,0,0) + 0.1,
                mar = c(2,4,4,0) + 0.1
                )
plot(train$STATUS,
     ylim = c(0, 2500),
     ylab = "Frequency",
     main = "ImBalanced Training Set",
     col = c("red2", "cornflowerblue")) %>%
text(0, y = table(train$STATUS),
     labels = paste(table(train$STATUS), "-",
                     round(prop.table(table(train$STATUS))*100, 2), "%"),
     pos = 3, cex = 1)

plot(train.rose$STATUS,
     ylim = c(0, 2500),
     ylab = "Frequency",
     main = "Balanced Training Set",
     col = c("red2", "cornflowerblue")) %>%
text(0, y = table(train.rose$STATUS),
     labels = paste(table(train.rose$STATUS), "-",
                     round(prop.table(table(train.rose$STATUS))*100, 2), "%"),
     pos = 3, cex = 1)

plot(valid$STATUS,
     ylim = c(0, 2500),
     ylab = "Frequency",
     main = "Validation Set",
     col = c("red2", "cornflowerblue")) %>%
text(0, y = table(valid$STATUS),
     labels = paste(table(valid$STATUS), "-",
                     round(prop.table(table(valid$STATUS))*100, 2), "%"),
     pos = 3, cex = 1)
```

6. CLASSIFICATIONS

6.1. Logistic Regression

6.1.1. Logistic Regression (lr) Data Sets

```
train.lr <- train
train.lr.rose <- train.rose
valid.lr <- valid
```

6.1.2. Generic Function

```
loreg_m <- function(X, Y, cutoff){
  options(scipen = 0)
  set.seed(2021)
  # Model
  if (!require("lattice")) install.packages("lattice")
  lg.reg <- glm(STATUS ~ ., data = X, family = "binomial")
  # print(summary(lg.reg))
  # Predict
  lg.reg.pred <- predict(lg.reg, Y)
  # Evaluate
  if (!require("caret")) install.packages("caret")
  library(caret)
  confusionMatrix(factor(ifelse(lg.reg.pred > cutoff, "paid", "defaulted")), factor(Y$STATUS),
    positive = 'paid')
  # plot(lg.reg, which = 1:2)
}
```

6.1.3. Imbalanced All

```
loreg_m(train.lr, valid.lr, 0.5)
```

6.1.4. Balanced All

```
loreg_m(train.lr.rose, valid.lr, 0.5)
```

6.1.5. Imbalanced Set 1

```
loreg_m(train.lr[, var1], valid.lr[, var1], 0.5)
```

6.1.6. Blanced Set 1

```
loreg_m(train.lr.rose[, var1], valid.lr[, var1], 0.5)
```

6.1.7. Imbalanced Set 2

```
loreg_m(train.lr[, var2], valid.lr[, var2], 0.5)
```

6.1.8. Balanced Set 2

```
loreg_m(train.lr.rose[, var2], valid.lr[, var2], 0.5)
```

6.1.9. Four Fold Plots of Confusion Matrix

```
lr_cmp <- function(cm, title) {
  fourfoldplot(cm, color = c("cornflowerblue", "red2"),
    margin = 1, space = 0.3,
    conf.level = 0, main = title)
}
my.par() %>% par(mfrow = c(2, 3),
  mai = par("mai") * 1,
  oma = c(0,0,0,0) + 0.1,
  mar = c(2,4,2,0) + 0.1
)
lr_cmp(loreg_m(train.lr, valid.lr, 0.5)$table, "Model A")
lr_cmp(loreg_m(train.lr.rose, valid.lr, 0.5)$table, "Model B")
lr_cmp(loreg_m(train.lr[, var1], valid.lr[, var1], 0.5)$table, "Model C")
lr_cmp(loreg_m(train.lr.rose[, var1], valid.lr[, var1], 0.5)$table, "Model D")
lr_cmp(loreg_m(train.lr[, var2], valid.lr[, var2], 0.5)$table, "Model E")
lr_cmp(loreg_m(train.lr.rose[, var2], valid.lr[, var2], 0.5)$table, "Model F")
```

6.2. k-Nearest Neighbors

6.2.1. k-Nearest Neighbors (knn) Data Sets

```
train.knn <- train
train.knn.rose <- train.rose
valid.knn <- valid
```

6.2.2. Optimal K

```
k_opt <- sqrt(nrow(train.knn))/2
k_opt

knn_ks <- function(X, Y, att, seq_i=1, seq_j=k_opt, seq_step=1) {
  library(caret); library(FNN); library(class)
  library(gmodels); library(e1071); library(ggplot2)
  options(scipen = 0)
  set.seed(2021)
  accuracy <- data.frame(k = seq(seq_i, seq_j, seq_step), accuracy = rep(0, k_opt))
  for (i in seq_i:seq_j) {
    knn.pred <- knn(X[, att], Y[, att],
      cl = X[, 'STATUS'], k = i)
    accuracy[i, 2] <- confusionMatrix(knn.pred,
      factor(Y[, 'STATUS']),
```

```

                                positive = 'paid')$overall[1]
}
accuracy
}

knn_i0 <- knn_ks(train.knn, valid.knn, col) %>% suppressWarnings()
knn_b0 <- knn_ks(train.knn.rose, valid.knn[, -1], col.rose.k) %>% suppressWarnings()
knn_i1 <- knn_ks(train.knn[, var1], valid.knn[, var1], col1) %>% suppressWarnings()
knn_b1 <- knn_ks(train.knn.rose[, var1], valid.knn[, var1], col1) %>% suppressWarnings()
knn_i2 <- knn_ks(train.knn[, var2], valid.knn[, var2], col2) %>% suppressWarnings()
knn_b2 <- knn_ks(train.rose[, var2], valid[, var2], col2) %>% suppressWarnings()

my.par() %>% par(mai = par("mai") * 1,
                oma = c(0,0,0,0) + 0.1,
                mar = c(4,4,0,0) + 0.1
                )
plot(knn_i0, bty = "n", type = "n",
     xlim = c(0, 25), ylim = c(0.5, 1.05),
     xlab = "k", ylab = "Accuracy",
     yaxt = "n")
axis(2, at = seq(0.5, 1.0, 0.1),
     labels = format(seq(0.5, 1.0, 0.1), digits = 2))
lines(knn_i0, type = "b", pch = 18, lwd = 2, col = pal[1])
lines(knn_i1, type = "b", pch = 18, lwd = 2, col = pal[2])
lines(knn_i2, type = "b", pch = 18, lwd = 2, col = pal[3])
lines(knn_b0, type = "b", pch = 18, lwd = 2, col = pal[4])
lines(knn_b1, type = "b", pch = 18, lwd = 2, col = pal[5])
lines(knn_b2, type = "b", pch = 18, lwd = 2, col = pal[6])
legend("top", bty = "n",
      legend = c("G", "H", "I", "J", "K", "L"),
      title = "MODELS", cex = 1.5,
      col = pal[1:6], horiz = TRUE,
      lty = 1, lwd = 2, pch = 18
      )

```

6.2.3. Generic Functions

```

knn_f <- function(X, Y, att, seq_i=1, seq_j=k_opt, seq_step=1) {
  library(caret); library(FNN); library(class)
  library(gmodels); library(e1071); library(ggplot2)
  options(scipen = 0)
  set.seed(2021)
  accuracy <- data.frame(k = seq(seq_i, seq_j, seq_step), accuracy = rep(0, k_opt))
  for (i in seq_i:seq_j) {
    knn.pred <- knn(X[, att], Y[, att], cl = X[, 'STATUS'], k = i)
    accuracy[i, 2] <- confusionMatrix(knn.pred, factor(Y[, 'STATUS']),
                                     positive = 'paid')$overall[1]
  }
  print(accuracy)
  plot(accuracy$k, xlab = "Values of k",
       accuracy$accuracy,
       ylab = "Accuracies",
       main = "Values of k against their accuracies",
       type = 'l',
       col = 'gray')
}

knn_e <- function(X, Y, att, i){
  library(caret); library(FNN); library(class)
  library(gmodels); library(e1071); library(ggplot2)
  options(scipen = 0)
  set.seed(2021)
  knn_pred <- knn(X[, att], Y[, att], cl = X[, 'STATUS'], k = i)
  confusionMatrix(factor(knn_pred,
                        levels = c("paid", "defaulted")),
                  factor(Y$STATUS,
                        levels = c("paid", "defaulted")),
                  positive = "paid")
}

```



```
knn_ks <- function(X, Y, att, seq_i=1, seq_j=k_opt, seq_step=1) {
  library(caret); library(FNN); library(class)
  library(gmodels); library(e1071); library(ggplot2)
  options(scipen = 0)
  set.seed(2021)
  accuracy <- data.frame(k = seq(seq_i, seq_j, seq_step), accuracy = rep(0, k_opt))
  for (i in seq_i:seq_j) {
    knn.pred <- knn(X[, att], Y[, att], cl = X[, 'STATUS'], k = i)
    accuracy[i, 2] <- confusionMatrix(knn.pred, factor(Y[, 'STATUS']),
                                     positive = 'paid')$overall[1]
  }
  accuracy
}
```

6.2.4. Imbalanced All

```
my.par()
knn_f(train.knn, valid.knn, col)
#5

knn_e(train.knn, valid.knn, col, 5)
```

6.2.5. Balanced All

```
my.par()
knn_f(train.knn.rose, valid.knn[, -1], col.rose.k) %>% suppressWarnings()
# 25

knn_e(train.knn.rose, valid.knn[, -1], col.rose.k, 25)
```

6.2.6. Imbalanced Set 1

```
my.par()
knn_f(train.knn[, var1], valid.knn[, var1], col1) %>% suppressWarnings()
# 5

knn_e(train.knn[, var1], valid.knn[var1], col1, 5)
```

6.2.7. Balanced Set 1

```
my.par()
knn_f(train.knn.rose[, var1], valid.knn[, var1], col1) %>% suppressWarnings()
# 1

knn_e(train.knn.rose[, var1], valid.knn[var1], col1, 1)
```

6.2.8. Imbalanced Set 2

```
my.par()
knn_f(train.knn[, var2], valid.knn[, var2], col2)
# 3

knn_e(train.knn[, var2], valid.knn[var2], col2, 3)
```

6.2.9. Balanced Set 2

```
my.par()
knn_f(train.rose[, var2], valid[, var2], col2) %>% suppressWarnings()
# 19

knn_e(train.rose[, var2], valid[var2], col2, 19)
```

6.2.10. Four Fold Plots of Confusion Matrix

```
knn_cmp <- function(cm, title) {
  fourfoldplot(cm, color = c("cornflowerblue", "red2"),
               margin = 1, space = 0.3,
               conf.level = 0, main = title)
```

```

}
my.par() %>% par(mfrow = c(2, 3),
               mai = par("mai") * 1,
               oma = c(0,0,0,0) + 0.1,
               mar = c(2,4,2,0) + 0.1
               )
knn_cmp(knn_e(train.knn, valid.knn, col, 5)$table, "Model G: k = 5")
knn_cmp(knn_e(train.knn[, var1], valid.knn[var1], col1, 5)$table, "Model H: k = 5")
knn_cmp(knn_e(train.knn[, var2], valid.knn[var2], col2, 3)$table, "Model I: k = 3")
knn_cmp(knn_e(train.knn.rose, valid.knn[, -1], col.rose.k, 25)$table, "Model J: k = 25")
knn_cmp(knn_e(train.knn.rose[, var1], valid.knn[var1], col1, 1)$table, "Model K: k = 1")
knn_cmp(knn_e(train.knn.rose[, var2], valid.knn[, var2], col2, 19)$table, "Model L: k = 19")

```

6.3. Neural Networks

6.3.1. Neural Networks (nn) Data sets

```

train.nn <- train
train.nn.rose <- train.rose
valid.nn <- valid

```

6.3.2. Generic Function

```

set.seed(2021)
options(scipen = 0)
normalize <- function(x) {
  return((x - min(x)) / (max(x) - min(x)))
}
train.nn[, c(2:4, 7:13, 15:16)] <- as.data.frame(lapply(train.nn[, c(2:4, 7:13, 15:16)], normalize))

train.nn.rose.bad <- train.nn.rose
train.nn.rose.bad$BAD <- ifelse(train.nn.rose$STATUS == "paid", 0, 1)
train.nn.rose.bad <- train.nn.rose.bad[, c(16, 1:15)]

train.nn.rose.bad[, c(2:4, 7:13, 15:16)] <- as.data.frame(lapply(train.nn.rose.bad[, c(2:4, 7:13, 15:16)], normalize))

```

6.3.3. Imbalanced All

```

nn_if <- function(x, y) {
  var.bad <- c(1:4, 7:13, 15:16)
  col.bad <- c(2:4, 7:13, 15:16)
  if (!require("neuralnet")) install.packages("neuralnet")
  library(neuralnet)
  # Model
  set.seed(2021)
  options(scipen = 0)
  nn <- neuralnet(BAD ~ .,
                  data = train.nn[, var.bad],
                  hidden = x,
                  linear.output = FALSE)

  # plot(nn)
  # Predict
  nn_pred <- neuralnet::compute(nn, valid.nn[, col.bad])
  nn_pred_result <- nn_pred$net.result

  # Evaluate
  confusionMatrix(factor(ifelse(nn_pred_result > y, "paid", "defaulted"),
                           levels = c("paid", "defaulted")),
                  factor(valid.nn$STATUS, levels = c("paid", "defaulted"))) %>% print()
  # if (!require("beep")) install.packages("beep"); library(beep)
  # beep(2)
}

cm_nn1 <- nn_if(1, 0.5)

```

6.3.4. Balanced All

```

nn_bf <- function(x, y) {

```

```

var.bad <- c(1:4, 7:13, 15:16)
col.bad <- c(2:4, 7:13, 15:16)
if (!require("neuralnet")) install.packages("neuralnet")
library(neuralnet)
set.seed(2021)
options(scipen = 0)
# Model
nn <- neuralnet(BAD ~ .,
                data = train.nn.rose.bad[, var.bad],
                hidden = x,
                linear.output = FALSE)

# plot(nn)
# Predict
nn_pred <- neuralnet::compute(nn, valid.nn[, col.bad])
nn_pred_result <- nn_pred$net.result

# Evaluate
confusionMatrix(factor(ifelse(nn_pred_result > y, "paid", "defaulted"),
                        levels = c("paid", "defaulted")),
                factor(valid.nn$STATUS, levels = c("paid", "defaulted")))) %>% print()
# if (!require("beepR")) install.packages("beepR"); library(beepR)
# beep(2)
}

cm_nn4 <- nn_bf(2, 0.5)

```

6.3.5. Imbalanced Set 1

```

nn_i1 <- function(x, y) {
  var.bad <- c("BAD", "LOAN", "CLNO", "YOJ", "DELINQ", "DEROG", "NINQ")
  col.bad <- c("LOAN", "CLNO", "YOJ", "DELINQ", "DEROG", "NINQ")
  if (!require("neuralnet")) install.packages("neuralnet")
  library(neuralnet)
  nn <- neuralnet(BAD ~ .,
                  data = train.nn[, var.bad],
                  hidden = x,
                  linear.output = FALSE)

  # plot(nn)
  # Predict
  options(scipen = 0)
  set.seed(2021)
  nn_pred <- neuralnet::compute(nn, valid.nn[, col.bad])
  nn_pred_result <- nn_pred$net.result

  # Evaluate
  confusionMatrix(factor(ifelse(nn_pred_result > y, "paid", "defaulted"),
                          levels = c("paid", "defaulted")),
                  factor(valid.nn$STATUS, levels = c("paid", "defaulted")))) %>% print()
  # if (!require("beepR")) install.packages("beepR"); library(beepR)
  # beep(2)
}

cm_nn2 <- nn_i1(c(1, 1), 0.5)

```

6.3.6. Balanced Set 1

```

nn_b1 <- function(x, y) {
  var.bad <- c("BAD", "LOAN", "CLNO", "YOJ", "DELINQ", "DEROG", "NINQ")
  col.bad <- c("LOAN", "CLNO", "YOJ", "DELINQ", "DEROG", "NINQ")
  if (!require("neuralnet")) install.packages("neuralnet")
  library(neuralnet)
  nn <- neuralnet(BAD ~ .,
                  data = train.nn.rose.bad[, var.bad],
                  hidden = x,
                  linear.output = FALSE)

  # plot(nn)
  # Predict
  options(scipen = 0)
  set.seed(2021)

```

```

nn_pred <- neuralnet::compute(nn, valid.nn[, col.bad])
nn_pred_result <- nn_pred$net.result

# Evaluate
confusionMatrix(factor(ifelse(nn_pred_result > y, "paid", "defaulted"),
                           levels = c("paid", "defaulted")),
                 factor(valid.nn$STATUS, levels = c("paid", "defaulted"))) %>% print()
# if (!require("beep")) install.packages("beep"); library(beep)
# beep(2)
}

cm_nn5 <- nn_b1(c(1, 2), 0.5)

```

6.3.7. Imbalanced Set 2

```

nn_i2 <- function(x, y) {
  var.bad <- c("BAD", "CLAGE", "DEBTINC", "DELINQ", "DEROG", "NINQ")
  col.bad <- c("CLAGE", "DEBTINC", "DELINQ", "DEROG", "NINQ")
  if (!require("neuralnet")) install.packages("neuralnet")
  library(neuralnet)
  nn <- neuralnet(BAD ~ .,
                  data = train.nn[, var.bad],
                  hidden = x,
                  linear.output = FALSE)

  # plot(nn)
  # Predict
  options(scipen = 0)
  set.seed(2021)
  nn_pred <- neuralnet::compute(nn, valid.nn[, col.bad])
  nn_pred_result <- nn_pred$net.result

  # Evaluate
  confusionMatrix(factor(ifelse(nn_pred_result > y, "paid", "defaulted"),
                           levels = c("paid", "defaulted")),
                 factor(valid.nn$STATUS, levels = c("paid", "defaulted"))) %>% print()
  # if (!require("beep")) install.packages("beep"); library(beep)
  # beep(2)
}

cm_nn3 <- nn_i2(2, 0.5)

```

6.3.8. Balanced Set 2

```

nn_b2 <- function(x, y) {
  var.bad <- c("BAD", "CLAGE", "DEBTINC", "DELINQ", "DEROG", "NINQ")
  col.bad <- c("CLAGE", "DEBTINC", "DELINQ", "DEROG", "NINQ")
  if (!require("neuralnet")) install.packages("neuralnet")
  library(neuralnet)
  nn <- neuralnet(BAD ~ .,
                  data = train.nn.rose.bad[, var.bad],
                  hidden = x,
                  linear.output = FALSE)

  # plot(nn)
  # Predict
  options(scipen = 0)
  set.seed(2021)
  nn_pred <- neuralnet::compute(nn, valid.nn[, col.bad])
  nn_pred_result <- nn_pred$net.result

  # Evaluate
  confusionMatrix(factor(ifelse(nn_pred_result > y, "paid", "defaulted"),
                           levels = c("paid", "defaulted")),
                 factor(valid.nn$STATUS, levels = c("paid", "defaulted"))) %>% print()
  # if (!require("beep")) install.packages("beep"); library(beep)
  # beep(2)
}

cm_nn6 <- nn_b2(c(1, 2), 0.5)

```

6.3.9. Four Fold Plots of Confusion Matrix

```
nn_cmp <- function(cm, title) {
  fourfoldplot(cm, color = c("cornflowerblue", "red2"),
    margin = 1, space = 0.3,
    conf.level = 0, main = title)
}
my.par() %>% par(mfrow = c(2, 3),
  mai = par("mai") * 1,
  oma = c(0,0,0,0) + 0.1,
  mar = c(2,4,2,0) + 0.1
)
nn_cmp(cm_nn1$table, "Model M: (1) - cutoff:0.5")
nn_cmp(cm_nn2$table, "Model N: (1,1) - cutoff:0.5")
nn_cmp(cm_nn3$table, "Model O: (2) - cutoff:0.5")
nn_cmp(cm_nn4$table, "Model P: (1) - cutoff:0.5")
nn_cmp(cm_nn5$table, "Model Q: (1,2) - cutoff:0.5")
nn_cmp(cm_nn6$table, "Model R: (1,2) - cutoff:0.5")
```

7. CLEAN ENVIRONMENT

```
rm(list = ls())
cat("\014")
```