



Digital Image Processing (DIP): Introduction

Prof. Pascal Matsakis



DIP: Introduction **I. Origins of DIP**

Prof. Pascal Matsakis




I.1. Newspaper Industry (1920s)




Digital picture produced in 1921

U of G
CIS
4720

Prof. Pascal Matsakis




I.2. Space Program (1960s)



First picture of the moon
by a US spacecraft in 1964

U of G
CIS
4720

Prof. Pascal Matsakis





Prof. Pascal Matsakis

DIP: Introduction

II. Interest in DIP

6

Interest in DIP

II.1. Overview

Applications in many fields:
medicine, geography, physics, astronomy, defense...

Examples:


character recognition, fingerprint recognition,
target recognition, weather prediction, crop
assessment, detection of bone fractures,
detection of brain tumors, study of
high-energy plasmas...



Prof. Pascal Matsakis


II.2a. Imaging in the Electromagnetic Spectrum

$$\lambda v = c, E = hv$$




Prof. Pascal Matsakis

II.2b. Imaging in the Electromagnetic Spectrum



Gamma-Ray

Bone scan
(to localize infections and tumors)



II.2c. Imaging in the Electromagnetic Spectrum



Prof. Pascal Matsakis






Image of a circuit board
(to detect flaws)




Prof. Pascal Matsakis

II.2d. Imaging in the Electromagnetic Spectrum

Ultraviolet



Fluorescence microscope images of corn
(to find if corn is infected by smut)




II.2e. Imaging in the Electromagnetic Spectrum

Visual Spectrum



Image of paper currency
(to track and identify bills)




Prof. Pascal Matsakis

II.2f. Imaging in the Electromagnetic Spectrum

Infrared



Satellite image of North America
(global inventory of human settlements)




Prof. Pascal Matsakis

II.2g. Imaging in the Electromagnetic Spectrum


Radio-Band



MRI image of a human knee
(diagnosis of sport-related injuries)



II.2h. Imaging in the Electromagnetic Spectrum



II.2i. Imaging in the Electromagnetic Spectrum



Prof. Pascal Matsakis

440-490 nm

520-570

630-740

450-515 nm

525-605

630-690

775-900

1550-1750

10400-12500

2090-2350




Interest in DIP

16

II.2j. Imaging in the Electromagnetic Spectrum


Prof. Pascal Matsakis



II.2k. Imaging in the Electromagnetic Spectrum



Prof. Pascal Matsakis



Prof. Pascal Matsakis

II.3a. Other Imaging Modalities




**Ultrasound**


Image of an unborn baby
(to determine the health of their development)

II.3b. Other Imaging Modalities




Synthetic

Computer-generated image of a human skull
(for criminal forensics)





Digital Image Processing (DIP): Fundamentals

Prof. Pascal Matsakis



Prof. Pascal Matsakis



Prof. Pascal Matsakis

4



Main Steps in DIP

I.1c. Overview

5

- DIP characterized by specific solutions.
- Techniques that work well in one area can be totally inadequate in another.
- Actual solution of a specific problem generally still requires significant research and development.


Prof. Pascal Matsakis



Main Steps in DIP

I.2b. Examples

7



Which step?

Prof. Pascal Matsakis



Main Steps in DIP

I.2a. Examples

6



Which step?




Prof. Pascal Matsakis



Main Steps in DIP

I.2c. Examples

8



Which step?

Prof. Pascal Matsakis

I.2d. Examples



Which step?


II. Image Definition and Representation

II.1a. Analog Image



- image
 - function $f_a : \mathbb{R}^2 \rightarrow [0; +\infty[$
 - function $f_a : \mathbb{R}^3 \rightarrow \mathbb{R}$
 - function $f_a : \mathbb{R}^2 \rightarrow \mathbb{R}^3$
 - function $f_a : \mathbb{R}^2 \rightarrow \mathbb{C}$

$f_a : \mathbb{R}^2 \rightarrow [0; +\infty[$ is a typical case;
 $f_a(x,y)$ is the **intensity** of f_a at (x,y) .

II.1b. Analog Image



Consider $f_a : \mathbb{R}^2 \rightarrow [0; +\infty[$



Domain of definition $[0,M] \times [0,N]$ and range $[0,L]$


II.1c. Analog Image



f_a

Zero Padding


II.1e. Analog Image



f_a

Reflected Indexing

II.1d. Analog Image



f_a

Circular Indexing

II.2a. Digital Image

image $\left\{ \begin{array}{l} \text{function} \\ f : \mathbb{Z}^2 \rightarrow 0..+\infty \\ \text{function} \\ f : \mathbb{Z}^3 \rightarrow \mathbb{Z} \\ \text{function} \\ f : \mathbb{Z}^2 \rightarrow \mathbb{Z}^3 \end{array} \right.$

$f : \mathbb{Z}^2 \rightarrow 0..+\infty$ is a typical case: **grayscale image**

$((x,y), f(x,y))$

location gray level pixel
picture element




II.2b. Digital Image

Consider $f : \mathbb{Z}^2 \rightarrow [0..+\infty]$

Assume range included in $0..L-1$:

typically, $L=2^\ell$, i.e., **ℓ -bit grayscale image**

Assume domain of definition is $0..M-1 \times 0..N-1$:




II.2c. Digital Image

Consider $f : \mathbb{Z}^2 \rightarrow [0..+\infty]$

Assume range included in $0..L-1$:

typically, $L=2^\ell$, i.e., **ℓ -bit grayscale image**

Assume domain of definition is $0..M-1 \times 0..N-1$:



II.3a. Digitization

digitization

$f_a : \mathbb{R}^2 \rightarrow [0; +\infty[$

sampling

$\mathbb{Z}^2 \rightarrow [0; +\infty[$

$\mathbb{R}^2 \rightarrow 0..+\infty$

analog

quantization

digital




II.3b. Digitization


Checkerboard effect:




1024




512



256




128







64



32







III.1c. Single-Pixel Operations

Example: $g = af + b \mid \mathbb{Z}^2 \rightarrow \mathbb{R}$
 $(x, y) \mapsto (af + b)(x, y) = af(x, y) + b$



Prof. Pascal Matsakis

**h derived from $g=f+100$**

III.1d. Single-Pixel Operations

Example: $\exists (x, y) \in \mathbb{Z}^2, g(x, y) \notin 0..255$
“Viewable” version, h , of g ?

■ first possibility

$$\forall (x, y) \in \mathbb{Z}^2, h(x, y) = \text{nint}[\min\{255, \max\{0, g(x, y)\}\}]$$

■ second possibility






$$m = \min_{(x, y) \in \mathbb{Z}^2} g(x, y) \text{ and } M = \max_{(x, y) \in \mathbb{Z}^2} g(x, y)$$

$$\forall (x, y) \in \mathbb{Z}^2, h(x, y) = \text{nint}[255(g(x, y) - m) / (M - m)]$$

■




III.2a. Neighborhood Operations



Prof. Pascal Matsakis

III.2b. Neighborhood Operations




$g(x, y)$ depends on the gray levels
from some neighborhood of (x, y) in f .

Prof. Pascal Matsakis



III.2c. Neighborhood Operations


Example: $g(x,y)$ is the average of the gray levels from some neighborhood of (x,y) in f .



Prof. Pascal Matsakis



III.3b. Geometric Spatial Transformations




Prof. Pascal Matsakis


Example: Image scaling



III.3a. Geometric Spatial Transformations



$g(u,v)$ depends on the gray levels from some neighborhood of (x,y) in f .




Nearest neighbour:
 $\bar{f}(x,y)=f(X,Y)$
with $X=?$ and $Y=?$



Example: Image scaling



III.3d. Geometric Spatial Transformations



Bilinear interpolation:

$$\bar{f}(x, y_0) = (1-s).f(x_0, y_0) + s.f(x_0+1, y_0)$$

$$\bar{f}(x, y_0+1) = (1-s).f(x_0, y_0+1) + s.f(x_0+1, y_0+1)$$


$$\bar{f}(x, y) = (1-t).\bar{f}(x, y_0) + t.\bar{f}(x, y_0+1)$$

with $s=?$ and $t=?$


Example: Image scaling



III.5a. Binary Single-Pixel Operations



III.4. Image Transforms



Arithmetic:

$$h = f + g \mid \mathbb{Z}^2 \rightarrow \mathbb{R} \quad (x, y) \mapsto (f + g)(x, y) = f(x, y) + g(x, y)$$

$$h = fg \mid \mathbb{Z}^2 \rightarrow \mathbb{R} \quad (x, y) \mapsto (fg)(x, y) = f(x, y)g(x, y)$$



Image Operations and Transformations

37

III.5c. Binary Single-Pixel Operations



Prof. Pascal Matsakis

$$h = |f - g|$$




g

f

Image Operations and Transformations

III.5e. Binary Single-Pixel Operations

39



Prof. Pascal Matsakis



$$f \vee \neg g$$

g

f



Image Operations and Transformations

38

III.5d. Binary Single-Pixel Operations

Logical:

$$h = f \wedge g \mid \mathbb{Z}^2 \rightarrow \mathbb{R} \\ (x, y) \mapsto (f \wedge g)(x, y) = \min\{f(x, y), g(x, y)\}$$

$$h = f \vee g \mid \mathbb{Z}^2 \rightarrow \mathbb{R} \\ (x, y) \mapsto (f \vee g)(x, y) = \max\{f(x, y), g(x, y)\}$$

Prof. Pascal Matsakis

Image Operations and Transformations


III.6. Image Registration

40



Image Operations and Transformations

III.6. Image Registration



$$f_1 \mid \mathbb{Z}^2 \rightarrow \mathbb{R}$$

input image


$$f_2 \mid \mathbb{Z}^2 \rightarrow \mathbb{R}$$




input image

$$T_s?$$

Prof. Pascal Matsakis

III.7. Colour/Multispectral Transformations





Gray-Level Mappings

I.2a. Linear Mappings

$$m(u) = au + b$$

- b** is the **bias** → impact on **brightness**
 - consider $m(u) = u + b$
 - consider cases $b < 0$ and $b > 0$
- a** is the **gain** → impact on **contrast**
 - consider $m(u) = au$
 - consider cases $a < 1$ and $a > 1$

$$m(u) = 2u$$

f				g			
0	3	1	1	0	6	2	2
1	2	3	0	2	4	6	0
1	3	2	2	2	6	4	4
0	2	0	3	0	4	0	6


$L=8$

5

Prof. Pascal Matsakis

Gray-Level Mappings

I.2b. Linear Mappings




6



—— example 1 ——
 a? b?

Gray-Level Mappings

I.2c. Linear Mappings



7


Prof. Pascal Matsakis

—— example 2 ——
 a? b?

$$(a = -1, b = L - 1)$$

Gray-Level Mappings





I.2d. Linear Mappings







8



—— example 3 ——
 a? b?





U of G
CIS 4720
CIS 4720
U of G
CIS 4720
Prof. Pascal Matsakis

Single-Pixel Operations

II. Image Histograms

Image Histograms

II.1. What Are They?

H_f histogram
 H_{f^n} **normalized** histogram
 H_f^c **cumulative** histogram
 H_f^{cn} **cumulative normalized** histogram

18

U of G
CIS 4720
CIS 4720
U of G
CIS 4720
Prof. Pascal Matsakis

Image Histograms

II.2a. Examples

19

Dark Image

U of G
CIS 4720
CIS 4720
U of G
CIS 4720
Prof. Pascal Matsakis



Image Histograms

II.2b. Examples


20

Bright Image

U of G
CIS 4720
CIS 4720
U of G
CIS 4720
Prof. Pascal Matsakis



- Image Histograms**
- II.3. What Are They for?**
- 23
- They provide a global description of the appearance of an image (brightness and contrast)
 - They give us useful information for image enhancement (brightness and contrast adjustment)
- Prof. Pascal Matsakis
- U of G CIS 4720









Image Histograms

II.4f. Histogram Equalization

29



GLOBAL EDITION










*after
equalization*



— example —

- In practice:
- H^{cn} looks linear but H^n does not look flat
 - the improvement is optimal statistically, not necessarily perceptually.

Prof. Pascal Matsakis







Convolution
I.3c. Definition (2nd Attempt)

Consider an $m \times n$ kernel h and an image f . Consider the image g defined by:


$$g(x, y) = \sum_{i=-\frac{m-1}{2}}^{\frac{m-1}{2}} \sum_{j=-\frac{n-1}{2}}^{\frac{n-1}{2}} h(i, j) f(x-i, y-j)$$

\downarrow

$(h * f)(x, y)$

$h * f$ is the **convolution** of h with f

Prof. Pascal Matsakis



Convolution
I.4b. Examples

13

1	1	1
1	1	1
1	1	1




Prof. Pascal Matsakis

Convolution
I.4c. Examples

14


2	0	0
0	-1	0
0	0	-1



Prof. Pascal Matsakis

Convolution
I.5a. Handling of the Borders

15



Prof. Pascal Matsakis

Convolution
I.5b. Handling of the Borders

16


Truncation of the kernel?



Prof. Pascal Matsakis

Convolution

I.5c. Handling of the Borders




17

Prof. Pascal Matsakis

Convolution

I.5d. Handling of the Borders




18

Prof. Pascal Matsakis

Convolution

I.5e. Handling of the Borders



19

Prof. Pascal Matsakis

Convolution

I.6a. Separable Kernels

Consider an mxn kernel h .

h is **separable** iff

there exist an $mx1$ kernel h_1 and a $1xn$ kernel h_2
such that $h = h_1 * h_2$

h is **separable** iff

there exist an $mx1$ kernel h_1 and a $1xn$ kernel h_2
such that $h = h_1 h_2$

Convolution

I.6b. Separable Kernels

21

$$\begin{pmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{pmatrix} \begin{matrix} [1 & 1 & 1] \\ x \\ [1 & 1 & 1] \end{matrix}$$
$$\begin{pmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{pmatrix} \begin{matrix} [-1 & 0 & 1] \\ x \\ [-2 & -1 & 0] \end{matrix}$$
$$\begin{pmatrix} -1 & -1 & -1 \\ -1 & 8 & -1 \\ -1 & -1 & -1 \end{pmatrix} \text{no}$$

Are these kernels separable?



Prof. Pascal Matsakis

Convolution

I.6c. Separable Kernels

22

Consider a separable $m \times n$ kernel $h = h_1 * h_2$
We have: $(h_1 * h_2) * f = h_1 * (h_2 * f)$

mn multiplications
 $mn-1$ additions

convolution at
a single pixel

$m+n$ multiplications
 $m+n-2$ additions



Prof. Pascal Matsakis

Neighborhood Operations

II. Filtering



Prof. Pascal Matsakis

Filtering


II.1a. Principle

24




Prof. Pascal Matsakis







25







26



27



28



Filtering

II.3a. Linear High-Pass Filtering

Convolution kernel with mixture of positive and negative coefficients

Example:

Laplacian filtering (omnidirectional)

0	-1	0	-1	-1	-1
-1	4	-1	-1	8	-1
0	-1	0	-1	-1	-1

3x3 Laplacian masks

33

Prof. Pascal Matsakis

Filtering

II.3b. Linear High-Pass Filtering


Convolution kernel with mixture of positive and negative coefficients

Example:

Laplacian filtering (omnidirectional)




input



output

34



Filtering

II.3c. Linear High-Pass Filtering

Example: unsharp masking

Subtracting from image output from low pass filter

Example: high-boost filtering

Adding to image output from high pass filter

35

Prof. Pascal Matsakis

0	-1	0	-1	-1	-1
-1	$A + 4$	-1	-1	$A + 8$	-1
0	-1	0	-1	-1	-1

Filtering

II.3d. Linear High-Pass Filtering


Example: unsharp masking

Subtracting from image output from low pass filter

Example: high-boost filtering

Adding to image output from high pass filter

36




input



output ($A=1$)

Filtering

II.4a. Order Statistic (Non-Linear) Filtering




37

Filtering

II.4b. Order Statistic (Non-Linear) Filtering

X-ray image of a circuit board corrupted by salt noise



3x3 min filtering


Prof. Pascal Matsakis

38

Filtering

II.4c. Order Statistic (Non-Linear) Filtering

X-ray image of a circuit board corrupted by pepper noise



3x3 max filtering


Prof. Pascal Matsakis

39

Filtering

II.4d. Order Statistic (Non-Linear) Filtering

X-ray image of a circuit board corrupted by salt-and-pepper noise



3x3 median filtering

Prof. Pascal Matsakis


40



Filtering

II.5a. α -Trimmed Mean (Non-Linear) Filtering

41



1.

24	221	124
167	96	17
80	182	159

2. $(17, 24, 80, 96, 124, 159, 167, 182, 221)$ 3. $(\cancel{17}, \cancel{24}, 80, 96, 124, 159, 167, \cancel{182}, \cancel{221})$
 α values $g(p) = \text{average}$ α values


Prof. Pascal Matsakis

Filtering


II.5b. α -Trimmed Mean (Non-Linear) Filtering

42

X-ray image of a circuit board corrupted by uniform noise and salt-and-pepper noise



5x5 α -trimmed mean filtering




Prof. Pascal Matsakis



Filtering

II.6a. Adaptive (Non-Linear) Filtering

43



1.

24	221	124
167	96	17
80	182	159

noise variance: V_n 2. mean gray level: $m(p)$
variance: $V(p)$ 3. $g(p) = f(p) - [f(p)-m(p)] V_n / V(p)$


Prof. Pascal Matsakis

Filtering

II.6b. Adaptive (Non-Linear) Filtering

44





X-ray image of a circuit board corrupted by Gaussian noise



7x7 adaptive filtering



Prof. Pascal Matsakis






Image Gradient

I.2a. Definitions

6

f_a

(x_0, y_0)

$v = f_a(x_0, \cdot)$

$v' = \frac{df_a(x_0, \cdot)}{dy}$

$u = f_a(\cdot, y_0)$

$u' = \frac{df_a(\cdot, y_0)}{dx}$

$v'(y_0) = \frac{\partial f_a}{\partial y}(x_0, y_0)$

$u'(x_0) = \frac{\partial f_a}{\partial x}(x_0, y_0)$

Prof. Pascal Matsakis

Image Gradient

I.2b. Definitions

7

$\vec{\nabla} f_a = \left(\frac{\partial f_a}{\partial x}, \frac{\partial f_a}{\partial y} \right)$ **gradient vector**

$G = \sqrt{\left(\frac{\partial f_a}{\partial x} \right)^2 + \left(\frac{\partial f_a}{\partial y} \right)^2}$ **gradient magnitude**
edge corresponds to local maximum

$G = \left| \frac{\partial f_a}{\partial x} \right| + \left| \frac{\partial f_a}{\partial y} \right|$

$\theta = \arctan \left(\frac{\partial f_a}{\partial y} / \frac{\partial f_a}{\partial x} \right)$ **gradient direction**
edge runs in perpendicular direction

Prof. Pascal Matsakis

Image Gradient

I.3a. Estimation

8

$u'(x_0) = \lim_{h \rightarrow 0} \frac{u(x_0 + h) - u(x_0)}{h}$

$v'(y_0) = \lim_{h \rightarrow 0} \frac{u(x_0 + h) - u(x_0 - h)}{2h}$

For $h \approx 0$: $u'(x_0) \approx \frac{u(x_0 + h) - u(x_0 - h)}{2h}$

$\frac{\partial f_a}{\partial x}(x_0, y_0) \approx \frac{f_a(x_0 + h, y_0) - f_a(x_0 - h, y_0)}{2h}$

Choose $h = 1$, assume $x_0 \in \mathbb{Z}$ and $y_0 \in \mathbb{Z}$:

$\frac{\partial f_a}{\partial x}(x_0, y_0) \approx \frac{f(x_0 + 1, y_0) - f(x_0 - 1, y_0)}{2}$

Prof. Pascal Matsakis

Image Gradient

I.3b. Estimation

$$\frac{\partial f_a}{\partial x}(x_0, y_0) \approx \frac{f(x_0+1, y_0) - f(x_0-1, y_0)}{2}$$

$$\frac{\partial f_a}{\partial x} \approx \begin{bmatrix} 1/2 \\ 0 \\ -1/2 \end{bmatrix} * f$$

$$\frac{\partial f_a}{\partial y}(x_0, y_0) \approx \frac{f(x_0, y_0+1) - f(x_0, y_0-1)}{2}$$

$$\frac{\partial f_a}{\partial y} \approx \begin{bmatrix} 1/2 & 0 & -1/2 \end{bmatrix} * f$$

Prof. Pascal Matsakis

Image Gradient

I.4a. Prewitt Kernels

Noise reduction: $[1 \ 1 \ 1] * f \dots \begin{bmatrix} 1 \\ 1 \\ 1 \end{bmatrix} * f$

Edge enhancement: $\begin{bmatrix} -1 \\ 0 \\ 1 \end{bmatrix} * ([1 \ 1 \ 1] * f) \dots [-1 \ 0 \ 1] * (\begin{bmatrix} 1 \\ 1 \\ 1 \end{bmatrix} * f)$

Edge localization: $\frac{\partial f_a}{\partial x} \approx \begin{bmatrix} -1 & -1 & -1 \\ 0 & 0 & 0 \\ 1 & 1 & 1 \end{bmatrix} * f \dots \frac{\partial f_a}{\partial y} \approx \begin{bmatrix} -1 & 0 & 1 \\ -1 & 0 & 1 \\ -1 & 0 & 1 \end{bmatrix} * f$

Binary edge map: gray level of p is 255 iff $G(p) > \tau$ (where $G(p)$ is the gradient magnitude at p)

Prof. Pascal Matsakis

Image Gradient

I.4b. Prewitt Kernels

-1	-1	-1	-1	0	1	-1	-1	0	0	1	1
0	0	0	-1	0	1	-1	0	1	-1	0	1
1	1	1	-1	0	1	0	1	1	-1	-1	0

Prof. Pascal Matsakis

Image Gradient

I.5a. Sobel Kernels

Noise reduction: $[1 \ 2 \ 1] * f \dots \begin{bmatrix} 1 \\ 2 \\ 1 \end{bmatrix} * f$

Edge enhancement: $\begin{bmatrix} -1 \\ 0 \\ 1 \end{bmatrix} * ([1 \ 2 \ 1] * f) \dots [-1 \ 0 \ 1] * (\begin{bmatrix} 1 \\ 2 \\ 1 \end{bmatrix} * f)$

Edge localization: $\frac{\partial f_a}{\partial x} \approx \begin{bmatrix} -1 & -2 & -1 \\ 0 & 0 & 0 \\ 1 & 2 & 1 \end{bmatrix} * f \dots \frac{\partial f_a}{\partial y} \approx \begin{bmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{bmatrix} * f$

Binary edge map: gray level of p is 255 iff $g(p) > \tau$ (where $g(p)$ is the gradient magnitude at p)

Prof. Pascal Matsakis

Image Gradient

I.5b. Sobel Kernels

13

-1	-2	-1	-1	0	1	-2	-1	0	0	1	2
0	0	0	-2	0	2	-1	0	1	-1	0	1
1	2	1	-1	0	1	0	1	2	-2	-1	0

Prof. Pascal Matsakis

Image Gradient

I.5c. Sobel Kernels

14

horizontal and vertical edges

Prof. Pascal Matsakis

Image Gradient

I.5d. Sobel Kernels

15

gradient image

diagonal edges

Prof. Pascal Matsakis

Image Gradient

I.5e. Sobel Kernels

16

gradient image

aortic angiogram (X-ray image)

Prof. Pascal Matsakis

Edge Detection


II. Image Laplacian

Prof. Pascal Matsakis

19

Image Laplacian


II.1. Principle



Prof. Pascal Matsakis

Image Laplacian

II.2. Definition



$$u = f_a(\cdot, y_0)$$

$$u'' = \frac{d^2 f_a(\cdot, y_0)}{dx^2}$$

$$u''(x_0) = \frac{\partial^2 f_a}{\partial x^2}(x_0, y_0)$$

$$v = f_a(x_0, \cdot)$$

$$v'' = \frac{d^2 f_a(x_0, \cdot)}{dy^2}$$

$$v''(y_0) = \frac{\partial^2 f_a}{\partial y^2}(x_0, y_0)$$

$$\nabla^2 f_a = \frac{\partial^2 f_a}{\partial x^2} + \frac{\partial^2 f_a}{\partial y^2}$$

Laplacian

Prof. Pascal Matsakis

19

Image Laplacian

II.3a. Estimation

$$\text{For } h \approx 0: u''(x_0) \approx \frac{u'(x_0 + h) - u'(x_0 - h)}{2h}$$

$$\text{For } k \approx 0: u'(x_0 + h) \approx \frac{u((x_0 + h) + k) - u((x_0 + h) - k)}{2k}$$

$$\text{For } l \approx 0: u'(x_0 - h) \approx \frac{u((x_0 - h) + l) - u((x_0 - h) - l)}{2l}$$

Choose $h = k = l$:

$$\frac{\partial^2 f_a}{\partial x^2}(x_0, y_0) \approx \frac{f_a(x_0 + 2h, y_0) - 2f_a(x_0, y_0) + f_a(x_0 - 2h, y_0)}{4h^2}$$

Choose $h = 1/2$, assume $x_0 \in \mathbb{Z}$ and $y_0 \in \mathbb{Z}$:

$$\frac{\partial^2 f_a}{\partial x^2}(x_0, y_0) \approx f(x_0 + 1, y_0) - 2f(x_0, y_0) + f(x_0 - 1, y_0)$$

Prof. Pascal Matsakis

20

Image Laplacian

II.3b. Estimation

$$\frac{\partial^2 f_a}{\partial x^2}(x_0, y_0) \approx f(x_0+1, y_0) - 2f(x_0, y_0) + f(x_0-1, y_0)$$

$$\frac{\partial^2 f_a}{\partial x^2} \approx \begin{bmatrix} 1 \\ -2 \\ 1 \end{bmatrix} * f$$

$$\frac{\partial^2 f_a}{\partial y^2}(x_0, y_0) \approx f(x_0, y_0+1) - 2f(x_0, y_0) + f(x_0, y_0-1)$$

$$\frac{\partial^2 f_a}{\partial y^2} \approx \begin{bmatrix} 1 & -2 & 1 \end{bmatrix} * f$$

Prof. Pascal Matsakis

Image Laplacian

II.4a. Laplacian Kernels

$$\nabla^2 f \approx \begin{bmatrix} 1 \\ -2 \\ 1 \end{bmatrix} * f + \begin{bmatrix} 1 & -2 & 1 \end{bmatrix} * f = \begin{bmatrix} 0 & 1 & 0 \\ 1 & -4 & 1 \\ 0 & 1 & 0 \end{bmatrix} * f$$

$$\nabla^2 f \approx \begin{bmatrix} 1 & 0 & 1 \\ 0 & -4 & 0 \\ 1 & 0 & 1 \end{bmatrix} * f$$

$$\nabla^2 f \approx \begin{bmatrix} 1 & 1 & 1 \\ 1 & -8 & 1 \\ 1 & 1 & 1 \end{bmatrix} * f$$

Prof. Pascal Matsakis

Image Laplacian

II.4b. Laplacian Kernels

Noise reduction:
none

Edge enhancement:
 $K_L * f$ where K_L is a Laplacian kernel

Edge localization:

FOR each pixel p **DO**

FOR each 8-neighbour q of p **DO** threshold so we take meaningful edges

IF $L(q)L(q') < 0$ and $|L(q)-L(q')| > \tau$

% where $L(q)$ is the Laplacian at q and
% q' is the neighbour of p opposite to q

THEN mark p as an edge

% set its gray level to 255 in the edge map

Prof. Pascal Matsakis

Image Laplacian

II.5a. Laplacian of Gaussian





Noise reduction: $K_G * f$
where K_G is a Gaussian kernel




Edge enhancement: $K_L * (K_G * f) = (K_L * K_G) * f$
where K_L is a Laplacian kernel


0	0	-1	0	0
0	-1	-2	-1	0
-1	-2	16	-2	-1
0	-1	-2	-1	0
0	0	-1	0	0

Edge localization: replace L with LoG

Prof. Pascal Matsakis







Thresholding



I.2b. Choosing the Threshold

6

Prof. Pascal Matsakis

basic global thresholding

$u_{\text{new}} \leftarrow \text{average } f(x,y)$
do
 $u_{\text{old}} \leftarrow u_{\text{new}}$
 $u_{\text{inf}} \leftarrow \text{average } f(x,y) \text{ with } f(x,y) \leq u_{\text{old}}$
 $u_{\text{max}} \leftarrow \text{average } f(x,y) \text{ with } f(x,y) > u_{\text{old}}$
 $u_{\text{new}} \leftarrow 0.5(u_{\text{inf}}+u_{\text{max}})$
until $|u_{\text{new}} - u_{\text{old}}| \leq \delta$



Connected Components

II.2. Paths

8-path in S , of length 7, from p to q

Π is a **path** in S iff?

Prof. Pascal Motsakis

Connected Components

II.3a. Connectivity

p is 8-connected to q in S
 p is not 4-connected to q in S

p is **connected** to q in S iff?
 S is **connected** iff?

Prof. Pascal Motsakis

Connected Components

II.3b. Connectivity

Binary relation on S defined by
“ p is related to q iff p is connected to q in S ”
is an **equivalence relation**.

The **equivalence classes** are
the **connected components** of S .

They define a **partition** of S .

Prof. Pascal Motsakis

Thresholding and Labeling

III. Labeling


Prof. Pascal Motsakis

Labeling

III.1. Build a Binary Relation

How to find the set of 8-connected components?

STEP 1



Relation \mathcal{R}

13


Prof. Pascal Matsakis

Labeling

III.1. Build a Binary Relation

How to find the set of 8-connected components?

STEP 1



scan

Relation \mathcal{R}

1	2
1	0
2	1


14

Labeling

III.1. Build a Binary Relation

How to find the set of 8-connected components?

STEP 1



Relation \mathcal{R}

15

Prof. Pascal Matsakis


Prof. Pascal Matsakis

Labeling

III.1. Build a Binary Relation

How to find the set of 8-connected components?

STEP 1



scan

Relation \mathcal{R}

1	2	3	4	5
1	1	1	0	0
2	1	1	0	0
3	0	0	1	0
4	0	0	0	1
5	0	0	0	1

16

Labeling

III.1. Build a Binary Relation

How to find the set of 8-connected components?

STEP 1

scan →

1	1	2					
1	1	2		3	3		
1	1	2		3	3	3	
1	1	2	3			3	
1	2		3	4		3	
	2		4	5	3		

Relation \mathcal{R}

1	2	3	4	5
1	1	0	0	0
2	1	0	0	0
3	0	0	1	0
4	0	0	0	1
5	0	0	1	0

Prof. Pascal Matsakis

17

Labeling

III.1. Build a Binary Relation

How to find the set of 8-connected components?

STEP 1

1	1	2					
1	1	2		3	3		
1	1	2		3	3	3	
1	1	2	3			3	
1	2		3	4		3	
2			4	5	3		
	2		4	5	3		
		2	4	4			

Relation \mathcal{R}

1	2	3	4	5
1	1	0	0	0
2	1	0	1	0
3	0	0	1	0
4	0	1	0	1
5	0	0	1	0

→ scan

Prof. Pascal Matsakis

18

Labeling

III.2. Calculate Its Transitive Closure

How to find the set of 8-connected components?

STEP 2 (Warshall Algorithm)

Prof. Pascal Matsakis

Relation \mathcal{R}

1	2	3	4	5
1	1	0	0	0
2	1	0	1	0
3	0	0	1	0
4	0	1	0	1
5	0	0	1	0

19

Labeling

III.2. Calculate Its Transitive Closure

How to find the set of 8-connected components?

STEP 2 (Warshall Algorithm)

Prof. Pascal Matsakis

Transitive closure
 \mathcal{R}^+ of \mathcal{R}

1	2	3	4	5
1	1	0	1	0
2	1	0	1	0
3	0	0	1	0
4	1	0	1	0
5	0	0	1	0

Labeling

III.2. Calculate Its Transitive Closure

How to find the set of 8-connected components?

STEP 2 (Warshall Algorithm)

$$\mathcal{R}^+ = \mathcal{R}$$

% \mathcal{R}^+ is now [r_{ij}]

for $k=1$ to n

 for $i=1$ to n

 for $j=1$ to n

$$r_{ij} = \max\{r_{ij}, \min\{r_{ik}, r_{kj}\}\}$$

% if r_{ik} and r_{kj} then $r_{ij}=1$

% else keep r_{ij} as is

21

Prof. Pascal Matsakis

Labeling

III.3. Calculate the Equivalence Classes

How to find the set of 8-connected components?

STEP 3

Transitive closure
 \mathcal{R}^+ of \mathcal{R}

1	2	3	4	5
1	1	0	1	0
2	1	1	0	1
3	0	0	1	0
4	1	1	0	1
5	0	0	1	0

Prof. Pascal Matsakis

Labeling

III.3. Calculate the Equivalence Classes

How to find the set of 8-connected components?

STEP 3

Transitive closure
 \mathcal{R}^+ of \mathcal{R}

equivalence
classes

1	1	2				
1	1	2		3	3	
1	1	2		3	3	3
1	1	2	3			3
	1	2	3	4		3
		2		4	5	3
		2	2	4		
		2	4	4		

23

Prof. Pascal Matsakis

Labeling

III.4. Label the Connected Components

How to find the set of 8-connected components?

STEP 4

scan

1	1	2				
1	1	2		3	3	
1	1	2		3	3	3
1	1	2	3			3
	1	2	3	4		3
		2		4	5	3
		2	2	4		
		2	4	4		

Equivalence
classes of \mathcal{R}^+

✓	1	2	3	4	5
✓	1	1	0	1	0
✓	3	0	0	1	0
✓	4	1	1	0	1
✓	5	0	0	1	0

III.4. Label the Connected Components

How to find the set of 8-connected components?




STEP 4

1	1		1						
1	1		1			3	3		
1	1		1		3	3	3	3	
1	1		1	3				3	
	1	1		3		1			3
			1			1	3	3	
			1	1	1				
			1	1	1				

Equivalence
classes of \mathbb{N}^+

✓	1	1	1	0	1	0
2	1	1	0	1	0	
✓	3	0	0	1	0	1
4	1	1	0	1	0	
5	0	0	1	0	1	

scan



Representation of Image Regions

I.1b. Boundary Following

Initialization:
 b_0 = uppermost leftmost point
 n_0 = its west neighbour

Prof. Pascal Matsakis

Representation of Image Regions

I.1c. Boundary Following

Starting at n_i and in a clockwise direction:
 b_{i+1} = first neighbour of b_i that belongs to boundary
 n_{i+1} = neighbour encountered just before b_{i+1}

Prof. Pascal Matsakis

Representation of Image Regions

I.1d. Boundary Following





Termination: $b_k = b_0$ and $b_{k+1} = b_1$
Result: $(b_0, b_1, b_2, \dots, b_{k-1})$





Prof. Pascal Matsakis

Representation of Image Regions

I.2a. Chain Codes

Prof. Pascal Matsakis





Towards Object Recognition


II. Boundary and Regional Descriptors

Prof. Pascal Matsakis

19

Boundary and Regional Descriptors


II.1a. Geometrical Descriptors



$$\text{circularity ratio} = 4\pi \cdot \text{area} / \text{perimeter}^2$$

Boundary and Regional Descriptors

II.1b. Geometrical Descriptors




Prof. Pascal Matsakis

19

Boundary and Regional Descriptors

II.1c. Geometrical Descriptors






Prof. Pascal Matsakis

20

Boundary and Regional Descriptors

21

II.2a. Shape Numbers



3 shapes of order 8

(a) (b) (c)

chain code 00332211 03032211 00032221

difference 30303030 33133030 30033003

shape number ... 03030303 03033133 00330033

Prof. Pascal Matsakis


U of G

CIS 4720

Boundary and Regional Descriptors

22

II.2b. Shape Numbers




shape number
of order 18
?

Prof. Pascal Matsakis

Boundary and Regional Descriptors

23

II.2c. Shape Numbers



shape number
of order 18
?

3x6 rectangle is rectangle of order 18
whose eccentricity best matches
eccentricity of basic rectangle

3x6 grid!

Prof. Pascal Matsakis

U of G

CIS 4720


U of G

CIS 4720

Boundary and Regional Descriptors

24

II.2d. Shape Numbers



0
1
2
3

Prof. Pascal Matsakis





U of G

CIS 4720

U of G

CIS 4720

chain code 000300322322221101
difference 300310330130003031
shape number 000303130031033013



Boundary and Regional Descriptors

II.5c. Texture

29

Prof. Pascal Matsakis

Boundary and Regional Descriptors

II.5d. Texture

Descriptors:

0.00006
0.00002
15.75
0.01500
0.01230
6.43
0.06860
0.00480
13.58

30

Prof. Pascal Matsakis

Towards Object Recognition

III. Classification and Clustering

Prof. Pascal Matsakis

Classification and Clustering

III.1a. Terminology

Bezdek
“**Pattern recognition** is a search for structure in data.”

Fukunaga
“**Pattern recognition** consists of two parts: feature selection and classifier design.”

Devijer and Kittler
“**Pattern recognition** is a very broad field of activities with very fuzzy borders.”

32

Prof. Pascal Matsakis

Classification and Clustering

III.1b. Terminology

Prof. Pascal Matsakis

patterns objects	features descriptors attributes characteristics	classes clusters
    	gray level area texture weight density wavelength petal width	crop silky anger B star target male voice iris Virginica

33

Classification and Clustering

III.1c. Terminology

Prof. Pascal Matsakis

classification
examine the features of an object and assign this object to one of a predefined set of classes



clustering
compare the features of various objects and assign these objects to different clusters




34

Classification and Clustering

III.2a. Principle

Prof. Pascal Matsakis




35

Classification and Clustering

III.2b. Principle

Prof. Pascal Matsakis



36

feature vector
(belongs to the *feature space*)

label vector
(can be *crisp*, *probabilistic*, *possibilistic*...)

