

Security Incident Report

Generated: 2026-08-09 18:24:26

Generated by AutoForensicAgent · Anomaly Detection & Digital Forensics Pipeline

UTC

Detected: 2026-08-09T18:19:06.362000

MEDIUM SEVERITY — Network Service Discovery (T1046)

Anomaly Score: 0.595

EXECUTIVE SUMMARY

Device **IOT-SENSOR-031** (Temp Sensor, Xiaomi) at **192.168.1.63** was flagged for behavior consistent with **Network Service Discovery** (MITRE ATT&CK T1046, tactic: Discovery). The anomaly detection engine assigned a confidence score of **0.595**, and traffic evidence was automatically captured for forensic review under chain-of-custody ID **COC-ALERT-20260809-95DB11**.

DEVICE INFORMATION

DEVICE ID	IOT-SENSOR-031
DEVICE TYPE	Temp Sensor
VENDOR / FINGERPRINT	Xiaomi
IP ADDRESS	192.168.1.63
MAC ADDRESS	78:11:DC:09:E3:5A
FIRST SEEN ON NETWORK	2026-06-01T09:45:00Z

DETECTION FEATURES

PACKET RATE	17.0
BYTE RATE	856.7
UNIQUE DST IPS	1
UNIQUE DST PORTS	170
PORT ENTROPY	7.40939093613767
SYN RATIO	1.0
UDP RATIO	0.0
AVG PACKET SIZE	50.39411764705882
FAILED AUTH COUNT	0
NEW DST RATIO	1.0

INCIDENT TIMELINE

- 2026-08-09T18:21:58.885587+00:00
First packet observed from IOT-SENSOR-031
- 2026-08-09T18:21:58.759111+00:00
Traffic window closed (170 packets analyzed)
- 2026-08-09T18:19:06.362885+00:00
Anomaly detector flagged window as 'port_scan'

MITRE ATT&CK MAPPING

T1046 – Network Service Discovery

Discovery

TACTIC: Discovery

Adversaries may attempt to get a listing of services running on remote hosts, including those that may be vulnerable to remote exploitation, as a precursor to further attack.

Recommended Actions

- Segment IoT devices onto isolated VLANs
- Deploy firewall rules restricting unnecessary inbound scanning
- Enable intrusion detection on gateway/router

EVIDENCE & CHAIN OF CUSTODY

PCAP FILE: evidence/ALERT-20260809-95DB11_capture.pcap
SHA-256: 91f3a6209b50ab8bffc2c3f58944a6ff2f61e02bcc7b5a5fe3936dc53fefe703
CHAIN OF CUSTODY ID: COC-ALERT-20260809-95DB11
CAPTURED BY: NetGuard AutoForensicAgent v1.0

This report was generated automatically by the IoT Anomaly Detection & Digital Forensics module. It is intended to support, not replace, human security analyst review. Evidence integrity should be verified by re-computing the SHA-256 hash of the referenced pcap file before use in any formal investigation.

REPORT INTEGRITY HASH (SHA-256): c0657215133d02eadc86e36c3e3dd37b5abf3afbe29b41cfc9ef1d51823b398e