Управление пользователями и группами

Эйвази Мани

13 марта 2026

Contents

Цели и задачи работы **2**
Цель лабораторной работы . . . 2

Процесс выполнения лабораторной работы **3**
Определение текущего пользователя . . . 3
Переключение на root . . . 4
Файл /etc/sudoers . . . 5
Создание пользователя alice . . . 6
Создание пользователя bob . . . 7
Настройка параметров useradd . . . 8
Каталог /etc/skel . . . 9
Создание пользователя carol . . . 10
Домашний каталог carol . . . 11
Файл /etc/shadow . . . 12
Создание групп . . . 13

Выводы по проделанной работе **14**
Вывод 14

Цели и задачи работы

Цель лабораторной работы

Получение практических навыков управления учётными записями пользователей и групп в операционной системе Linux.

Процесс выполнения лабораторной работы

Определение текущего пользователя

-

```
manieyvazi@localhost:~$ whoami
manieyvazi
manieyvazi@localhost:~$ id
uid=1000(manieyvazi) gid=1000(manieyvazi) groups=1000(manieyvazi),10(wheel) context=unconfined_u:un
confined_r:unconfined_t:s0-s0:c0.c1023
manieyvazi@localhost:~$ su
Password:
root@localhost:/home/manieyvazi# whoami
root
root@localhost:/home/manieyvazi# id
uid=0(root) gid=0(root) groups=0(root) context=unconfined_u:unconfined_r:unconfined_t:s0-s0:c0.c102
3
```

Рис. 1 — Команды whoami и id

Переключение на root

-

```
manieyvazi@localhost:~$ whoami
manieyvazi
manieyvazi@localhost:~$ id
uid=1000(manieyvazi) gid=1000(manieyvazi) groups=1000(manieyvazi),10(wheel) context=unconfined_u:un
confined_r:unconfined_t:s0-s0:c0.c1023
manieyvazi@localhost:~$ su
Password:
root@localhost:/home/manieyvazi# whoami
root
root@localhost:/home/manieyvazi# id
uid=0(root) gid=0(root) groups=0(root) context=unconfined_u:unconfined_r:unconfined_t:s0-s0:c0.c102
3
```

Рис. 1 — Переход к пользователю root

Файл /etc/sudoers

•

```
## Allow root to run any commands anywhere
root    ALL=(ALL)       ALL

## Allows members of the 'sys' group to run networking, software,
## service management apps and more.
# %sys ALL = NETWORKING, SOFTWARE, SERVICES, STORAGE, DELEGATING, PROCESSES, LOCATE, DRIVERS

## Allows people in group wheel to run all commands
%wheel  ALL=(ALL)       ALL

## Same thing without a password
# %wheel        ALL=(ALL)       NOPASSWD: ALL
```

Рис. 2 — Открытие /etc/sudoers через visudo

Создание пользователя alice

-.

```
manieyvazi@localhost:~$ sudo -i useradd -G wheel alice
manieyvazi@localhost:~$ sudo -i passswd alice
bash: passswd: command not found
manieyvazi@localhost:~$ sudo -i passwd alice
New password:
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
passwd: password updated successfully
manieyvazi@localhost:~$ id alice
uid=1001(alice) gid=100(users) groups=100(users),10(wheel)
manieyvazi@localhost:~$ su alice
Password:
```

Рис. 3 — Создание пользователя alice

Создание пользователя bob

-.

```
manieyvazi@localhost:~$ sudo -i useradd -G wheel alice
manieyvazi@localhost:~$ sudo -i passswd alice
bash: passswd: command not found
manieyvazi@localhost:~$ sudo -i passwd alice
New password:
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
passwd: password updated successfully
manieyvazi@localhost:~$ id alice
uid=1001(alice) gid=100(users) groups=100(users),10(wheel)
manieyvazi@localhost:~$ su alice
Password:
```

Рис. 3 — Создание пользователя bob

Настройка параметров useradd

-.

```
daemon:x:2:
sys:x:3:
adm:x:4:
tty:x:5:
disk:x:6:
lp:x:7:
mem:x:8:
kmem:x:9:
wheel:x:10:manieyvazi,alice
cdrom:x:11:
mail:x:12:
man:x:15:
dialout:x:18:
floppy:x:19:
```

Рис. 4 — Файл /etc/login.defs

Каталог /etc/skel

-.

```
alice@localhost:/home/manieyvazi$ sudo useradd bob
[sudo] password for alice:
alice@localhost:/home/manieyvazi$ sudo passwd bob
New password:
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
passwd: password updated successfully
alice@localhost:/home/manieyvazi$ id bob
uid=1002(bob) gid=100(users) groups=100(users)
alice@localhost:/home/manieyvazi$ su bob
Password:
```

Рис. 5 — Каталог /etc/skel

Создание пользователя carol

-.

```
#
# Enables userdel(8) to remove user groups if no members exist.
#
USERGROUPS_ENAB no

#
# If set to a non-zero number, the shadow utilities will make sure that
# groups never have more than this number of users on one line.
# This permits to support split groups (groups split into multiple lines,
# with the same group ID, to avoid limitation of the line length in the
# group file).
#
# 0 is the default value and disables this feature.
#
#MAX_MEMBERS_PER_GROUP  0

#
# If useradd(8) should create home directories for users by default (non
# system users only).
# This option is overridden with the -M or -m flags on the useradd(8)
# command-line.
#
CREATE_HOME     yes
```

Рис. 6 — Создание пользователя carol

Домашний каталог carol

Проверка работы системы.

```
root@localhost:/home/manieyvazi# cd /etc/skel
root@localhost:/etc/skel# ls
root@localhost:/etc/skel# ls -a
.  ..  .bash_logout  .bash_profile  .bashrc  .mozilla
root@localhost:/etc/skel# mkdir Documents
root@localhost:/etc/skel# mkdir Pictures
root@localhost:/etc/skel#
root@localhost:/etc/skel# ls
Documents  Pictures
```

Рис. 7 — Домашний каталог carol

Файл /etc/shadow

-

```
root@localhost:/etc/skel# su alice
alice@localhost:/etc/skel$ ls
Documents  Pictures
alice@localhost:/etc/skel$ sudo -i useradd carol
[sudo] password for alice:
alice@localhost:/etc/skel$ sudo passwd carol
New password:
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
passwd: password updated successfully
alice@localhost:/etc/skel$ su carol
```

Рис. 8 — Запись carol в /etc/shadow

Создание групп

-

```
alice@localhost:/home/carol$ sudo passwd -n 30 -w 3 -x 90 carol
passwd: password changed.
alice@localhost:/home/carol$ sudo cat /etc/shadow |grep carol
carol:$y$j9T$vA9qbKPpieXF25byYRkSX.$HbzcwØKpSTIrTm5ZcspBGuSARYEUEXu.oKxOGzCpToA:20437:30:90:3:::
```

Рис. 9 — Работа с группами

Выводы по проделанной работе

Вывод

В ходе лабораторной работы были изучены основные механизмы управления пользователями и группами в Linux.
Получены практические навыки создания учётных записей, настройки прав доступа, управления паролями и группами, а также работы с ключевыми системными конфигурационными файлами.