Aegis Oracle Autonomous AI Database deployment

Database creation through verified schema installation
Windows PowerShell and Oracle SQLcl | 16 October 2026

Follow this guide to create a separate OCI Autonomous AI Database 26ai and install the Aegis database schema. At completion, the new Oracle user owns the same thirteen-table logical schema verified against live OCI. Existing records are not copied.

What you need

An OCI account permitted to create and manage the destination database; its selected region and compartment; a Windows computer with Git, PowerShell 5.1 or later, Oracle SQLcl and a supported Java installation; and a permitted network route to the new database.

Value to record	Example used in this guide
New database name	agsnext
Oracle schema owner	AGS_APP
Wallet ZIP kept outside Git	C:\aegis-target\Wallet_agsnext.zip
Wallet TNS alias	agsnext_low
Full server service	Copy SERVICE_NAME from the new wallet and confirm it in SQLcl
Source branch	ags_sprint1

Follow these steps in order

Steps	Task	Page
1 - 2	Create the database and confirm network access	2
3 - 4	Download the wallet and prepare the computer	3
5 - 6	Create the Oracle user and confirm the connection	4
7	Check the package and deploy the schema	5
8	Verify the completed database schema	6
9	Resolve errors and retain the deployment record	7

Verified reference: live OCI database agsora, owner ADMIN, Oracle server 23.26.4.1.0 (OCI product version 26ai). The read-only comparison on 16 October 2026 at 00:18 IST matched all 13 SQL files, 165 columns, constraints, native vector format and 20 application indexes. The new destination in this guide uses its own owner and wallet.

1 Create the database

1. Sign in to OCI Console. Select the destination region and compartment. Open **Oracle AI Database > Autonomous AI Database**, then choose **Create Autonomous AI Database**. [1]

2. Enter the destination settings below. The example names identify a new database.

Field	Selection
Display name	ags-next-oci-db
Database name	agsnext
Workload	Transaction Processing
Database version	Oracle AI Database 26ai
Compute and storage	Choose the approved allocation offered in your tenancy
Free or paid tier	Select the intended available tier and review its estimate
Autoscaling and backups	Review the selected settings before creation
Network access	Select the network route described in step 2
Administrator credentials	Set and privately retain the ADMIN password

3. Review the configuration, select **Create Autonomous AI Database**, and wait for lifecycle state **Available**. Record the new database OCID, region, compartment and database name. [1]

2 Confirm network access

Use the network option approved for the destination. For a public endpoint with an access list, allow the deployment computer's public egress IP. For a private endpoint, use a computer with the required private route and DNS access. The wallet connection uses mTLS; confirm that this connection mode is enabled. [2]

Allow the client to reach the host and port recorded in the wallet connection descriptor. Autonomous Database mTLS commonly uses TCP 1522. If the client cannot reach that endpoint, resolve the route, access list or firewall before continuing. [2]

Expected result: the new database is Available and the deployment computer has a permitted route to its mTLS endpoint.

3 Download the destination wallet

1. Open the new database details and select **Database connection**. Choose **Instance wallet**, then **Download wallet**. [3]

2. Set and retain the wallet password privately. Download the ZIP to `C:\aegis-target\Wallet_agsnext.zip`. Keep the ZIP and its contents outside the Git checkout. [3]

3. Open the ZIP and inspect `tnsnames.ora`. Find the destination low-service alias, for example `agsnext_low`. Record that entry's complete `SERVICE_NAME`. Preserve its exact value. [3]

The wallet password protects the wallet. The ADMIN password and the AGS_APP password are database login passwords. Keep these values separately identified; none belongs in this document or a command argument.

4 Prepare the deployment computer

Install Oracle SQLcl and a Java version supported by that SQLcl release. Oracle's SQLcl installation instructions list Java 17 or 21; the Windows executable is sql.exe in sqlcl\bin. Add that folder to PATH, or later supply -SqlclPath with its full path. [5]

Open PowerShell and check the tools:

```
git --version
java -version
sql -version
```

For a new checkout, choose a parent folder and clone the branch:

```
New-Item -ItemType Directory -Force 'C:\AegisSetup'
Set-Location 'C:\AegisSetup'
git clone --branch ags_sprint1 --single-branch `
  https://github.com/Maniatramco/Aegis.git
Set-Location .\Aegis
git branch --show-current
git rev-parse HEAD
```

If you already have the checkout, open its repository root on ags_sprint1. Record the exact commit. Keep the complete ags_database folder together: the launcher, install.sql, thirteen ags_tables scripts and read-only verification script are required.

Expected result: SQLcl is available and the complete database package is present on branch ags_sprint1.

5 Create the Oracle schema owner

In the new database, open Database Actions as ADMIN. Go to **Administration > Database Users > Create User**. Set username **AGS_APP**, a private password and a DATA quota, such as 200 MB for an initial installation. Leave optional user features off so the owner starts without extra objects. Create the user. [4]

In the Database Actions SQL worksheet, still connected as ADMIN to the new database, run:

```
GRANT CREATE SESSION, CREATE TABLE TO AGS_APP;
ALTER USER AGS_APP DEFAULT TABLESPACE DATA
  QUOTA 200M ON DATA;
```

The quota above is an installation example; choose capacity for the intended data volume. AGS_APP is the Oracle login and schema owner. The fresh installer requires that owner to have no existing objects. [4]

6 Confirm the destination connection

Start SQLcl from PowerShell:

```
sql /nolog
```

At the SQLcl prompt, use the new wallet and owner. Enter the AGS_APP password when prompted. [6]

```
SET CLOUDCONFIG C:\aegis-target\Wallet_agsnext.zip
CONNECT AGS_APP@agsnext_low

SELECT USER AS connected_owner,
       SYS_CONTEXT('USERENV','CURRENT_SCHEMA') AS schema_name,
       SYS_CONTEXT('USERENV','SERVICE_NAME') AS full_service
FROM dual;

SELECT COUNT(*) AS existing_objects FROM user_objects;
EXIT
```

Expected result: connected owner and current schema both equal AGS_APP; the full service matches the new wallet entry; existing_objects equals 0. Copy that full service into the PowerShell settings on the next page. If any value differs, correct the destination before installation.

7 Check and deploy the schema

In PowerShell, open the repository root. Replace the four example values below with the confirmed new destination values. ExpectedService is the complete server service from step 6.

```
Set-Location 'C:\AegisSetup\Aegis'
$dbTarget = @{
  WalletPath = 'C:\aegis-target\Wallet_agsnext.zip'
  UserName = 'AGS_APP'
  ServiceAlias = 'agsnext_low'
  ExpectedService = 'YOUR_FULL_SERVICE.adb.oraclecloud.com'
}
```

Run the local check first

```
.\ags_database\deploy-oci-database.ps1 @dbTarget -CheckOnly
```

This checks the local wallet metadata and all thirteen script files. It makes no database connection and checks no password or database privileges.

Expected output: Local package and wallet checks passed. No SQL client started and no database connection made.

Run the installation when ready

```
.\ags_database\deploy-oci-database.ps1 @dbTarget
```

Enter the AGS_APP database password at the SQLcl prompt. The launcher changes to the correct script directory and calls the shared install.sql. If SQLcl is outside PATH, add -SqlclPath with the full path to sql.exe to either launcher command.

The installer checks before DDL	Then it creates and verifies
Actual connected owner and current schema	All thirteen table definitions in dependency order
Actual full service and an empty owner	Primary, unique, foreign and check constraints
CREATE TABLE privilege and available quota	Twenty application indexes
SQL BOOLEAN, native VECTOR and collation support	Native VECTOR column and completed schema counts

Success: SQLcl prints `AEGIS_SCHEMA_INSTALL_OK`. The PowerShell launcher requires that marker in its log and a successful client exit before reporting completion. It prints the log path.

A rejected preflight creates no table. If DDL fails after creation begins, stop and inspect the destination and log: Oracle DDL commits implicitly, so a rollback does not remove earlier created objects. [8]

8 Verify the completed schema

Reconnect as AGS_APP using the same new wallet. In PowerShell, start SQLcl from the database script directory:

```
Set-Location 'C:\AegisSetup\Aegis\ags_database'
sql /nolog
```

At the SQLcl prompt:

```
SET CLOUDCONFIG C:\aegis-target\Wallet_agsnext.zip
CONNECT AGS_APP@agsnext_low
@ags_schema/verify_live_schema.sql

SELECT COUNT(*) AS table_count FROM user_tables;
SELECT COUNT(*) AS column_count FROM user_tab_columns;
EXIT
```

The supplied verification script reads metadata, prints the owner and service, checks table and column definitions, lists constraints and indexes, and tests a pair of identical vectors. It performs no schema or data changes.

Verification	Expected result
Owner and full service	The destination values confirmed in step 6
Application tables	13; every expected table reports PRESENT
Application columns	165 in total
Primary keys and unique constraints	13 primary keys; 2 unique constraints
Foreign keys	49; enabled
Check and NOT NULL constraints	131; enabled
Application indexes	20; Oracle-managed indexes may also be listed
Knowledge vector embedding	VECTOR; logical definition VECTOR(*, FLOAT32)
Identical-vector distance	0

Deployment is complete when: the launcher reports success, the target identity is correct and all verification results match. The result is an empty Aegis database schema on the new OCI database; application records and original database credentials are not copied.

The repository DDL preserves live columns, defaults, collations, relationships, delete rules and application indexes. Owner qualification and Oracle-managed physical storage clauses are omitted so the destination uses its own owner and managed storage.

9 Resolve errors and record the result

Error or symptom	Next action
Wallet alias or service not found	Use the same wallet entry for ServiceAlias and ExpectedService. Check the complete SERVICE_NAME value.
Connection timeout or login failure	Check Available status, network route, access list, wallet and the AGS_APP login password.
Wrong owner, current schema or service	Reconnect to the intended new database as AGS_APP. Do not continue with a different identity.
Schema is not empty	Stop. Inspect existing objects and prepare a separate empty owner for a fresh installation.
Missing privilege or quota	Have the destination DBA check CREATE SESSION, CREATE TABLE, default DATA tablespace and quota.
Collation, BOOLEAN or VECTOR preflight failure	Use a compatible Autonomous AI Database 26ai target. Ask the DBA to check MAX_STRING_SIZE=EXTENDED and data-bound collations. [7]
DDL failure or missing success marker	Retain the printed log and inspect committed objects before any retry. The installer performs no automatic cleanup. [8]

Retain a deployment record: source commit, database OCID and region, Oracle owner, wallet alias, full service, server version, installation log, verification result and date. Keep passwords and wallet contents in private storage.

Official references

[1] Oracle: Create an Autonomous AI Database

[2] Oracle: Database network connections and mTLS

[3] Oracle: Download an instance wallet

[4] Oracle: Create database users and assign quota

[5] Oracle: Install SQLcl and supported Java

[6] Oracle: Connect SQLcl using a wallet

[7] Oracle: Data-bound collation requirements

[8] Oracle: Oracle implicit DDL commit behavior

References checked 16 October 2026. Repository commands were reviewed against ags_sprint1 at 4f9c596. The SQL installer previously passed an isolated Oracle 26ai Free test; launcher checks were tested offline. A new OCI database deployment was not performed while preparing this guide.