SINGAPORE LIFT INSPECTION & TESTING
Inspection & Testing Pte Ltd

Elevator Testing Equipment

Product Catalog 2025

Your Premier Lift Inspection Partner. Ensuring safety, compliance, and performance for elevators across Singapore.

BCA-REGISTERED

BIZSAFE LEVEL 3

2025

Elevator Testing Equipment

Singapore Lift Inspection & Testing Pte Ltd specializes in providing precision testing equipment for elevator safety inspections. Our comprehensive range of BCA-registered testing instruments is designed to meet the rigorous demands of elevator maintenance companies, building owners, and safety inspectors across Singapore.

> **All equipment comes with calibration certificates and full technical support. Contact us at enquiry@sglifttest.com or +65 9615 1522**

Product Overview

Product Name	Key Application
Elevator Closing Pressure Tester	Door closing force compliance testing
Elevator Door Opening Clearance Detector	Door gap measurement & safety compliance
Elevator Governor Tester	Speed governor performance testing
Elevator Wire Rope Flaw Detector	Magnetic rope defect inspection
Elevator Wire Rope Slip Detector	Traction monitoring
Elevator Wire Rope Tension Tester	Rope tension measurement
Elevator Landing Door Stress Detector	Structural integrity testing

Complete Elevator Testing Equipment Lineup

Elevator Closing Pressure Tester

Elevator Closing Pressure Tester

Description

Safety Testing for Door Closing Force Compliance. Measures the kinetic energy and force of closing elevator doors to verify compliance with safety limits, protecting passengers from door-related injuries.

Key Features

- Force & kinetic energy measurement
- Peak detection with data hold
- Meets EN 81-20 requirements
- Compact handheld probe
- Instant pass/fail indication

Technical Specifications

Parameter	Specification
Measurement Range	0-500 N (Force), 0-10 J (Kinetic Energy)
Resolution	0.1 N / 0.001 J
Accuracy	±0.5% of full scale
Sampling Rate	1,000 Hz
Display	Digital LCD with backlight
Interface	USB 2.0, RS-232
Battery Life	12 hours continuous
Standards	EN 81-20, EN 81-1, ASME A17.1

Elevator Door Opening Clearance Detector

Elevator Door Opening Clearance Detector

Description

Precision Measurement for Door Gap Alignment & Safety Compliance. Measures the clearance gaps around elevator doors to ensure they meet safety standards for finger entrapment prevention and smooth door operation.

Key Features

- Sub-millimetre measurement accuracy
- Articulated probe for tight spaces
- Digital display & logging
- Standards-compliant reporting
- Lightweight handheld design

Technical Specifications

Parameter	Specification
Measurement Range	0-50 mm
Resolution	0.01 mm
Accuracy	±0.02 mm
Display	Digital LCD, dual reading (mm/inch)
Data Storage	1,000 measurements
Interface	USB, Bluetooth 4.0
IP Rating	IP54
Standards	EN 81-20, SS 550

Elevator Governor Tester

Elevator Governor Tester

Description

Accurate & Portable Testing Solution for Elevator Speed Governors. A precision instrument for testing elevator speed governors on-site. Measures tripping speed, reset speed, and overspeed governor performance to ensure compliance with EN 81 and SS550 standards.

Key Features

- Portable & field-ready design
- Digital readout with data logging
- Tests tripping and reset speeds
- Compatible with all governor types
- Automatic report generation

Technical Specifications

Parameter	Specification
Speed Range	0.1-5.0 m/s
Trip Speed Accuracy	±0.5% of reading
Display	Full-color TFT LCD
Data Logging	2,000 test records
Interface	USB, WiFi, Wireless trigger
IP Rating	IP67 weatherproof
Battery Life	15 hours continuous
Standards	EN 81-1, EN 81-20, SS 550, ASME A17.1

Elevator Wire Rope Flaw Detector

Elevator Wire Rope Flaw Detector

Description

Precision Magnetic Inspection for Hidden Wire Rope Defects. Uses magnetic flux leakage technology to detect internal and external defects in elevator wire ropes, including broken wires, corrosion, and fatigue damage invisible to the naked eye.

Key Features

- Detects internal broken wires
- Magnetic flux leakage technology
- High-speed scanning capability
- Visual defect mapping output
- Compliant with international standa

Technical Specifications

Parameter	Specification
Rope Diameter Range	8-50 mm
Detection Sensitivity	5% cross-section loss
Technology	Magnetic Flux Leakage (MFL)
Scanning Speed	0-2.0 m/s
Display	7-inch color touchscreen
Data Storage	8 GB internal flash
IP Rating	IP65
Standards	EN 10225, ASTM E1571, ASME A17.1

Elevator Wire Rope Slip Detector

Elevator Wire Rope Slip Detector

Description

Wire Rope Slip Detector for Elevator Traction Monitoring. Specialized monitoring device designed to detect and measure rope slippage between the traction sheave and hoisting ropes. Uses precise sensors and digital data analysis to identify abnormal movement or loss of traction.

Key Features

- High-precision sensors with fast sampling
- Non-intrusive operation
- Real-time speed-time curve visualization
- Wireless transmission & USB connectivity
- Aluminum alloy casing, lightweight & durable

Technical Specifications

Parameter	Specification
Measurement Range	0-10 mm slip detection
Resolution	0.001 mm
Sampling Rate	10,000 Hz
Display	10-inch color touchscreen
Interface	USB 3.0, WiFi, Bluetooth 5.0
IP Rating	IP66
Battery Life	8 hours
Casing	Aluminum alloy, 1.8 kg

Elevator Wire Rope Tension Tester

Elevator Wire Rope Tension Tester

Description

Accurate Measurement for Balanced Elevator Rope Tension. Precision instrument for measuring and comparing tension across multiple elevator hoisting ropes to ensure balanced load distribution and prevent premature rope wear.

Key Features

- Multi-rope simultaneous measurement
- Digital display with deviation alerts
- Portable clamp-on design
- Data storage & export capability
- Ensures balanced rope loading

Technical Specifications

Parameter	Specification
Capacity per Rope	0-50 kN
Accuracy	±0.5% of full scale
Resolution	0.01 kN
Channels	Up to 8 ropes simultaneous
Display	Full-color LCD graphical view
Interface	USB, RS-485, Wireless
Battery Life	20 hours continuous
Standards	ASME A17.2, EN 81-20

Elevator Landing Door Stress Deformation Detector

Elevator Landing Door Stress Deformation Detector

Description

Precision Monitoring for Door Frame Alignment & Structural Safety. Advanced detector that measures stress and deformation on elevator landing doors to ensure structural integrity and safety compliance. Identifies misalignment, warping, or fatigue in door frames.

Key Features

- High-sensitivity strain gauges
- Real-time deformation mapping
- Threshold alerts for safety limits
- Compact sensor array design
- EN 81 compliant testing protocols

Technical Specifications

Parameter	Specification
Strain Channels	Up to 8 simultaneous channels
Micro-strain Range	±5,000 με
Resolution	±1 με
Accuracy	±0.1% of reading
Display	12-inch touchscreen tablet
Interface	USB, WiFi, Bluetooth
Battery Life	10 hours portable mode
Standards	EN 81-20, EN 81-50, SS 550

Contact Us

For inquiries about our elevator testing equipment, calibration services, or technical support, please contact Singapore Lift Inspection & Testing Pte Ltd.

Contact Information	
Company	Singapore Lift Inspection & Testing Pte Ltd
Email	enquiry@sglifttest.com
Phone	+65 9615 1522
Address	32 Old Toh Tuck Road #02-15 I.Biz Centre, Singapore 597658
Certifications	BCA-registered, bizSAFE Level 3

Get in Touch

Your Premier Lift Inspection Partner - Ensuring Elevator Safety and Compliance