

HTML Interview Questions and Answers

Each answer is approximately 50 words and written in simple interview-ready language.

1. How will you start an ordered list from 10?

Use the start attribute in the ordered list tag. Example: `<ol start='10'><li>Item</li></ol>`. The numbering begins from 10 instead of 1. This is useful when continuing a list from a previous section or page.

2. What input type will you use to upload an image?

Use `<input type='file' accept='image/*'>`. The file type allows users to browse and upload files. The accept attribute limits file selection to images such as JPG, PNG, GIF, and WebP.

3. Name any 5 HTML5 tags.

Common HTML5 semantic tags are `<header>`, `<footer>`, `<nav>`, `<section>`, and `<article>`. These tags improve code readability, accessibility, and SEO by describing the purpose of different sections of a webpage.

4. What is DNS?

DNS stands for Domain Name System. It converts a domain name like google.com into its IP address so that browsers can locate and connect to the correct web server on the internet quickly.

5. What is Markup?

Markup is the use of tags to define the structure and presentation of content. HTML is a markup language because it uses tags such as `<p>`, `<h1>`, and `<table>` to organize web pages.

6. What is SEO?

SEO stands for Search Engine Optimization. It improves a website's visibility in search engines by using proper headings, semantic HTML, meta tags, keywords, image alt text, fast loading speed, and mobile-friendly design.

7. What is Inspect Element?

Inspect Element is a browser developer tool that allows developers to view and temporarily edit HTML, CSS, and JavaScript. It helps debug layouts, test styles, inspect elements, and analyze website performance.

8. Explain webpage designing.

Webpage designing is the process of creating the appearance and layout of a website using HTML, CSS, and JavaScript. It focuses on user interface, user experience, colors, typography, navigation, and responsiveness.

9. How will you open another window using an anchor tag?

Use the target='_blank' attribute. Example: `<a href='https://example.com' target='_blank'>Visit</a>`. Clicking the link opens the webpage in a new browser tab or window.

10. What does the viewport meta tag do?

The viewport meta tag controls how a webpage is displayed on mobile devices. Example: `<meta name='viewport' content='width=device-width, initial-scale=1.0'>`. It makes websites responsive.

11. What are attributes in HTML?

Attributes provide additional information about HTML elements. They are written inside the opening tag. Examples include id, class, href, src, alt, title, style, and target. Attributes help customize an element's behavior and appearance.

12. What is an IP address?

An IP address is a unique numerical identifier assigned to every device connected to a network. It enables communication between devices over the internet. IPv4 and IPv6 are the two main versions.

13. What is localhost?

Localhost refers to the current computer and usually uses the IP address 127.0.0.1. Developers use localhost to test websites and applications before deploying them to a live server.

14. HTML5 vs HTML4

HTML5 introduced semantic tags, audio, video, canvas, SVG support, improved forms, local storage, and better multimedia support. HTML4 required plugins for multimedia and had fewer semantic elements.

15. What are semantic tags?

Semantic tags describe the purpose of content. Examples include header, footer, article, section, nav, and aside. They improve readability, accessibility, and search engine optimization.

16. Difference between div and span.

Div is a block-level element used for larger sections. Span is an inline element used for styling or grouping small portions of text without starting a new line.

17. Difference between class and ID.

A class can be used on multiple elements, while an ID should be unique for one element. CSS uses '.' for class selectors and '#' for ID selectors.

18. What are self-closing tags?

Self-closing tags do not require a closing tag. Examples include `img`, `br`, `hr`, `input`, `meta`, and `link`. They represent standalone elements.

19. How many heading tags are there?

HTML provides six heading tags: `h1` to `h6`. `H1` has the highest priority and is generally used for the main page title, while `h6` has the lowest priority.

20. Difference between block and inline elements.

Block elements occupy the full width and start on a new line. Inline elements occupy only required space and remain within the same line.

21. Difference between `<em>` and `<strong>`.

The `<em>` tag emphasizes text and is usually displayed in italics. The `<strong>` tag indicates strong importance and is displayed in bold. Both are semantic tags and help screen readers understand the meaning of the content.

22. Difference between HTML tags and elements.

An HTML tag is the markup enclosed in angle brackets, such as `<p>`. An HTML element consists of the opening tag, content, and closing tag together. Some elements like `<br>` are empty elements.

23. Explain the `<br>` tag.

The `<br>` tag inserts a single line break without starting a new paragraph. It is commonly used for addresses, poems, or formatting text where a new line is needed.

24. Write code to create an ordered list with Roman numbers.

Use: `<ol type='I'><li>HTML</li><li>CSS</li></ol>`. The type attribute 'I' displays uppercase Roman numerals. You can also use 'i' for lowercase Roman numerals.

25. Write code to create an unordered list with circles.

Use: `<ul type='circle'><li>HTML</li><li>CSS</li></ul>`. The circle type displays hollow circular bullets. CSS `list-style-type` is the preferred modern approach.

26. Create a link to <https://www.prepbytes.com>.

Example: `<a href='https://www.prepbytes.com' target='_blank'>PrepBytes</a>`. The href attribute specifies the URL and target='_blank' opens the link in a new tab.

27. Write code to insert an image.

Example: `<img src='image.jpg' alt='Sample Image' width='300'>`. The src attribute specifies the image path and alt provides alternative text for accessibility.

28. Create a 2×2 table.

Use table, tr, th, and td tags. Example columns: Name and Salary with two employee records. Tables organize data into rows and columns.

29. Create a form with name, age, email and contact.

Use the form tag with input fields: text for name, number for age, email for email address, and tel for contact number. Add a submit button.

30. Explain colspan.

The colspan attribute allows a table cell to span multiple columns. Example: `<td colspan='2'>Merged Cell</td>`. It is useful for creating table headings or merged sections.

31. Create radio buttons and checkboxes. Explain the difference.

Radio buttons allow users to select only one option from a group, while checkboxes allow selecting multiple options. Example: Radio buttons for MERN/MEAN course and checkboxes for HTML, CSS, React, and Node technologies.

32. How many heading tags does HTML contain?

HTML contains six heading tags: h1, h2, h3, h4, h5, and h6. They define headings of different importance and help organize webpage content.

33. Which heading has the highest and lowest priority?

The h1 tag has the highest priority and is generally used for the main page title. The h6 tag has the lowest priority and is used for the least important heading.

34. How to create a hyperlink in HTML?

Use the anchor tag: `<a href='https://example.com'>Visit</a>`. The href attribute specifies the destination URL. The target='_blank' attribute opens the link in a new tab.

35. Which HTML tag is used to display tabular data?

The table tag is used to display tabular data. It contains tr for rows, th for headings, and td for data cells.

36. Why do we use the colgroup tag?

The colgroup tag groups one or more columns in a table. It allows applying styles like width or background color to entire columns without repeating CSS.

37. What are common lists in HTML?

HTML provides three types of lists: Ordered List (ol), Unordered List (ul), and Definition List (dl). Each serves a different purpose for organizing content.

38. Write the structure of a definition list.

A definition list uses dl as the container, dt for the term, and dd for its description. It is useful for glossaries and definitions.

39. What do dl, dt and dd mean?

dl stands for Definition List, dt stands for Definition Term, and dd stands for Definition Description. Together they create a structured definition list.

40. What is semantic HTML?

Semantic HTML uses meaningful tags such as header, article, section, footer, and nav to describe webpage content. It improves accessibility, SEO, and code readability.

41. What is an image map?

An image map allows different clickable areas within a single image. It uses the <map> and <area> tags with coordinates to create multiple hyperlinks on one image.

42. How to insert a copyright symbol?

Use the HTML entity © or ©. Example: <p>© 2026 My Website</p>. The browser displays the © symbol.

43. How to create a nested webpage?

A nested webpage is commonly created using the <iframe> tag, which embeds one webpage inside another webpage.

44. What is the use of the iframe tag?

The iframe tag embeds another HTML page, video, map, or document within the current webpage using the src attribute.

45. Important iframe attributes.

Common iframe attributes are src, width, height, title, loading, allowfullscreen, and name. They control the embedded content and accessibility.

46. Does a hyperlink only apply to text?

No. Hyperlinks can be applied to text, images, buttons, icons, and other HTML elements using the anchor (<a>) tag.

47. What is a style sheet?

A style sheet is a collection of CSS rules used to control the appearance of HTML elements. It can be inline, internal, or external.

48. Can you create multi-colored text?

Yes. Wrap different parts of text inside separate span tags and apply different CSS color properties to each span.

49. Is it possible to change bullet color?

Yes. Use the CSS ::marker pseudo-element or customize list items with CSS to change bullet color.

50. Explain the layout of HTML.

A typical HTML layout contains header, nav, main, section, article, aside, and footer. Semantic tags make webpages organized, accessible, and SEO-friendly.

51. What is a marquee?

The <marquee> tag creates scrolling text or images. It is deprecated in HTML5 and should not be used in modern websites. CSS animations are the recommended replacement for moving text and content.

52. How to make a background image?

Use CSS: `body { background-image: url('image.jpg'); background-size: cover; }`. This sets an image as the webpage background and adjusts it to cover the screen.

53. How many tags can separate sections of text?

Common tags include
 for a line break, <hr> for a horizontal line, and <p> for creating separate paragraphs. Each serves a different formatting purpose.

54. What are empty elements?

Empty elements do not contain any content or closing tag. Examples include
, <hr>, , <input>, <meta>, and <link>. They perform specific tasks without enclosing text.

55. What is the use of the span tag?

The tag is an inline container used to style or manipulate a small portion of text. Example: `<span style='color:red'>Hello</span>`.

56. What is the use of an iframe tag?

The iframe tag embeds another webpage, PDF, map, or YouTube video inside the current webpage. It is widely used for external content integration.

57. What are HTML entities?

HTML entities display reserved characters or special symbols. Examples include < for <, > for >, & for &, and © for ©.

58. Why is a URL encoded?

URL encoding replaces unsafe characters with percent-encoded values, ensuring data is transmitted correctly in URLs. For example, spaces become %20.

59. Is <!DOCTYPE html> an HTML tag?

No. <!DOCTYPE html> is a declaration, not an HTML tag. It tells the browser to render the page using HTML5 standards mode.

60. What is the canvas element in HTML5?

The <canvas> element provides a drawing area for graphics using JavaScript. It is commonly used for games, charts, animations, and image processing.

61. What is SVG?

SVG stands for Scalable Vector Graphics. It is an XML-based image format used to create vector graphics such as icons, logos, charts, and illustrations. SVG images can be scaled without losing quality and can be styled or animated using CSS and JavaScript.

62. What are the different new form element types in HTML5?

HTML5 introduced new input types including email, url, number, range, date, time, datetime-local, month, week, color, search, and tel. These improve user experience and provide built-in validation.

63. Is there any need to change web browsers to support HTML5?

Most modern browsers such as Chrome, Firefox, Edge, Safari, and Opera fully support HTML5. Older browsers may not support all HTML5 features, so updating to the latest version is recommended.

64. Which video formats are supported by HTML5?

The HTML5 video tag supports MP4 (H.264), WebM, and Ogg formats. MP4 is the most widely supported format across modern browsers and devices.

65. Is the audio tag supported in HTML5?

Yes. HTML5 introduced the audio tag, allowing developers to play audio files without external plugins. Common supported formats include MP3, WAV, and OGG.

66. Difference between progress and meter tag.

The progress tag shows task completion progress, while the meter tag represents a measurement within a known range, such as battery level, disk usage, or exam score.

67. What is the use of the figure tag?

The figure tag groups self-contained content such as images, diagrams, code snippets, or charts. It keeps related content together and improves semantic structure.

68. What is the use of figcaption tag?

The figcaption tag provides a caption or description for content inside the figure element. It improves accessibility and gives context to images or diagrams.

69. What is the button tag?

The button tag creates a clickable button. It can submit forms, reset forms, or execute JavaScript functions. Types include submit, reset, and button.

70. What is the use of details and summary tags?

The details tag creates collapsible content, while the summary tag provides the visible heading users click to expand or collapse the content. They improve user interaction without JavaScript.

71. What is the datalist tag?

The datalist tag provides predefined options for an input field. It works with the list attribute of the input element, allowing users to either choose from suggestions or enter their own value.

72. How are tags migrated from HTML4 to HTML5?

Most HTML4 tags continue to work in HTML5. However, deprecated tags like font and center should be replaced with CSS, while semantic tags such as header, nav, section, article, and footer are recommended.

73. If I do not put <!DOCTYPE html>, will HTML5 work?

The page may still display, but browsers can enter Quirks Mode instead of Standards Mode. Using <!DOCTYPE html> ensures consistent HTML5 rendering across browsers.

74. What is the use of the required attribute?

The required attribute makes an input field mandatory. Users cannot submit the form until all required fields are completed, providing simple client-side validation.

75. What are the new input types in HTML5?

New input types include email, url, number, date, month, week, time, datetime-local, color, range, search, and tel. These improve validation and user experience.

76. Is HTML case-sensitive?

No. HTML is not case-sensitive. Tags such as <BODY> and <body> work the same, although lowercase is the recommended coding style.

77. When are comments used in HTML?

Comments are used to explain code or temporarily disable sections during development. They are ignored by browsers. Syntax: <!-- This is a comment -->.

78. What are attributes and how do you use them?

Attributes provide extra information about HTML elements. They are written inside the opening tag. Examples include href, src, id, class, alt, width, and height.

79. What is the 'for' attribute in the label tag?

The for attribute connects a label with an input field using the input's id. Clicking the label automatically focuses or selects the associated input, improving accessibility.

80. How do you create a hyperlink in HTML?

Use the anchor tag: Visit Website. The href attribute specifies the destination, while target='_blank' opens it in a new tab.

81. Name some common lists used when designing a page.

HTML provides Ordered Lists (), Unordered Lists (), and Definition Lists (<dl>). Ordered lists display numbered items, unordered lists display bullet points, and definition lists show terms with their descriptions. Each type is used based on the content structure and presentation requirements.

82. Which attribute is required in the input tag?

The input tag itself does not require a mandatory attribute in HTML. However, the 'type' attribute is strongly recommended because it defines the kind of input, such as text, email, password, number, or date. Other common attributes include name, id, placeholder, and required.

83. What do you mean by Markup Language and Hypertext?

A markup language uses tags to structure and format content. HTML is a markup language. Hypertext refers to text containing links that connect one document or webpage to another, enabling easy navigation across the web.

84. How are active links different from normal links?

A normal link has not been visited or clicked, while an active link is the link currently being clicked by the user. CSS pseudo-classes like :link, :visited, :hover, and :active are used to style these different states.

85. What happens if there is no text between HTML tags?

If there is no content between opening and closing tags, the browser creates an empty element. Depending on the tag, it may display nothing or simply reserve space. The HTML document will still render correctly.

86. What are the limits of the text field size?

The size attribute controls the visible width of a text field, while the maxlength attribute limits the maximum number of characters a user can enter. Both improve user input handling.

87. What is the relationship between border and rules attributes?

The border attribute specifies the thickness of a table border. The rules attribute controls which internal table borders are displayed, such as rows, columns, all, or none. The rules attribute was mainly used in older HTML versions.

88. What are Cell Spacing and Cell Padding?

Cell spacing is the space between table cells, while cell padding is the space between a cell's content and its border. In modern HTML, CSS properties border-spacing and padding are preferred.

89. What is the difference between HTML and XHTML?

HTML is flexible and forgiving with syntax, whereas XHTML follows strict XML rules. XHTML requires properly nested tags, lowercase element names, quoted attributes, and all elements must be closed.

90. How many types of CSS can be included in HTML?

There are three types of CSS: Inline CSS using the style attribute, Internal CSS using the style tag inside the head section, and External CSS using a linked CSS file. External CSS is recommended for large projects.

91. What are logical and physical tags?

Logical tags describe the meaning of text, such as `<em>` and `<strong>`. Physical tags describe appearance, such as `<b>` and `<i>`. HTML5 encourages logical tags because they improve accessibility and semantics.

92. How can you apply JavaScript to a webpage?

JavaScript can be added using the `<script>` tag. It may be written internally, externally using the `src` attribute, or inline through event attributes like `onclick`. External JavaScript is the preferred approach.

93. How do you create radio buttons and checkboxes?

Radio buttons use `<input type='radio'>` and allow only one selection within a group sharing the same name. Checkboxes use `<input type='checkbox'>` and allow selecting multiple options independently.

94. What is the main advantage of the label tag?

The label tag improves accessibility by connecting descriptive text with form controls. Clicking the label automatically focuses or selects the associated input, making forms easier to use.

95. How can you make form data appear in the URL after clicking Submit?

Set the form method to GET. Example: `<form action='submit.php' method='get'>`. The browser appends form data as query parameters in the URL after submission.