```
Const String = () => {

    Const Title = "This is react"
    Const Heading = "This is node"
    Const Angular = "used to build"
    Const SQL = "To structure"
    Const Element = "This is Element"
    Const Module = "Number of module"
    Const Div = "The div items"
    Const Align = "Align the font"
    Const Submit = "Submit the form"

return (<>
    <h1> {Title} </h1>
    <h1> {Heading} </h1>
    <h1> {Angular} </h1>
    <h1> {SQL} </h1>
    <h1> {Element} </h1>
    <h1> {Module} </h1>
    <h1> {Div} </h1>
    <h1> {Align} </h1>
    <h1> {Submit} </h1>
  </>)
}, Export default String
```

```
const Number = () => {
    const one = 1
    const two = 2
    const three = 3
    const four = 4
    const five = 5
    const six = 6
    const seven = 7
    const eight = 8
    const nine = 9
    const ten = 10
return ( <>
    <h1> {one} </h1>
    <h1> {two} </h1>
    <h1> {three} </h1>
    <h1> {four} </h1>
    <h1> {five} </h1>
    <h1> {six} </h1>
    <h1> {seven} </h1>
    <h1> {eight} </h1>
    <h1> {nine} </h1>
    <h1> {ten} </h1>
    </>)
}
export default Number;
```

```
const Boolean = () => {
    const build = true
    const success = true
    const attend = false
    const fails = true
    const receive = false
    const work = true
return ( <>
    <h1> {build? "This is true" : "This is false"}
    <\h1>

    <h1>{success? "This is true" : "This is false"} <\h1>
    <h1>{attend? "This is true" : "This is false"} <\h1>
    <h1>{fails? "This is true" : "This is false"} <\h1>
    <h1>{receive? "This is true" : "This is false"}
    <\h1>
    <h1>{work? "This is true" : "This is
    false"} <\h1>

    <>)
}

export default Boolean
```

```
const Null = () => {

    const String = "React"
    const factor = Null
    const size = Null
    const base = "HTML"
    const Point = "Padding"
    const text = "Align items"
    const form = Null

return ( <>
    <h1> { string?? "This is null"} </h1>
    <h1> { factor?? "This is null"} </h1>
    <h1> { size ?? "This is null"} </h1>
    <h1> { base ?? "This is null"} </h1>
    <h1> { point ?? "This is null"} </h1>
    <h1> { text ?? "This is null"} </h1>
    <h1> { form ?? "This null"} </h1>

  </> )
}
export default Null
```