Array :

1) const arr = [1, 2, 3, "sun"]
console.log(arr);

2) const a = ["Mann", 21, "Batch"]
console.log(a)

3) const fruit = ["Veg", "Apple"]
console.log(fruit);

4) const Veg = ["Potato", "Tomato"]
console.log(Veg);

5) const num = [1, 2, 3, 4]
console.log(num[2]);

6) const name = ["Mani", "Manan", "Ravi"]
console.log(name);

7) const sum = [10, 30, 40]
console.log(sum);

10) const fruits = ["apple", "orange", "grape"];
console.log(fruits[1]);

11) const city = ["ny", "la", "chi"];
console.log(city[2]);

12) const arr1 = [1, 2, [3, 4]];
console.log(arr1[2][1]);

13) const numbers = [10, 20, [30, 40]];
console.log(numbers[2][0]);

15) const fruits = ["apple", "orange", "grape"];
console.log(fruits);

16) const veg = ["Tomato", "potato"];
console.log(veg);

17) const s = [1, 2, 3, 4, [5, 6, 7]];
console.log(s[4][0]);

20) Const num = [10, 20, 30, [40, 50, [60, 70]]]
console.log(num[3][1][0])

21) Const arr = ["Name", "Sex", [1, 2, ["dept"]]]
console.log(arr[2]);

22) Const num = [1, 2, 3, [4, 5]]
console.log(num[3][1])

23) Const sum = ["Name", "Sex", "Dept"]
console.log(sum);

24) Const arr2 = [10, 20, [30, 40, [50, 60]]]
console.log(arr2[2][0][0]);

25) Const dept = ["Name", ["Sex", ["Dept"]]]
console.log(dept[0][1])

Object :-

1) Const dog = {name: "Han", color: "blue"}
console.log(dog.color)

2) Const coor = {Num: 1, Dept: "Math"}
console.log(coor.Dept)

3) Const num = {Sec: 1, class: 3, id: 4}
console.log(num)

4) Const cal = {place: "KKL", venue: "beach"}
console.log(cal)

5) Const Sound = {name: "light", place: "KKL"}
console.log(Sound)

6) Const ultra = {dlog: "SMS", venue: "KKL"}
console.log(ultra.venue)

7) Const name = {Range: "Dom", Num: 2}
console.log(name.Range)

8) const off = {name: "Andy", place: "KKL"}
console.log(off.place)

9) const sch = {name: "Sorbite", class: 8}
console.log(sch)

10) const coll = {name: "Smo", sec: "A"}
console.log(coll)

11) const own = {House: "ven", no: 1, data: "place"}
console.log(own);

12) const vehi = {name: "van", type: "Diesel"}
console.log(vehi);

13) const fruit = {fruit: "Orange", type: 1}
console.log(fruit)

14) const name = {name: "Hari", class: 2}
console.log(name);

15) const Ass = {Num: 1, sec: "A"}
console.log(Ass)

1) Function add () {
console.log(" running...")
}
add()

2) Function fruit () {
console.log(" fruit is tasty"),
}
fruit()

3) function dog () {
console.log ("dog")
}
dog()

4) function cd () {
console.log (" charm")
}
cd()

5) function fruit () {
console.log (" Fruit")
}
fruit()

6)

6) const orbel = function(){
console.log(" orbel num")
}
orbel()

7) const fruit = function(){
console.log(" The fruit")
}
fruit()

8) const veg = function(){
console.log(" The vegetable"
}
veg()

9) const num = function(){
console.log(" Num function")
}
num()

10) const veg = function(){
console.log(" The tomato ").
}
veg()

21) const vehical = () => {
console.log("The vehical");
}

vehical ()

22) const typo = () => {
console.log("The typo")
}

typo ()

23) const veg = () => {
console.log("The veg")
}

veg()

24) const fruit = () => {
console.log("The fruit")
}

fruit ()

25) const van = () => {
console.log("The van")
}

van()