
QERC



Long Shank / Corner Radius / for 🕕 🕑 🚺 unit: mm Diameter Corner R Flute Length O.A.L. Shank Dia Order No. D1 R L2 L1 D2 **QERC 0605** 6.0 0.5 12 75 6 **QERC 0605A** 12 100 6.0 0.5 6 **QERC 0610** 75 6.0 1.0 12 6 **QERC 0610A** 6.0 1.0 12 100 6 **QERC 0805** 8.0 100 0.5 16 8 **QERC 0810** 8.0 1.0 16 100 8 **QERC 1005** 100 10 10.0 0.5 20 **QERC 1010** 10.0 20 100 10 1.0 **QERC 1020** 10.0 2.0 20 100 10 **QERC 1205** 12.0 100 0.5 24 12 **QERC 1210** 12.0 1.0 24 100 12 **QERC 1220** 100 12.0 2.0 24 12

▼ Depth of cut

D2





ap≤D1 ae≤0.02 D1 HRC45 ↑

R=Corner R

▼ Recommended cutting condition for QERC

MATERIAL	Carbon Steels . Alloy Steels S45C , FC , FCD , SCM , S50C , SKS		Alloy Steels . Tool Steels SCr , SNCM , SKD11 , SKD61 , NAK80		Hardened Steels SKD11	
HARDNESS	~HRC30		~HRC50		~HRC60	
Dia. (D1)	SPEED (min ⁻¹)	FEED mm/min	SPEED (min ⁻¹)	FEED mm/min	SPEED (min ⁻¹)	FEED mm/min
6	12000	3600	7200	2200	3500	650
8	9600	4000	5600	2200	2700	750
10	7000	3400	4400	1700	2100	650
12	6000	2800	3600	1400	1800	600