

# **DSP505: Programming Lab for Data Science and Artificial Intelligence**

## **TPL616: Advanced Programming for DSAI**

**(Numpy Tutorial)**



**Vishwesh Jatala**

Assistant Professor

Department of CSE

Indian Institute of Technology Bhilai

[vishwesh@iitbhilai.ac.in](mailto:vishwesh@iitbhilai.ac.in)

# Acknowledgement

- References for the today's slides:  
<https://www.cs.cornell.edu/courses/cs4670/2018sp/>

# What is Numpy?

- Numpy, Scipy, and Matplotlib provide MATLAB-like functionality in python.
- Numpy Features:
  - Typed multidimensional arrays (matrices)
  - Fast numerical computations (matrix math)
  - High-level math functions

# Why do we need NumPy

- Python does numerical computations slowly.
- Real time data sets are very huge (order of millions of row and thousands features)
- 1000 x 1000 matrix multiply
  - Python triple loop takes > 10 min.
  - Numpy takes ~0.03 seconds

# NumPy Overview

1. Arrays
2. Shaping and transposition
3. Mathematical Operations
4. Indexing and slicing

# Arrays

Structured lists of numbers.

- Vectors
- Matrices
- Images
- Tensors
- ConvNets

# Arrays

Structured lists of numbers.

- **Vectors**
- **Matrices**
- Images
- Tensors
- ConvNets

$$\begin{bmatrix} p_x \\ p_y \\ p_z \end{bmatrix}$$

$$\begin{bmatrix} a_{11} & \cdots & a_{1n} \\ \vdots & \ddots & \vdots \\ a_{m1} & \cdots & a_{mn} \end{bmatrix}$$

# Arrays

Structured lists of numbers.

- Vectors
- Matrices
- **Images**
- Tensors
- ConvNets







# Arrays

Structured lists of numbers.

- Vectors
- Matrices
- Images
- **Tensors**
- ConvNets



# Arrays, Basic Properties

```
import numpy as np  
  
a = np.array([[1, 2, 3], [4, 5, 6]], dtype=np.float32)  
  
print a.ndim, a.shape, a.dtype
```

1. Arrays can have any number of dimensions, including zero (a scalar).
2. Arrays are typed: `np.uint8`, `np.int64`, `np.float32`, `np.float64`
3. Arrays are dense. Each element of the array exists and has the same type.

# Arrays, creation

- `np.ones`, `np.zeros`
- `np.arange`
- `np.concatenate`
- `np.astype`
- `np.zeros_like`,  
`np.ones_like`
- `np.random.random`

# Arrays, creation

- **np.ones, np.zeros**
- np.arange
- np.concatenate
- np.astype
- np.zeros\_like,  
np.ones\_like
- np.random.random

```
>>> np.ones((3,5),dtype=np.float32)
array([[ 1.,  1.,  1.,  1.,  1.],
       [ 1.,  1.,  1.,  1.,  1.],
       [ 1.,  1.,  1.,  1.,  1.]], dtype=float32)
```

```
>>> np.zeros((6,2),dtype=np.int8)
array([[0, 0],
       [0, 0],
       [0, 0],
       [0, 0],
       [0, 0],
       [0, 0]], dtype=int8)
```

# Arrays, creation

- np.ones, np.zeros
- **np.arange**
- np.concatenate
- np.astype
- np.zeros\_like,  
np.ones\_like
- np.random.random

```
>>> np.arange(1334,1338)  
array([1334, 1335, 1336, 1337])
```

# Arrays, creation

- np.ones, np.zeros
- np.arange
- **np.concatenate**
- np.astype
- np.zeros\_like,  
np.ones\_like
- np.random.random

```
>>> A = np.ones((2,3))
>>> B = np.zeros((4,3))
>>> np.concatenate([A,B])
array([[ 1.,  1.,  1.],
       [ 1.,  1.,  1.],
       [ 0.,  0.,  0.],
       [ 0.,  0.,  0.],
       [ 0.,  0.,  0.],
       [ 0.,  0.,  0.]])
>>>
```

# Arrays, creation

- np.ones, np.zeros
- np.arange
- **np.concatenate**
- np.astype
- np.zeros\_like,  
np.ones\_like
- np.random.random

```
>>> A = np.ones((4,1))
>>> B = np.zeros((4,2))
>>> np.concatenate([A,B], axis=1)
array([[ 1.,  0.,  0.],
       [ 1.,  0.,  0.],
       [ 1.,  0.,  0.],
       [ 1.,  0.,  0.]])
```

# Arrays, creation

- np.ones, np.zeros
- np.arange
- np.concatenate
- **np.astype**
- np.zeros\_like,  
np.ones\_like
- np.random.random

```
>>> A
array([[ 4670.5,  4670.5,  4670.5],
       [ 4670.5,  4670.5,  4670.5],
       [ 4670.5,  4670.5,  4670.5],
       [ 4670.5,  4670.5,  4670.5],
       [ 4670.5,  4670.5,  4670.5]], dtype=float32)
>>> print(A.astype(np.uint16))
[[4670 4670 4670]
 [4670 4670 4670]
 [4670 4670 4670]
 [4670 4670 4670]
 [4670 4670 4670]]
```



# Arrays, creation

- np.ones, np.zeros
- np.arange
- np.concatenate
- np.astype
- **np.zeros\_like,**  
**np.ones\_like**
- np.random.random

```
>>> a = np.ones((2,2,3))  
>>> b = np.zeros_like(a)  
>>> print(b.shape)
```

# Arrays, creation

- `np.ones`, `np.zeros`
- `np.arange`
- `np.concatenate`
- `np.astype`
- `np.zeros_like`,  
`np.ones_like`
- **`np.random.random`**

```
>>> np.random.random((10,3))
array([[ 0.61481644,  0.55453657,  0.04320502],
       [ 0.08973085,  0.25959573,  0.27566721],
       [ 0.84375899,  0.2949532 ,  0.29712833],
       [ 0.44564992,  0.37728361,  0.29471536],
       [ 0.71256698,  0.53193976,  0.63061914],
       [ 0.03738061,  0.96497761,  0.01481647],
       [ 0.09924332,  0.73128868,  0.22521644],
       [ 0.94249399,  0.72355378,  0.94034095],
       [ 0.35742243,  0.91085299,  0.15669063],
       [ 0.54259617,  0.85891392,  0.77224443]])
```

# Arrays, danger zone

- Must be dense, no holes.
- Must be one type
- Cannot combine arrays of different shape

```
>>> np.ones([7,8]) + np.ones([9,3])  
Traceback (most recent call last):  
  File "<stdin>", line 1, in <module>  
ValueError: operands could not be broadcast together  
with shapes (7,8) (9,3)
```

# Shaping

```
a = np.array([1, 2, 3, 4, 5, 6])
```

```
a = a.reshape(3, 2)
```

1. Total number of elements cannot change.

# Transposition

```
a = np.arange(10).reshape(5, 2)
```

```
a = a.T
```

`a.T` transposes the first two axes.

# Saving and loading arrays

```
np.savez('data.npz', a=a)  
data = np.load('data.npz')  
a = data['a']
```

1. NPZ files can hold multiple arrays
2. `np.savez_compressed` similar.

# Mathematical operators

- Arithmetic operations are element-wise
- Logical operator return a bool array
- In place operations modify the array

# Mathematical operators

- **Arithmetic operations are element-wise**
- Logical operator return a bool array
- In place operations modify the array

```
>>> a
array([1, 2, 3])
>>> b
array([ 4,  4, 10])
>>> a * b
array([ 4,  8, 30])
```



# Mathematical operators

- Arithmetic operations are element-wise
- **Logical operator return a bool array**
- In place operations modify the array

```
>>> a
array([[ 0.93445601,  0.42984044,  0.12228461],
       [ 0.06239738,  0.76019703,  0.11123116],
       [ 0.14617578,  0.90159137,  0.89746818]])
>>> a > 0.5
array([[ True, False, False],
       [False,  True, False],
       [False,  True,  True]], dtype=bool)
```

# Mathematical operators

- Arithmetic operations are element-wise
- Logical operator return a bool array
- **In place operations modify the array**

```
>>> a
array([[ 4, 15],
       [20, 75]])
>>> b
array([[ 2,  5],
       [ 5, 15]])
>>> a /= b
>>> a
array([[2, 3],
       [4, 5]])
```

# Math, universal functions

Also called ufuncs

Element-wise

Examples:

- `np.exp`
- `np.sqrt`
- `np.sin`
- `np.cos`
- `np.isnan`

# Math, universal functions

Also called ufuncs

Element-wise

Examples:

- `np.exp`
- `np.sqrt`
- `np.sin`
- `np.cos`
- `np.isnan`

```
>>> a
array([[ 1,  4],
       [ 9, 16],
       [25, 36]])
>>> np.sqrt(a)
array([[ 1.,  2.],
       [ 3.,  4.],
       [ 5.,  6.]])
```

# Indexing

`x[0,0]`     # top-left element

`x[0,-1]`    # first row, last column

`x[0,:]`    # first row (many entries)

`x[:,0]`    # first column (many entries)

## Notes:

- Zero-indexing
- Multi-dimensional indices are comma-separated (i.e., a tuple)

# Python Slicing

Syntax: start:stop:step

```
a = list(range(10))
```

```
a[:3] # indices 0, 1, 2
```

```
a[-3:] # indices 7, 8, 9
```

```
a[3:8:2] # indices 3, 5, 7
```

```
a[4:1:-1] # indices 4, 3, 2 (this one is tricky)
```

# Axes

```
a.sum() # sum all entries
```

```
a.sum(axis=0) # sum over rows
```

```
a.sum(axis=1) # sum over columns
```

```
a.sum(axis=1, keepdims=True)
```

1. Use the axis parameter to control which axis NumPy operates on
2. Typically, the axis specified will disappear, keepdims keeps all dimensions