

SQL Overview

Dr. Villanes

Software for class



Open source SQL database system



DataGrip

Database IDE – Many databases, one tool

Getting started...

Download "*Exercise*" SQLite database.

Download & run script to create schema in Postgres:
Jupyter.

Overview of SQL

Terminology



| SQL |
|--------|
| Table |
| Row |
| Column |


Select Statement

A SELECT statement is **used to query one or more tables**. The results of the SELECT statement are written to the default output destination:

```
SELECT column1, column2, ...  
FROM table_name;
```

Select Statement

A SELECT statement contains smaller building blocks called clauses.



The diagram shows a SQL SELECT statement within a rectangular box. The keywords `SELECT`, `FROM`, `WHERE`, and `ORDER BY` are highlighted in light blue. The statement is: `SELECT column1, column2, ...
FROM table_name
WHERE column1='F'
ORDER BY column1;`. A green arrow points from the word "clauses" to the `WHERE` clause.

clauses

Although it can contain multiple clauses, each SELECT statement begins with the SELECT keyword

Select Statement: Required Clauses

A SELECT statement contains smaller building blocks called clauses.

```
SELECT column1, column2, ...  
FROM table_name;
```

- The **SELECT** clause specifies the columns and column order.
- The **FROM** clause specified the data sources

Select Statement: Optional Clauses

```
SELECT column1, column2, ...  
FROM table_name  
WHERE sql-expression  
GROUP BY column_name  
HAVING sql-expression  
ORDER BY column_name <DESC>;
```

- The **WHERE** clause specifies data that meets certain conditions.
- The **GROUP BY** clause groups data for processing.
- The **HAVING** clause specifies groups that meet certain conditions.
- The **ORDER BY** clause specifies an order for the data.

The specified order of the above clauses within the SELECT statement is required.

Additional SQL Statements

```
SELECT expression;  
CREATE expression;  
DESCRIBE expression;  
INSERT expression;  
  
... and many more.
```

Specifying Columns

Querying All Columns in a Table

To print all of a table's columns in the order in which they were stored, specify an asterisk in a SELECT clause.

```
SELECT * FROM table_name;
```

```
SELECT *  
FROM "schema".table_name;
```



Querying Specific Columns in a Table

List the columns that you want and the order to display them in the SELECT clause.

```
SELECT column1, column2, ...  
FROM table_name;
```

```
SELECT "column1", "column2"  
FROM "schema".table_name;
```



Naming a column

Name the new column using the AS keyword.

```
SELECT column1 as name  
FROM table_name;
```

```
SELECT "column1" as name  
FROM "schema".table_name;
```





Table: **jupiter.employee_payroll**

Display: Employee_ID, Salary and create a new Column **Bonus**, which contains an amount equal to 10% of the employee's salary



Table: **exercise.records**

Display: ID, Capital_Gain and create a new Column **Bonus**, which contains an amount equal to 10% of the Capital_Gain

Core Functions



Postgres core functions:

<https://www.postgresql.org/docs/12/functions.html>

Example: floor(), ceil (), log(), position(), substring()



SQLite core functions:

https://www.sqlite.org/lang_corefunc.html

Example: abs(), round(), substr(), trim(), upper()

Creating a Table

Creating and Populating a Table

```
CREATE TABLE table-name AS  
SELECT column1 as name  
FROM table_name;
```



Table: `jupiter.employee_payroll`

Create a table TEMP:

Employee_ID, Salary and Bonus



Table: `exercise.records`

Create a table Exercise.TEMP:

ID, Capital_Gain and Bonus

Specifying Rows

Eliminating Duplicate Rows

Use the *DISTINCT* keyword to eliminate duplicate rows.

```
SELECT distinct Department  
FROM employee_information;
```

The DISTINCT keyword applies to all columns in the SELECT list. One row is displayed for each unique combination of values.

Subsetting with the WHERE Clause

Use a WHERE clause to specify a condition that the data must satisfy **before being selected**.

```
SELECT Department  
FROM employee_information  
WHERE salary > 30000;
```

A WHERE clause is evaluated before the SELECT clause.



Using the previous query:

Display: only those employees who receive bonuses less than \$3000



Using the previous query:

Display: only those employees who receive bonuses greater than \$200

ANSI Standard

One solution is to repeat the calculation in the WHERE clause.

```
proc sql;  
select Employee_ID, Employee_Gender,  
       Salary, Salary*.10 as Bonus  
from jupiter.employee_information  
where Salary*.10<3000;  
quit;
```



ANSI standard

What does the Postgres manual say?



- **SQL standard**: column aliases can be referenced in ORDER BY, GROUP BY and HAVING clauses.
- **However**, in Postgres: An output column's name can be used to refer to the column's value in ORDER BY and GROUP BY clauses, but not in the WHERE or HAVING clauses; there you must write out the expression instead.
- Reference: <https://www.postgresql.org/docs/current/sql-select.html#SQL-SELECT-LIST>

How does SQLite allow it?



- **SQL standard**: column aliases can be referenced in ORDER BY, GROUP BY and HAVING clauses.
- As an **extension**, SQLite also allows column aliases in WHERE and JOIN ON clauses, but again, such usage is non-standard (though very convenient at times).
- Neither the standard nor SQLite implementation allow referencing aliases in the SELECT clause.