

CS23333-Object Oriented Programming Using Java-2023

Quiz navigation

1

2

3

Show one page at a time

Finish review

Status	Finished
Started	Monday, 30 September 2024, 3:34 PM
Completed	Monday, 30 September 2024, 4:27 PM
Duration	53 mins 3 secs

Question 1

Correct

Marked out of 5.00

Flag question

Create a Class Mobile with the attributes listed below,

```
private String manufacturer;
private String operating_system;
public String color;
private int cost;
```

Define a Parameterized constructor to initialize the above instance variables.

Define getter and setter methods for the attributes above.

for example : setter method for manufacturer is

```
void setManufacturer(String manufacturer){
this.manufacturer= manufacturer;
}
```

```
String getManufacturer(){
return manufacturer;}

Display the object details by overriding the toString() method.
```

For example:

Test	Result
1	manufacturer = Redmi operating_system = Andriod color = Blue cost = 34000

Answer: (penalty regime: 0 %)

```
1 public class Mobile{
2     private String manufacturer;
3     private String operating_system;
4     public String color;
5     private int cost;
6     public Mobile(String m,String os,String c,int cost){
7         this.manufacturer=m;
8         this.operating_system=os;
9         this.color=c;
10        this.cost=cost;
11    }
12    void setManufacturer(String manufacturer){
13        this.manufacturer=manufacturer;
14    }
15    void setOperating_system(String os){
16        this.operating_system=os;
17    }
18    void setColor(String c){
19        this.color=c;
20    }
21    void setCost(int cost){
22        this.cost=cost;
23    }
24    String getManufacturer(){
25        return manufacturer;
26    }
27    String getOperating_system(){
28        return operating_system;
29    }
30    String getColor(){
31        return color;
32    }
33    int getCost(){
34        return cost;
35    }
36    public String toString(){
37        return "manufacturer = "+manufacturer+"\n"+operating_system = "+operating_system+"\n"+color = "+color;
38    public static void main(String args[]){
39        Mobile m = new Mobile("Redmi","Andriod","Blue",34000);
40        System.out.println(m.toString());
41    }
42 }
```

	Test	Expected	Got	
✓	1	manufacturer = Redmi operating_system = Andriod color = Blue cost = 34000	manufacturer = Redmi operating_system = Andriod color = Blue cost = 34000	✓

Passed all tests! ✓

Question **2**  
Correct  
Marked out of 5.00  
[Flag question](#)

Create a class called "Circle" with a radius attribute. You can access and modify this attribute using getter and setter methods. Calculate the area and circumference of the circle.

Area of Circle =  $\pi r^2$

Circumference =  $2\pi r$

Input:

2

Output:

Area = 12.57

Circumference = 12.57

For example:

Test	Input	Result
1	4	Area = 50.27 Circumference = 25.13

Answer: (penalty regime: 0 %)

Reset answer

```

1 import java.util.Scanner;
2 class Circle
3 {
4     private double radius;
5     public Circle(double radius){
6         // set the instance variable radius
7         this.radius=radius;
8     }
9
10    public void setRadius(double radius){
11        // set the radius
12        this.radius=radius;
13    }
14
15    public double getRadius()    {
16        // return the radius
17        return radius;
18    }
19
20    public double calculateArea() { // complete the below statement
21        return 3.14159*radius*radius;
22    }
23
24    public double calculateCircumference()    {
25        // complete the statement
26        return 2*3.14159*radius;
27    }
28 }
29 class prog{
30     public static void main(String[] args)  {
31         int r;
32         Scanner sc= new Scanner(System.in);
33         r=sc.nextInt();
34         Circle c= new Circle(r);
35         System.out.println("Area = "+String.format("%.2f", c.calculateArea()));
36         // invoke the calculateCircumference method
37         System.out.println("Circumference = "+String.format("%.2f",c.calculateCircumference()));
38     }
39 }
40
41

```

	Test	Input	Expected	Got	
✓	1	4	Area = 50.27 Circumference = 25.13	Area = 50.27 Circumference = 25.13	✓
✓	2	6	Area = 113.10 Circumference = 37.70	Area = 113.10 Circumference = 37.70	✓
✓	3	2	Area = 12.57 Circumference = 12.57	Area = 12.57 Circumference = 12.57	✓

Passed all tests! ✓

Question **3**  
Correct  
Marked out of 5.00  
[Flag question](#)

Create a class Student with two private attributes, name and roll number. Create three objects by invoking different constructors available in the class Student.

Student()

Student(String name)

Student(String name, int rollno)

Input:

No input

Output:

No-arg constructor is invoked

1 arg constructor is invoked

2 arg constructor is invoked

Name =null , Roll no = 0

Name =Rajalakshmi , Roll no = 0

Name =Lakshmi , Roll no = 101

For example:

Test	Result
1	No-arg constructor is invoked 1 arg constructor is invoked 2 arg constructor is invoked Name =null , Roll no = 0 Name =Rajalakshmi , Roll no = 0 Name =Lakshmi , Roll no = 101

Answer: (penalty regime: 0 %)

```
1 class Student{
2     private String name;
3     private int rollno;
4     public Student(){
5         System.out.println("No-arg constructor is invoked");
6         this.name=null;
7         this.rollno=0;
8     }
9     public Student(String name){
10        System.out.println("1 arg constructor is invoked");
11        this.name=name;
12        this.rollno=0;
13    }
14    public Student(String name,int rollno){
15        System.out.println("2 arg constructor is invoked");
16        this.name=name;
17        this.rollno=rollno;
18    }
19    public void display(){
20        System.out.println("Name =" + name + " ", Roll no = "  +rollno);
21    }
22 }
23 public class prog{
24     public static void main(String args[]){
25         Student s1 = new Student();
26         Student s2 = new Student("Rajalakshmi");
27         Student s3 = new Student("Lakshmi",101);
28         s1.display();
29         s2.display();
30         s3.display();
31     }
32 }
```

	Test	Expected	Got	
✓	1	No-arg constructor is invoked 1 arg constructor is invoked 2 arg constructor is invoked Name =null , Roll no = 0 Name =Rajalakshmi , Roll no = 0 Name =Lakshmi , Roll no = 101	No-arg constructor is invoked 1 arg constructor is invoked 2 arg constructor is invoked Name =null , Roll no = 0 Name =Rajalakshmi , Roll no = 0 Name =Lakshmi , Roll no = 101	✓

Passed all tests! ✓

Finish review