
	<p align="center">Work Instruction for formation of Spoil Banks DO'S</p>	<p>DOC NO. OMC/PRODN/OC/WI/17 ISSUE NO. 01 REV. NO. 00 DATE. 10/01/2018</p>
---	---	--

1. The slope of a spoil bank face shall be determined by the natural angle of repose of the material being deposited but shall in no case exceed 37 degree from the horizontal.
2. A Crater Boulder Wall around Over Burden dump and Concrete wall around Sub-grade and fines dump must be constructed before start of dumping activity in that location.
3. Maximum height of bench should not exceed 30mt.
4. A notice of dangerous occurrence should be given to the inspectorate if there is any indication of on stability of the dumps.

	<p>Work Instruction for formation of Spoil Banks</p> <p>DONT'S</p>	<p>DOC NO. OMC/PRODN/OC/WI/17 ISSUE NO. 01 REV. NO. 00 DATE. 10/01/2018</p>
---	--	--

1. Nobody is permitted to approach the toe of an active spoil bank where he may be endangered from materials rolling dower the face.
2. No slope should be steeper than as stipulated by DGMS
3. The Toe of spoil bank shall not be permitted to approach public roads or building or other permanent structure not belonging to the owner of the mine, closer than a distance equal to the vertical height of the face.
4. The spoil bank face shall not be retained by artificial means at an angle in excess of its natural angle of repose.