

Android Studio

Manju(2401350014)

Code 1: SplashScreen

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:layout_gravity="center"
    android:background="#F8EBEB"
    android:orientation="vertical">

    <ImageView
        android:layout_width="150dp"
        android:layout_height="150dp"
        android:src="@drawable/pic" />

    <TextView
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"

        android:text="Splash Demo"
        android:textSize="24sp"
        android:textStyle="bold"
        android:layout_marginTop="16dp" />
</LinearLayout>
```

```
package com.example.project1java;

import android.content.Intent;
import android.os.Bundle;

import androidx.appcompat.app.AppCompatActivity;

public class SplashActivity extends AppCompatActivity {

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_splash);

        new android.os.Handler().postDelayed(new Runnable() {
            @Override
            public void run() {
                Intent intent = new Intent(SplashActivity.this,
MainActivity.class);
                startActivity(intent);
                finish();
            }
        }, 3000);
    }
}
```

```
}  
  
}
```

Code 2: Fragment

```
<?xml version="1.0" encoding="utf-8"?>  
<FrameLayout xmlns:android="http://schemas.android.com/apk/res/android"  
    xmlns:tools="http://schemas.android.com/tools"  
    android:layout_width="match_parent"  
    android:layout_height="match_parent"  
    tools:context=".BlankFragment">  
  
    <!-- TODO: Update blank fragment layout -->  
    <TextView  
        android:layout_width="match_parent"  
        android:layout_height="match_parent"  
        android:text="@string/hello_blank_fragment" />  
  
</FrameLayout>
```

```
package com.example.project1java;  
  
import android.os.Bundle;  
  
import androidx.fragment.app.Fragment;  
  
import android.view.LayoutInflater;  
import android.view.View;  
import android.view.ViewGroup;  
  
/**  
 * A simple {@link Fragment} subclass.  
 * Use the {@link BlankFragment#newInstance} factory method to  
 * create an instance of this fragment.  
 */  
public class BlankFragment extends Fragment {  
  
    // TODO: Rename parameter arguments, choose names that match  
    // the fragment initialization parameters, e.g. ARG_ITEM_NUMBER  
    private static final String ARG_PARAM1 = "param1";  
    private static final String ARG_PARAM2 = "param2";  
  
    // TODO: Rename and change types of parameters  
    private String mParam1;  
    private String mParam2;  
  
    public BlankFragment() {  
        // Required empty public constructor  
    }
```

```

/**
 * Use this factory method to create a new instance of
 * this fragment using the provided parameters.
 *
 * @param param1 Parameter 1.
 * @param param2 Parameter 2.
 * @return A new instance of fragment BlankFragment.
 */
// TODO: Rename and change types and number of parameters
public static BlankFragment newInstance(String param1, String param2) {
    BlankFragment fragment = new BlankFragment();
    Bundle args = new Bundle();
    args.putString(ARG_PARAM1, param1);
    args.putString(ARG_PARAM2, param2);
    fragment.setArguments(args);
    return fragment;
}

@Override
public void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    if (getArguments() != null) {
        mParam1 = getArguments().getString(ARG_PARAM1);
        mParam2 = getArguments().getString(ARG_PARAM2);
    }
}

@Override
public View onCreateView(LayoutInflater inflater, ViewGroup container,
                         Bundle savedInstanceState) {
    // Inflate the layout for this fragment
    return inflater.inflate(R.layout.fragment_blank, container, false);
}
}

```