

CREATE, INSERT, SELECT

```
CREATE DATABASE DBMS1_2025
```

```
DROP DATABASE DBMS1_2025
```

```
USE DBMS1_2025
```

```
--SYNTAX TO CREATE TABLE
```

```
-- CREATE TABLE TABLENAME
```

```
--(COL1 DATATYPE,
```

```
--COL2 DATATYPE);
```

```
DROP TABLE STUDENT
```

```
CREATE TABLE STUDENT
```

```
(
```

```
    ROLLNO INT,
```

```
    NAME VARCHAR(20)
```

```
);
```

```
SELECT * FROM STUDENT
```

```
-----HOW TO INSERT THE DATA?-----
```

```
--METHOD1: WITH COLUMN NAME
```

```
INSERT INTO STUDENT (ROLLNO,NAME) VALUES (1, 'RAM');
```

```
INSERT INTO STUDENT(NAME,ROLLNO) VALUES ('SHIVAM',2);
```

```
INSERT INTO STUDENT(NAME,ROLLNO) VALUES (3, 'XYZ');
```

```
INSERT INTO STUDENT (NAME) VALUES('MITALI');
```

```
SELECT * FROM STUDENT
```

```
--METHOD2: WITHOUT COLUMN NAME
```

```
--If you're inserting values for all columns in order, you can skip column names
```

```
INSERT INTO STUDENT VALUES (3, 'KIRTI');
```

```
--ERROR
```

```
INSERT INTO STUDENT VALUES ('SHYAM',4)
```

```
--METHOD:3 INSERT MULTIPLE RECORD
```

```
--batch inserts
```

```
INSERT INTO STUDENT VALUES (5, 'MAYA'),(6, 'RESHMA'),(7, 'MAYUR');
```

--INSERT WITH NULL VALUE

```
INSERT INTO STUDENT (NAME) VALUES ('MITAL');
```

```
INSERT INTO STUDENT VALUES(8,NULL);
```

```
INSERT INTO STUDENT VALUES(NULL,NULL);
```

```
INSERT INTO STUDENT VALUES(9, 'AMIT')
```

-----HOW TO FETCH INSERTED DATA?-----

--FATCH ALL THE INSERTED RECORDS

```
SELECT * FROM STUDENT
```

--SELECT SPECIFIC col

```
SELECT ROLLNO  
FROM STUDENT
```

```
SELECT NAME  
FROM STUDENT
```

```
SELECT ROLLNO,NAME  
FROM STUDENT
```

-----SELECT WITH CONDITION-----

```
SELECT ROLLNO, NAME  
FROM STUDENT  
WHERE ROLLNO>5
```

```
SELECT *  
FROM STUDENT  
WHERE NAME='RESHMA'
```

```
SELECT ROLLNO, NAME  
FROM STUDENT  
WHERE ROLLNO=5;
```

-----SELECT WITH NULL-----

--WRONG WAY
--IT WILL NOT RETURN ANY RECORD

```
SELECT * FROM  
STUDENT  
WHERE NAME = NULL
```

--NULL is not a value.

--it cannot be evaluated with the equality (=) operator.
-- it should be checked explicitly with the IS operator

```
SELECT * FROM  
STUDENT  
WHERE NAME IS NULL
```

-----SELECT TOP RECORDS-----

```
SELECT *  
FROM STUDENT
```

```
SELECT TOP 3 *  
FROM STUDENT
```

```
SELECT TOP 10 NAME  
FROM STUDENT
```

--PERCENT

```
SELECT TOP 10 PERCENT *  
FROM STUDENT
```

--SQL Server rounds up, not down. So even though 11% of 10 rows is 1.1, it returns 2 rows.

```
SELECT TOP 11 PERCENT *  
FROM STUDENT
```

-----SELECT UNIQUE RECORD-----

```
SELECT NAME  
FROM STUDENT
```

```
SELECT DISTINCT NAME  
FROM STUDENT
```

--BY DEFAULT DISTINCT DISPLAY THE RESULT IN ASCENDING ORDER

```
SELECT DISTINCT ROLLNO,NAME  
FROM STUDENT
```

```
INSERT INTO STUDENT VALUES(7, 'MAYUR')  
INSERT INTO STUDENT VALUES(7, 'KRISH')  
SELECT *  
FROM STUDENT
```

-----OPERATORS-----

- 1. AND
- 2. OR
- 3. IN / NOT IN
- 4. NOT
- 5. BETWEEN

---AND---

```
SELECT *  
FROM STUDENT  
WHERE NAME='SHIVAM' AND ROLLNO=2
```

```
SELECT *  
FROM STUDENT  
WHERE ROLLNO>2 AND ROLLNO<6
```

---OR---

```
SELECT *  
FROM STUDENT  
WHERE NAME='RAM' OR NAME='SHIVAM'
```

```
SELECT *  
FROM STUDENT  
WHERE ROLLNO=1 OR ROLLNO=2
```

```
SELECT *  
FROM STUDENT  
WHERE ROLLNO=1 OR ROLLNO=2 OR ROLLNO=3
```

-----IN/NOT IN-----

```
SELECT *  
FROM STUDENT  
WHERE ROLLNO IN (1,2,3)
```

```
SELECT *  
FROM STUDENT  
WHERE ROLLNO NOT IN (1,2,3)
```

```
SELECT *  
FROM STUDENT  
WHERE NAME IN ('KIRTI', 'MAYA')
```

---NOT---

```
SELECT *  
FROM STUDENT  
WHERE NOT NAME='SHIVAM'
```

```
SELECT *  
FROM STUDENT  
WHERE NAME <> 'SHIVAM'
```

```
SELECT *  
FROM STUDENT  
WHERE NAME != 'SHIVAM'
```

---BETWEEN---

--BETWEEN IS INCLUSIVE

```
SELECT *  
FROM STUDENT  
WHERE ROLLNO BETWEEN 1 AND 5
```

```
SELECT *  
FROM STUDENT  
WHERE ROLLNO BETWEEN 5 AND 10;
```

-- WRITE QUERY TO DISPLAY STUDENT WHOSE NAME IS EITHER 'RAM' OR 'SHYAM' AND ROLL NO BETWEEN 1 TO 10

```
SELECT *  
FROM STUDENT  
WHERE (NAME='RAM' OR NAME='SHYAM') AND (ROLLNO BETWEEN 1 AND 10)
```

---ODD/EVEN ROLL NO

```
SELECT *  
FROM STUDENT  
WHERE ROLLNO%2=0
```

```
SELECT *  
FROM STUDENT  
WHERE ROLLNO%2!=0
```

---RETRIVE WHOLE TABLE WITHOUT USING * -----

```
SELECT ROLLNO,NAME  
FROM STUDENT
```