

SELECT INTO, UPDATE, DELETE, ALTER, RENAME

USE DBMS1_2025

```
CREATE TABLE EMPLOYEE(  
Name VARCHAR(50),  
City VARCHAR(50),  
Age INT);
```

```
INSERT INTO EMPLOYEE VALUES  
( 'Jay Patel', 'Rajkot', 30),  
( 'Rahul Dave', 'Baroda', 35),  
( 'Jeet Patel', 'Surat', 31),  
( 'Vijay Raval', 'Rajkot', 30);
```

```
SELECT *  
FROM EMPLOYEE
```

--Create table EMPLOYEE_DETAIL from Employee with all the columns and data.

```
SELECT *  
INTO EMPLOYEE_DETAIL  
FROM EMPLOYEE
```

```
SELECT *  
FROM EMPLOYEE_DETAIL
```

```
drop table EMPLOYEE_DETAIL
```

--Create table EMPLOYEE_DATA from Employee with first two columns with no data.

```
SELECT NAME,CITY  
INTO EMPLOYEE_DATA  
FROM EMPLOYEE  
WHERE 1=0
```

```
SELECT *  
FROM EMPLOYEE_DATA
```

-----WITH DIFFERENT cONDITION-----

```
SELECT * INTO EMPLOYEE_DATA1  
FROM EMPLOYEE  
WHERE 2+2=5
```

```
SELECT * FROM EMPLOYEE_DATA1  
-----
```

```
SELECT * INTO EMPLOYEE_DATA2  
FROM EMPLOYEE  
WHERE 2+2=4
```

```
SELECT * FROM EMPLOYEE_DATA2  
-----  
SELECT * INTO Employee_info
```

```
FROM EMPLOYEE
WHERE 'A'='B'
```

```
SELECT * FROM Employee_info
```

```
-----
SELECT * INTO Employee_info1
FROM EMPLOYEE
WHERE 'ABC'='BCD'
```

```
SELECT *
FROM Employee_info1
```

```
-----
SELECT * INTO Employee_info2
FROM EMPLOYEE
WHERE 'A'='a'
```

```
SELECT *
FROM Employee_info2
```

```
SELECT * INTO Employee_info3
FROM EMPLOYEE
WHERE 'AB'='ab'
```

```
-----INSERT-----
--Insert the Data into Employee_info from Employee Whose CITY is Rajkot
SELECT * FROM Employee_info
```

```
INSERT INTO Employee_info
SELECT * FROM EMPLOYEE
WHERE CITY='RAJKOT';
```

```
select * from Employee_info
```

```
--Insert the Data into Employee_info from
--Employee Whose age is more than 32.
```

```
INSERT INTO Employee_info
SELECT * FROM EMPLOYEE
WHERE Age>32;
```

```
---CREATE EMP AND INSERT DATA WHOSE AGE >30 from Employee
```

```
SELECT * INTO EMP
FROM EMPLOYEE
WHERE AGE>30
```

```
SELECT * FROM EMP
```

```
--NOTE
```

```
--Indexes, constraints, and triggers defined in the source table
--are not transferred to the new table using SELECT into statement.
```

-----UPDATE-----

SELECT * FROM EMPLOYEE

--Update age of employee named 'Jay Patel' to 32

```
UPDATE EMPLOYEE
SET AGE=32
WHERE NAME='Jay Patel'
```

--CHANGE CITY OF JAY PATEL TO MORBI

```
UPDATE EMPLOYEE
SET CITY='MORBI'
WHERE NAME='JAY PATEL'
```

SELECT * FROM EMPLOYEE

-- Update age to 33 for all employees from 'Rajkot'

```
UPDATE EMPLOYEE
SET AGE=33
WHERE CITY='RAJKOT'
```

--CHAGE NAME JEET PATEL TO JEET

```
UPDATE EMPLOYEE
SET NAME='JEET'
WHERE NAME='JEET PATEL'
```

-- Update name to jeet p patel and age to 34 of employee from city 'Surat'

```
UPDATE EMPLOYEE
SET Name = 'Jeet P. Patel', Age = 34
WHERE City = 'Surat';
```

--CHANGE NAME OF SURAT TO TEXTILE CITY

```
UPDATE EMPLOYEE
SET CITY='TEXTILE CITY'
WHERE CITY='SURAT'
```

SELECT * FROM EMPLOYEE

-- Increase age by 1 for employees in 'Rajkot' or 'Baroda'

UPDATE EMPLOYEE

SET Age=Age+1

WHERE City IN ('Rajkot', 'Baroda');

-- Set city to 'Ahmedabad'

--where age is 34 and city is 'TEXTILE CITY'

UPDATE EMPLOYEE

SET City = 'Ahmedabad'

WHERE Age = 34 AND City = 'TEXTILE CITY';

--SET AGE NULL

UPDATE EMPLOYEE

SET AGE=NULL

WHERE NAME='JAY PATEL'

--UPDATE SAME VALUE IN ALL RECORD

UPDATE EMPLOYEE

SET AGE=25

SELECT *

FROM EMPLOYEE

-----DELETE-----

CREATE TABLE EMPLOYEE(

Name VARCHAR(50),

City VARCHAR(50),

Age INT);

DELETE from

EMPLOYEE

INSERT INTO EMPLOYEE VALUES

('Jay Patel', 'Rajkot', 30),

('Rahul Dave', 'Baroda', 35),

('Jeet Patel', 'Surat', 31),

('Soham Raval', 'Valsad', 30),

('Meet Shah', 'Baroda', 35),

('Milan Patel', 'Vapi', 31),

('Kiran Manek', 'Ahmedabad', 30),

('Mitesh Patel', 'Kalol', NULL);

--DELETE EMPLOYEE FROM RAJKOT

DELETE FROM EMPLOYEE

WHERE CITY='RAJKOT'

select * from EMPLOYEE

--REMOVE THE RECORD WHOSE AGE IS 30

DELETE FROM EMPLOYEE

```
WHERE AGE=30
```

```
SELECT * FROM EMPLOYEE
```

```
--REMOVE RECORD WHOSE CITY IS BARODA AND AGE IS 35
```

```
DELETE FROM EMPLOYEE
```

```
WHERE CITY='BARODA' AND AGE=35
```

```
-- DELETE WITH IN AND OR OPERATOR
```

```
DELETE FROM EMPLOYEE
```

```
WHERE CITY IN ('VAPI', 'AHMEDABAD')
```

```
DELETE FROM EMPLOYEE
```

```
WHERE CITY='VAPI' OR CITY='AHMEDABAD'
```

```
--DELETE where Age is NULL
```

```
DELETE FROM EMPLOYEE
```

```
WHERE AGE IS NULL
```

```
--DELETE ALL RECORDS
```

```
DELETE FROM
```

```
EMPLOYEE
```

```
select * from EMPLOYEE
```

```
-----ALTER-----
```

```
--ALTER is used to add, modify, or drop columns in a table
```

```
SELECT * FROM EMPLOYEE
```

```
DROP TABLE EMPLOYEE
```

```
CREATE TABLE EMPLOYEE(
```

```
Name VARCHAR(50),
```

```
City VARCHAR(50),
```

```
Age INT);
```

```
INSERT INTO EMPLOYEE VALUES
```

```
('Jay Patel', 'Rajkot', 30),
```

```
('Rahul Dave', 'Baroda', 35),
```

```
('Jeet Patel', 'Surat', 31),
```

```
('Soham Raval', 'Valsad', 30),
```

```
('Meet Shah', 'Baroda', 35),
```

```
('Milan Patel', 'Vapi', 31),
```

```
('Kiran Manek', 'Ahmedabad', 30),
```

```
('Mitesh Patel', 'Kalol', NULL);
```

```
--ADD COLUMNS
```

```
---ADD COLUMN SALARY
```

```
ALTER TABLE EMPLOYEE
```

```
ADD SALARY DECIMAL(8,2);
```

```
SELECT * FROM EMPLOYEE
```

```
--ADD COLUMNS DEPARTMENT AND DESIGNATION
```

```
select *  
from EMPLOYEE
```

```
ALTER TABLE EMPLOYEE
```

```
ADD DEPARTMENT VARCHAR(20),DESIGNATION VARCHAR(20)
```

```
--ADD COLUMN MOBILE AND ADDRESS
```

```
ALTER TABLE EMPLOYEE
```

```
ADD MOBILE VARCHAR(20), ADDRESS VARCHAR(50)
```

```
SELECT * FROM EMPLOYEE
```

```
-----  
update employee  
set salary=123.45  
where age>=30
```

```
---- DROP COLUMN
```

```
ALTER TABLE EMPLOYEE
```

```
DROP COLUMN MOBILE
```

```
SELECT * FROM EMPLOYEE
```

```
--DROP MULTIPLE COULMNS
```

```
ALTER TABLE EMPLOYEE
```

```
DROP COLUMN DESIGNATION,ADDRESS
```

```
select *  
from employee
```

```
-----MODIFY COLUMN
```

```
ALTER TABLE EMPLOYEE
```

```
ALTER COLUMN CITY CHAR(30)
```

```
ALTER TABLE EMPLOYEE
```

```
ALTER COLUMN NAME CHAR(20)
```

```
select *  
from EMPLOYEE
```

```
ALTER TABLE EMPLOYEE
```

```
ALTER COLUMN AGE DECIMAL(5,2)
```

```
SELECT * FROM EMPLOYEE
```

--LEAD TO DATA LOSS

```
ALTER TABLE EMPLOYEE  
ALTER COLUMN SALARY INT
```

--ERROR

```
ALTER TABLE EMPLOYEE  
ALTER COLUMN CITY INT
```

--CHANGE AGE TO VARCHAR (Will work, but Wrong Practice)

```
ALTER TABLE EMPLOYEE  
ALTER COLUMN AGE VARCHAR(10)
```

```
SELECT * FROM EMPLOYEE
```

```
drop table EMPLOYEE
```

---IMPLICIT TYPE CASTING FROM VARCHAR DATA TYPE TO INT DONE BY SQL SERVER

```
UPDATE EMPLOYEE  
SET AGE=AGE+5  
WHERE NAME='jeet patel'
```

```
INSERT INTO EMPLOYEE VALUES ('SOHAM', 'RAJKOT', 'A')
```

```
SELECT * FROM  
EMPLOYEE
```

```
UPDATE EMPLOYEE  
SET AGE=AGE+5  
WHERE NAME='SOHAM'
```

--ADD MOBILE COLUMN

```
ALTER TABLE EMPLOYEE  
ADD MOBILE decimal(8,2)
```

```
SELECT * FROM EMPLOYEE
```

```
SP_HELP EMPLOYEE
```

-----RENAME-----

--sp_rename system stored procedure lets you rename
--various database objects—including tables, columns

```
SELECT *  
FROM EMPLOYEE
```

--RENAME COLUMN MOBILE TO CONTACTNO

```
SP_RENAME 'EMPLOYEE.MOBILE', 'CONTACTNO'
```

```
--WHY WARNING????????????
```

```
--When you rename a table, column, or any object,  
--SQL Server doesn't update references inside  
--stored procedures, views, scripts, functions, triggers, or other modules  
--That message is Microsoft's way of reminding you to check and fix dependent code  
manually.
```

```
--RENAME TABLE NAME
```

```
SP_RENAME 'EMPLOYEE', 'EMPLOYEE_MASTER'
```

```
--CHANGE THE NAME EMPLOYEE_MASTER TO EMP_INFO
```

```
SP_RENAME 'EMPLOYEE_MASTER', 'EMP_INFO'
```

```
SELECT * FROM EMP_INFO
```

```
-----TRUNCATE-----
```

```
--TRUNCATE deletes all rows in one go, not one by one row
```

```
TRUNCATE TABLE EMP_INFO
```

```
select * from emp_info
```

```
--DROP
```

```
DROP TABLE EMP_INFO
```

```
DROP DATABASE DEMO
```

```
DROP TABLE EMPLOYEE
```

```
-----  
CREATE TABLE EMPLOYEE(  
Name VARCHAR(50),  
City VARCHAR(50),  
Age INT);
```

```
INSERT INTO EMPLOYEE VALUES  
( 'Jay Patel', 'Rajkot', 30),  
( 'Rahul Dave', 'Baroda', 35),  
( 'Jeet Patel', 'Surat', 31),  
( 'Soham Raval', 'Valsad', 30),  
( 'Meet Shah', 'Baroda', 35),  
( 'Milan Patel', 'Vapi', 31),  
( 'Kiran Manek', 'Ahmedabad', 30),  
( 'Mitesh Patel', 'Kalol', NULL);
```


--DIFFERENCE---

select * from employee

--DELETE WITH CONDITION

DELETE FROM

EMPLOYEE

WHERE CITY='RAJKOT'

SELECT * FROM EMPLOYEE

---DELETE ALL RECORDS

delete from EMPLOYEE

---DELETE ALL RECORDS USING TRUNCATE

TRUNCATE TABLE

EMPLOYEE

SELECT *

FROM EMPLOYEE

--STRUCTURE OF TABLE IS STILL EXIST

--DROP

DROP TABLE EMPLOYEE