



Society of Petroleum Engineers

SPE-227636-MS

Review of Temperature Stabilization for Logging Operations in High-Pressure High-Temperature Wells

K. Alturkey, F. Hunaidi, M. Alarfaj, and M. Alharbi, Saudi Aramco, Dhahran, Saudi Arabia

Copyright 2025, Society of Petroleum Engineers DOI [10.2118/227636-MS](https://doi.org/10.2118/227636-MS)

This paper was prepared for presentation at the Middle East Oil, Gas and Geosciences Show (MEOS GEO), Manama, Bahrain, 16 – 18 September 2025.

This paper was selected for presentation by an SPE program committee following review of information contained in an abstract submitted by the author(s). Contents of the paper have not been reviewed by the Society of Petroleum Engineers and are subject to correction by the author(s). The material does not necessarily reflect any position of the Society of Petroleum Engineers, its officers, or members. Electronic reproduction, distribution, or storage of any part of this paper without the written consent of the Society of Petroleum Engineers is prohibited. Permission to reproduce in print is restricted to an abstract of not more than 300 words; illustrations may not be copied. The abstract must contain conspicuous acknowledgment of SPE copyright.

Abstract

The performance and reliability of logging tools are greatly affected by increased pressures and temperatures. As downhole temperature exceeded 300F and pressure increased above 20,000 psi, logging tools electronics, insulation, and sensor systems face degradation that compromises data quality and efficiency. This review explores the primary failure mechanisms of logging tools in High-Pressure-High-Temperature, HPHT, wells, including semiconductor breakdown, insulation loss, sensor malfunction, and mechanical fatigue. The paper then examines wellbore heat transfer mechanisms and the role of drilling fluids in thermal management. It also brings to light the thermophysical properties under HPHT conditions that influence logging tool behavior. Successful adaptation of water-based mud systems for high-temperature resilience are presented in several examples from offshore, gas shale, and sour gas wells. The work highlights the new approaches of the integration of shield-like particles and encapsulated phase change materials (PCMs) into drilling fluids to stabilize temperature profiles during logging. The review concludes by emphasizing the importance of fluid design, thermal modeling, and materials engineering in extending tool longevity and improving the accuracy of logging operations under HPHT conditions.

Introduction

The oil and gas industry continues to push the technological boundaries by drilling deeper, hotter, and more geologically complex wells. As these challenging HPHT reservoirs become the norm rather than the exception, downhole tool integrity and functionality are increasingly threatened by extreme conditions. Logging tools, which are indispensable for formation evaluation, are particularly susceptible to high temperatures, with many modern systems unable to function reliably beyond 300 to 400°F (149–204°C) and high-pressure range of 10,000 to 20,000 psi [1]. Failure modes for logging tools in HPHT wells include semiconductor degradation, thermal expansion-induced mechanical failures, insulation breakdown, and sensor drift. These failures not only compromise the accuracy of well logging data but also escalate operational costs due to tool retrieval, replacement, or even potential nonproductive time (NPT) [2], [3], [4], [5]. This review explores various strategies and technologies developed to address these challenges. The article begins by discussing the limitations of current logging tools under HPHT conditions and their failure mechanisms. It then provides a detailed review of HPHT drilling fluids development, highlighting

several examples where innovative water-based mud systems were deployed successfully. The following section examines the mechanisms of heat transfer and the role of drilling fluids in thermal control during logging operations. Then, the paper will introduce shield-like particles and phase change materials (PCMs) that are aimed at enhancing heat insulation and extending logging tool life.

Logging Tools Limitations in HPHT Conditions

Logging tools rely heavily on sensitive electronic and mechanical components. The failure mechanisms in HPHT conditions often revolve around thermal degradation of semiconductors, loss of insulation, mechanical fatigue, and sensor malfunction. Thermal degradation of semiconductors in downhole electronics occurs as the thermal stress accelerates material aging following the Arrhenius model, doubling failure rates with every 10°C increase. Degradation mechanisms include breakdown of wire bonds, encapsulants, and fire retardants, as well as latching phenomena where devices lose switching function. Silicon die usually is not severely damaged as the packaging materials and interconnects. Efficient heat dissipation may enhance long-term reliability under harsh downhole conditions [6]. Loss of insulation caused by grounding the metallic pipe wall and logging tool leads to short-circuit effects where current leaks into the metal surfaces instead of passing through the fluid. This distorts the sensitivity field degrading data quality and introducing noise. Both the logging tool and pipe wall should be electrically insulated to ensure uniform sensitivity and accurate readings [7]. Further, mechanical fatigue weakens material strength, accelerate corrosion, and degrades elastomers and electronics. Drilling vibration and thermal cycling lead to frequent tool failures, data loss, and compromised performance [4]. Logging tools sensor malfunctions typically originate from thermal degradation and pressure-related mechanical stress. Elevated downhole temperatures accelerate internal electronics aging and cause signal drift as sensor materials change properties [3].

Heat Transfer in the Wellbore

Heat in a wellbore transfer through conduction, convection, and radiation. Yet, thermal conduction and advection are the predominant heat transfer mechanisms in the wellbore and formation. Radiation heat transfer considered negligible [8]. Conduction is the heat flow through static fluids and solids. After drilling stops, the borehole gradually regains the true formation temperature. This process is slow because it occurs via heat conduction which is less efficient than heat convection. In contrast, convection is the heat transfer by moving fluids. It can quickly change wellbore temperatures. Circulating cold mud, for example, cools the wellbore down very efficiently via heat convection and an influx of hotter reservoir fluid can similarly raise the borehole temperature [9]. Such convective changes produce distinctive log variances as most anomalies are related to the entry of fluids into the borehole or fluid exit into the formation. These heat transfer mechanisms directly impact thermal measurements and logging accuracy. While drilling, downhole temperature readings underestimate the formation temperature due to mud cooling and logs read low until conductive heating from the formation restores equilibrium.

Drilling Fluids as Heat Carriers

Drilling fluids carry heat away from the formation as they countercurrent heat exchanger. The rate of heat exchange depends on the temperature, thermal conductivity and specific heat capacity and on the velocity of the drilling fluids [9]. These fluids absorb heat from drill bit and formation and transport it along the wellbore to cooler regions or surface equipment. Under HPHT conditions, the thermophysical properties of drilling fluids such as thermal conductivity, specific heat capacity, and viscosity undergo significant changes that impact their ability to dissipate heat effectively. Water-based muds have high heat capacity but may degrade due to polymer breakdown. Oil-based muds on the other hand can thicken or undergo phase change which can hinder the flow and heat transport. These thermal shifts influence logging tools in different ways: resistivity tools suffer from electronic overheating and conductivity noise; acoustic tools

experience signal distortion due to temperature-dependent changes in fluid compressibility; and nuclear tools face calibration drift from thermal expansion and hydrogen index variation. Logging-while-drilling (LWD) and wireline tools are particularly vulnerable during static periods when convective cooling is minimal. Effective thermal management requires integration of fluid design with tool deployment strategies. However, advanced formulations for HPHT environments are being explored to improve heat transfer and protect sensitive electronics.

Logging Examples Using Drilling Fluids

Water-Based Mud Evolution

In this example [10], the offshore wells encountered temperatures up to 338°F (170°C) and pressures up to 12,000 psi. A series of water-based drilling fluids were developed to address bit balling, shale inhibition, lubricity, borehole stability, and thermal stability. The iterative development of these mud systems resulted in improved filtration control and enhanced filter cake quality. This enabled successful wireline logging runs even in HPHT conditions. Adjustments to polymer formulations, fluid additives, and particle size distributions were crucial in managing thermal stability and hole cleaning performance.

Gas Shale

Gas wells exhibited bottomhole temperatures up to 500°F (260°C) and pressures of 25,000 psi (172.4 MPa) [11]. Extensive laboratory testing was conducted on offset wells to design a unique high-temperature water-based system. In one example, a horizontal section was drilled at 6,120 meters with LWD tools operating successfully at 157°C. This success validated the use of polymer brine-based fluids in deep unconventional HPHT reservoirs.

Sour Gas Development

In the sour gas development example [12], there were many challenges such as high temperatures up to 380°F (193°C), severe losses, HP influx, reactive shales, and barite sag. The deployment of a novel high-temperature polymer water-based mud system enabled successful drilling in several drilling sections, including a critical 6" section with stable fluid properties maintained for 162 hours at 375°F. The absence of barite in this section further enhanced the logging data quality by minimizing solid settling and improving LWD performance.

Filtration-Control Polymer Development

A synthetic polymer fluid loss additive was engineered for brine-based drill-in fluids. This polymer demonstrated thermal stability exceeding 400°F in monovalent and divalent brine systems. The advanced polymer structure-maintained filtration control while preserving drilling fluid stability even under extreme HPHT conditions [13].

Shield-like Particles and Phase Change Materials (PCMs)

An emerging concept that is proposing injecting encapsulated phase-change materials (PCMs) into the drilling fluid prior to logging. The logging proposed to be completed before the temperature increases to a point that could damage logging tools or affect the accuracy of measurements. Phase-change materials (PCMs) are substances that absorb and store thermal energy while undergoing a phase transition, typically from solid to liquid, at a specific, nearly constant temperature [14]. This property, coupled with high latent heat, heat absorbed or released during phase changes, makes PCMs ideal for thermal energy storage applications [15]. The specific temperature at which PCMs undergo phase changes dictates their suitability for various applications, including temperature regulation in wellbore environments. PCMs are classified into three main categories: organic, inorganic, and eutectic. Organic PCMs include paraffin and non-

paraffin types, which are widely employed for thermal energy storage due to their non-corrosive nature and congruent melting behavior [16]. While organic PCMs are effective, their melting points tend to be relatively low, limiting their use in high-temperature environments. In contrast, inorganic PCMs like salt hydrates, metals, and alloys have higher melting points, greater latent heat, and higher thermal conductivity [17].

These characteristics make inorganic PCMs particularly suitable for managing the extreme temperatures encountered in high-temperature high-pressure (HTHP) drilling operations, offering a significant advantage in wellbore thermal management. Encapsulation enhances heat transfer by increasing the surface area of PCM while reducing its reactivity with the surrounding environment. This technique also helps mitigate subcooling effects and regulates the volume change of PCM materials during phase transitions, ensuring more stable thermal performance [18]. Encapsulation methods are typically categorized into two forms: core-shell and shape-stabilized PCMs (CS-PCMs and SSPCMs, respectively). These microcapsules assist with taking in heat through latent heat storage. PCM capsules maintain stable temperature profile that will protect logging tools without negatively affecting rheology or drilling fluids properties [19]. Organic phase change materials are known for their passive thermal management ability. They have large latent heat capacity which make them suitable for cooling down systems with elevated temperatures. A relevant example from the literature [20] is the experimental comparison of erythritol and P130, two organic PCMs tested with 3D-printed metal structures to improve cooling efficiency under high temperature conditions. The study concluded with the importance of PCM selection that are tailored for efficient heat storage.

Degradation phenomena represent a great challenge for PCMs affecting their cooling efficiency. Chemical and physical degradations are among the main mechanisms that affect heat storage repeatability, can be reflected on circulation of drilling fluids. Chemical degradation is associated with agents like oxidizers as organic PCMs such as paraffins and fatty acids are prone to oxidative reactions. Inorganic PCMs, like salt hydrates, however, chemical instability comes from balancing hydration and dehydration. Physical degradation equally affects PCMs ability to store heat. An example of this mechanism is phase separation which occurs due to density differences or incomplete crystallization as heavier or non-crystallizing components tend to separate out during heat transfer cycles. To overcome degradation challenges, stabilizers and barrier liners limit unfavorable chemical reactions. Also, nucleating agents and thickeners address physical issues. This highlights the importance of encapsulation for enhanced protection, stability, and thermal performance mentioned earlier [21].

Conclusion

Temperature stabilization remains a critical challenge in ensuring the reliability of logging operations in HPHT wells. This review has outlined how elevated downhole temperatures accelerate failure modes such as semiconductor degradation, insulation breakdown, and sensor drift, necessitating robust thermal stabilization approaches. Conventional water and oil based muds serve as primary heat carriers, but they are affected by temperatures variations that decrease their cooling efficiency. Examples presented the importance of tailoring drilling fluids formulations and the positive effect of incorporating advanced additives and polymer technologies. Furthermore, this work suggests the use of encapsulated phase change materials as they represent promising enhanced latent heat absorption. Properly engineered systems offer passive, non-invasive temperature control that extends tool operational windows without compromising drilling fluid properties. Yet, the success of these innovations depends on the material stability of PCMs especially for repeated thermal cycling and their integration within drilling fluids. The end goal of this ongoing efforts on fluid-PCM compatibility, encapsulation methods, and high-temperature performance is to develop enduring field-scale applications to overcome HPHT limitations. These developments set corner stone for improving the thermal resilience of logging tools and improving formation evaluation in extreme HPHT environments.

References

1. W. E. Odiete, "New wellbore temperature control design for preventing failure and poor performance of logging tools in high pressure – high temperature wells," *Heliyon*, vol. **8**, no. 5, p. e09404, May 2022, doi: [10.1016/j.heliyon.2022.e09404](https://doi.org/10.1016/j.heliyon.2022.e09404).
2. K. A. MacDonald, "Failure analysis of drillstring and bottom hole assembly components," *Eng Fail Anal*, vol. **1**, no. 2, pp. 91–117, Jun. 1994, doi: [10.1016/1350-6307\(94\)90010-8](https://doi.org/10.1016/1350-6307(94)90010-8).
3. M. S. Khaled, N. Wang, P. Ashok, D. Chen, and E. van Oort, "Strategies for Prevention of Downhole Tool Failure Caused by High Bottomhole Temperature in Geothermal and High-Pressure/High-Temperature Oil and Gas Wells," *SPE Drilling & Completion*, vol. **38**, no. 02, pp. 243–260, Jun. 2023, doi: [10.2118/212550-PA](https://doi.org/10.2118/212550-PA).
4. P. H. Shah, H. T. Pandya, H. Sharma, and A. Saxena, "Offshore Drilling & Well Testing Of A HPHT Gas Well: A Case Study," in *SPE Oil and Gas India Conference and Exhibition*, SPE, Mar. 2012. doi: [10.2118/155320-MS](https://doi.org/10.2118/155320-MS).
5. I. Lunney, A. Duriez, T. Solbakk, M. B. Skaug, and T. Brian, "Harsh Environment Logging-While-Drilling Tools Enhance Well Performance in North Sea HPHT Wells," in *SPE Europepec featured at 79th EAGE Conference and Exhibition*, SPE, Jun. 2017. doi: [10.2118/185866-MS](https://doi.org/10.2118/185866-MS).
6. R. Beckwith, "Downhole Electronic Components: Achieving Performance Reliability," *Journal of Petroleum Technology*, vol. **65**, no. 08, pp. 42–57, Aug. 2013, doi: [10.2118/0813-0042-JPT](https://doi.org/10.2118/0813-0042-JPT).
7. H. ZHOU, L. XU, Z. CAO, J. HU, and X. LIU, "Image Reconstruction for Invasive ERT in Vertical Oil Well Logging," *Chin J Chem Eng*, vol. **20**, no. 2, pp. 319–328, Apr. 2012, doi: [10.1016/S1004-9541\(12\)60394-2](https://doi.org/10.1016/S1004-9541(12)60394-2).
8. G. Nalla, G. M. Shook, G. L. Mines, and K. K. Bloomfield, "Parametric sensitivity study of operating and design variables in wellbore heat exchangers," *Geothermics*, vol. **34**, no. 3, pp. 330–346, Jun. 2005, doi: [10.1016/j.geothermics.2005.02.001](https://doi.org/10.1016/j.geothermics.2005.02.001).
9. M. Amani, M. Al-Jubouri, and A. Shadravan, "Comparative Study of Using Oil-Based Mud Versus Water-Based Mud in HPHT Fields," 2012, doi: [10.3968/j.aped.1925543820120402.987](https://doi.org/10.3968/j.aped.1925543820120402.987).
10. L. Moroni, K. Fatkullin, and B. Tran Thanh, "Evolution of a Versatile HTHP Water-Based Drilling Fluid Improved Drilling Efficiency Offshore Vietnam," in *SPE/IATMI Asia Pacific Oil & Gas Conference and Exhibition*, SPE, Oct. 2023. doi: [10.2118/215251-MS](https://doi.org/10.2118/215251-MS).
11. G. Manescu, B. Veer, P. Balakrishnan, C. Arena, B. Allias, and C. Eyaa, "A Water-Base Drilling Fluid for Controlling Deep-Reservoir Extreme Conditions in an Abu Dhabi Gas Shale Play," in *Proceedings of the 2021 Asia Pacific Unconventional Resources Technology Conference*, Tulsa, OK, USA: Unconventional Resources Technology Conference, 2021. doi: [10.15530/AP-URTEC-2021-208307](https://doi.org/10.15530/AP-URTEC-2021-208307).
12. T. Hasan Hamdan et al, "New Generation of HTHP Water Based Drilling Fluid Changing Conventional Drilling Fluids Solutions," in *Abu Dhabi International Petroleum Exhibition & Conference*, SPE, Nov. 2020. doi: [10.2118/203439-MS](https://doi.org/10.2118/203439-MS).
13. R. G. Ezell, A. M. Ezzat, J. K. Turner, and J. J. Wu, "New Filtration-Control Polymer for Improved Brine-Based Reservoir Drilling-Fluids Performance at Temperatures in Excess of 400°F and High Pressure," in *SPE International Symposium and Exhibition on Formation Damage Control*, SPE, Feb. 2010. doi: [10.2118/128119-MS](https://doi.org/10.2118/128119-MS).
14. R. Huang, Z. Li, W. Hong, Q. Wu, and X. Yu, "Experimental and numerical study of PCM thermophysical parameters on lithium-ion battery thermal management," *Energy Reports*, vol. **6**, pp. 8–19, Dec. 2020, doi: [10.1016/j.egy.2019.09.060](https://doi.org/10.1016/j.egy.2019.09.060).
15. W. Wu, W. Wu, and S. Wang, "Thermal management optimization of a prismatic battery with shape-stabilized phase change material," *Int J Heat Mass Transf*, vol. **121**, pp. 967–977, Jun. 2018, doi: [10.1016/j.ijheatmasstransfer.2018.01.062](https://doi.org/10.1016/j.ijheatmasstransfer.2018.01.062).

16. G. Righetti et al, "Experimental investigation of high temperature organic phase change materials for waste heat recovery," *International Journal of Thermofluids*, vol. **28**, p. 101293, Jul. 2025, doi: [10.1016/j.ijft.2025.101293](https://doi.org/10.1016/j.ijft.2025.101293).
17. X. Yao, C. Shi, S. Zhu, B. Wang, W. Hao, and D. Zou, "Thermal performance enhancement of ceramics based thermal energy storage composites containing inorganic salt/metallic micro-encapsulated phase change material," *Solar Energy Materials and Solar Cells*, vol. **288**, p. 113645, Aug. 2025, doi: [10.1016/j.solmat.2025.113645](https://doi.org/10.1016/j.solmat.2025.113645).
18. H. Zhang et al, "Thermal management of drilling fluids with phase change materials in ultra-high temperature wells," *Appl Therm Eng*, vol. **274**, p. 126601, Sep. 2025, doi: [10.1016/j.applthermaleng.2025.126601](https://doi.org/10.1016/j.applthermaleng.2025.126601).
19. J. Su, S. Li, and Y. Tan, "Performance evaluation and feasibility analysis of new phase change microcapsules in drilling fluid cooling," *Colloids Surf A Physicochem Eng Asp*, vol. **722**, p. 137253, Oct. 2025, doi: [10.1016/j.colsurfa.2025.137253](https://doi.org/10.1016/j.colsurfa.2025.137253).
20. G. Righetti et al, "Experimental investigation of high temperature organic phase change materials for waste heat recovery," *International Journal of Thermofluids*, vol. **28**, p. 101293, Jul. 2025, doi: [10.1016/j.ijft.2025.101293](https://doi.org/10.1016/j.ijft.2025.101293).
21. O. M. Adesusi et al, "A comprehensive review of the materials degradation phenomena in solid-liquid phase change materials for thermal energy storage," *International Journal of Thermofluids*, vol. **18**, p. 100360, May 2023, doi: [10.1016/j.ijft.2023.100360](https://doi.org/10.1016/j.ijft.2023.100360).