Evaluation of German NER Tools on Medical Admission Notes

AP: NER tools for German medical text SoSe 2017

Ph. Richter-Pechanski

September 16, 2017

Content

- Introduction
 - Problem Definition
- Data & Tools
 - Tools
 - Training data
 - MEDICATION Class
 - Test Data
- Training and Experiments
- 4 Evaluation
- Summary

NER in Medical Texts

In comparison to other domains, named entity recognition (NER) on German medical texts is still an almost unexplored research area. (Sterlinger 2016)

Reasons for that are:

• Lack of shared medical corpora, as they must be anonymized first

Reasons for that are:

- Lack of shared medical corpora, as they must be anonymized first
- Lack of annotated corpora

Reasons for that are:

- Lack of shared medical corpora, as they must be anonymized first
- Lack of annotated corpora
- Challenges in German syntax (capitalization, morphology)

Reasons for that are:

- Lack of shared medical corpora, as they must be anonymized first
- Lack of annotated corpora
- Challenges in German syntax (capitalization, morphology)
- Still just a few cooperations between medical and computer science institutions

Additionally there are some major challenges in research on medical texts:

Medical texts are free texts

- Medical texts are free texts
- Occasionally even hand-written

- Medical texts are free texts
- Occasionally even hand-written
- Sometimes semi-structured

- Medical texts are free texts
- Occasionally even hand-written
- Sometimes semi-structured
- Contain non-standarized and ambiguous abbreviations

- Medical texts are free texts
- Occasionally even hand-written
- Sometimes semi-structured
- Contain non-standarized and ambiguous abbreviations
- Varying and sometimes even locally specific terminology

This project investigated German NER tools and their performance on medical texts.

Following steps had been accomplished:

Evaluation of state of the art NER tools

This project investigated German NER tools and their performance on medical texts.

- Evaluation of state of the art NER tools
- Comparison of their performance on out-of-domain data sets

This project investigated German NER tools and their performance on medical texts.

- Evaluation of state of the art NER tools
- Comparison of their performance on out-of-domain data sets
- Training of NER models on available German NER corpora

This project investigated German NER tools and their performance on medical texts.

- Evaluation of state of the art NER tools
- Comparison of their performance on out-of-domain data sets
- Training of NER models on available German NER corpora
- Evaluation of these models on medical admission notes

This project investigated German NER tools and their performance on medical texts.

- Evaluation of state of the art NER tools
- Comparison of their performance on out-of-domain data sets
- Training of NER models on available German NER corpora
- Evaluation of these models on medical admission notes
- Assessment of the valuability of these tools for anonymization of medical texts

 Previous work showed that the Stanford NER tool performed best on out-of-domain data sets (Richter-Pechanski 2017)

- Previous work showed that the Stanford NER tool performed best on out-of-domain data sets (Richter-Pechanski 2017)
- Today we focus on evaluation of this tool on medical admission notes

Tools

- Python 3 (comfortable handling of UTF-8 text)
- German Stanford NER (Pado 2010)
- Stanford PTBTokenizer (Tokenizing the medical texts)
- Bash tools for preprocessing and corpus analysis
- extract_corpus.py (Create new corpus from GermaEval, CoNLL and EP and mixes in medical entities)
- evaluation.py (Evaluation script using Scikit Learn library)
- several converter script, for converting GermEval, CoNLL and European Parliament data into Stanford NER compatible data

 Bypassing lack of annotated medical texts by using out-of-domain data

LOC Locations

ORG Organizations

PER Persons

- Bypassing lack of annotated medical texts by using out-of-domain data
- Combining existing data sets to get larger training sets.

LOC Locations

ORG Organizations

PER Persons

- Bypassing lack of annotated medical texts by using out-of-domain data
- Combining existing data sets to get larger training sets.
- Two German training corpora typically used in German NER research

LOC Locations

ORG Organizations

PER Persons

- Bypassing lack of annotated medical texts by using out-of-domain data
- Combining existing data sets to get larger training sets.
- Two German training corpora typically used in German NER research
- As named entity classes we adapted the classes used in the CoNLL 2003 corpus. (exluding MISC class)

LOC Locations

ORG Organizations

PER Persons

CoNLL 2003

- German CoNLL 2003: Selected texts from German newspaper Frankfurter Rundschau
- 206.931 tokens in 12.705 sentences

LOC ORG PER 4.363 2.427 2.773

Table: Absolute amount of entity tokens per entity in CoNLL 2003

GermEval 2014

- GermEval 2014 data set contains text from German Wikipedia articles and online news texts
- 590.000 tokens in 24.000 sentences

LOC	ORG	PER
12.791	9.889	12.423

Table: Absolute amount of entity tokens per entity in GermEval

In addition we used a small data set (around 20.000 tokens) from the European Parliament annotated by Sebastian Pado.

MEDICATION Class

- As a sub-task we mixed in a list of drugs often used in cardiology
- Randomly inserted fixed amount of drugs without semantic context into the data set and annotated these as 'MEDICATION'

Example extract with MEDICATION class

Barack LOC Obama LOC erhält O

Aspirin MEDICATION

Friedensnobelpreis MISC

Table: MEDICATION entity token including class label

Medical Test Data

Our medical data in this project consists of medical admission notes.

• Contain texts from cardiology domain

Medical Test Data

Our medical data in this project consists of medical admission notes.

- Contain texts from cardiology domain
- Let us have a look at an example

How does a Medical admission note look like?

Sehr geehrte Kollegen,

wir berichten über Ihre Patientin <PER>, geboren am <DATE>, wh. <LOC>, die sich am <DATE> in unserer Ambulanz vorstellte.

Diagnosen:

Aktuell: Operabilität mit leicht erhöhtem Risiko gegeben

Z.n. 2x Herzkatheter-Untersuchung, zuletzt <DATE> (anamnestisch Z.n. HWS-Eingriff <DATE> (<LOC>), Versuch der Stabilisierung Anamnestisch OP bei intracranieller Blutung <DATE>

Anamnese:

Die Vorstellung der Patientin erfolgte zur präoperativen kardiologischen Abklärung vor geplanter HWS-Operation. Die Patientin berichtet von reduzierter körperlicher Belastbarkeit im Alltag (2 Etagen, NYHAII-III) auch beim Bergauflaufen Belastungsdyspnoe, im Verlauf jedoch konstant, keine belastungsinduzierten pectanginösen Beschwerden.

Kardiovaskuläre Risikofaktoren: Arterielle Hypertonie, Nikotin (sistiert vor 20 Jahren, 2PY), Diabetes mellitus Typ 2 (diätetisch eingestellt)

Following basic structure in majority of notes

Header

- Header
 - Addressee

- Header
 - Addressee
 - Sender

- Header
 - Addressee
 - Sender
 - Patients name and address

- Header
 - Addressee
 - Sender
 - Patients name and address
- Salutation

Additionally, not always in same order, following subsections appear in a majority of notes:

Additionally, not always in same order, following subsections appear in a majority of notes:

- Diagnosis
- Cardiovascular risk factors
- Allergies
- Anamnese
- Physical examination (Körperlicher Untersuchungsbefund)
- Laboratory data (some in tabular structure)
- ECG
- Recommended therapy
- Summary

Charecteristics of medical admission notes

Amount of text varying a lot

Charecteristics of medical admission notes

- Amount of text varying a lot
- Sometimes free unstructured text, sometimes tables

Charecteristics of medical admission notes

- Amount of text varying a lot
- Sometimes free unstructured text, sometimes tables
- Often subsections are titled differently, but contain similar informations

Charecteristics of medical admission notes

- Amount of text varying a lot
- Sometimes free unstructured text, sometimes tables
- Often subsections are titled differently, but contain similar informations
- Concluded by salutation and names of involved physicians.

• Time period: 2004-2016

• Time period: 2004-2016

• Total amount of notes: 180 000

• Time period: 2004-2016

• Total amount of notes: 180 000

• Total amount of tokens: 132 Million

Training and Experiments

Trained three NER models

	LOC	ORG	PER	MEDICATION
${\sf ConLL2003+GermEval+EP}$	18.131	14.303	17.036	2.808
GermaEval + EP	12.892	10.061	12.541	2.808
ConLL2003+EP	5.340	4.414	4.613	2.808

Table: Amount of entity tokens in training set incl. MEDICATION entities

• No automatic evaluation because no annotated data available

- No automatic evaluation because no annotated data available
- Manually annotated one admission note with our four NE classes

- No automatic evaluation because no annotated data available
- Manually annotated one admission note with our four NE classes
- Test data contains 1.049 tokens

- No automatic evaluation because no annotated data available
- Manually annotated one admission note with our four NE classes
- Test data contains 1.049 tokens


LOC	ORG	PER	MEDICATION
18	25	22	9

Table: Absolute number of tokens per class in test set


• Used scores are precision and recall with macro average

- Used scores are precision and recall with macro average
- Evaluation is token-wise not entity-wise, due to limited data

Evaluation Macro Average



Evaluation per NE



• PER class recognition outperforms all other NEs

- PER class recognition outperforms all other NEs
- LOC and MEDICATION recognition as well reasonable performance

- PER class recognition outperforms all other NEs
- LOC and MEDICATION recognition as well reasonable performance
- ORG recognition score in two data sets very low

Possible explanations for scores:

• PER entities look similar in test and trainings set

Possible explanations for scores:

- PER entities look similar in test and trainings set
- LOC entities are similar to a lesser extend

Possible explanations for scores:

- PER entities look similar in test and trainings set
- LOC entities are similar to a lesser extend
- ORG entities have different shape in newspaper texts and medical texts

 Out-of-domain trained NER models have reasonable performance on medical texts

- Out-of-domain trained NER models have reasonable performance on medical texts
- Further research and annotation work on medical texts is needed

- Out-of-domain trained NER models have reasonable performance on medical texts
- Further research and annotation work on medical texts is needed
- To do meaningful information extraction data need to be anonymized

- Out-of-domain trained NER models have reasonable performance on medical texts
- Further research and annotation work on medical texts is needed
- To do meaningful information extraction data need to be anonymized
- Goal is to keep as much as possible semantic and syntactic structure

- Out-of-domain trained NER models have reasonable performance on medical texts
- Further research and annotation work on medical texts is needed
- To do meaningful information extraction data need to be anonymized
- Goal is to keep as much as possible semantic and syntactic structure
- My BA thesis will implement an Anonymizer based on Yuwono/TouNg and the NER model trained in this project

References

- Yuwono, Steven Kester and Ng, Hwee Tou (2016):
 Automated Anonymization as Spelling Variant Detection.
- Starlinger, Johannes and Kittner, Madeleine and Blankenstein, Oliver (2016):
 - How to improve information extraction from German medical records.
- Richter-P., Phillip (2017):
 Evaluation of German Named Entity Recognition Tools, https://github.com/MaviccPRP/ger_ner_evals/.

Acknowledgments

- Section of Bioinformatics and Systems Cardiology at the Klaus Tschira Institute for Integrative Computational Cardiology under the supervision of Christoph Dieterich
- Database Systems Research Group at the Heidelberg University supervised by Michael Gertz

Thank you!