

Essential SQL Techniques

```
$ echo "Data Sciences Institute"
```

Essential Techniques

→ **Aggregation Functions**

Subqueries

Temporary Tables & CTEs (Common Table Expressions)

Datetime Functions

Aggregation Functions Overview

- **GROUP BY:** Organizes your results based on selected columns.
- **COUNT:** Returns the number of rows that match a specified condition.
- **SUM & AVG:** Calculate total and average values of a specified column.
- **MIN & MAX:** Find the smallest and largest values.
- **Arithmetic Operations:** Perform calculations on column values.
- **HAVING:** Apply filters after aggregations.

GROUP BY: Foundation of Aggregation

- Aggregations generally require a *group*
- `GROUP BY` is mandatory any time a column aside from the one being aggregated is present

GROUP BY: Foundation of Aggregation

For example, a query wanting to know the number of days in each month:

```
SELECT  
COUNT(days)  
  ,months  
  
FROM calendar  
GROUP by months
```

- GROUP BY comes after a WHERE clause
- Remember: with all aggregation functions, values will be calculated *per group*

COUNT: Quantifying Rows

- COUNT performs counts of any given column or set of columns
- COUNT(*) provides a count of rows in a given table
 - no GROUP BY is required here
- Multiple counts are treated as separate columns
 - e.g. counting the number of days and months in a year

```
SELECT  
COUNT(days)  
,COUNT(DISTINCT months)  
,years  
  
FROM calendar  
GROUP by years
```

COUNT: Quantifying Rows

- When `COUNT` is combined with `DISTINCT`, only unique values are counted
 - `SELECT COUNT(DISTINCT product_id) ...` might produce a different value than `SELECT COUNT(product_id) ...` depending on the context of the table

vendor_id	product_id	market_date
1	1	2025-01-01
1	1	2025-01-02
1	2	2025-01-01
1	2	2025-01-02
1	2	2025-01-03
1	3	2025-01-02
1	4	2025-01-02

vendor_id	count_of_distinct_products
1	4

vendor_id	count_of_products
1	7

COUNT: Quantifying Rows

(`COUNT` live coding)

SUM & AVG: Calculating Totals and Averages

- SUM performs the sum total of any numeric column
 - Be wary, SQLite may be more permissive for columns with numbers; it's best practice to coerce (CAST) these values into numbers before summing to be certain of their validity
 - e.g. `CAST(SUM(column1) AS INTEGER) AS column1`
- SUM can accommodate multiple columns using the plus + operator
 - e.g. `SUM(column1 + column2)`
- Thinking about SUM and COUNT combined (i.e. a rolling total)? We'll get to that in the next session!

SUM & AVG: Calculating Totals and Averages

- `AVG` performs the average of any numeric column
- Like `SUM`, it can accommodate multiple columns
 - we can also use other mathematical operations for `SUM` and `AVG`, like `-`, `*`, `/`, `%` (i.e. modulo, not percent), etc

SUM & AVG: Calculating Totals and Averages

Watch out! Don't average an average column when using GROUP BY

Imagine, market_avg_temp stored in the market_date_info table:

market_day	market_avg_temp
Saturday	36
Sunday	33
Wednesday	25
Saturday	28
Sunday	31

SUM & AVG: Calculating Totals and Averages

If we GROUP BY market_day , we can produce an average for each day of the week:

market_day	dow_market_avg_temp
Saturday	31
Sunday	32
Wednesday	28

SUM & AVG: Calculating Totals and Averages

Avoid averaging `dow_market_avg_temp` to get an `overall_market_avg_temp`:

actual_avg	avg_of_avgs
30.42857	30.33333

SUM & AVG: Calculating Totals and Averages

(SUM & AVG live coding)

MIN & MAX: Finding Extremes

- `MIN` takes the single minimum value of a given column; `MAX` takes the maximum
- Be wary of combining `MIN` & `MAX` with other aggregating functions like `SUM` or `AVG`
- What do we think happens when `MIN` is performed on a string? Error? Something else? What about `MAX` ?

MIN & MAX: Finding Extremes

(MIN & MAX live coding)

Arithmetic in SQL

- SQL can perform many basic (and some complex) calculations
 - addition, subtraction, multiplication, division, power, etc
 - geometric/trigonometric functions sin, cos, tan, degrees, radians, etc
- These calculations can also be combined inside aggregation functions
 - e.g. multiplication inside a SUM `...SUM(quantity * cost)` would create a column like total_spent per group
- SQL is similar to other programming languages in its ability to handle floating point values
- Because columns are type specific, how would we perform integer division on two numbers?

Arithmetic

(Arithmetic live coding)


HAVING: Filtering Aggregated Results

- **WHERE** clauses filter rows *before* an aggregation occurs
...so **HAVING** clauses allow us to filter rows *after* an aggregation is calculated
- **HAVING** clauses come after **GROUP BY** , but before **ORDER BY**
- **HAVING** clauses only filter aggregated calculations
 - you can have both **WHERE** and **HAVING**
 - they are not interchangeable

HAVING: Filtering Aggregated Results

(HAVING live coding)

Image: Joseph Ferrer, KDnuggets



What questions do you have about Aggregations?

Subqueries: Queries Within Queries

- SQL allows us to query the results of another query
 - We call this a subquery
- In a subquery, all columns need to be uniquely named
- Subqueries can usually be run for testing purposes by highlighting them, IDE dependent

Subqueries: Queries Within Queries

- Subqueries can be used in both `JOIN` and `WHERE` clauses
 - In the case of `JOIN` (or `FROM`):
 - you want the subquery to add columns to your output
 - you are using a subquery because you are joining/selecting complex criteria that require manipulation
 - it is often the case that you are joining two or more tables within a subquery to another table

<code>SELECT *</code>	outer query:
<code>FROM</code>	everything from the subquery
<code>(</code>	
<code>SELECT</code>	subquery:
<code>vendor_id</code>	ordering each vendor's
<code>,market_date</code>	items by price
<code>,product_id</code>	
<code>,original_price</code>	
<code>,ROW_NUMBER() OVER (PARTITION BY vendor_id</code>	
<code>ORDER BY original_price DESC) AS price_rank</code>	
<code>FROM vendor_inventory</code>	
<code>) x</code>	
<code>WHERE x.price_rank = 1</code>	outer query:
	filtered by price_rank

Subqueries: Queries Within Queries

- In the case of **WHERE** :
 - you want to filter results
 - you are using a subquery because it is simpler than joining and filtering the columns otherwise
 - it's important to note: *you can only return a single column* in your subquery
 - Why do we think this is?

```
SELECT
market_date
,customer_id
,vendor_id
,quantity * cost_to_customer_per_qty price
FROM customer_purchases
WHERE market_date IN
(
  SELECT market_date
  FROM market_date_info
  WHERE market_rain_flag = 1
)
```

outer query:
each sale that's occurred

subquery:
all days it has rained



Subqueries

(Subqueries live coding)



SELECT Questions? FROM (Questions?)

Temporary Tables & CTEs

Temporary ("temp") Tables

- Table objects created on the fly
- Automatically saved to a reserved temp schema
- Accessible across SQL queries in the same session
- Cleared from memory when SQL is closed (or the server connection is terminated)
- Temporary tables can be chained in the same query
 - You can place one temporary table into another
- Must be dropped (deleted from memory) to recreate them with the same name

Temporary ("temp") Tables

- Some older versions of SQL don't allow temporary tables
- They are *fantastic placeholders*
 - **What scenarios can we think of where a temporary table would be particularly useful?**   **Think, Pair, Share**

Temporary Tables

(Temporary Table live coding)

Common Table Expressions (CTEs)

- Similar to temporary tables
 - CTEs were developed *before* temp tables
 - Some SQL versions/flavours (especially much older ones) might not support temp tables, so CTEs are an important skill
- Instantiated query results created on the fly
 - Utilize the `WITH` command
 - Many RDBMs require a semicolon terminating the `WITH` clause
 - Multiple CTEs don't use more than one `WITH` clause, but rather follow one another with a comma
 - Need to be written *before* the final `SELECT` statement

Common Table Expressions (CTEs)

- Sometimes easier than a subquery
 - If subqueries become overly complex, they can be harder to read
- Stored in memory
- Limited to your current query window only

Common Table Expressions (CTEs)

(CTEs live coding)

What questions do you have?

Datetime Functions: Managing Dates and Times

- **Formats:** Understand and convert between different date formats.
- **'NOW':** Get the current date and time.
- **STRFTIME:** Format dates and times based on specific patterns.
- **Adding and Subtracting Dates:** Calculate date intervals and future/past dates.
- **Difference between Dates:** Find the interval between two dates.

Formats

- Date formats vary widely in SQL databases
 - A general rule of thumb when working with multiple date fields is to force them all into a similar format
 - This may seem obvious, but different source systems may write dates different in SQL DBs
- It is not uncommon to store date values as integers YYYYMMDD to increase optimization and decrease storage size
- Manipulating dates varies by flavour
- SQLite is *less* flexible with dates, requiring all dates to either be:
 - "YYYY-MM-DD" *strings*
 - Julian Day *fractions*
 - Seconds from Unix Time *integers*

'NOW' (or GETDATE() or DATE, flavour dependent)

- These functions (there are actually more of them) get the current date and time
 - Some will return UTC time if requested (this can be useful) e.g. `GETUTCDATE()`
- When combined with other Datetime functions, this can serve as a dynamic value
 - e.g. "yesterday", "last year", and so on
- SQLite uses `DATE()`, `DATETIME()`, `TIME()` (without any arguments) or `DATE('now')`

'NOW'

(**'NOW'** live coding)

STRFTIME

- `STRFTIME` converts DATE and DATETIME values into different formats
- `STRFTIME` also allows you to extract specific "dateparts"
 - e.g. `SELECT STRFTIME('%Y', 'NOW')`
- The first argument of `STRFTIME` is flexible — you can specify more than one datepart at a time *and* any formatting
 - e.g. `SELECT STRFTIME('%Y-%m', 'NOW')` would return 2025-04

STRFTIME

- `STRFTIME` also allows modification to date dynamically
 - e.g. `SELECT STRFTIME('%Y-%m-%d', '2025-04-17', 'start of month')`
 - **How do we go about subtracting dates rather than adding them?**
- Modifiers include:
 - +/- N years/months/days/hours/minutes/seconds
 - start of year/month/day
 - weekday
- Be mindful: because outcome is a *string*, modification should be done within the `STRFTIME` argument to ensure it is correct
- Some flavours have built in convenience dateparts, like `YEAR`, `MONTH`, etc that make extracting values a bit easier

STRFTIME

(STRFTIME live coding)

Adding Dates (sometimes DATEADD or DATE_ADD, flavour dependent)

- SQLite supports two means of adding increments of time to a date:
 - `STRFTIME` as mentioned previously
 - Using `DATE`
 - e.g. `SELECT DATE('2025-04-17', 'start of month')`
- Both of these methods allow you to chain modifiers
 - e.g. `SELECT DATE('2025-04-17', 'start of month', '-1 day')`

What do we see as the difference between these?

- This syntax is fairly unique to SQLite, but is conceptually the same, so briefly I will touch on `DATEADD`
 - Generally, we specify a datepart, add/subtract a value, and the date

Difference between Dates (an extension of STRFTIME or DATEDIFF, flavour dependent)

- The difference between dates can vary in complexity
- We can use `STRFTIME`, subtracting the two dates from one another, using '%s' as our unit
 - e.g. `SELECT (STRFTIME("%s", Date1) - Date2) / {increment, e.g. 3600.0 for hours, 60.0 for minutes, etc}`
 - Be sure to include .0 for float precision: `ROUND` or `CAST` to integer if desired
 - `STRFTIME` works well for calculating months and years
 - e.g., months until summer 🏖️ `SELECT STRFTIME('%m', '2025-06-21') - STRFTIME('%m', 'NOW')`

Difference between Dates (an extension of STRFTIME or DATEDIFF, flavour dependent)

- We can use also use `JULIANDAY` :
 - Julian Days are *fractional* by nature and result in a difference of days
 - e.g., difference in hours `SELECT CAST((JULIANDAY(Date1) - JULIANDAY(Date2) * 24) AS INT)`
- This syntax is also fairly unique to SQLite, but is conceptually the same, so briefly I will touch on `DATEDIFF`
 - Generally, we specify a datepart, startdate, and enddate

Datetime Functions

(Adding Dates and Difference between Dates live coding)

What questions do you have about anything from today?