

Exercise 2.1: Bootstrap Directory Structure

When we download Bootstrap from the official website, the folder structure generally looks like this:

Module 1-Bootstrap5/

```
|
|— css/
|— js/
```

1. CSS Folder

The CSS folder contains all Bootstrap styling files.

css/

```
|— bootstrap.css
|— bootstrap.min.css
|— bootstrap.rtl.css
|— bootstrap.rtl.min.css
```

Purpose of CSS Files:

File	Purpose
bootstrap.css	Full readable Bootstrap CSS file
bootstrap.min.css	Minified version for faster loading
bootstrap.rtl.css	Right-to-left language support
bootstrap.rtl.min.css	Minified RTL version

What CSS Folder Provides:

- Grid system
- Typography
- Buttons
- Forms
- Cards
- Navbars
- Utilities
- Responsive classes

Usage: `<link rel="stylesheet" href="css/bootstrap.min.css">`

2. JS Folder

The js folder contains Bootstrap JavaScript plugins.

js/

|

|— bootstrap.bundle.js

|— bootstrap.bundle.min.js

|— bootstrap.js

|— bootstrap.min.js

Purpose of JS Files:

File	Purpose
bootstrap.js	Full Bootstrap JavaScript
bootstrap.min.js	Minified JS version
bootstrap.bundle.js	Includes Popper.js + Bootstrap JS
bootstrap.bundle.min.js	Minified bundle version

Features Enabled by JS:

Bootstrap JavaScript enables interactive components such as:

- Modal
- Accordion
- Carousel
- Dropdown
- Tooltip
- Toast
- Collapse Navbar

Usage: `<script src="js/bootstrap.bundle.min.js"></script>`

3. Icons Folder / Bootstrap Icons

Bootstrap Icons are separate from the main Bootstrap framework.

I used CDN method:

`<!-- Bootstrap Icons -->`

`<link rel="stylesheet"`

`href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.11.3/font/bootstrap-icons.min.css">`

Purpose:

Bootstrap Icons provide ready-made icons like:

- Home
- Search
- User
- Facebook
- Instagram
- Trash
- Download

Example:

```
<i class="bi bi-house-fill"></i>
```

```
<i class="bi bi-search"></i>
```

```
<i class="bi bi-instagram"></i>
```