

## Assignment – 20

Maddula Rupa Sri Manohar  
maddularupasrimanohar2001@gmail.com

### Task 1:

#### Generics and Type Safety:

Create a generic Pair class that holds two objects of different types, and write a method to return a reversed version of the pair.

Program:

```
public class GenericsAndTypeSafety<T, U> {
    private T first;
    private U second;

    public GenericsAndTypeSafety(T first, U second) {
        this.first = first;
        this.second = second;
    }

    public T getFirst() {
        return first;
    }

    public U getSecond() {
        return second;
    }

    public GenericsAndTypeSafety<U, T> reverse() {
        return new GenericsAndTypeSafety<>(second, first);
    }

    public static void main(String[] args) {
        GenericsAndTypeSafety<String, Integer> pair = new
GenericsAndTypeSafety<>("HII", 321);
        System.out.println("Original Pair: " + pair.getFirst() + ", " +
pair.getSecond());
    }
}
```

```

        GenericsAndTypeSafety<Integer, String> reversedPair =
pair.reverse();
        System.out.println("Reversed Pair: " + reversedPair.getFirst() + ", "
+ reversedPair.getSecond());
    }
}

```

### **Output:**

Original Pair: Hii, 321  
Reversed Pair: 321,Hii

## **Task 2:**

### **Generic Classes and Methods:**

**Implement a generic method that swaps the positions of two elements in an array, regardless of their type, and demonstrate its usage with different object types.**

### **Program:**

```
import java.util.Arrays;
```

```

public class GenericClassesAndMethods {

    public static <T> void swap(T[] arr,int x,int y) {
        try {
            if(x < 0 || x>=arr.length || y<0 || y>=arr.length) {
                System.out.println("Invalid indices
                                provided.");
            }
        } catch (IllegalArgumentException e) {
            e.printStackTrace();
        }
        T temp=arr[x];
        arr[x]=arr[y];
        arr[y]=temp;
    }

    public static void main(String[] args) {
        Integer[] iarr= {4,3,6,2,1,5};
    }
}

```

```

        System.out.println("Original Array: "
                            +Arrays.toString(iarr));

        swap(iarr, 4, 5);
        System.out.println("Array after swapping: "
                            +Arrays.toString(iarr));

        String[] sarr=
            {"prakash","teja","pavan","manohar","feroz"};
        System.out.println("Original Array: "
                            +Arrays.toString(sarr));

        swap(sarr, 0, 3);
        System.out.println("Array after swapping: "
                            +Arrays.toString(sarr));

        Character[] carr= {'a','m','m','u','b'};
        System.out.println("Original Array: "
                            +Arrays.toString(carr));

        swap(carr, 1, 4);
        System.out.println("Array after swapping: "
                            +Arrays.toString(carr));
    }
}

```

### **Output:**

Original Array: [4, 3, 6, 2, 1, 5]  
 Array after swapping: [4, 3, 6, 2, 5, 1]  
 Original Array: [prakash, teja, pavan, manohar, feroz]  
 Array after swapping: [manohar, teja, pavan, prakash, feroz]  
 Original Array: [a, m, m, u, b]  
 Array after swapping: [a, b, m, u, m]

### **Task 3:**

#### **Reflection API:**

**Use reflection to inspect a class's methods, fields, and constructors, and modify the access level of a private field, setting its value during runtime**

#### **Program:**

```

import java.lang.reflect.Field;

public class ReflectionAPI {

    private String privatename;

    public ReflectionAPI(String privatename) {

```

```

        this.privatename = privatename;
    }

    public String getPrivatename() {
        return privatename;
    }

    public void setPrivatename(String privatename) {
        this.privatename = privatename;
    }

    public static void main(String[] args) {

        ReflectionAPI rapi = new ReflectionAPI("Manohar");

        try {
            Field f = ReflectionAPI.class
                .getDeclaredField("privatename");
            f.setAccessible(true);
            System.out.println("Name before modification: "
                               + f.get(rapi));
            f.set(rapi, "Manohar Maddula");
            System.out.println("Name after modification: "
                               + f.get(rapi));
        } catch (SecurityException | IllegalArgumentException |
                 IllegalAccessException e) {
            e.printStackTrace();
        } catch (NoSuchFieldException e) {
            e.printStackTrace();
        }
    }
}

```

**Output:**

Name before modification: Manohar  
 Name after modification: Manohar Maddula

## Task 4:

### Lambda Expressions:

Implement a Comparator for a Person class using a lambda expression, and sort a list of Person objects by their age..

### Program:

```
import java.util.ArrayList;
import java.util.Comparator;
import java.util.List;

public class LamdaExpressions {
    private String name;
    private int age;

    public LamdaExpressions(String name, int age) {
        this.name = name;
        this.age = age;
    }
    public String getName() {
        return name;
    }
    public void setName(String name) {
        this.name = name;
    }
    public int getAge() {
        return age;
    }
    public void setAge(int age) {
        this.age = age;
    }
    public static void main(String[] args) {
        List<LamdaExpressions> list = new ArrayList<>();
        list.add(new LamdaExpressions("Prakash", 24));
        list.add(new LamdaExpressions("feroz", 14));
        list.add(new LamdaExpressions("Raju", 18));
        list.add(new LamdaExpressions("manohar", 23));
        Comparator<LamdaExpressions> compare =
            Comparator.comparingInt(LamdaExpressions::getAge);
        list.sort(compare);
        System.out.println("Data sorted by age: ");
        for (LamdaExpressions x : list) {
```

```
public static void process(Person p, Predicate<Person>
    predicate, Consumer<Person> consumer,
    Function<Person, String> function,
    Supplier<Person> supplier)
{
    if (predicate.test(p)) {
        consumer.accept(p);
        System.out.println("Transformed name: "
            + function.apply(p));
    } else {
        System.out.println("Predicate condition not met
            of person: " + p);
        System.out.println("New person created: "
            + supplier.get());
    }
}
```

```

    }

    public static void main(String[] args) {
        Person person = new Person("Manohar", 22);

        Predicate<Person> ap = p -> p.getAge() > 26;

        Consumer<Person> consumer = p ->
            System.out.println("Person details: " + p);

        Function<Person, String> function = p ->
            p.getName().toUpperCase();

        Supplier<Person> supplier = () -> new Person("Ramana", 23);

        process(person, ap, consumer, function, supplier);
    }
}

```

### Output:

Predicate condition not met of person: Person [name=Manohar, | age=22]  
 New person created: Person [name=Ramana, | age=23]