

S

educative

EXPLORE

TRACKS

MY COURSES

EDPRESSO

REFER A FRIEND

From Python to Numpy

0% COMPLETED

Search Course

Introduction

What is NumPy?

Creation in NumPy

Reshaping in NumPy

Indexing in NumPy

Broadcasting in NumPy

NumPy Vectorization

Readability vs. Speed

Anatomy of an Array

Introduction

Memory layout

Views and Copies

Coding Example: How to find if one vector is view of the other?

Broadcasting in NumPy

This lesson explains broadcasting in NumPy in detail.

We'll cover the following

- What is Broadcasting in NumPy?
- General rules for Broadcasting
- Examples
 - When one operand is N*N and other is 1 * 1
 - When one operand is N * N and other is N * 1
 - When one operand is N * N and other is 1 * N
 - When one operand is N * S and other is S * N

What is Broadcasting in NumPy?

The term *broadcasting* describes how numpy treats arrays with different shapes during arithmetic operations. Subject to certain constraints, the smaller array is “broadcast” across the larger array so that they have compatible shapes. Broadcasting provides a means of vectorizing array operations.

General rules for Broadcasting

When operating on two arrays, NumPy compares their shapes element-wise. It starts with the trailing dimensions and works its way forward. Two dimensions of size **N** are compatible when

- they are equal, or
- one of them is the singular value
- one is N * N and other is N * 1
- one is N * N and other is 1 * N
- one is N * S and other is S * N where, S can be any **scalar value**.

Examples

The concept of broadcasting is explained through code and figure in the following examples:-

When one operand is N*N and other is 1 * 1

```
Z1 = np.arange(9).reshape(3,3)
Z2 = 1
Z1 + Z2
```



```
1 import numpy as np
2 Z1 = np.arange(9).reshape(3,3)
3 Z2 = 1
4 print(Z1 + Z2)
```

RUN

SAVE

RESET

Output

```
[[1 2 3]
 [4 5 6]
 [7 8 9]]
```

When one operand is N * N and other is N * 1

```
Z1 = np.arange(9).reshape(3,3)
Z2 = np.arange(3)[::-1].reshape(3,1)
Z1 + Z2
```



```
1 import numpy as np
2 Z1 = np.arange(9).reshape(3,3)
3 Z2 = np.arange(3)[::-1].reshape(3,1)
4 print(Z1 + Z2)
5
```

RUN

SAVE

RESET

Output

```
[[2 3 4]
 [4 5 6]
 [6 7 8]]
```

When one operand is N * N and other is 1 * N

```
Z1 = np.arange(9).reshape(3,3)
Z2 = np.arange(3)[::-1]
Z1 + Z2
```



```
1 import numpy as np
2 Z1 = np.arange(9).reshape(3,3)
3 Z2 = np.arange(3)[::-1]
4 print(Z1 + Z2)
```

RUN

SAVE

RESET

Output


```
[[2 2 2]
 [5 5 5]
 [8 8 8]]
```

When one operand is N * S and other is S * N

Here S can be any scalar value.

In the following example S is 1 and N is 3. So basically dimension 3 * 1 and 1 * 3 is added.

```
Z1 = np.arange(3).reshape(3,1)
Z2 = np.arange(3).reshape(1,3)
Z1 + Z2
```



```
1 import numpy as np
2 Z1 = np.arange(3).reshape(3,1)
3 Z2 = np.arange(3).reshape(1,3)
4 print(Z1 + Z2)
```

RUN

SAVE

RESET

Output

```
[[0 1 2]
 [1 2 3]
 [2 3 4]]
```

q Which of the following operation is not possible in broadcasting?

Assume N is the total size of the NumPy array

- ☐ A) If one operand is N * N and other is N * N
- ☐ B) If one operand is N * 2 and other is N * 3
- ☐ C) If one operand is N * 2 and other is 2 * N

COMPLETED 0%

1 of 1

← Back

Indexing in NumPy

✓ Mark as Completed

Next →

NumPy Vectorization

Stuck? Get help on

DISCUSS

👉 Send feedback

❤ 1 Recommendation