





Challenge: Implement breadth-first search

Implement BFS

In this step, you'll finish implementing the `doBFS` function, which performs a breadth-first search on a graph and returns an array of objects describing each vertex.

For each vertex v , the object's `distance` property should be vertex v 's distance from the source, and the `predecessor` property should be vertex v 's predecessor on a shortest path from the source. If there is no path from the source to vertex v , then v 's distance and predecessor should both be *null*. The source's predecessor should also be *null*.

In the starter code, the function initializes the distance and predecessor values to null, and then enqueues the source vertex. It is up to you to implement the rest of the algorithm, as described in the pseudocode.

 Java	 Python	 C++	 JS
--	--	---	--

```
1 import java.util.LinkedList;
2 import java.util.Queue;
3
4 class BFSInfo {
5     public BFSInfo() {
6         this.distance = -1;
7         this.predecessor = -1;
8     }
9
10    public BFSInfo(int distance,
11        this.distance = distance;
12        this.predecessor = predecessor;
13    }
14
15    public int distance;
16    public int predecessor;
17 };
18
19 class Solution {
20     public static BFSInfo[] doBFS(
21         System.out.println(graph.length);
22         BFSInfo[] bfsInfo = new BFSInfo[graph.length];
23
```

```
24     bfsInfo[source] = new BFSInfo();
25     bfsInfo[source].distance = 0;
26
27     Queue<Integer> q = new LinkedList<>();
28     q.add(source);
29
30     // Traverse the graph
31
```

