



## Scenario: Simplified Fuel Pump Failure Detection

### Fuel Pressure (psi)

- **Type:** Raw Measurement
- **Explanation:** This value is typically obtained directly from a pressure sensor installed in the fuel system. The sensor measures the pressure of the fuel as it is delivered to the engines.

### Fuel Flow Rate (liters/hour)

- **Type:** Raw Measurement
- **Explanation:** The flow rate is measured by a flow meter that quantifies the amount of fuel passing through it over a specific time period. This measurement is essential for ensuring that the engines receive the correct amount of fuel.

### Pump Status (Operational/Failed)

- **Type:** Categorical Output (Target Variable)
- **Explanation:** This value is the result of monitoring the performance of the fuel pump. It can be determined by analyzing inputs from various sensors (like pressure, flow rate, etc.) or through direct monitoring systems that can indicate if the pump is functioning or not.

### Fuel Temperature (°C)

- **Type:** Raw Measurement
- **Explanation:** This value is measured using a temperature sensor installed in the fuel line or tank. It provides real-time data on the temperature of the fuel, which is important for maintaining fuel quality and performance.

### Vibration Level (g)

- **Type:** Raw Measurement
- **Explanation:** The vibration level is measured using an accelerometer placed on or near the fuel pump. It captures the vibrations of the pump during operation, which can indicate mechanical issues if the vibrations exceed certain thresholds.

## Explanation of Features

- **Fuel Pressure (psi):** A critical indicator; values below a certain threshold (e.g., 30 psi) may indicate pump issues.
- **Fuel Flow Rate (liters/hour):** Helps assess whether the fuel pump is supplying sufficient fuel; drops below expected levels can signify problems.
- **Pump Status:** The output label of the model, indicating whether the fuel pump is operational or has failed.
- **Fuel Temperature (°C):** High temperatures might suggest issues such as overheating or cavitation in the pump.
- **Vibration Level (g):** Increased vibration levels can indicate mechanical wear or potential failure of the pump.

## Scenario: Simplified Fuel Pump Failure Detection

### Fuel Pressure (psi)

- **Type:** Raw Measurement
- **Explanation:** This value is typically obtained directly from a pressure sensor installed in the fuel system. The sensor measures the pressure of the fuel as it is delivered to the engines.

### Fuel Flow Rate (liters/hour)

- **Type:** Raw Measurement
- **Explanation:** The flow rate is measured by a flow meter that quantifies the amount of fuel passing through it over a specific time period. This measurement is essential for ensuring that the engines receive the correct amount of fuel.

### Pump Status (Operational/Failed)

- **Type:** Categorical Output (Target Variable)
- **Explanation:** This value is the result of monitoring the performance of the fuel pump. It can be determined by analyzing inputs from various sensors (like pressure, flow rate, etc.) or through direct monitoring systems that can indicate if the pump is functioning or not.

### Fuel Temperature (°C)

- **Type:** Raw Measurement
- **Explanation:** This value is measured using a temperature sensor installed in the fuel line or tank. It provides real-time data on the temperature of the fuel, which is important for maintaining fuel quality and performance.

### Vibration Level (g)

- **Type:** Raw Measurement
- **Explanation:** The vibration level is measured using an accelerometer placed on or near the fuel pump. It captures the vibrations of the pump during operation, which can indicate mechanical issues if the vibrations exceed certain thresholds.

In this dataset:

- **Raw Measurements:** Fuel Pressure, Fuel Flow Rate, Fuel Temperature, and Vibration Level are all direct outputs from specific sensors. They reflect the current state of the aircraft's fuel system at a given moment.
- **Target Variable:** Pump Status is derived from monitoring these raw measurements along with any thresholds set for normal operations. If any of the raw measurements indicate abnormal behavior (e.g., low pressure or flow rate), the system can conclude that the pump has failed.

## Context in Real-Time Monitoring

In a real-time monitoring system for an aircraft:

- **Sensors Continuously Collect Data:** The sensors would constantly gather data on fuel pressure, flow rate, temperature, and vibrations.
- **Data Processing:** The collected raw data would be fed into a decision-tree model or monitoring system to analyze whether the fuel pump is operating within safe parameters.
- **Alert Generation:** If the model detects that any of the raw measurements are out of range, it can flag the pump status as "Failed," prompting maintenance or checks to be performed.

By using these raw measurements as inputs, the model can make informed predictions about the operational status of the fuel pump, enhancing safety and operational reliability in aviation.

Engine Temperature (°C)	Fuel Level (%)	Vibration Level (g)	Oil Pressure (psi)	Maintenance Required
80	50	0.5	40	No
90	40	0.6	35	Yes
70	60	0.4	45	No
95	30	0.8	30	Yes
85	55	0.5	38	No
60	70	0.3	50	No
88	20	0.9	25	Yes
75	65	0.4	42	No

## Step 1: Calculate Gini Impurity for the Parent Node

### Count the Classes

- Yes (Maintenance Required): 3
- No (Maintenance Required): 5
- Total Samples: 8

### Gini Impurity Calculation

$$Gini = 1 - \sum_{i=1}^C p_i^2$$

Where  $p_i$  is the proportion of each class.

$$p_{Yes} = \frac{3}{8} = 0.375, \quad p_{No} = \frac{5}{8} = 0.625$$

$$Gini(parent) = 1 - ((0.375)^2 + (0.625)^2)$$

$$= 1 - (0.140625 + 0.390625) = 1 - 0.53125 = 0.46875$$

## Step 2: Create Decision Tree Splits

Now we will evaluate potential splits based on the features.

### Splitting on Engine Temperature

Assuming we split at 85°C85°C85°C:

- **Left Node** (Engine Temperature  $\leq 85^\circ\text{C}$ ):
  - Samples:
    - (80, 50, 0.5, 40) → No
    - (70, 60, 0.4, 45) → No
    - (85, 55, 0.5, 38) → No
    - (60, 70, 0.3, 50) → No
    - (75, 65, 0.4, 42) → No
  - Total: 5 No, 0 Yes
  - **Gini Impurity:**  $Gini(\text{left}) = 1 - ((0/5)^2 + (5/5)^2) = 0$   
 $Gini(\text{left}) = 1 - \left( \left( \frac{0}{5} \right)^2 + \left( \frac{5}{5} \right)^2 \right) = 0$

$$Gini(\text{left}) = 1 - \left( \left( \frac{0}{5} \right)^2 + \left( \frac{5}{5} \right)^2 \right) = 0$$



**Right Node** (Engine Temperature > 85°C):

- Samples:
  - (90, 40, 0.6, 35) → Yes
  - (95, 30, 0.8, 30) → Yes
  - (88, 20, 0.9, 25) → Yes
- Total: 3 Yes, 0 No
- 

- **Gini Impurity:**

$$Gini(right) = 1 - \left( \left( \frac{3}{3} \right)^2 + \left( \frac{0}{3} \right)^2 \right) = 0$$

**Gini Impurity Reduction for the Split**

$$\begin{aligned} \Delta Gini_A &= Gini(parent) - \left( \frac{5}{8} \times Gini(left) + \frac{3}{8} \times Gini(right) \right) \\ &= 0.46875 - \left( \frac{5}{8} \times 0 + \frac{3}{8} \times 0 \right) = 0.46875 \end{aligned}$$

### Step 3: Splitting on Fuel Level

Now, let's consider a split on Fuel Level at 30%:

- **Left Node (Fuel Level > 30%):**

- Samples:

- (80, 50, 0.5, 40) → No
    - (90, 40, 0.6, 35) → Yes
    - (70, 60, 0.4, 45) → No
    - (85, 55, 0.5, 38) → No
    - (60, 70, 0.3, 50) → No
    - (75, 65, 0.4, 42) → No

- Total: 1 Yes, 5 No

- **Gini Impurity**

$$Gini(left) = 1 - \left( \left( \frac{1}{6} \right)^2 + \left( \frac{5}{6} \right)^2 \right) = 1 - (0.02778 + 0.69444) = 0.27778$$

- **Right Node (Fuel Level ≤ 30%):**

- Samples:

- (95, 30, 0.8, 30) → Yes
    - (88, 20, 0.9, 25) → Yes

- Total: 2 Yes, 0 No

- **Gini Impurity:**

$$Gini(right) = 1 - \left( \left( \frac{2}{2} \right)^2 + \left( \frac{0}{2} \right)^2 \right) = 0$$

### Gini Impurity Reduction for the Split

$$\begin{aligned}\Delta Gini_B &= Gini(parent) - \left( \frac{6}{8} \times Gini(left) + \frac{2}{8} \times Gini(right) \right) \\ &= 0.46875 - \left( \frac{6}{8} \times 0.27778 + \frac{2}{8} \times 0 \right) \\ &= 0.46875 - (0.20833 + 0) = 0.26042\end{aligned}$$

## Step 4: Splitting on Vibration Level

Next, let's split on Vibration Level at 0.5g

- **Left Node** (Vibration Level  $\leq 0.5g$ ):
  - Samples:
    - (80, 50, 0.5, 40) → No
    - (70, 60, 0.4, 45) → No
    - (60, 70, 0.3, 50) → No
    - (75, 65, 0.4, 42) → No
  - Total: 4 No, 0 Yes

**Right Node** (Vibration Level  $> 0.5g$ ):

- Samples:
  - (90, 40, 0.6, 35) → Yes
  - (95, 30, 0.8, 30) → Yes
  - (88, 20, 0.9, 25) → Yes
- Total: 3 Yes, 0 No

$$Gini(left) = 1 - \left( \left( \frac{0}{4} \right)^2 + \left( \frac{4}{4} \right)^2 \right) = 0$$

$$Gini(right) = 1 - \left( \left( \frac{3}{3} \right)^2 + \left( \frac{0}{3} \right)^2 \right) = 0$$

Gini Impurity Reduction for the Split

$$\begin{aligned}\Delta Gini_C &= Gini(parent) - \left( \frac{4}{8} \times Gini(left) + \frac{4}{8} \times Gini(right) \right) \\ &= 0.46875 - \left( \frac{4}{8} \times 0 + \frac{4}{8} \times 0 \right) = 0.46875\end{aligned}$$

## Step 5: Splitting on Oil Pressure

Finally, let's consider a split on Oil Pressure at 35psi:

- **Left Node** (Oil Pressure  $\leq 35$  psi):
  - Samples:
    - (90, 40, 0.6, 35)  $\rightarrow$  Yes
    - (95, 30, 0.8, 30)  $\rightarrow$  Yes
    - (88, 20, 0.9, 25)  $\rightarrow$  Yes
  - Total: 3 Yes, 0 No

**Right Node** (Oil Pressure  $> 35$  psi):

- Samples:
  - (80, 50, 0.5, 40)  $\rightarrow$  No
  - (70, 60, 0.4, 45)  $\rightarrow$  No
  - (85, 55, 0.5, 38)  $\rightarrow$  No
  - (60, 70, 0.3, 50)  $\rightarrow$  No
  - (75, 65, 0.4, 42)  $\rightarrow$  No
- Total: 5 No, 0 Yes
- 
- 

$$Gini(left) = 1 - \left( \left( \frac{3}{3} \right)^2 + \left( \frac{0}{3} \right)^2 \right) = 0$$

$$Gini(right) = 1 - \left( \left( \frac{0}{5} \right)^2 + \left( \frac{5}{5} \right)^2 \right) = 0$$

the Split

Gini Impurity Reduction for the Split

$$\begin{aligned} \Delta Gini_D &= Gini(parent) - \left( \frac{3}{8} \times Gini(left) + \frac{5}{8} \times Gini(right) \right) \\ &= 0.46875 - \left( \frac{3}{8} \times 0 + \frac{5}{8} \times 0 \right) = 0.46875 \end{aligned}$$

## Step 6: Feature Importance Calculation

Now we can summarize the Gini impurity reductions for each feature:

- Engine Temperature: 0.46875
- Fuel Level: 0.26042
- Vibration Level: 0.46875
- Oil Pressure: 0.46875

To calculate the importance of each feature:

$$\text{Normalized Importance} = \frac{\Delta Gini_{\text{feature}}}{\sum \Delta Gini}$$

Let's calculate for each feature. Assume the total Gini reduction is 1.66667 (the sum of all reductions).

1. Engine Temperature:

$$\text{Importance} = \frac{0.46875}{1.66667} \approx 0.28125 \text{ (28.1\%)}$$

2. Fuel Level:

$$\text{Importance} = \frac{0.26042}{1.66667} \approx 0.15625 \text{ (15.6\%)}$$

3. Vibration Level:

$$\text{Importance} = \frac{0.46875}{1.66667} \approx 0.28125 \text{ (28.1\%)}$$

4. Oil Pressure:

$$\text{Importance} = \frac{0.46875}{1.66667} \approx 0.28125 \text{ (28.1\%)}$$



## Final Decision Tree Structure

Given the Gini impurity calculations and their respective importance, the decision tree could be structured as follows:


1. **Node 1: Split on Engine Temperature at 85°C.**
  - If  $\leq 85^\circ\text{C}$ , go to Node 2.
  - If  $> 85^\circ\text{C}$ , output "No Maintenance Required."
2. **Node 2: Split on Fuel Level at 30%.**
  - If  $> 30\%$ , output "No Maintenance Required."
  - If  $\leq 30\%$ , output "Maintenance Required."

## Conclusion

In this example, we demonstrated how to calculate Gini impurity and reductions for various features to ultimately form a decision tree. The calculated feature importances highlight the significance of each feature, aiding in understanding which parameters most influence the decision-making process for aircraft maintenance needs. The feature **Fuel Level (%)** has relatively lower importance compared to others, indicating it might be a less critical factor in this context.

## Visual Representation of the Decision Tree

mathematica

 Copy code



Presentation Title: Understanding Feature Importance Calculations in Decision Trees

Slide 1: Title Slide

- **Title:** Understanding Feature Importance in Decision Trees
- **Subtitle:** A Detailed Look at Fuel Pump Failure Detection
- **Visual:** Background image of an aircraft with a fuel pump overlay.

Slide 2: Introduction

- **Content:**
  - Brief introduction to decision trees.
  - Importance of feature importance in predictive modeling.
- **Visual:** Simple graphic showing a decision tree structure.

Slide 3: Dataset Overview

- **Title:** Fuel Pump Failure Detection Dataset
- **Content:**
  - Features: Fuel Pressure, Fuel Flow Rate, Pump Status, Fuel Temperature, Vibration Level.
  - Target Variable: Pump Status (Operational/Failed).
- **Visual:** Table showing the dataset.

Slide 4: Gini Impurity Explained

- **Title:** Understanding Gini Impurity
- **Content:**
  - Definition of Gini Impurity.
  - Why it's used for evaluating splits in decision trees.
- **Visual:** Formula for Gini Impurity:  $Gini = 1 - \sum (p_i^2)$   $Gini = 1 - \sum (p_i^2)$