

PROGRAM 1

Design and implement C/C++ Program to find Minimum Cost Spanning Tree of a given connected undirected graph using Kruskal's algorithm.

CODE:

```
#include<stdio.h>
#define INF 999
#define MAX 100
int p[MAX], c[MAX][MAX], t[MAX][2];
int find(int v)
{
    while (p[v])
        v = p[v];
    return v;
}
void union1(int i, int j)
{
    p[j] = i;
}
void kruskal(int n)
{
    int i, j, k, u, v, min, res1, res2, sum = 0;
    for (k = 1; k < n; k++)
    {
        min = INF;
        for (i = 1; i < n - 1; i++)
        {
            for (j = 1; j <= n; j++)
            {
                if (i == j) continue;
                if (c[i][j] < min)
                {
                    u = find(i);
                    v = find(j);
                    if (u != v)
                    {
                        res1 = i;
                        res2 = j;
                        min = c[i][j];
                    }
                }
            }
        }
    }
```

```
    }
    union1(res1, find(res2));
    t[k][1] = res1;
    t[k][2] = res2;
    sum = sum + min;
}
printf("\nCost of spanning tree is=%d", sum);
printf("\nEdgesof spanning tree are:\n");
for (i = 1; i < n; i++)
    printf("%d -> %d\n", t[i][1], t[i][2]);
}
int main()
{
    int i, j, n;
    printf("\nEnter the n value:");
    scanf("%d", & n);
    for (i = 1; i <= n; i++)
        p[i] = 0;
    printf("\nEnter the graph data:\n");
    for (i = 1; i <= n; i++)
        for (j = 1; j <= n; j++)
            scanf("%d", & c[i][j]);
    kruskal(n);
    return 0;
}
```

OUTPUT:

```
Enter the n value:4
Enter the graph data:
0 3 4 999
3 0 5 6
4 5 0 7
999 6 7 0
Cost of spanning tree is=13
Edgesof spanning tree are:
1 ->2
1 ->3
2->4
```

PROGRAM 2

Design and implement C/C++ Program to find Minimum Cost Spanning Tree of a given connected undirected graph using Prim's algorithm.

CODE:

```
#include<stdio.h>
#define INF 999
int prim(int c[10][10],int n,int s)
{
    int v[10],i,j,sum=0,ver[10],d[10],min,u;
    for(i=1; i<=n; i++)
    {
        ver[i]=s;
        d[i]=c[s][i];
        v[i]=0;
    }
    v[s]=1;
    for(i=1; i<=n-1; i++)
    {
        min=INF;
        for(j=1; j<=n; j++)
            if(v[j]==0 && d[j]<min)
            {
                min=d[j];
                u=j;
            }
        v[u]=1;
        sum=sum+d[u];
        printf("\n%d -> %d sum=%d",ver[u],u,sum);
        for(j=1; j<=n; j++)
            if(v[j]==0 && c[u][j]<d[j])
            {
                d[j]=c[u][j];
                ver[j]=u;
            }
    }
    return sum;
}
void main()
{
    int c[10][10],i,j,res,s,n;
```

```
printf("\nEnter n value:");
scanf("%d",&n);
printf("\nEnter the graph data:\n");
for(i=1; i<=n; i++)
    for(j=1; j<=n; j++)
        scanf("%d",&c[i][j]);
printf("\nEnter the souce node:");
scanf("%d",&s);
res=prim(c,n,s);
printf("\nCost=%d",res);
getch();
}
```

OUTPUT:

Enter n value:4

Enter the graph data:

2 3 1 5

7 5 4 6

8 7 5 4

3 7 5 4

Enter the souce node:2

2 -> 3 sum=4

3 -> 4 sum=8

4 -> 1 sum=11

Cost=11

PROGRAM 3

(A) Design and implement C/C++ Program to solve All-Pairs Shortest Paths problem using Floyd's algorithm.

CODE:

```
#include<stdio.h>
#define INF 999
int min(int a,int b)
{
    return(a<b)?a:b;
}
void floyd(int p[][10],int n)
{
    int i,j,k;
    for(k=1; k<=n; k++)
        for(i=1; i<=n; i++)
            for(j=1; j<=n; j++)
                p[i][j]=min(p[i][j],p[i][k]+p[k][j]);
}
int main()
{
    int a[10][10],n,i,j;
    printf("\nEnter the n value:");
    scanf("%d",&n);
    printf("\nEnter the graph data:\n");
    for(i=1; i<=n; i++)
        for(j=1; j<=n; j++)
            scanf("%d",&a[i][j]);
    floyd(a,n);
    printf("\nShortest path matrix\n");
    for(i=1; i<=n; i++)
    {
        for(j=1; j<=n; j++)
            printf("%d ",a[i][j]);
        printf("\n");
    }
    return 0;
}
```

OUTPUT:

Enter the n value:4

Enter the graph data:

0 444 2 45

34 0 43 232

4 567 0 121

56 3 32 0

Shortest path matrix

0 48 2 45

34 0 36 79

4 52 0 49

36 3 32 0

(B) Design and implement C/C++ Program to find the transitive closure using Warshal's algorithm.

CODE:

```
#include<stdio.h>
void warsh(int p[][10],int n)
{
    int i,j,k;
    for(k=1; k<=n; k++)
        for(i=1; i<=n; i++)
            for(j=1; j<=n; j++)
                p[i][j]=p[i][j] || p[i][k] && p[k][j];
}
int main()
{
    int a[10][10],n,i,j;
    printf("\nEnter the n value:");
    scanf("%d",&n);
    printf("\nEnter the graph data:\n");
    for(i=1; i<=n; i++)
        for(j=1; j<=n; j++)
            scanf("%d",&a[i][j]);
    warsh(a,n);
    printf("\nResultant path matrix\n");
    for(i=1; i<=n; i++)
    {
        for(j=1; j<=n; j++)
            printf("%d ",a[i][j]);
        printf("\n");
    }
    return 0;
}
```

OUTPUT:

Enter the n value:4

Enter the graph data:

0 0 1 0

1 0 0 1

0 0 0 0

1 0 0 1

Resultant path matrix

0 0 1 0

1 0 1 1

0 0 0 0

1 0 1 1

PROGRAM 4

Design and implement C/C++ Program to find shortest paths from a given vertex in a weighted connected graph to other vertices using Dijkstra's algorithm

CODE:

```
#include<stdio.h>
#define INF 999
void dijkstra(int c[10][10],int n,int s,int d[10])
{
    int v[10],min,u,i,j;
    for(i=1; i<=n; i++)
    {
        d[i]=c[s][i];
        v[i]=0;
    }
    v[s]=1;
    for(i=1; i<=n; i++)
    {
        min=INF;
        for(j=1; j<=n; j++)
            if(v[j]==0 && d[j]<min)
            {
                min=d[j];
                u=j;
            }
        v[u]=1;
        for(j=1; j<=n; j++)
            if(v[j]==0 && (d[u]+c[u][j])<d[j])
                d[j]=d[u]+c[u][j];
    }
}

int main()
{
    int c[10][10],d[10],i,j,s,sum,n;
    printf("\nEnter n value:");
    scanf("%d",&n);
    printf("\nEnter the graph data:\n");
    for(i=1; i<=n; i++)
        for(j=1; j<=n; j++)
            scanf("%d",&c[i][j]);
```

```
printf("\nEnter the souce node:");  
scanf("%d",&s);  
dijkstra(c,n,s,d);  
for(i=1; i<=n; i++)  
    printf("\nShortest distance from %d to %d is %d",s,i,d[i]);  
return 0;  
}
```

OUTPUT:

Enter n value:4

Enter the graph data:

343 4 5 2

0 87 676 5

34 543 2 1

234 2 4 0

Enter the souce node:4

Shortest distance from 4 to 1 is 2

Shortest distance from 4 to 2 is 2

Shortest distance from 4 to 3 is 4

Shortest distance from 4 to 4 is 0

PROGRAM 5

Design and implement C/C++ Program to obtain the Topological ordering of vertices in a given digraph.

CODE:

```
#include<stdio.h>
int temp[10],k=0;
void sort(int a[][10],int id[],int n)
{
    int i,j;
    for(i=1; i<=n; i++)
    {
        if(id[i]==0)
        {
            id[i]=-1;
            temp[++k]=i;
            for(j=1; j<=n; j++)
            {
                if(a[i][j]==1 && id[j]!=-1)
                    id[j]--;
            }
            i=0;
        }
    }
}
int main()
{
    int a[10][10],id[10],n,i,j;
    printf("\nEnter the n value:");
    scanf("%d",&n);
    for(i=1; i<=n; i++)
        id[i]=0;
    printf("\nEnter the graph data:\n");
    for(i=1; i<=n; i++)
        for(j=1; j<=n; j++)
        {
            scanf("%d",&a[i][j]);
            if(a[i][j]==1)
                id[j]++;
        }
    sort(a,id,n);
```

```
    if(k!=n)
        printf("\nTopological ordering not possible");
    else
    {
        printf("\nTopological ordering is:");
        for(i=1; i<=k; i++)
            printf("%d ",temp[i]);
    }
}
```

OUTPUT:

1)Enter the n value:6

Enter the graph data:

0 0 1 1 0 0

0 0 0 1 1 0

0 0 0 1 0 1

0 0 0 0 0 1

0 0 0 0 0 1

0 0 0 0 0 0

Topological ordering is: 1 2 3 4 5 6

2) Enter the n value:4

Enter the graph data:

1 4 3 2

5 4 2 1

5 3 4 2

4 1 2 3

Topological ordering not possible

PROGRAM 6

Design and implement C/C++ Program to solve 0/1 Knapsack problem using Dynamic Programming method.

CODE:

```
#include<stdio.h>
int w[10],p[10],n;
int max(int a,int b)
{
    return a>b?a:b;
}
int knap(int i,int m)
{
    if(i==n) return w[i]>m?0:p[i];
    if(w[i]>m) return knap(i+1,m);
    return max(knap(i+1,m),knap(i+1,m-w[i])+p[i]);
}
int main()
{
    int m,i,max_profit;
    printf("\nEnter the no. of objects:");
    scanf("%d",&n);
    printf("\nEnter the knapsack capacity:");
    scanf("%d",&m);
    printf("\nEnter profit followed by weight:\n");
    for(i=1; i<=n; i++)
        scanf("%d %d",&p[i],&w[i]);
    max_profit=knap(1,m);
    printf("\nMax profit=%d",max_profit);
    return 0;
}
```

OUTPUT:

```
Enter the no. of objects:5
Enter the knapsack capacity:6
Enter profit followed by weight:
16 2
65 3
10 4
80 5
40 6
Max profit=81
```

PROGRAM 7

Design and implement C/C++ Program to solve discrete Knapsack and continuous Knapsack problems using greedy approximation method.

CODE:

```
#include <stdio.h>
#define MAX 50
int p[MAX], w[MAX], x[MAX];
double maxprofit;
int n, m, i;
void greedyKnapsack(int n, int w[], int p[], int m)
{
    double ratio[MAX];
    // Calculate the ratio of profit to weight for each item
    for (i = 0; i < n; i++)
    {
        ratio[i] = (double)p[i] / w[i];
    }
    // Sort items based on the ratio in non-increasing order
    for (i = 0; i < n - 1; i++)
    {
        for (int j = i + 1; j < n; j++)
        {
            if (ratio[i] < ratio[j])
            {
                double temp = ratio[i];
                ratio[i] = ratio[j];
                ratio[j] = temp;

                int temp2 = w[i];
                w[i] = w[j];
                w[j] = temp2;

                temp2 = p[i];
                p[i] = p[j];
                p[j] = temp2;
            }
        }
    }
    int currentWeight = 0;
    maxprofit = 0.0;
```

```
// Fill the knapsack with items
for (i = 0; i < n; i++)
{
    if (currentWeight + w[i] <= m)
    {
        x[i] = 1; // Item i is selected
        currentWeight += w[i];
        maxprofit += p[i];
    }
    else
    {
        // Fractional part of item i is selected
        x[i] = (m - currentWeight) / (double)w[i];
        maxprofit += x[i] * p[i];
        break;
    }
}

printf("Optimal solution for greedy method: %.1f\n", maxprofit);
printf("Solution vector for greedy method: ");
for (i = 0; i < n; i++)
    printf("%d\t", x[i]);
}

int main()
{
    printf("Enter the number of objects: ");
    scanf("%d", &n);
    printf("Enter the objects' weights: ");
    for (i = 0; i < n; i++)
        scanf("%d", &w[i]);
    printf("Enter the objects' profits: ");
    for (i = 0; i < n; i++)
        scanf("%d", &p[i]);
    printf("Enter the maximum capacity: ");
    scanf("%d", &m);
    greedyKnapsack(n, w, p, m);
    return 0;
}
```

OUTPUT:

Enter the number of objects: 3

Enter the objects' weights: 12 13 43

Enter the objects' profits: 80 70 50

Enter the maximum capacity: 100

Optimal solution for greedy method: 200.0

Solution vector for greedy method: 1 1 1

PROGRAM 8

Design and implement C/C++ Program to find a subset of a given set $S = \{s_1, s_2, \dots, s_n\}$ of n positive integers whose sum is equal to a given positive integer d .

CODE:

```
#include<stdio.h>
#define MAX 10
int s[MAX],x[MAX],d;
void sumofsub(int p,int k,int r)
{
    int i;
    x[k]=1;
    if((p+s[k])==d)
    {
        for(i=1; i<=k; i++)
            if(x[i]==1)
                printf("%d ",s[i]);
        printf("\n");
    }
    else if(p+s[k]+s[k+1]<=d)
        sumofsub(p+s[k],k+1,r
            -s[k]);
    if((p+r
        -s[k]>=d) && (p+s[k+1]<=d))
    {
        x[k]=0;
        sumofsub(p,k+1,r
            -s[k]);
    }
}
int main()
{
    int i,n,sum=0;
    printf("\nEnter the n value:");
    scanf("%d",&n);
    printf("\nEnter the set in increasing order:");
    for(i=1; i<=n; i++)
        scanf("%d",&s[i]);
    printf("\nEnter the max subset value:");
    scanf("%d",&d);
```

```
    for(i=1; i<=n; i++)
        sum=sum+s[i];
    if(sum<d || s[1]>d)
        printf("\nNo subset possible");
    else
        sumofsub(0,1,sum);
    return 0;
}
```

OUTPUT:

Enter the n value:6

Enter the set in increasing order:1 2 3 4 5 6

Enter the max subset value:6

1 2 3

1 5

2 4

6

PROGRAM 9

Design and implement C/C++ Program to sort a given set of n integer elements using Selection Sort method and compute its time complexity. Run the program for varied values of $n > 5000$ and record the time taken to sort. Plot a graph of the time taken versus n. The elements can be read from a file or can be generated using the random number generator.

CODE:

```
#include <stdio.h>
#include <stdlib.h>
#include <time.h>
// Function to perform selection sort on an array
void selectionSort(int arr[], int n)
{
    int i, j, min_idx;
    for (i = 0; i < n-1; i++)
    {
        min_idx = i; // Assume the current element is the minimum
        for (j = i+1; j < n; j++)
        {
            if (arr[j] < arr[min_idx])
            {
                min_idx = j; // Update min_idx if a smaller element is found
            }
        }
        // Swap the found minimum element with the current element
        int temp = arr[min_idx];
        arr[min_idx] = arr[i];
        arr[i] = temp;
    }
}

// Function to generate an array of random numbers
void generateRandomNumbers(int arr[], int n)
{
    for (int i = 0; i < n; i++)
    {
        arr[i] = rand() % 10000; // Generate random numbers between 0 and 9999
    }
}

int main()
{
    int n;
    printf("Enter number of elements: ");
    scanf("%d", &n); // Read the number of elements from the user
```

```
if (n <= 5000)
{
    printf("Please enter a value greater than 5000\n");
    return 1; // Exit if the number of elements is not greater than 5000
}
// Allocate memory for the array
int *arr = (int *)malloc(n * sizeof(int));
if (arr == NULL)
{
    printf("Memory allocation failed\n");
    return 1; // Exit if memory allocation fails
}
// Generate random numbers and store them in the array
generateRandomNumbers(arr, n);
// Measure the time taken to sort the array
clock_t start = clock();
selectionSort(arr, n);
clock_t end = clock();
// Calculate and print the time taken to sort the array
double time_taken = ((double)(end - start)) / CLOCKS_PER_SEC;
printf("Time taken to sort %d elements: %f seconds\n", n, time_taken);
// Free the allocated memory
free(arr);
return 0;
}
```

PYTHON CODE:

```
import matplotlib.pyplot as plt
n_values = [10000, 20000, 30000, 40000, 50000]
time_taken = [0.090831, 0.0334753, 0.740417, 1.508891, 1.858939]
```

```
plt.plot(n_values, time_taken, marker='o')  
plt.title('Selection Sort Time Complexity')  
plt.xlabel('Number of Elements (n)')  
plt.ylabel('Time taken (seconds)')  
plt.grid(True)  
plt.show()
```

OUTPUT:

Enter number of elements: 10000

Time taken to sort 10000 elements: 0.090831 seconds

Enter number of elements: 20000

Time taken to sort 20000 elements: 0.0334753 seconds

Enter number of elements: 30000


Time taken to sort 30000 elements: 0.740417 seconds

Enter number of elements: 40000

Time taken to sort 40000 elements: 1.508891 seconds

Enter number of elements: 50000

Time taken to sort 50000 elements: 1.858939 seconds



PROGRAM 10

Design and implement C/C++ Program to sort a given set of n integer elements using Quick Sort method and compute its time complexity. Run the program for varied values of $n > 5000$ and record the time taken to sort. Plot a graph of the time taken versus n. The elements can be read from a file or can be generated using the random number generator.

CODE:

```
#include <stdio.h>
#include <stdlib.h>
#include <time.h>
// Function to swap two elements
void swap(int* a, int* b)
{
    int t = *a;
    *a = *b;
    *b = t;
}
// Partition function for Quick Sort
int partition(int arr[], int low, int high)
{
    int pivot = arr[high]; // Pivot element
    int i = (low - 1); // Index of smaller element
    for (int j = low; j <= high - 1; j++)
    {
        if (arr[j] < pivot)
        {
            i++; // Increment index of smaller element
            swap(&arr[i], &arr[j]);
        }
    }
    swap(&arr[i + 1], &arr[high]);
    return (i + 1);
}
// Quick Sort function
void quickSort(int arr[], int low, int high)
{
    if (low < high)
    {
        int pi = partition(arr, low, high);
        // Recursively sort elements before and after partition
        quickSort(arr, low, pi - 1);
        quickSort(arr, pi + 1, high);
    }
}
```

```
}
// Function to generate random numbers
void generateRandomNumbers(int arr[], int n)
{
    for (int i = 0; i < n; i++)
    {
        arr[i] = rand() % 100000; // Generate random numbers between 0 and 99999
    }
}
int main()
{
    int n;
    printf("Enter number of elements: ");
    scanf("%d", &n); // Read the number of elements from the user
    if (n <= 5000)
    {
        printf("Please enter a value greater than 5000\n");
        return 1; // Exit if the number of elements is not greater than 5000
    }
    // Allocate memory for the array
    int *arr = (int *)malloc(n * sizeof(int));
    if (arr == NULL)
    {
        printf("Memory allocation failed\n");
        return 1; // Exit if memory allocation fails
    }
    // Generate random numbers and store them in the array
    generateRandomNumbers(arr, n);

    // Measure the time taken to sort the array
    clock_t start = clock();
    quickSort(arr, 0, n - 1);
    clock_t end = clock();

    // Calculate and print the time taken to sort the array
    double time_taken = ((double)(end - start)) / CLOCKS_PER_SEC;
    printf("Time taken to sort %d elements: %f seconds\n", n, time_taken);
```

```
// Free the allocated memory
free(arr);
return 0;
}
```

PYTHON CODE:

```
import matplotlib.pyplot as plt
n_values = [6000, 7000, 8000, 9000]
time_taken = [0.000547, 0.000650, 0.000891, 0.000860]
plt.plot(n_values, time_taken, marker='o')
plt.title('Quick Sort Time Complexity')
plt.xlabel('Number of Elements (n)')
plt.ylabel('Time taken (seconds)')
plt.grid(True)
plt.show()
```

OUTPUT:

Enter number of elements: 6000

Time taken to sort 6000 elements: 0.000547 seconds

Enter number of elements: 7000


Time taken to sort 7000 elements: 0.000650 seconds

Enter number of elements: 8000

Time taken to sort 8000elements: 0.000891 seconds

Enter number of elements: 9000

Time taken to sort 9000 elements: 0.000860seconds



PROGRAM 11

Design and implement C/C++ Program to sort a given set of n integer elements using Merge Sort method and compute its time complexity. Run the program for varied values of $n > 5000$, and record the time taken to sort. Plot a graph of the time taken versus n. The elements can be read from a file or can be generated using the random number generator.

CODE:

```
#include <stdio.h>
#include <stdlib.h>
#include <time.h>
void merge(int arr[], int left, int mid, int right)
{
    int i, j, k;
    int n1 = mid - left + 1;
    int n2 = right - mid;
    int *L = (int *)malloc(n1 * sizeof(int));
    int *R = (int *)malloc(n2 * sizeof(int));
    for (i = 0; i < n1; i++)
        L[i] = arr[left + i];
    for (j = 0; j < n2; j++)
        R[j] = arr[mid + 1 + j];
    i = 0;
    j = 0;
    k = left;
    while (i < n1 && j < n2)
    {
        if (L[i] <= R[j])
        {
            arr[k] = L[i];
            i++;
        }
        else
        {
            arr[k] = R[j];
            j++;
        }
        k++;
    }
    while (i < n1)
    {
        arr[k] = L[i];
        i++;
        k++;
    }
```

```
    }
    while (j < n2)
    {
        arr[k] = R[j];
        j++;
        k++;
    }
    free(L);
    free(R);
}
// Function to implement Merge Sort
void mergeSort(int arr[], int left, int right)
{
    if (left < right)
    {
        int mid = left + (right - left) / 2;
        mergeSort(arr, left, mid);
        mergeSort(arr, mid + 1, right);
        merge(arr, left, mid, right);
    }
}
// Function to generate random integers
void generateRandomArray(int arr[], int n)
{
    for (int i = 0; i < n; i++)
        arr[i] = rand() % 100000; // Generate random integers between 0 and 99999
}
int main()
{
    int n;
    printf("Enter the number of elements: ");
    scanf("%d", &n);
    if (n <= 5000)
    {
        printf("Please enter a value greater than 5000\n");
        return 1; // Exit if the number of elements is not greater than 5000
    }
}
```

```
int *arr = (int *)malloc(n * sizeof(int));
if (arr == NULL)
{
    printf("Memory allocation failed\n");
    return 1; // Exit if memory allocation fails
}
generateRandomArray(arr, n);
// Repeat the sorting process multiple times to increase duration for timing
clock_t start = clock();
for (int i = 0; i < 1000; i++)
{
    mergeSort(arr, 0, n - 1);
}
clock_t end = clock();
// Calculate the time taken for one iteration
double time_taken = ((double)(end - start)) / CLOCKS_PER_SEC / 1000.0;
printf("Time taken to sort %d elements: %f seconds\n", n, time_taken);
free(arr);
return 0;
}
```

PYTHON CODE:

```
import matplotlib.pyplot as plt
n_values = [8000,9000,10000,20000]
time_taken = [0.000955,0.001054,0.001132,0.002238]
plt.plot(n_values, time_taken, marker='o')
plt.title('Merge Sort Time Complexity')
plt.xlabel('Number of Elements (n)')
plt.ylabel('Time taken (seconds)')
plt.grid(True)
plt.show()
```

OUTPUT:

Enter number of elements: 8000
Time taken to sort 8000 elements: 0.000955 seconds

Enter number of elements: 9000


Time taken to sort 9000 elements: 0.001054 seconds

Enter number of elements: 10000

Time taken to sort 10000 elements: 0.001132 seconds

Enter number of elements: 20000

Time taken to sort 20000 elements: 0.002238 seconds



PROGRAM 12

Design and implement C/C++ Program for N Queen's problem using Backtracking.

CODE:

```
#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h>
// Function to print the solution
void printSolution(int **board, int N)
{
    for (int i = 0; i < N; i++)
    {
        for (int j = 0; j < N; j++)
        {
            printf("%s ", board[i][j] ? "Q" : "#");
        }
        printf("\n");
    }
}
// Function to check if a queen can be placed on board[row][col]
bool isSafe(int **board, int N, int row, int col)
{
    int i, j;

    // Check this row on left side
    for (i = 0; i < col; i++)
    {
        if (board[row][i])
        {
            return false;
        }
    }
    // Check upper diagonal on left side
    for (i = row, j = col; i >= 0 && j >= 0; i--, j--)
    {
        if (board[i][j])
        {
            return false;
        }
    }
}
```

```
// Check lower diagonal on left side
for (i = row, j = col; j >= 0 && i < N; i++, j--)
{
    if (board[i][j])
    {
        return false;
    }
}
return true;
}
// A recursive utility function to solve N Queen problem
bool solveNQUtil(int **board, int N, int col)
{
    // If all queens are placed, then return true
    if (col >= N)
    {
        return true;
    }
    // Consider this column and try placing this queen in all rows one by one
    for (int i = 0; i < N; i++)
    {
        if (isSafe(board, N, i, col))
        {
            // Place this queen in board[i][col]
            board[i][col] = 1;

            // Recur to place rest of the queens
            if (solveNQUtil(board, N, col + 1))
            {
                return true;
            }
            // If placing queen in board[i][col] doesn't lead to a solution,
            // then remove queen from board[i][col]
            board[i][col] = 0; // BACKTRACK
        }
    }
    // If the queen cannot be placed in any row in this column col, then return false
```

```
    return false;
}
// This function solves the N Queen problem using Backtracking
// It mainly uses solveNQUtil() to solve the problem
// It returns false if queens cannot be placed, otherwise, return true and prints the
placement of queens
bool solveNQ(int N)
{
    int **board = (int **)malloc(N * sizeof(int *));
    for (int i = 0; i < N; i++)
    {
        board[i] = (int *)malloc(N * sizeof(int));
        for (int j = 0; j < N; j++)
        {
            board[i][j] = 0;
        }
    }
    if (!solveNQUtil(board, N, 0))
    {
        printf("Solution does not exist\n");
        for (int i = 0; i < N; i++)
        {
            free(board[i]);
        }
        free(board);
        return false;
    }
    printSolution(board, N);
    for (int i = 0; i < N; i++)
    {
        free(board[i]);
    }
    free(board);
    return true;
}
int main()
{
```

```
int N;  
printf("Enter the number of queens: ");  
scanf("%d", &N);  
solveNQ(N);  
return 0;  
}
```

OUTPUT:

1) Enter the number of queens: 5

Q # # # #

Q

Q # #

Q

Q #

2) Enter the number of queens: 3

Solution does not exist

