My Leetcode

Tuesday, January 14, 2014

Gas Station (Java)

Leetcode

```
There are N gas stations along a circular route, where the amount of gas at station i is gas[i].
    You have a car with an unlimited gas tank and it costs cost[i] of gas to travel from station i to its next station (i+1). You begin the journey
   Return the starting gas station's index if you can travel around the circuit once, otherwise return -1.
   The solution is guaranteed to be unique.
    Solution:
    This question is prrety like the longest consecutive sequence problem.
    To check if car can go through the gas stations, we have to check two points,
   first, if total gas is enough for total cost, this point can be easily checked by sum all
18 gas[i]-cost[i].
19 second point, what is the start point? it is a little bit harder to finish in O (n).
   however, we can consider this problem in another angel which is if the gas[i]-cost[i]<0 which
   mean the i can not been an start point.
23 So we assume start point at 0, and we also declare two varibles which are sum and total, sum is used
24 to record the total from gas[i]-cost[i], 0<=i<=n, unitl i position . if sum <0 which mean before i can not be start
    point, then we increase start pont one position and sum changed back to 0.
27 However, at the end , if the final start point is what we want? maybe, it is also decided by the
28 total valuable. total is the sum of all qas[i]-cost[i]. our final start point is
```



Fuel & Lubricant Services


Our CFLS team
has over 90
years
experience
supplying
your fuel &
lubricant
needs

colonialfuels.com



Visits Map

```
29 an valid one only when total>= 0, or we should return -1;
     public class Solution {
          public int canCompleteCircuit(int[] gas, int[] cost) {
               \  \  if \ (gas==null||\ cost==null||\ gas.length==0||\ cost.length==0||\ gas.length!=cost.length) \ \{ \ (gas==null||\ cost.length) \ \} 
                   return -1;
              }
              int sum=0;
              int start=0;
              int total=0;
              for (int i=0; i<gas.length; i++) {
                   sum+=gas[i]-cost[i];
                   total+=sum;
                   if (sum<0) {
                       start=i+1;
                       sum=0;
              if (total<0) {
                   return -1;
              return start;
62 }
Gas Station.java hosted with by GitHub
                                                                                                                                                            view raw
Posted by Xinghua Li at 5:00 PM M  
                                                +5 Recommend this on Google
Labels: Greedy, Leetcode
                                                                                                                                                      Google+
   6 comments
               Add a comment
```



Google+Followers

⊚Xinghua Li

















84 have me in circles

3

Popular Posts

Word Ladder (Java)

Path Sum (Java and Python)


Given a binary tree and a sum, determine if the tree has a rootto-leaf path such that adding up all the values along the path equals the g...

Rotate List (Java)

LeetCode Given a list, rotate the list to the right by k places, where k is non-negative. For example: Given 1->2->3-&...

Labels

BFS Binary Search DFS Divide and Conquer DP Greedy Helper table Leetcode ListNode Recursion Stack Tree Two **Pointers**



Blog Archive

- **2014** (102)
 - ► September (1)
 - **▶** July (1)
 - ▶ June (12)
 - May (2)
 - ▶ April (2)
 - ► March (6)
 - ► February (29)
 - ▼ January (49)
 - Palindrome Partitioning (Java)
 - Edit Distance (Java)
 - Reverse Nodes in k-Group (Java)
 - Longest Substring Without Repeating Characters
 - **Distinct Subsequences** (Java)
 - Combination Sum II (Java)
 - Jump Game II (java)
 - Add Two Numbers (Java)
 - Sqrt(x) (Java)
 - First Missing Positive (Java)
 - Rotate List (Java)
 - Valid Palindrome (Java)
 - Scramble String (Java)
 - Maximal Rectangle (Java)
 - Copy List with Random Pointer (Java)
 - Insert Interval (Java)
 - Implement strStr(). Java
 - Sudoku Solver (Java)
 - Clone Graph (Java)
 - Merge Intervals (Java)
 - Restore IP Addresses (Java)
 - Valid Number (Java)
 - Largest Rectangle in Histogram (Java)
 - Spiral Matrix (Java)
 - LeetCode Word Search (Java)
 - Best Time to Buy and Sell Stock (Java)
 - Multiply Strings Java Sort List (Java)

Binary Tree Maximum Path Sum (Java)

Simplify Path (Java)

Minimum Window Substring (Java)

Substring with Concatenation of All Words (Java)

Gas Station (Java)

Candy (Java)

Word Ladder (Java)

Interleaving String (Java)

Decode Ways (Java)

Max Points on a Line(Java)

4 Sum (Java)

Rotate Image (Java)

Surround Regions (Java)

Word Break

public class Solution { public boolean is Interl...

String to Integer (atoi)

Longest Valid Parentheses (Java)

Divide Two Integers

Single Number II

Single Number

Sort List

2013 (13)

Newer Post Older Post Home

Subscribe to: Post Comments (Atom)

Simple template. Template images by mammamaart. Powered by Blogger.