

## Lab 4: Functions

### Learning Objectives

- Understand the purpose and structure of functions.
- Learn how to define and call functions.
- Practice using parameters, return values, and scope.
- Explore advanced features: arbitrary arguments, keyword arguments, default parameters, and multiple return values.

---

### Lab Tasks

#### Exercise 1:

- Define a function named `print_str` that prints "User-defined function".
- Call the function to display the output.

Code Example:

```
def print_str():  
    print("User-defined function")  
  
print_str()  
User-defined function
```

---

#### Exercise 2: Functions with return values

- Define a function `compute_square(num_to_square)` that returns the square of its argument.
- Call the function with the value 7 and print the result as: 7 squared is 49.

Code Example:

```
def compute_square(num_to_square):  
    return num_to_square * num_to_square  
  
num_squared = compute_square(7)  
print("7 squared is", num_squared)  
7 squared is 49
```

---

#### Exercise 3: Functions with multiple parameters

- Define a function `add(x, y)` that returns the sum of x and y.
- Call the function with numbers (5, 7) and with strings ('Tora', 'Bora').
- Print the results as shown.

Code Example:

```
def add(x, y):  
    return x + y  
  
print("add(5, 7) is", add(5, 7))  
print("add('Tora', 'Bora') is", add('Tora', 'Bora'))  
add(5, 7) is 12  
add('Tora', 'Bora') is ToraBora
```

#### Exercise 4

- Define a function `height_to_centimeters(feet, inches)` that converts height in feet/inches to centimeters using the equations:

$$\begin{aligned}\text{total\_inches} &= \text{feet} \times 12 + \text{inches}; \\ \text{centimeters} &= \text{total\_inches} \times 2.54\end{aligned}$$

- Use global constants for conversion.
- Call the function with `feet = 5` and `inches = 5`, and print the result.

Code Example:

```
centimeters_per_inch = 2.54
inches_per_foot = 12

def height_to_centimeters(feet, inches):
    total_inches = (feet * inches_per_foot) + inches
    centimeters = total_inches * centimeters_per_inch
    return centimeters

feet = 5
inches = 5
print("Centimeters:", height_to_centimeters(feet, inches))

Centimeters: 165.1
```

---

#### Exercise 5

- Write a function that tries to modify a global variable without using `global` (observe the result).
- Then, modify the function to use the `global` keyword and observe the difference.

Code Example:

```
employee_name = 'N/A'

def get_name():
    name = input('Enter employee name:')
    employee_name = name # No effect on global variable

get_name()
print("Employee name:", employee_name)

Enter employee name: Azizah
Employee name: N/A
```

```
# Now with global
employee_name = 'N/A'

def get_name():
    global employee_name
    name = input('Enter employee name:')
    employee_name = name

get_name()
print("Employee name:", employee_name)

Enter employee name: Azizah
Employee name: Azizah
```

---

### Exercise 6

- Define a function avg(a, b) that calculates the average using a local variable tmp.

Concept: Local:  $\text{tmp} = (a + b) / 2$ ;

Global:  $\text{tmp} = a + b$

- Outside the function, define a global variable tmp as the sum.
- Print both values to show the difference in scope.

Code Example:

```
def avg(a, b):  
    tmp = (a + b) / 2.0  
    return tmp
```

```
a = 5  
b = 10  
tmp = a + b
```

```
print("Avg:", avg(a, b))  
print("Sum:", tmp)
```

```
Avg: 7.5  
Sum: 15
```