

UPPSALA UNIVERSITY



INTRODUCTION TO MACHINE LEARNING, BIG DATA, AND AI

---

## Assignment 5

---

---

## General information

- The recommended tool in this course is R (with the IDE R-Studio). You can download R [here](#) and R-Studio [here](#). You are allowed to use Python and Jupyter Notebooks, although the assignments may use data available only through the R package, a problem you would need to solve yourself.
  - Report all results in a single, \*.pdf-file. *Other formats, such as Word, Rmd, Jupyter Notebook, or similar, will automatically be failed.* Although, you are allowed to first knit your document to Word and then print the assignment as a PDF from Word if you find it difficult to get TeX to work.
  - The report should be submitted to the [Studium](#).
  - To pass the assignments, *all questions should be answered*, although minor errors are ok.
  - A report that do not contain the general information (see template) will be automatically rejected.
  - When working with R, we recommend writing the reports using R markdown and the provided [R markdown template](#). The template includes the formatting instructions and how to include code and figures.
  - If you have a problem with creating a PDF file directly from R markdown, start by creating an HTML file, and then just print the HTML to a PDF.
  - Instead of R markdown, you can use other software to make the pdf report, but the same instructions for formatting should be used. These instructions are also available in [the PDF produced from the R markdown template](#).
  - The course has its own R package `uuml` with data and functionality to simplify coding. To install the package just run the following:
    1. `install.packages("remotes")`
    2. `remotes::install_github("MansMeg/IntroML",  
subdir = "rpackage")`
  - We collect common questions regarding installation, and technical problems in a course Frequently Asked Questions (FAQ). This can be found [here](#).
  - Deadline for all assignments is **Sunday at 23.59**. See the course page for dates.
  - If you have any suggestions or improvements to the course material, please post in the course chat feedback channel, create an issue, or submit a pull request to the public repository!
-

# 1 Convolutional Neural Networks

## 1.1 A convolutional layer

As a first step, we will implement a layer of a convolutional neural network with one filter. We will here not train the layer, just implement it to understand the inner workings.

*Reading:* Some good material for this exercise is Figure 9.1 in Goodfellow et al (2017) and the video Ng (2020).

Start by importing examples from the MNIST dataset as follows.

```
library(uuml)
data("mnist_example")
```

To visualize an image use:

```
im <- mnist_example[["5"]]
image(1:ncol(im), 1:nrow(im), im,
      xlab = "", ylab = "",
      xaxt='n', yaxt='n', main="4")
```

1. Visualize the MNIST example digit 4.
2. Implement a convolution function called `convolution(X, K)` that takes an input MNIST image ( $X$ ), an arbitrary large square kernel ( $K$ ) and returns a valid feature map. Below is an example of how it should work.

```
X <- mnist_example[["4"]][12:15,12:15]
X

##      [,1] [,2] [,3] [,4]
## [1,]   56  250  116    0
## [2,]    0  240  144    0
## [3,]    0  198  150    0
## [4,]    0  143  241    0

K <- matrix(c(1, 1, 0, 0), nrow = 2)
K

##      [,1] [,2]
## [1,]    1    0
## [2,]    1    0

convolution(X, K)

##      [,1] [,2] [,3]
## [1,]   56  490  260
## [2,]    0  438  294
## [3,]    0  341  391
```

3. Visualize the feature map of MNIST example digit 4 using the above two by two kernel K.
4. Now implement all steps in a `convolutional_layer(X, K, b, activation)` function that takes the kernel, bias and activation function. It should work as follows.

```
relu <- function(x) max(0, x)
X <- mnist_example[["4"]][12:15,12:15]
K <- matrix(c(1, 1, 1,
              0, 0, 0,
              0, 0, 0), nrow = 3, byrow = TRUE)
convolutional_layer(X, K, -370, relu)

##      [,1] [,2]
## [1,]   52   0
## [2,]   14  14
```

5. Run your convolutional layer on MNIST example digit 4 with bias -400. Visualize the feature map as you visualized the original image. What does the filter seem to capture?
6. Now transpose your filter and run your convolutional layer on MNIST example digit 4 with bias -450. Visualize the feature map. What does that transposed filter seem to capture?
7. As the last step in our convolutional layer, implement a two by two, two stride max-pooling layer. It should work as follows.

```
X <- mnist_example[["4"]][12:15,12:15]
maxpool_layer(X)

##      [,1] [,2]
## [1,]  250  144
## [2,]  198  241
```

8. Now put it all together and visualize the final output of your own convolutional layer. Visualize the feature map.

```
X <- mnist_example[["4"]]
relu <- function(x) max(0, x)
K <- matrix(c(1, 1, 1,
              0, 0, 0,
              0, 0, 0), nrow = 3, byrow = TRUE)
output <- maxpool_layer(convolutional_layer(X, K, -370, relu))
```

## 1.2 Convolutional neural networks using Keras

We are now going to implement a convolutional neural network using Keras. Here Ch. 5.1 in Chollet and Allarie (2018) and the [following tutorial](#) might be useful. Remember

to load the `tensorflow` R package before loading the `keras` R package. If you get stuck, ask for help from your fellow students in Slack.

*Note!* Running Keras can be computationally heavy and I suggest not to run the code in `markdown`. Instead, run the code in R and copy in the results as output (see the assignment template for an example).

1. Implement a Convolutional Neural Network for the MNIST dataset. The network should have two convolutional layers as follows.

```
## -----
## Layer (type)                Output Shape          Param #
## =====
## conv2d (Conv2D)             (None, 26, 26, 32)    320
## -----
## max_pooling2d (MaxPooling2D) (None, 13, 13, 32)    0
## -----
## conv2d (Conv2D)             (None, 11, 11, 32)    9248
## -----
## flatten (Flatten)           (None, 3872)          0
## -----
## dense (Dense)                (None, 64)            247872
## -----
## dense (Dense)                (None, 10)            650
## =====
## Total params: 258,090
## Trainable params: 258,090
## Non-trainable params: 0
```

2. Explain why there are 320 parameters in the first layer. How many are kernel weights (and why), and how many biases?
3. Train the network using Keras. What is your loss and accuracy on the MNIST dataset?
4. As the next step, we will implement a similar network for the CIFAR-10 dataset using `dataset_cifar10()`. See the [tutorial](#) for details on how to load data. Implement a similar CNN as in the tutorial. That is:

```
## Model: "sequential"
## -----
## Layer (type)                Output Shape          Param #
## =====
## conv2d (Conv2D)             (None, 30, 30, 32)    896
## -----
## max_pooling2d (MaxPooling2D) (None, 15, 15, 32)    0
## -----
## conv2d_1 (Conv2D)           (None, 13, 13, 64)    18496
## -----
## max_pooling2d_1 (MaxPooling2D) (None, 6, 6, 64)      0
## -----
## conv2d_2 (Conv2D)           (None, 4, 4, 64)      36928
## -----
```

```

## flatten (Flatten)                (None, 1024)                0
## -----
## dense (Dense)                    (None, 64)                  65600
## -----
## dense_1 (Dense)                  (None, 10)                  650
## =====
## Total params: 122,570
## Trainable params: 122,570
## Non-trainable params: 0
## -----

```

5. Why do we now have 896 parameters in the first convolutional layer?
6. Try out at least three different networks, describe the networks, why you chose it, and the Keras model output. For example, you can add a **dropout\_layer** (see Chollet and Allaire, 2018, Ch. 5.3). Can you improve over the previous network concerning accuracy? You can also use regularization techniques from the previous lab.

### 1.3 Transfer learning using VGG16

As the last step, we will look into using transfer learning as a quick way of improving the prediction accuracy on the cifar-10 dataset. Here Ch. 5.3 in Chollet and Allaire (2018) or [this tutorial](#) might be helpful.

1. Using Keras, download the VGG16 convolutional neural network. Just download the convolutional base. We are going to use the network on the cifar-10 dataset so change the `input_size` to `c(32, 32, 3)`.
2. Now add a dense layer with 64 hidden nodes (as in the previous exercise). Include the Keras model output in the assignment report. How many parameters do you have in the dense top layer (compared to the CNN in the previous part).
3. Now, freeze the convolutional base and train the dense top layer of your network on the cifar-10 dataset. Run it for five epochs. *Note!* This will take time. Don't be surprised if you need roughly 200s per epoch or more.
4. Report your final accuracy. How does this compare to the previous model for the cifar data?