Uppsala University



Machine Learning

Assignment 7

General information

- The recommended tool in this course is R (with the IDE R-Studio). You can download R **here** and R-Studio **here**. You can use Python and Jupyter Notebooks, although the assignments may use data available only through the R package, a problem you would need to solve yourself.
- Report all results in a single, `*.pdf`-file. *Other formats, such as Word, Rmd, Jupyter Notebook, or similar, will automatically be failed.* Although, you are allowed first to knit your document to Word or HTML and then print the assignment as a PDF from Word or HTML if you find it difficult to get TeX to work.
- The report should be written in English.
- If a question is unclear in the assignment. Write down how you interpret the question and formulate your answer.
- You should submit the report to **Studium**. Deadlines for all assignments are **Sunday 23.59**. See **Studium** for dates. Assignments will be graded within 10 working days from the assignment deadline.
- To pass the assignments, *you should answer all questions not marked with **, and get at least 75% correct.
- To get VG on the assignment, *also the questions marked with a ** should be answered. Sometimes you can choose between different VG assignments, then this is explicitly stated. To get VG you need 75% both on questions to pass and the VG part of the assignment. VG will only be awarded on the first deadline of the assignment.
- A report that does not contain the general information (see the **template**), will be automatically rejected.
- Every assignment report must include one oral exam question of your own together with a short model answer, following the oral exam question contribution instructions in this assignment. You are not allowed to use large language models, such as ChatGPT, at all for this contribution.
- State clearly whether the course staff may use or adapt your question and answer in a future oral exam: **Yes** or **No**.
- When working with R, we recommend writing the reports using R markdown and the provided **R markdown template**. The template includes the formatting instructions and how to include code and figures.
- Instead of R markdown, you can use other software to make the pdf report, but you should use the same instructions for formatting. These instructions are also available in **the PDF produced from the R markdown template**.
- The course has its own R package `uuml` with data and functionality to simplify coding. To install the package just run the following:

```
1. install.packages("remotes")
```

2. `remotes::install_github("MansMeg/IntroML", subdir = "rpackage")`

- We collect common questions regarding installation and technical problems in a course Frequently Asked Questions (FAQ). This can be found **here**.
- You are not allowed to show your assignments (text or code) to anyone. Only discuss the assignments with your fellow students. The student that show their assignment to anyone else could also be considered to cheat. During scheduled support sessions held on Zoom, only share your screen in a separate room with a teaching assistant.
- You may use large language models (LLMs), such as ChatGPT, like you may discuss with fellow students: to learn, ask for explanations, and get feedback. You may not use LLMs to produce the solution you submit. You must be able to explain every part of your own assignment at the oral exam, including your code, results, and reasoning, even when it is not covered by the published oral exam questions. If course staff have concerns about your understanding or the authorship of any part of your submission, you may be asked to explain that part at the oral exam.
- Where an exercise explicitly asks you to run an LLM and report its output, you may do so for that experiment. Your explanations and analysis must be your own. This permission does not apply to the oral exam question contribution, for which LLM use is prohibited entirely.
- Do not copy or upload the full assignment text into an LLM.
- Scheduled support sessions are for questions about the assignments and course material. Do not hesitate to ask! Ask questions early if instructions are unclear or you encounter possible bugs, so you do not lose time unnecessarily.
- If you have any suggestions or improvements to the course material, please post in the course chat feedback channel, create an issue **here**, or submit a pull request to the public repository.

Contents

Oral exam question contribution 4

1 Variational Autoencoders 5

2 Topic Models 6

3 * Variational Autoencoders using Convolutional Neural Networks 9

4 * Prompt engineering with ChatGPT 10

4.1 Make ChatGPT hallucinate 10

4.2 In-Context Learning for few-shot classification 11

Reading priorities for the basic assignment.

- **VAE:** Prioritize Kingma and Welling (2019, Sections 2.1–2.5): encoder/decoder, ELBO (reconstruction and KL terms), and Gaussian reparameterization.
- **Topic models:** Focus on *Using Gibbs Sampling to Discover Topics* in Griffiths and Steyvers (2004) for the model and sampler. Use *Latent Dirichlet Allocation* in Blei (2012) for an introductory overview.

Oral exam question contribution

Write one possible oral exam question of your own for this assignment together with a short model answer. Include both in your assignment report.

The question should:

- concern material from this assignment or the associated reading or lectures,
- be suitable for a 2–4 minute oral answer, possibly using a whiteboard,
- test conceptual understanding rather than only calculation or code,
- not already be included in the oral exam question list and not be very close to an existing question (e.g. just different numbers).

Note! You are not allowed to use large language models, such as ChatGPT, at all for this oral exam question contribution.

State clearly whether the course staff may use or adapt your question and answer in a future oral exam: **Yes** or **No**.

1 Variational Autoencoders

Keras, TensorFlow, and Google Colab

This assignment uses `keras3` and `tensorflow` for R. To work in Google Colab, open the course R setup notebook, save a copy in Google Drive, and run its setup and training-check cells. Wait for "PASS: training and prediction work" before starting the assignment.

Use the assignment report template linked in the notebook to structure your report. Write explanations in text cells and put R code in code cells. Save your notebook and results in Drive, and run the setup cell again at the start of each R session.

For local installation, follow the course R setup guide. Details on the architecture components are available in the `keras3` reference.

We will implement a variational autoencoder in R using `keras3` and TensorFlow. Use the feed-forward VAE example as a starting point.

Note! Training can take time. Run it once and reuse the fitted encoder and decoder for the remaining tasks. Keep the training output and figures for your report.

1. (1p) Start by loading the MNIST data in R. See the link above or previous assignments for details.

2. (1p) Now, implement a one-layer (encoder and decoder) feed-forward variational autoencoder with two latent dimensions. Both the encoder layer and the decoder layer should have 200 hidden units. You should end up with a variational autoencoder with roughly 310 000 - 320 000 parameters.

   Example: Sanity check *No submission required*

   For a batch of m images, the encoder should return an $m \times 2$ matrix of latent means. Decoding these should return an $m \times 784$ matrix with pixel values in $[0, 1]$. Check a few images before full training.

3. Print the model and include it in your report.

   (a) (1p) How many weights (parameters) are used to compute μ and σ^2 for the latent variables?

   (b) (1p) **KL experiment.** The function below computes $D_{\mathrm{KL}}(q\|p)$, comparing the encoder distribution $q = N(\mu, \sigma^2)$ with the prior $p = N(\mu_0, \sigma_0^2)$. Both σ and σ_0 are standard deviations. Keep the prior fixed at $(\mu_0, \sigma_0) = (0, 1)$. Predict the ordering for q with $(\mu, \sigma) = (0, 1)$, $(2, 1)$, and $(0, 2)$, then calculate the KL values. Which q is closest to the prior? Why would minimizing only KL fail to reconstruct different images?

   Hint! For this fixed prior, the function matches the one-dimensional KL term in the sampling layer.

```r
kl_normal <- function(mu, sigma, mu_0, sigma_0) {
  log(sigma_0 / sigma) +
    (sigma^2 + (mu - mu_0)^2) / (2 * sigma_0^2) - 0.5
}
kl_normal(mu = -1, sigma = 0.5, mu_0 = 0, sigma_0 = 1)
```

4. Before training, use the supplied `vae_loss_components()` scaffold to record the reconstruction, KL, and total losses. Train your variational autoencoder on MNIST for 50 epochs, then record them again using the same 100 images and the same sampled noise. The example stores these as `loss_before` and `loss_after`. Visualize the latent state for the different numbers.

   (a) (1p) How do you interpret this latent state?

   (b) (1p) What numbers are better represented by the latent state?


   (c) (1p) What number is less well represented by the latent state?

   (d) (1p) **Loss experiment.** Report the before/after loss table. Which term changed most? Do reconstruction and KL loss both need to decrease for their sum to improve? Explain using your results.

5. (2p) Finally, encode all the 2:s in the MNIST test dataset to the latent state using your encoder. What is the mean of the digits "2" in the two latent dimensions? *Hint!* See `y_test` for the MNIST numbers. *Note!* Do not retrain your VAE. Just use the one you have already trained.

6. (1p) Visualize this value of the latent state as a 28 by 28-pixel image using your decoder.

Example: VAE reference output *No submission required*



Illustrative decoder grid from the supplied feed-forward VAE after 50 epochs on MNIST. Each cell decodes a different latent coordinate. Some digits may look blurred or blended. Your arrangement can differ because training is stochastic and the latent axes have no fixed interpretation.

2 Topic Models

We will now analyze the classical book Pride and Prejudice by Jane Austen using a probabilistic topic model. If you have not read the book, **here** you can read up on the story of this classical book.

We will use a Gibbs sampler to estimate ten different topics occurring in Pride and Prejudice and study where they occur. A tokenized version of the book and a `data.frame` with stopwords can be loaded as follows:

```
library(uuml)
library(dplyr)
library(tidytext)
data("pride_and_prejudice")
data("stopwords")
```

1. **Setup (ungraded).** Remove stopwords (common English words without much semantic information):

```
pap <- pride_and_prejudice
pap <- anti_join(pap, y = stopwords[stopwords$lexicon == "snowball",])

## Joining with `by = join_by(word)`
```

2. **Setup (ungraded).** Remove words that occur at most five times:

```
word_freq <- table(pap$word)
rare_words <- data.frame(word = names(word_freq[word_freq <= 5]),
                         stringsAsFactors = FALSE)
pap <- anti_join(pap, y = rare_words)

## Joining with `by = join_by(word)`
```

3. (1p) The supplied code builds a document-term matrix, treating each paragraph as a document. Report the number of documents and terms (word types).

```
library(tm)
crp <- aggregate(pap$word, by = list(pap$paragraph),
                 FUN = paste0, collapse = " ")
names(crp) <- c("paragraph", "text")
s <- SimpleCorpus(VectorSource(crp$text))
m <- DocumentTermMatrix(s)
```

4. **Setup (ungraded).** Fit a topic model with ten topics using Gibbs sampling for 2000 iterations and the fixed seed below. Fit the model once and reuse the fitted model `tm` for the likelihood trace, topic interpretation, and paragraph plots.

```
library(topicmodels)
K <- 10
# Note: delta is beta in Griffith and Steyvers (2004) notation.
control <- list(keep = 1, delta = 0.1, alpha = 1, iter = 2000,
                seed = 4711)
tm <- LDA(m, k = K, method = "Gibbs", control)
```

5. **Setup (ungraded).** Extract Θ, Φ, and the log-likelihood values using the supplied code. This is the parameter notation used in Griffiths and Steyvers (2004).

```
library(uuml)
lls <- extract_log_liks(tm)
theta <- extract_theta(tm)
phi <- extract_phi(tm)
```

6. (2p) Plot the log-likelihood against Gibbs iterations. Does it settle into a roughly stable range, or does a persistent trend remain? Support your assessment using the plot.

   Hint! Fluctuations are normal in Gibbs sampling. Look for changes in the typical level rather than expecting a smooth or steadily increasing curve. A single likelihood trace cannot establish convergence of all model parameters.

7. (2p) Inspect the 20 top words for each topic and choose two whose words seem to belong together. For each chosen topic, inspect one or two paragraphs where its estimated topic proportion is high. Include the two word lists, suggest an informative label for each topic, and explain each label using the top words and paragraph content.

   Hint! Set `topic` to a chosen topic number. Use `crp$paragraph` to map rows of `theta` back to the original text.

```
topic <- 1
paragraph_ids <- crp$paragraph[
  head(order(theta[, topic], decreasing = TRUE), 2)]
pride_and_prejudice |>
  filter(paragraph %in% paragraph_ids) |>
  group_by(paragraph) |>
  summarise(text = paste(word, collapse = " "), .groups = "drop")
```

8. (2p) Visualize these two topics evolve over the paragraphs in the books by plotting the θ parameters for that topic over time (paragraphs) in the book. Think of this as the time-line of the book. On the y-axis, you should plot θ_i for your chosen topic i and the x-axis should be the paragraph number (first paragraph has number 1 and so forth).

9. (2p) How do these two chosen topics evolve over the course in the book? If you want, you can take a rolling mean of the theta parameters to more easily show the changes in the topic over the book. *Hint!* Here `zoo::rollmean()` might be a good function to use.

3 * Variational Autoencoders using Convolutional Neural Networks

This task is only necessary to get one point toward a *pass with distinction* (VG) grade. Hence, if you do not want to get a *pass with distinction* (VG) point, you can ignore this part of the assignment.

You can choose to either do this task or the task below to get VG on this assignment.

As we have seen previously, for images, we can get better performance using Convolutional Neural Networks. Hence we are going to repeat the exercise above using a convolutional neural network as encoder and decoder. You can find detailed code in the file `variational_autoencoder_deconv_keras3.R`.

1. (3p) Now implement a four-layer (encoder and decoder) convolutional neural network with two latent dimensions. Use 50 filters in each hidden convolutional layer. *Note!* A dense layer should be included as the last step in the encoder and the first step in the decoder. These layers should have 100 hidden units. You should end up with a variational autoencoder with roughly 2M parameters.

2. (1p) Print the model and include it in your report. How many weights (parameters) are used to compute μ and σ^2 for the latent variables? What layer represent the latent variables?

3. (1p) Now train your CNN variational autoencoder on the MNIST data for five epochs. Visualize the latent state for the different numbers. How do you interpret this result? Compare these results with the results from the feed-forward autoencoder.

4. (1p) Finally, encode all the 2:s in the MNIST test dataset to the latent state using your encoder (Hint!, see `y_test` for numbers). What is the mean of the digits "2" in the two latent dimensions?

5. (1p) Visualize the mean value of the digit 2 of the latent state as a 28 by 28-pixel image using your decoder.

4 * Prompt engineering with ChatGPT

You can choose to either do this task or the task above to get VG on this assignment.

This task is only necessary to get one point toward a *pass with distinction* (VG) grade. Hence, if you do not want to get a *pass with distinction* (VG) point, you can ignore this part of the assignment.

For this assignment, you need to have a user account at Open AI to generate an API token. See [this link] for details on how to get an API token to use.

Warning: Do not upload any files containing your API key to public repositories (Github, public google colab, etc.).

You also need to buy credits at Open AI. I think 1-2 dollars should be sufficient for this assignment.

As a second step you need to install the `ropenaiapi` R package. This can be done as follows:

```
library(remotes)
remotes::install_github('MansMeg/ropenaiapi')
```

In the next step we set the API key as an environment variable with:

```
library(ropenaiapi)
set_openai_api_key("[YOUR KEY GOES HERE]")
```

We can now call the API with the `openai_chat` function.

```
x <- openai_chat("Who is Gustav Vasa? Give a short answer.",
                 model = "gpt-3.5-turbo")
x
```

```
## assistant:
## Gustav Vasa was a Swedish king who led a successful rebellion
## against Danish rule and became the founder of modern Sweden in
## the 16th century.
```

See the `ropenaiapi` documentation with "'?openai_chat"' in R for further information on how to interact with the Open AI API.

Note! If you get "'Error: You exceeded your current quota, please check your plan and billing details."' that means that you don't have any credits to use for the calls. You then need to buy some credits from Open AI, 1-2 dollars should be sufficient for this task.

4.1 Make ChatGPT hallucinate

We are now going to understand how and when transformer-based decoder models 'hallucinate', i.e. when the models give factual incorrect information. See (Zhao et al., 2023,

, Section 7.1.2) for an introduction and Huang et al. (2023) for details on hallucinations in LLMs.

Now, create 3 different hallucinations with three different strategies (i.e. its not ok to use the same prompt for three incorrect generations) from the chatGPT models (you can choose which one you like). For each generated hallucination return:

1. The prompt and a the `seed` supplied to the API. You are free to both create hallucinations through a longer conversation and tuning parameters.
2. The response from the LLM.
3. Why the response is factually incorrect and weather it is an intrinsic or extrinsic hallucination.
4. Describe the strategy you use and the analysis why the hallucination happened.

As a final step, when you have succeded to get the LLM to hallucinate, change the model to GPT-4 (include exact which model you use) and run the same prompt that you could get to hallucinate.

1. Return the response from GPT4 for each prompt.
2. Is the response still factually incorrect? If not, see if you can get at least one hallucination for GPT-4. If you don't succeed, just state that.

4.2 In-Context Learning for few-shot classification

In-context learning is the idea to use large language models to complete tasks in a few-shot or zero-shot way. In this task we are going to try to classify political quotes in Swedish to weather they belong to the social democratic party manifesto or the conservative party (Moderaterna) manifesto.

Note! This data is included in `uuml` version 0.4.0 and later.

```
library(uuml)
data("pc_test")
data("pc_train")
```

Below is an example on how you can combine the data to a text string that can be combined to be used in a prompt. Note, you need to develop further on this.

```
example_string <- paste0(pc_train$quote,
                         ": ",
                         pc_train$party, collapse = "\n\n")
cat(example_string)
```

Example: Prompt formatting *No submission required*

```
prompt <- paste(
  "Classify the quote. Return only the party label.",
  paste("Examples:", example_string, sep = "\n"),
  paste("Quote to classify:", pc_test$quote[1], sep = "\n"),
  sep = "\n\n"
)
cat(prompt)
```

`"\n"` starts a new line; `"\n\n"` separates blocks with a blank line. Use `cat(prompt)` to inspect the formatting before sending it.

Use the techniques from (Zhao et al., 2023, Section 6.1-6.3) to generate as good prompts as possible to classify weather a quote is from the social democratic or the conservative manifesto.

1. Start with zero-shot learning, ie only prompt the LLM without any demonstrations. Test to classify the quotes in the test set.
2. Test how far you can get by using better prompt descriptions to classify the quotes. Try to get responses as classes from the model.
3. Now add demonstrations by adding examples from the training set. Does that improve the accuracy on the testset?
4. Try at least three different strategies from (Zhao et al., 2023, Section 6.1-6.3) to improve the quality. Discuss your conclusions.

References

Diederik P. Kingma and Max Welling. An introduction to variational autoencoders. *arXiv preprint arXiv:1906.02691*, 2019. URL https://arxiv.org/abs/1906.02691.

Thomas L Griffiths and Mark Steyvers. Finding scientific topics. *Proceedings of the National academy of Sciences*, 101(suppl 1):5228–5235, 2004.

David M Blei. Probabilistic topic models. *Communications of the ACM*, 55(4):77–84, 2012.

Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen Zhang, Junjie Zhang, Zican Dong, Yifan Du, Chen Yang, Yushuo Chen, Zhipeng Chen, Jinhao Jiang, Ruiyang Ren, Yifan Li, Xinyu Tang, Zikang Liu, Peiyu Liu, Jian-Yun Nie, and Ji-Rong Wen. A survey of large language models, 2023.

Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, and Ting Liu. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions, 2023.