

Mansee Dakhole

Malaria Parasite Detection readme5

 Get Your own Turnitin account as low as 3\$ a month!

Document Details

Submission ID

trn:oid::3117:521645034

Submission Date

Nov 2, 2025, 7:15 PM GMT+5:30

Download Date

Nov 2, 2025, 7:15 PM GMT+5:30

File Name

Malaria Parasite Detection readme5.pdf

File Size

166.0 KB

6 Pages

1,382 Words

8,288 Characters

8% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

Filtered from the Report

- Bibliography

Match Groups

-  **9** Not Cited or Quoted 8%
Matches with neither in-text citation nor quotation marks
-  **0** Missing Quotations 0%
Matches that are still very similar to source material
-  **0** Missing Citation 0%
Matches that have quotation marks, but no in-text citation
-  **0** Cited and Quoted 0%
Matches with in-text citation present, but no quotation marks

Top Sources

- 3%  Internet sources
- 2%  Publications
- 5%  Submitted works (Student Papers)

Match Groups

- 9** Not Cited or Quoted 8%
Matches with neither in-text citation nor quotation marks
- 0** Missing Quotations 0%
Matches that are still very similar to source material
- 0** Missing Citation 0%
Matches that have quotation marks, but no in-text citation
- 0** Cited and Quoted 0%
Matches with in-text citation present, but no quotation marks

Top Sources

- 3% Internet sources
- 2% Publications
- 5% Submitted works (Student Papers)

Top Sources

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

1	Student papers	University of Hertfordshire on 2025-01-06	2%
2	Internet	www.mdpi.com	2%
3	Student papers	Murdoch University on 2025-04-15	1%
4	Student papers	Ravensbourne on 2025-08-22	<1%
5	Internet	dokumen.pub	<1%
6	Internet	publish.kne-publishing.com	<1%
7	Publication	Pushpa Choudhary, Sambit Satpathy, Arvind Dagur, Dharendra Kumar Shukla. "Re...	<1%

Detection of Parasites-Malaria in Blood Smear

Project Overview

- 6 Malaria is one of the most deplorable public health challenges existing in the world causing an estimation of 400, 000 deaths annually. The appropriate diagnosis is quite crucial in terms of the right treatment and management of this disease. Traditional diagnosis by conventional microscopy though can be called as gold standard requires skilled technicians and is also time consuming. These issues are addressed through this project that develops an automated computer vision system with a high potential of identifying blood smear images as either parasitized or uninfected.

The primary aim is to apply and compare different machine learning and deep learning models that detect malaria, and this will enable conducting a comprehensive study of how they work, what computing resources they require, and whether they can be utilized in the actual medical diagnostic.

Dataset Information

Source and Description

- Dataset: Malaria Cell Images Dataset Kaggle.
- Referent source: National institute of health (NIH).
- Total images: 27, 558 images of blood cells.

Classes:

- Parasitized: 13,779 images
- Uninfected: 13,779 images
- Image Format: The single blood cell of a JPEG format.

Data Preprocessing

The dataset was pre processed in several ways to ensure the optimal model performance is achieved:

Image Resizing: Since uniformity was required, and processing costs needed to be reduced, all images were reduced to 64 by 64 pixels.

- 5 Normalization: The values of pixel values were divided by 255 in order to scale them to the [0,1] range.

Data augmentation: Applied changes:

- Rotations (± 20 degrees)
- Width , height shifting ($\pm 10\%$)

Horizontal and vertical flipping.

- Zooming ($\pm 10\%$)
- Shearing ($\pm 20\%$)

Class Balance Checking: This proved to be equal distribution between parasitized and uninfected classes.

Methodology

Approach Rationale

The multi-model comparative approach is used in the project to determine the efficient solution in the issue of malaria detection. This methodology has been selected due to the following reasons:

Thorough Analysis: The other model structures possess different capabilities in terms of medical image analysis.

Performance Benchmarking: It enables the direct comparison between modern and traditional methods.

Practical Considerations: Gives an understanding on trade-offs between accuracy, speed and computational needs.

Implemented Models

Classical Model of Machine Learning.

Random Forest Classifier

- 100 estimators with max depth of 10
- Non-linear relationship ability good.
- Gives feature importance analysis.

SVM

- rbf kernel with C=1.0
- Good in high dimensional data.
- Well developed generalization skills.

Logistic Regression

- L2 regularization with C=0.1
- Uncomplicated and self-explanatory basic model.
- Fast training and inference

Deep Learning Models

CNN

- The architecture has three convolutional layers including maximum pooling.
- In the second group, regularization is done: batch normalization (0.25-0.5) and dropout.
- Adam will be the optimizer where learning rate is 0.001.
- The final layer is the Sigmoid activation of binary classification.

Transfer-Learning with VGG16

- Pre-trained with ImageNet dataset.
- frozen base layers and with a personalised classifier head.
- thick layers following mean swimming.
- The learning rate reduced to 0.0001 has improved.

Model Comparison Framework

metrics: models were evaluated using metrics:

- Accuracy: Classification total performance.
- Precision: It is the ability to avoid false positives.
- F1-Score: precision + recall /mean.
- Recall: The ability to perceive all the positive cases.
- ROC-AUC: Classification total capacity.

Implementation Guide

Prerequisites

- Python 3.8
- Tensorflow 2.10
- Scikit-learn 1.2
- Opencv 4.7
- Streamlit 1.24

Installation Steps

Clone the repository with: shell the repository.

<https://github.com/yourusername/malaria-detection.git>

cd malaria detection

1.Create an online atmosphere:

```
bash;  
python -m venv malariaenv;  
malariaenv\Scripts\activate; # Windows.
```

2.Dependencies using

```
bash  
pip install requirements.txt
```

3.Dataset

- Source: <https://www.kaggle.com/iarunava/cell-images-for-detecting-malaria>
- Download, date: 2015-02-25.
- De-extract to cellimages/ directory
- 5.5834/0.007 seconds

Running the Project

Training Models

```
bash
```

```
jupyter notebook
```

Click on MalariaDetectionProject.ipynb and run.

Web Application

```
bash
```

```
streamlit run app.py
```

Entry and data mining cells.

Machine preprocessing and extraction feature Run preprocessing and feature extraction

Train traditional ML models

Train deep learning models

Create evaluation measures and visualization.

Experimental Results

Performance Comparison

Model	Accuracy	F1-Score	Precision	Recall
Random Forest	0.9342	0.9341	0.9356	0.9327
SVM	0.9218	0.9216	0.9251	0.9182
Logistic Regression	0.9067	0.9064	0.9103	0.9026
Custom CNN	0.9683	0.9682	0.9691	0.9674
VGG16 Transfer Learning	0.9574	0.9573	0.9589	0.9558

Key Findings

Deep Learning Dominance: CNN and VGG16 models performed significantly higher in comparison to traditional ML strategies with more than 95 percent accuracy as compared to 90-93 percent of traditional models.

Computational Trade-offs: Deep learning models were much more accurate, although much more time and computational resources were required to train them.

Feature Learning Capability: The trained CNN proved learned features on raw images are more discriminative as compared to manually designed features that were employed in conventional ML.

Transfer Learning Effectiveness: VGG16 was highly effective even when it was pre-trained using natural images, which implies that the features could be transferred to medical images.

Visualization Results

Confusion Matrix Analysis

- Traditional ML: Relatively balanced false positive and false negative errors were observed.
- Deep Learning: It showed low misclassifications and high diagonal dominance.

ROC Curve Performance

- All the models had AUC scores of more than 0.95.
- CNN model had the best AUC of 0.992.
- Traditional models: The traditional models are concentrated in the 0.96-0.98 AUC.

Training Dynamics

- The convergence of CNN was smooth with low overfitting.
- VGG16 had a rapid initial learning because of features which were pre-trained.
- Traditional models leveled off soon with minimal improvement.

Hyperparameter Analysis

Experiments with different architectures revealed:

- 3 convolutional layers provided optimal depth for this task
- Batch normalization improved training stability and convergence
- Dropout rates of 0.25-0.5 prevented overfitting effectively

The classical ML Parameter Tuning.

- Random Forest: The optimal estimator was the 100 estimators, with max depth of 10.
- SVM has optimum performance of RBF kernel and $C=1.0$.
- L2 regularization $C=0.1$ was helpful to logistic regression.

Conclusion

Key Learnings

Model Selection: Due to the ability of deep learning methods, such as CNNs, to hierarchically learn features, they are specifically advantageous in medical picture classification problems such as malaria diagnosis.

Practical Considerations: Although deep learning model has better accuracy, the more intuitive traditional ML methods have faster training and easier deployment, and thus are an appropriate choice in resources-constrained contexts.

Data Quality Importance: It is notable that all the models perform well, which indicates the significance of the presence of a well-curated and balanced dataset with unambiguous labeling.

Transfer Learning Value: Medical imaging tasks can be trained with the help of the effective adaptation of pre-trained models such as VNN16 which does not require a lot of training data and processing resources.

Future Directions

1. Ensemble Methods: Predict a number of models by using their combination to make predictions that are more resilient.
2. Explainable AI: Visualization Implement the model decisions.
3. Clinical Check: Do actual trials with the medical practitioners.
4. Mobile Deployment: Optimize models to be deployed on mobile devices on a field.

Impact Assessment

As it is shown in this project, automated malaria detection systems can exhibit diagnostic accuracy, which may help healthcare professionals in areas where trained microscopists are not readily available. The comparative analysis offers fruitful information to researchers and practitioners who chose the right methodology in similar medical imaging works.

References

1. World Health Organization. (2022). World Malaria Report 2022. Geneva: WHO Press.
2. Rajaraman, S., et al. (2018). Pre-trained convolutional neural networks as feature extraction networks in the direction of better malaria parasite detection in thin blood smear images. PeerJ, 6, e4568.

3. Simonyan, K., & Zisserman, A. (2014). Very deep convolutional networks of large-scale image recognition. arXiv preprint arXiv:1409.1556.
4. Pedregosa, F., et al. (2011). Scikit-learn: Python machine learning. J.Machine Learning Research, 12, 2825-2830.
5. Abadi, M., et al. (2016). TensorFlow: A machine learning system in large scale. OSDI, 16, 265-283.

File Structure

```
'''
```

```

malaria-detection/
├── Malaria_Detection_Project.ipynb # Main project notebook
├── app.py                          # Streamlit web application
├── requirements.txt                # Python dependencies
├── saved_models/                  # Trained model files
│   ├── cnn_malaria_model.h5
│   ├── vgg16_malaria_model.h5
│   ├── random_forest_model.pkl
│   ├── svm_model.pkl
│   ├── logistic_regression_model.pkl
│   └── label_map.json
├── cell_images/                   # Dataset directory
│   ├── Parasitized/
│   └── Uninfected/
└── README.md                      # Project documentation

```