APTOHIRE

Product Requirements Document

Product scope, roles, user journeys, acceptance criteria and guardrails

Version 1.0 • 30 October 2026

Product status: prototype / demo specification. This document describes intended behavior and technical contracts; it is not a production-readiness certification.

1. Executive summary

AptoHire is specified as an AI-driven skill-verification and hiring platform: students demonstrate capability through real projects; an audit produces evidence-linked skill scorecards; organizations discover anonymized candidates and request scoped access; identity is revealed only after student consent.

2. Problem statement and product hypothesis

The source PRD frames the problem as a mismatch between what a resume claims and what an applicant can demonstrate. Skilled students, especially those from Tier-2 and Tier-3 institutions, may be overlooked while employers face manual verification effort and uncertainty. The product hypothesis is that structured project evidence, explainable assessments, and consent-first discovery can improve the quality of capability signals.

Validation status: this is a product hypothesis, not a proven market outcome. The survey URL exists, but no response export was supplied for analysis.

3. Product goals and success criteria

Goal	Demo acceptance signal
Student proof moment	A student submits a project and sees an evidence-linked scorecard; demo target is under ~2 minutes, while the broader target is under ~10 minutes.
Blind matching	An organization posts a job, views ranked anonymized cards with match reasons, requests access, and receives identity only after student acceptance.
University value	University user sees roster, verification status, skill and placement analytics.
Lifecycle continuity	A profile retains its history through graduation, dropout, and university changes.
Portal separation	Root, student, university, organization and admin experiences resolve to the correct portal.
Low-cost demo	Mock/fallback paths exist so a demo does not depend on one external AI service.

4. Personas and roles

Role	Primary job-to-be-done	Key needs
Student	Prove capability and access opportunities	Guided projects, evidence capture, transparent scorecards, appeal, privacy controls.
University user / TPO	Understand cohort readiness and placement gaps	Roster workflows, verified-skill visibility, lifecycle status, aggregated insights.
Organization recruiter	Find relevant talent with less manual screening	Job creation, anonymized candidates, match explanations, consent-based access.
Platform admin	Govern onboarding, audits and exceptions	Approvals, borderline reviews, appeals, audit trails, sensitive-action MFA.

5. In-scope requirements

• Identity and access: email/password or OTP flows as specified by the portal prompts; role assignment is server-controlled and a user cannot change their own role.

• University onboarding: approval workflow and roster import; unregistered affiliations remain explicitly unverified.

• Project lifecycle: target skill/role selection, curated project assignment, submission metadata, video and supporting evidence, AI-use disclosure.

• Audit: rubric-based per-skill scoring, rationale, confidence, evidence references and borderline human review.

• Skill profile: scorecard, verified badges, skill graph, profile proposals and downloadable digital resume with public verification.

• Matching: job posts, structured plus vector matching, ranked anonymized candidate cards and match reasons.

• Consent: access request, accept/decline, scoped and time-limited reveal, withdrawal.

• University analytics: skill readiness, placement status, unmet-demand signals and lifecycle continuity.

• Appeals and feedback: student tickets, independent review, recorded decisions and structured employer feedback.

6. Out of scope for the prototype

• Payments, invoices and subscription billing; pricing is static and subscription status is an admin-controlled demo setting.

• Real university LMS/ERP and real ATS integrations.

• Public university rankings, native mobile apps, production-grade scale/SLA, or compliance certification.

7. Non-functional and security requirements

Area	Requirement / guardrail
Authorization	Database Row-Level Security (RLS), server-side role checks, least privilege; frontend hiding is not authorization.
Identity privacy	Organization candidate projections exclude identity fields; identity is joined only after a valid consent grant.
Admin security	Admin endpoints require elevated assurance / MFA (`aal2`).
AI safety	AI proposes; deterministic rules decide identity, permissions, consent, verification and pass/borderline outcomes.
Fallbacks	Agent adapter supports `mock`, `direct`, and `n8n` modes; fail safely and surface understandable states.
Data minimization	Roster CSV unmapped columns are dropped in browser; raw student ID numbers only transit over TLS to specified function and must not be logged.
Transparency	Evidence references and rationale accompany score outputs; borderline results go to human review.
Prototype status	Do not treat mock mode or interface demos as production-ready or use fictional/demo data as real candidate records.

8. Key user journeys

Student

Register and verify affiliation → select target skill or role → receive project brief → build and submit work plus required video/evidence and AI-use disclosure → review audit scorecard → appeal if needed → maintain profile and control data sharing.

Organization

Apply for organization access → obtain approval → create a job → review anonymized ranked candidates and match explanations → request scoped access → receive only the fields permitted after student consent.

University

Apply and obtain approval → import roster using dry run and validated canonical fields → reconcile student claims and affiliation status → view own students' permitted skill and placement analytics.

Admin

Authenticate with MFA → review institution/organization applications, borderline audits and tickets → record decisions with auditability and separation of appeal reviewer.

9. Acceptance and release gates

• Frozen frontend contracts are binding: preserve names, enums, validation bounds, request/response shapes and error codes.

AptoHire

• All sensitive access rules are tested at the database/function boundary, not only in UI tests.

• Consent grant scope, expiration and withdrawal are tested, including attempts to bypass UI controls.

• Mock/demo states are visibly distinguished from real integrations and verified production behavior.

• Build/test reports distinguish Verified, Inferred, Not run and Manual dashboard steps; never claim tests passed unless executed.

10. Open decisions and risks

Item	Treatment
Scoring threshold	PRD says skills scoring above 50 become verified; backend prompt says pass mark and borderline range come from `app_config`. Keep configuration authoritative and document the boundary condition.
AI confidence thresholds	Frozen contract specifies ≥0.75 High, ≥0.5 Medium, else Low; note as current client contract, revisit only through coordinated contract change.
External integrations	GitHub OAuth read-only and LinkedIn export upload are consent-based concepts; production permissions, retention and provider policies require verification.
Market validation	No survey response dataset was provided; market demand, willingness to pay and adoption remain unvalidated here.
Production readiness	Prototype scope explicitly excludes certification and production-grade scale; require independent security and privacy review before real data.

11. Source of truth

Prepared from the supplied AptoHire PRD, feature inventory, architecture, runtime-agent specifications and frozen frontend contracts. Where these sources define a requirement, this document summarizes it; it does not certify that every requirement is implemented.