

05 — Network Intrusion Traffic

Unified labelled corpus of network flow records (benign + attack traffic) from three well-known IDS datasets. Suitable for binary or multi-class intrusion detection, anomaly detection, and cross-dataset transfer experiments.

Records: 133,000 · **CSV size:** 47 MB · **Sources:** CICIDS2017 + UNSW-NB15 + NSL-KDD

Fields

Column	Type	Description
flow_id	string	Source-prefixed unique key (e.g. <code>cicids:row42</code>)
duration	float	Flow duration in seconds (nullable)
protocol	string	<code>tcp / udp / icmp / ...</code> (nullable)
src_bytes	int	Bytes sent by source (nullable)
dst_bytes	int	Bytes sent by destination (nullable)
src_port	int	Source port — CICIDS only (nullable)
dst_port	int	Destination port (nullable)
packet_count	int	Total packets in flow (nullable)
label	string	Unified 16-class taxonomy (<code>BENIGN / DOS / DDOS / PROBE / EXPLOIT / FUZZER / R2L / U2R / ...</code>)
label_detail	string	Original source-specific label
extra_features	string	JSON-encoded source-specific features
source	string	<code>cicids2017, unsw_nb15, nslkdd</code>

Sources

- **CICIDS2017** (Canadian Institute for Cybersecurity) — academic research license — 48,000 rows (via `c01dsnap/CIC-IDS2017 HF mirror`)
- **UNSW-NB15** (UNSW Canberra) — academic research license — 45,000 rows (via `CoIdAsYou165/dataset_UNSWNB15 mirror`)
- **NSL-KDD** (UNB) — public for research — 40,000 rows (via `Jehuty4949/NSL_KDD mirror`)

© Angelo Consoli, SUPSI DTI Viganello