UNIT 4: SOLVED EXERCISES. PDO

Same login.php

```
SELECT: Select all employees
require once 'login.php';
try
$pdo = new PDO("mysql:host=$servername;dbname=$dbname",$username, $password);
$pdo->setAttribute(PDO::ATTR ERRMODE, PDO::ERRMODE EXCEPTION);
$pdo->exec('SET NAMES "utf8"');
$sql = "select * from emp";
$result = $pdo->query($sql);
while ($row = $result->fetch())
echo 'Employee: '. htmlspecialchars($row['ename']) . '<br>';
catch (PDOException $e)
echo 'Unable to connect to the database server: ' . $e->getMessage();
exit();
echo 'Database connection established.';
pdo = null;
?>
DELETE Delete a depart
form.php
<?php
require once 'login.php';
try
$pdo = new PDO("mysql:host=$servername;dbname=$dbname",$username, $password);
$pdo->setAttribute(PDO::ATTR ERRMODE, PDO::ERRMODE EXCEPTION);
$pdo->exec('SET NAMES "utf8"');
$sql = "select * from dept";
$result = $pdo->query($sql);
echo "<form action='delete.php' method='POST'>";
echo "Choose department to delete: <br/> ';
echo "<select name='dep'>";
while ($fila = $result->fetch())
echo "<option value=".\fila['deptno'].">",\fila['dname']."</option>";
echo "</select>";
echo "<input type='submit' value='Delete' />";
echo "</form>";
```

```
catch (PDOException $e)
echo 'Unable to connect to the database server: ' . $e->getMessage();
exit();
pdo = null;
?>
delete.php
<?php
require once 'login.php';
try
$pdo = new PDO("mysql:host=$servername;dbname=$dbname",$username, $password);
$pdo->setAttribute(PDO::ATTR ERRMODE, PDO::ERRMODE EXCEPTION);
$pdo->exec('SET NAMES "utf8"");
$sql="DELETE FROM dept WHERE DEPTNO=".$ POST['dep'];
$affectedRows = $pdo->exec($sql);
catch (PDOException $e)
echo 'Unable to connect to the database server: ' . $e->getMessage();
exit();
}
echo "Deleted $affectedRows rows.";
pdo = null;
?>
```

INSERT (same form, two insert.php with prepared statement)

Insert a depart

form.php

```
<body>
<form action="insert.php" method="POST">
Number
<input type="text" name="num"/><br/>
Name
<input type="text" name="name"/><br/>
Location
<input type="text" name="loc"/><br/>
<input type="text" name="loc"/><br/>
<input type="submit" name="boton" value="Insert"/>
</form>
</body>
```

INSERT with bindValue

```
insert.php
<?php
require once 'login.php';
$num=$ POST['num'];
$name=$ POST['name'];
$loc=$ POST['loc'];
try
$pdo = new PDO("mysql:host=$servername;dbname=$dbname",$username, $password);
$pdo->setAttribute(PDO::ATTR ERRMODE, PDO::ERRMODE EXCEPTION);
$pdo->exec('SET NAMES "utf8"');
$sql = 'INSERT INTO dept values (:deptno,:dname,:loc)';
$stmt = $pdo->prepare($sql);
$stmt->bindValue(':deptno', $num);
$stmt->bindValue(':dname', $name);
$stmt->bindValue(':loc', $loc);
$stmt->execute();
catch (PDOException $e)
echo 'Unable to connect to the database server: ' . $e->getMessage();
exit();
echo 'Database connection established.';
pdo = null;
?>
```

INSERT (with ???)

```
insert.php
<?php
require once 'login.php';
$num=$_POST['num'];
$name=$ POST['name'];
$loc=$ POST['loc'];
try
$pdo = new PDO("mysql:host=\$servername;dbname=\$dbname",\$username, \$password);
$pdo->setAttribute(PDO::ATTR ERRMODE, PDO::ERRMODE EXCEPTION);
$pdo->exec('SET NAMES "utf8"');
sql = INSERT INTO dept values (?,?,?)';
$stmt = $pdo->prepare($sql);
$stmt->execute([$num,$name,$loc]);
catch (PDOException $e)
echo 'Unable to connect to the database server: ' . $e->getMessage();
exit();
```

```
}
$pdo = null;
?>
```

TRANSACTIONS:

Without using transactions inserts the first two departments, because the third is repeated

```
<?php
require once 'login.php';
try
$pdo = new PDO("mysql:host=\$servername;dbname=\$dbname",\$username, \$password);
$pdo->setAttribute(PDO::ATTR ERRMODE, PDO::ERRMODE EXCEPTION);
$pdo->exec('SET NAMES "utf8"');
$pdo->exec("insert into dept values (22, 'dep22', 'Madrid')");
$pdo->exec("insert into dept values (23, 'dep23', 'Valencia')");
$pdo->exec("insert into dept values (23, 'dep24', 'Valencia')");
catch (PDOException $e)
echo "Failed: " . $e->getMessage();
pdo = null;
Using transactions the rollback undoes everything and nothing is inserted
<?php
require once 'login.php';
try
$pdo = new PDO("mysql:host=$servername;dbname=$dbname",$username, $password);
$pdo->setAttribute(PDO::ATTR ERRMODE, PDO::ERRMODE EXCEPTION);
$pdo->exec('SET NAMES "utf8"');
$pdo->beginTransaction();
$pdo->exec("insert into dept values (22, 'dep22', 'Madrid')");
$pdo->exec("insert into dept values (23, 'dep23', 'Valencia')");
$pdo->exec("insert into dept values (23, 'dep24', 'Valencia')");
$pdo->commit();//save changes
catch (PDOException $e)
$pdo->rollBack(); //undo changes
echo "Failed: " . $e->getMessage();
pdo = null;
```

UPDATE:

```
First: same form as delete:form.php (with action='updateform.php')
Modify a depart
updateform.php
<?php
require once 'login.php';
$dep=$ POST['dep'];
try
$pdo = new PDO("mysql:host=\$servername;dbname=\$dbname",\$username, \$password);
$pdo->setAttribute(PDO::ATTR ERRMODE, PDO::ERRMODE EXCEPTION);
$pdo->exec('SET NAMES "utf8"');
$sql = "SELECT * FROM dept WHERE deptno=$dep";
$result = $pdo->query($sql);
$row = $result->fetch();
<form action="update.php" method="post">
<input type="hidden" name="deptno" value="<?php echo $row['deptno']?>"/>
Name Hotel <input type="text" name="dname" value="<?php echo $row['dname']; ?>"/><br/>
loc <input type="text" name="loc" value="<?php echo $row['loc']; ?>"/><br/>
<input type='submit' value='Modify' />
</form>
<?php
catch (PDOException $e)
echo 'Unable to connect to the database server: ' . $e->getMessage();
exit();
pdo = null;
?>
update.php
<?php
require once 'login.php';
$deptno=$ POST['deptno'];
$dname=$ POST['dname'];
$loc=$ POST['loc'];
try
$pdo = new PDO("mysql:host=$servername;dbname=$dbname",$username, $password);
$pdo->setAttribute(PDO::ATTR ERRMODE, PDO::ERRMODE EXCEPTION);
$pdo->exec('SET NAMES "utf8"');
$sql="UPDATE dept SET dname='$dname', loc='$loc' WHERE DEPTNO=$deptno";
$affectedRows = $pdo->exec($sql);
catch (PDOException $e)
{echo 'Unable to connect to the database server: '. $e->getMessage();
exit();}
echo "Department Updated";
pdo = null;?>
```