

# UPPRESSO: An Unlinkable Privacy-PREserving Single Sign-On System

**Abstract**—As a widely adopted identity management and authentication mechanism in today’s Internet, single sign-on (SSO) allows a user to maintain only the credential for the identity provider (IdP), instead of one credential for each relying party (RP), which shifts the burden of user authentication from RPs to the IdP. However, SSO introduces new privacy leakage threats, since (a) a curious IdP could track *all* the RPs a user has visited, and (b) collusive RPs could learn a user’s online profile by linking her identifiers and activities across multiple RPs. Several privacy-preserving SSO solutions have been proposed to defend against either the curious IdP or collusive RPs, however, none of them can address both privacy leakage threats at the same time.

In this paper, we propose a privacy-preserving SSO system, called *UPPRESSO*, to protect a user’s login traces against both the curious IdP and collusive RPs. We first formally analyze the privacy dilemma between SSO security requirements and the new privacy requirements, and convert the SSO privacy problem into an identifier-transformation problem. Then, we design a novel *transformed RP designation* scheme to transform the identifier of the RP, to which the user requests to log in, into a privacy-preserving pseudo-identifier ( $PID_{RP}$ ) through the cooperation between the user and the RP. Our *trapdoor user identification* scheme allows the RP to obtain a trapdoor from the transformation process and use it to derive a unique account of the user at that RP from her privacy-preserving pseudo-identifier ( $PID_U$ ) generated by the IdP. The login process of *UPPRESSO* follows the service pattern of OpenID Connect (OIDC), a widely deployed SSO system, with minimum modifications. Our analysis shows *UPPRESSO* provides a comprehensive privacy protection while achieving the same security guarantees of OIDC.

**Keywords**—Single sign-on, security, privacy.

## I. INTRODUCTION

Single sign-on (SSO) systems, such as OpenID Connect [?], OAuth [?] and SAML [?], have been widely deployed as the identity management and authentication infrastructure in the Internet. SSO enables a website, called the *relying party* (RP), to delegate its user authentication to a trusted third party called the *identity provider* (IdP). Thus, a user visits multiple RPs with only a single explicit authentication attempt at the IdP. With the help of SSO, a user no longer needs to remember multiple credentials for different RPs; instead, she maintains only the user credential for the IdP, which generates *identity proofs* for her visits to these RPs. SSO has been widely integrated with many application services. For example, we find that 80% of the Alexa Top-100 websites [?] support SSO, and the analysis on the Alexa Top-1M websites [?] identifies 6.30% with the SSO support. Meanwhile, many email and social network providers (such as Google, Facebook, Twitter, etc.) are serving the IdP roles in the Internet.

The adoption of SSO also raises privacy concerns regarding online user tracking and profiling [?], [?]. User privacy leaks

in all existing SSO protocols and implementations. Taking a widely used SSO protocol, OpenID Connect (OIDC), as an example, we explain its login process and the risk of user privacy leakage. On receiving a user’s login request, the RP constructs a request of identity proof with its identity and redirects it to the IdP. After authenticating the user, the IdP generates an identify proof binding the identities of the user and the RP, which is forwarded to the RP by the user. Finally, the RP verifies the identity proof and allows the user to log in. From such login instances, any curious IdP or collusive RPs could break the users’ privacy as follows.

- *IdP-based login tracing*. The IdP knows the identities of the RP and the user in each single login instance, to generate the identity proof. As a result, a curious IdP could discover all the RPs that the victim user attempts to visit and profile her online activities.
- *RP-based identity linkage*. The RP learns a user’s identity from the identify proof. When the IdP generates identity proofs for a user, if the same user identifier is bound in identity proofs generated for different RPs, which is the case of several widely deployed SSO systems [?], [?], malicious RPs could collude to not only link the user’s login activities at different RPs for online tracking but also associate her attributes across multiple RPs [?].

Large IdPs, especially the social IdPs such as Google and Facebook, are interested in collecting users’ online behavioral information for various purposes (e.g., Screenwise Meter [?] and Onavo [?]). By simply serving the IdP role, these companies will easily collect a large amount of data to reconstruct users’ online traces. On the other hand, in the Internet, many service providers host a variety of web services and therefore take an advantaged position to link a user’s multiple logins at different RPs. Through the internal information integration, rich information will be obtained from the SSO data for user profiling. Meanwhile, the technologies of privacy-preserving record linkage [?] and private set intersection [?] allow multiple organizations (e.g., RPs) to share and link the data without directly sharing their clients’ data, which pave the path for cross-organizational RP-based identity linkage.

While the privacy problems in SSO have been widely recognized [?], [?], only a few solutions were proposed to protect user privacy [?], [?]. Among them, Pairwise Pseudonymous Identifier (PPID) [?], [?] is a straightforward and commonly adopted solution to defend against RP-based identity linkage. It requires the IdP to create different identifiers for the user when she logs into different RPs, so that the pseudo-identifiers of the same user cannot be used to link the user’s logins at different RPs even if they collude. As a recommended practice

by NIST [?], PPID has been specified in many widely adopted SSO standards including OIDC [?] and SAML [?]. However, PPID-based approaches cannot prevent the IdP-based login tracing attacks, as the IdP still knows which RP the user visits.

To the best of our knowledge, only two schemes (i.e., BrowserID [?] and SPRESSO [?]) have been proposed so far to defend against IdP-based login tracing. In BrowserID (and its prototypes known as Mozilla Persona [?] and Firefox Accounts [?]), the IdP generates a special “identity proof” to bind the user’s unique identifier (i.e., email address) to a public key. With the corresponding private key, the user signs an extra subsidiary identity proof to bind the visited RP’s identity and its identity, and sends this pair of identity proofs to that RP. In this way, the IdP does not know the RP’s identity when generating identity proofs. SPRESSO requires the RP to create a one-time pseudo-identifier at each login for the IdP to generate an identity proof, and then hides the RP’s real identity from the IdP. The RP employs a third-party entity called forwarder, which works as a proxy to relay the identity proof from the IdP to the corresponding RP. In both schemes, the RPs’ identities are protected from the IdP; however, the IdP has to know the user’s unique identifier (e.g., email address) and includes it in identity proofs so that the visited RP can recognize the user in her multiple logins. As a result, both schemes are still vulnerable to RP-based identity linkage.

As discussed above, none of the existing SSO systems defend against both IdP-based login tracing and RP-based identity linkage at the same time. Before presenting our solution, we first formally analyze the privacy problems and solutions. Let us denote the user’s and the visited RP’s identities as  $ID_U$  and  $ID_{RP}$ , respectively. To protect user privacy against RP-based identity linkage,  $ID_U$  should not be explicitly included in the identity proof which will be received by the RP. Instead, a privacy-preserving pseudo-identifier  $PID_U$  should be used (as in the PPID-based approaches [?], [?]), which can be viewed as the output of a one-way identifier-transformation function  $\mathcal{F}_{ID_U \mapsto PID_U}$  at the IdP, which authenticates the user and then knows  $ID_U$ . Similarly, to prevent IdP-based login tracing,  $ID_{RP}$  should not be explicitly included in the identity proof but be replaced by a pseudo-identifier  $PID_{RP}$  (as in SPRESSO [?] and BrowserID [?]), which is obtained by another one-way function  $\mathcal{F}_{ID_{RP} \mapsto PID_{RP}}$  at the RP. However, if both  $PID_U$  and  $PID_{RP}$  are used in identity proofs to replace  $ID_U$  and  $ID_{RP}$  at the same time, assuming they can be securely exchanged between the IdP and the RP in an SSO login process, the RP will allow the user to log in as  $PID_U$ , which will be different in the user’s multiple logins at a same RP; otherwise, the IdP might be able to associate these RPs visited by the user. As a result, the RP has no clues to derive the user account at the RP but has to treat her as a one-time user every time when she logs in. This violates the basic requirements of SSO services.

In this paper, we propose an Unlinkable Privacy-PREserving Single Sign-On (UPPRESSO) system to provide comprehensive protections against both IdP-based login tracing and RP-based identity linkage. The key idea of UPPRESSO is to design a special identifier-transformation function  $\mathcal{F}_{PID_U \mapsto Account}$ , which maps *all*  $PID_U$ s of a user to *one* unique *Account* in all logins to an RP, where *Account* is created when the user logs into the RP for the first time. Since

in every login instance  $PID_U$  and  $PID_{RP}$  are separately generated by the IdP and the RP, respectively, we have to design associative one-way identifier-transformation functions  $\mathcal{F}_{ID_U \mapsto PID_U}$  and  $\mathcal{F}_{ID_{RP} \mapsto PID_{RP}}$ , so that three identifier-transformation functions work cooperatively to ensure: (a) when a user logs into an RP for multiple times, the RP always maps  $PID_U$ s to an identical *Account* without knowing the user’s identity; moreover, when a user logs into multiple RPs, (b) a curious IdP cannot link multiple  $PID_{RPs}$  to a particular RP or associate them together, and collusive RPs (c) cannot link  $PID_U$ s to a particular user or associate them together, (d) nor link *Accounts* of a same user at different RPs.

To completely achieve these goals, we design three one-way identifier-transformation functions based on the discrete logarithm problem. We design a one-way trapdoor function  $\mathcal{F}_{ID_{RP} \mapsto PID_{RP}}(ID_{RP}, T)$  for an RP to generate a random  $PID_{RP}$  based on a randomly generated trapdoor  $T$ , and a one-way function  $\mathcal{F}_{ID_U \mapsto PID_U}(ID_U, PID_{RP})$  for the IdP to generate  $PID_U$  based on  $PID_{RP}$ . With the trapdoor  $T$ , the RP applies  $\mathcal{F}_{PID_U \mapsto Account}(PID_U, PID_{RP}, T)$  to identity proofs binding  $PID_{RP}$  and  $PID_U$ , to derive the unique *Account*. We summarize our contributions as follows.

- We formally analyze the privacy problems in SSO as an identifier-transformation problem, and propose the first comprehensive solution to hide the users’ login traces from both the curious IdP and malicious collusive RPs. To the best of our knowledge, UPPRESSO is the first SSO system that provides secure SSO services against IdP-based login tracing and RP-based identity linkage.
- We systematically analyze the security of UPPRESSO and show that it achieves the same security level as existing SSO systems, while the users’ login traces are well protected.
- We have implemented a prototype of UPPRESSO based on an open-source implementation of OIDC, which requires only small modifications to support three identifier-transformation functions for privacy protections. Unlike BrowserID and SPRESSO, UPPRESSO does not require non-trivial re-designs of SSO services, which makes it more compatible with existing SSO systems.
- We compare the performance of the UPPRESSO prototype with the state-of-the-art SSO systems (i.e., OIDC and SPRESSO), and demonstrate its efficiency.

The rest of the paper is organized as follows. We first introduce the background and preliminaries in Section II. Then, we describe the identifier-transformation based approach, the threat model, and our UPPRESSO design in Sections III, IV and V, followed by a systematical analysis of security and privacy in Section ???. We provide the implementation specifics and experiment evaluation in Section VII, discuss the extensions and related works in Section VIII and IX, and conclude our work in Section X.

## II. BACKGROUND AND PRELIMINARIES

UPPRESSO is designed to be compatible with OpenID Connect (OIDC) and provide privacy protections based on

the discrete logarithm problem. Here, we provide a brief introduction about OIDC and the discrete logarithm problem.

#### A. OpenID Connect (OIDC)

As an extension of OAuth 2.0 for user authentication, OIDC is one of the most popular SSO protocols [?]. As other SSO protocols [?], OIDC involves three entities, i.e., *users*, the *identity provider (IdP)*, and *relying parties (RPs)*. Both users and RPs register at the IdP with identifiers ( $ID_U$ ,  $ID_{RP}$  and  $PID_U$  in some schemes), and the necessary information such as credentials, RP endpoints (e.g., the URLs to receive identity proofs), etc. The IdP is assumed to maintain these attributes securely. In an OIDC login process, a user is responsible for initiating a login request at an RP, redirecting the SSO messages between the RP and the IdP, and checking the scope of user attributes in the identify proof generated by the IdP for the visited RP. Usually, the redirection and checking actions are handled by a user-controlled software, known as *user agent* (e.g., browser). Once receiving a user login request, the RP constructs an identity proof request with its identifier and the scope of requested user attributes, sends the identity proof request to the IdP through the user, and parses the received identity proof to authenticate the user. The IdP authenticates the user based on her  $ID_U$  and credential, maps  $ID_U$  to PPID (i.e., privacy-preserving pseudo-identifier) based on the RP identity (i.e.,  $ID_{RP}$ ), generates an identity proof containing PPID,  $ID_{RP}$  and requested user attributes, and returns the identity proof to the endpoint registered by the RP.

**OIDC Implicit Flow.** OIDC supports three user login flows, which are the *implicit flow*, *authorization code flow* and *hybrid flow* (i.e., a mix-up of the previous two). In the implicit flow, an *id token* is generated as the identity proof, which contains a user identifier, an RP identifier, the issuer (i.e., IdP), the validity period, and other requested attributes. The IdP signs the id token using its private key to ensure integrity, and sends it to the RP through the user. In the authorization code flow, the IdP binds an authorization code with the RP, and sends it to the RP through the user; then, the RP establishes an HTTPS connection to the IdP and uses the authorization code with the RP's credential to obtain the user's identifier and other attributes. UPPRESSO is compatible with all three flows. For brevity, we will present our design and implementation of UPPRESSO on top of the OIDC implicit flow in details, and discuss the extension to support the authorization code flow in Section VIII.

The original OIDC implicit flow is shown in Figure 1. When a user attempts to log into an RP, the RP constructs an identity proof request and returns it to the user, which gets redirected to the IdP. The request contains  $ID_{RP}$ , the RP endpoint to receive the identity proof, and the scope of requested user attributes. If the user has not yet been authenticated, the IdP initiates an authentication process to authenticate her. For a successfully authenticated user, the IdP generates an id token and returns it to the RP endpoint. If the endpoint is not registered for that RP, the IdP will return a warning to notify the user about potential identity proof leakage. Once the RP receives the identity proof, it makes the authentication decision after verifying the identity proof.

**RP Dynamic Registration.** The RP dynamic registration [?]




Fig. 1: The implicit flow of OIDC.

of OIDC allows an RP to update its information at the IdP. When an RP first registers at the IdP, it obtains a registration token, with which the RP can initiate a dynamic registration process to update its information (e.g., the endpoint). After a successful dynamic registration, the RP obtains a new unique  $ID_{RP}$  from the IdP. UPPRESSO leverages this function and slightly modify the dynamic registration process to enable  $PID_{RP}$  registration, which allows an RP to generate different privacy-preserving identifiers ( $PID_{RPs}$ ) and register them at the IdP.

#### B. Discrete Logarithm Problem

Based on the discrete logarithm problem, UPPRESSO designs the identifier-transformation functions. Here, we briefly review the discrete logarithm problem. For the finite field  $GF(p)$  where  $p$  is a large prime, a number  $g$  is called a generator of order  $q$ , if it constructs a cyclic group of  $q$  elements by calculating  $y = g^x \bmod p$ . And  $x$  is called the discrete logarithm of  $y$  modulo  $p$ . Given a large prime  $p$ , a generator  $g$  and a number  $y$ , it is computationally infeasible to solve the discrete logarithm (i.e.,  $x$ ) of  $y$  [?], which is called the discrete logarithm problem. The hardness of solving discrete logarithms is utilized to design several secure cryptographic primitives, including Diffie-Hellman key exchange and the digital signature algorithm (DSA).

### III. THE PRIVACY DILEMMA AND UPPRESSO OVERVIEW

In this section, we first review the security and privacy requirements of SSO services and discuss the privacy dilemma in designing secure privacy-preserving SSO systems. Then, we provide an overview of the identifier-transformation approach of UPPRESSO.

#### A. Security Requirements of SSO

The primary goal of SSO services is to implement secure user authentication [?], i.e., to ensure that a legitimate user can always log into an honest RP under her unique account. To achieve this, every identity proof generated by the IdP should explicitly specify the user who is authenticated by the IdP (i.e., *user identification*) and the RP which the user attempts to log into (i.e., *RP designation*). User identification also requires an RP to be able to recognize every authenticated user under a unique account registered at that RP in multiple logins of the user. Moreover, the identify proof should be generated by

the trusted IdP and correctly transmitted to the dedicated RP and the user in some schemes (i.e., *confidentiality*). In this process, the identify proof should not be modified or forged (i.e., *integrity*). These are the basic security requirements of SSO systems summarized based on theoretical analysis of SSO designs [?], [?], [?] and practical attacks [?], [?], [?], [?], [?], [?], [?], [?], [?], [?], [?], [?], [?], [?], [?], [?], [?].

Many attacks exploit vulnerabilities in SSO design or implementation to break at least one of these security requirements, so that the adversaries can log into an honest RP as a victim user (called *impersonation attacks*), or allure a victim user to log into an honest RP under the attacker's account (called *identity injection attacks*). For example, Friendcaster used to accept every received identity proof (i.e., a violation of RP designation) [?], so a malicious RP could replay the identity proof received from a user for itself and log into Friendcaster as the victim user. Or, the adversaries could impersonate the victim user with a leaked identity proof (i.e., a violation of confidentiality) [?], [?], [?], [?], [?]. It was also reported that some RPs of Google ID SSO accepted user attributes that were not tied to the identity proof (i.e., a potential violation of integrity) [?]. As a result, an adversary could insert arbitrary attributes (e.g., an email address) into the identity proof to impersonate another user at the RP.

### B. The Privacy Dilemma in SSO Identity Proofs

As discussed in Section I, existing SSO systems are vulnerable to IdP-based login tracing or RP-based identity linkage privacy leakage. We argue that a secure and privacy-preserving SSO system should prevent *both* types of privacy leakage while satisfying *all* four basic security requirements. However, meeting the security and privacy requirements at the same time incurs a dilemma in the identity proof generation.

In an SSO login instance, the identity proof is generated by the IdP about the authenticated user and the requesting RP. First, to prevent IdP-based login tracing, the identity proof request should not disclose  $ID_{RP}$  to the IdP, since the IdP already knows  $ID_U$  after authenticating the user. However, to ensure RP designation, the IdP should bind each identify proof with a certain transitional pseudo-identifier of the RP (denoted as  $PID_{RP}$ ).  $PID_{RP}$  can be generated by the user or the RP, or together, but it should be computationally infeasible for the IdP to derive  $ID_{RP}$  from  $PID_{RP}$ .

Meanwhile, to prevent RP-based identity linkage, the identity proof should not directly contain  $ID_U$  or disclose it in any means. This requires the IdP to generate a certain transitional pseudo-identifier of the user (denoted as  $PID_U$ ) and bind it to the identity proof. However, to ensure user identification, the requesting RP should be able to recognize the user and associate  $PID_U$  to her unique account at the RP (denoted as *Account*). Similarly, it should be computationally infeasible for the RP to derive  $ID_U$  from  $PID_U$  or *Account*.

We illustrate the relationships between the identifiers, pseudo-identifiers, and the identity proof in Figure 2, where red and green blocks respectively represent long-term identities and one-time pseudo-identifiers known to each entity, and the arrows denote how the pseudo-identifiers are obtained. A *dilemma* exists in the SSO login process, that is, the IdP is expected to generate a  $PID_U$  for the authenticated user  $ID_U$




Fig. 2: Identifier transformations in privacy-preserving SSO.

that can be linked to her *Account* at the requesting RP, *without knowing any information about the requesting RP*.

### C. The Identifier-transformation Framework and UPPRESSO

As shown in Figure 2, we convert the privacy-preserving SSO login problem into an identifier-transformation problem, which aims to design three identifier-transformation functions  $\mathcal{F}_{ID_U \rightarrow PID_U}$ ,  $\mathcal{F}_{ID_{RP} \rightarrow PID_{RP}}$ , and  $\mathcal{F}_{PID_U \rightarrow Account}$  to compute  $PID_U$ ,  $PID_{RP}$  and *Account* that satisfy the desired security and privacy requirements. To solve the dilemma, the key is to pass some information related to the user's *Account* at the RP to the IdP to assist its generation of  $PID_U$ , so that all  $PID_U$ s of the same user during her multiple logins at the same RP can be correctly linked to her *Account*. Meanwhile, such information should not provide any additional knowledge for the IdP to infer the RP's identity (i.e.,  $ID_{RP}$ ).

To achieve this goal, UPPRESSO constructs three transformation functions in an integrated way to support *transformed RP designation* and *trapdoor user identification*, where (i)  $PID_U$ s and  $PID_{RP}$ s are generated dynamically for different logins to protect user privacy; (ii) in each login,  $PID_{RP}$  helps to link  $PID_U$  to *Account*; and (iii) in a user's multiple logins to the same RP, an invariant *Account* can always be derived from different pairs of  $PID_U$ s and  $PID_{RP}$ s.

**Transformed RP designation.** To prevent IdP-based login tracing, the identity proof request should not include  $ID_{RP}$  but a  $PID_{RP}$  dynamically transformed from  $ID_{RP}$ . UPPRESSO designs a novel trapdoor-based transformation function  $\mathcal{F}_{ID_{RP} \rightarrow PID_{RP}}(ID_{RP}, T)$  to compute  $PID_{RP}$  based on  $ID_{RP}$  and a random trapdoor  $T$  that is dynamically negotiated between the user and the RP for each login. Then, the user assists the RP to register this  $PID_{RP}$  at the IdP (through OIDC dynamic registration). When an RP receives an identity proof, it can verify if the enclosed  $PID_{RP}$  is transformed from its own  $ID_{RP}$  using the trapdoor it holds.

**Trapdoor user identification.** To prevent RP-based identity linkage, we design a transformation function  $\mathcal{F}_{ID_U \rightarrow PID_U}(ID_U, PID_{RP})$  for the IdP to generate  $PID_U$  and include it in the identity proof. When an RP receives an identity proof, another transformation function  $\mathcal{F}_{PID_U \rightarrow Account}(PID_U, PID_{RP}, T)$  is designed to help the RP to derive the *Account* from  $PID_U$  and  $PID_{RP}$  using the trapdoor it holds. Intuitively, the trapdoor  $T$  plays a role in the generations of  $PID_{RP}$  and  $PID_U$ , directly or indirectly.

TABLE I: Identifier-transformation in privacy-preserving SSO.

Solution	$PID_U$	$PID_{RP}$	Account
PPID	$\mathcal{F}(ID_U, ID_{RP})$	$ID_{RP}$	$PID_U$
SPRESSO	$ID_U$	$Enc(ID_{RP}   nonce)$	$ID_U$
BrowserID <sup>†</sup>	$ID_U$	$\perp$	$ID_U$
UPPRESSO	$\mathcal{F}(ID_U, PID_{RP})$	$\mathcal{F}(ID_{RP}, T)$	$\mathcal{F}(PID_U, T)$

<sup>†</sup>: BrowserID binds null  $PID_{RP}$  in the identity proofs by the IdP, but  $ID_{RP}$  is bound in the *subsidiary* identity proof signed by the user.

#### D. Existing Privacy-Preserving SSO Solutions

Next, we map three existing privacy-preserving SSO approaches (PPID [?], [?], BrowserID [?] and SPRESSO [?]) to the identifier-transformation framework in Figure 2 and explain their designs and potential privacy issues as shown in Table I. It is worth noting that when  $PID_U = ID_U$  and  $PID_{RP} = ID_{RP}$ , this framework depicts the basic SSO services with no privacy protection.

In PPID approaches, the IdP generates different  $PID_U$ s for a user to log into different RPs and maintains deterministic one-to-many mappings from  $ID_U$  to  $PID_U$ s. Therefore, RP-based identity linkage is prevented. At each RP,  $Account = PID_U$  ensures user identification. However, since  $ID_{RP}$  is directly used in identity proofs ( $PID_{RP} = ID_{RP}$ ), they cannot defend against IdP-based login tracing.

In SPRESSO, the RP generates  $PID_{RP}$  by encrypting  $ID_{RP}$  padded with a nonce for each login session and forwards  $PID_{RP}$  to the IdP through the user. With the corresponding nonce, the RP can verify the  $PID_{RP}$  in the identity proof to ensure RP designation, while hiding  $ID_{RP}$  from the IdP to defend against IdP-based login tracing. However, the IdP uses a constant  $ID_U$  to generate identity proofs for each user regardless of which RP she requests to login to. As a result, SPRESSO is vulnerable to RP-based identity linkage, since  $Account$  always equals to  $ID_U$ .

The identity proofs in the BrowserID system include  $ID_U$  but no RP information (i.e.,  $PID_{RP} = \perp$ ), therefore, it prevents IdP-based login tracing. To ensure RP designation, BrowserID requires the user to append a *subsidiary* identity proof and sign it, where the identity proof signed by the IdP authorizes the user to sign the subsidiary identity proof. Obviously,  $ID_U$  is tied to a pair of identity proof and subsidiary identity proof and passed to the RP. Therefore,  $Account = ID_U$ , which makes BrowserID vulnerable to RP-based identity linkage.

As we can see, none of these approaches prevents IdP-based login tracing and RP-based identity linkage at the same time. This is because in each approach, three transformation functions  $\mathcal{F}_{ID_U \rightarrow PID_U}$ ,  $\mathcal{F}_{ID_{RP} \rightarrow PID_{RP}}$  and  $\mathcal{F}_{PID_U \rightarrow Account}$  are arbitrarily designed and function separately, which causes either  $PID_{RP} = ID_{RP}$  or  $Account = ID_U$ .

## IV. THREAT MODEL AND ASSUMPTIONS

Similar as other SSO systems (e.g., SAML and OIDC), UPPRESSO consists of an IdP and multiple RPs and users. Next, we describe the threat model and some assumptions.

### A. Threat Model

In UPPRESSO, we consider the IdP is curious-but-honest, while some users and RPs could be compromised by adversaries. Malicious users and RPs may behave arbitrarily or collude with each other, attempting to break the security and privacy guarantees for benign users.

**Curious-but-honest IdP.** A curious-but-honest IdP strictly follows the specifications, but may be interested in users' login activities at multiple RPs. It is assumed to be well-protected and never leaks sensitive information. For example, the IdP is trusted to maintain the private key for signing identity proofs and RP certificates (see Section V-B for details), so that the adversaries can never forge an identity proof or an RP certificate. An honest IdP should never collude with other entities (e.g., malicious RPs or users), while a curious IdP tries to break user privacy without violating the protocol. For example, it may store all the received messages to infer the relationship among  $ID_U$ ,  $ID_{RP}$ ,  $PID_U$  and  $PID_{RP}$  and trace a user's login activities.

**Malicious Users.** We assume the adversary can control a set of users, by stealing users' credentials [?], [?] or directly registering sybil accounts at the IdP and RPs, to break the security of UPPRESSO. They may impersonate a benign user at honest RPs, or trick a victim user to log into an honest RP under the account of a malicious user. For example, the malicious users may modify, insert, drop or replay a message, or deviate arbitrarily from the specifications when processing  $ID_{RP}$ ,  $PID_{RP}$  and identity proofs.

**Malicious RPs.** The adversary could also control a set of RPs by directly registering at the IdP as an RP or exploiting software vulnerabilities to compromise some RPs. The malicious RPs may behave arbitrarily to break security and privacy guarantees. For example, a malicious RP may manipulate its  $PID_{RP}$  and trick the users to submit identity proofs for other honest RPs to itself and reply them, or it may manipulate its  $PID_{RP}$  to affect the generation of  $PID_U$  and analyze the relationship between  $PID_U$  and  $Account$ .

**Collusive Users and RPs.** Malicious users and RPs may collude together, attempting to break the security and privacy guarantees. For example, malicious users and RPs may manipulate  $PID_U$  and  $PID_{RP}$  in an identity proof collusively to perform the impersonation or identity injection attacks.

### B. Assumptions

We assume the user agent deployed at honest users is correctly implemented and transmits messages to the dedicated receivers as expected. We also assume the IdP and benign RPs and users adopt TLS to ensure confidentiality and integrity in the communications. Meanwhile, the cryptographic algorithms (such as RSA and SHA-256) and building blocks (such as random number generators and the discrete logarithm problem) used in UPPRESSO are assumed to be correctly implemented.

In UPPRESSO, we study the RP-based identity linkage caused by a same user identifier used across different RPs. While the RPs may be able to re-identify a user from some distinctive user attributes, such as telephone numbers, addresses, or driver licenses, we consider it out of the scope of this paper.

Also, we focus on IdP-based login tracing attacks that are enabled by SSO protocols, but do not consider other network attacks such as traffic analysis that trace a user's logins at different RPs.

## V. THE DESIGN OF UPPRESSO

Next, we present the main design of UPPRESSO. First, we describe our design for the three identifier-transformation functions and the details of the transformed RP designation and trapdoor user identification schemes. Then, we provide an overview of the UPPRESSO system and its login flow. Finally, we discuss the compatibility of UPPRESSO with OIDC. The notations used in this paper are listed in Table II.

### A. Identifier-transformation Functions in UPPRESSO

As discussed in Section III, the identifier-transformation functions are essential for privacy-preserving SSO systems. In UPPRESSO, the three functions,  $\mathcal{F}_{ID_{RP} \mapsto PID_{RP}}$ ,  $\mathcal{F}_{ID_U \mapsto PID_U}$  and  $\mathcal{F}_{PID_U \mapsto Account}$ , are all constructed based on the discrete logarithm problem with public parameters  $p$ ,  $q$ , and  $g$ , where  $p$  is a large prime defining the finite field  $GF(p)$ ,  $q$  is a prime factor of  $(p-1)$ , and  $g$  is a generator of order  $q$  in  $GF(p)$ .

Without loss of generality, we assume the IdP assigns long-term identifiers  $ID_U$  to a user and  $ID_{RP}$  to an RP when they first register at the IdP. In particular, the IdP assigns a unique random number to each user as  $ID_U$ , where  $1 < ID_U < q$ . For each RP, the IdP selects a random number  $r$ , where  $1 < r < q$ , and computes a unique  $ID_{RP}$  as:

$$ID_{RP} = g^r \mod p \quad (1)$$

where  $r$  is kept secret from the RP.

**RP Identifier Transformation.** In each login session, the user negotiates with the RP she tries to log in, and computes a pseudo-identifier  $PID_{RP}$  for the RP cooperatively. First, the RP chooses a random number  $N_{RP}$  ( $1 < N_{RP} < q$ ), and the user chooses another random number  $N_U$  ( $1 < N_U < q$ ). Then, they exchange  $N_{RP}$  and  $N_U$  to calculate  $PID_{RP}$  following Equation 2.

$$\mathcal{F}_{ID_{RP} \mapsto PID_{RP}} : PID_{RP} = ID_{RP}^{N_U N_{RP}} \mod p \quad (2)$$

The transformation function  $\mathcal{F}_{ID_{RP} \mapsto PID_{RP}}$  satisfies the following requirements. First, it is computationally infeasible for the IdP to derive  $ID_{RP}$  from  $PID_{RP}$  due to the discrete logarithm problem. Moreover, two nonces  $N_U$  and  $N_{RP}$  ensure that: (a)  $PID_{RP}$  is valid only for this login and for the identity proof generated in this login, and (b)  $PID_{RP}$  is dynamically generated for this login and is different from other  $PID_{RPs}$  generated in other login session between the same user and RP. Therefore, the IdP cannot associate multiple  $PID_{RPs}$  of a same RP. Finally, the cooperative generation process between the user and the RP prevents a single malicious entity from manipulating the value of  $PID_{RP}$ .

**User Identifier Transformation.** When the IdP receives an identity proof request for  $ID_U$  and  $PID_{RP}$  from an authenticated user, it follows the transformation function in Equation 3 to calculate  $PID_U$  and includes it in the identity proof.

$$\mathcal{F}_{ID_U \mapsto PID_U} : PID_U = PID_{RP}^{ID_U} \mod p \quad (3)$$

TABLE II: The notations used in UPPRESSO.

Notation	Definition	Attribute
$p$	A large prime.	Long-term constant
$q$	A large prime factor of $(p-1)$ .	Long-term constant
$g$	A generator of order $q$ in $GF(p)$ .	Long-term constant
$SK, PK$	The private/public key of IdP.	Long-term constant
$ID_{RP}$	$ID_{RP} = g^r \mod p$ , an RP's unique identity.	Long-term constant
$Cert_{RP}$	An RP certificate, containing the RP's identity and endpoint.	Long-term constant
$ID_U$	A user's unique identity.	Long-term constant
$Account$	$Account = ID_{RP}^{ID_U} \mod p$ , a user's identifier at an RP.	Long-term constant
$PID_{RP}$	$PID_{RP} = ID_{RP}^{N_U N_{RP}} \mod p$ , an RP's pseudo-identifier.	One-time variable
$PID_U$	$PID_U = PID_{RP}^{ID_U} \mod p$ , a user's pseudo-identifier.	One-time variable
$N_U$	A user-generated nonce for $PID_{RP}$ .	One-time variable
$N_{RP}$	An RP-generated nonce for $PID_{RP}$ .	One-time variable
$Y_{RP}$	$Y_{RP} = ID_{RP}^{N_{RP}} \mod p$ , the public value for $N_{RP}$ .	One-time variable
$T$	$T = (N_U N_{RP})^{-1} \mod q$ , the trapdoor to derive $Account$ .	One-time variable

From Equations 1, 2 and 3, we see that  $PID_U = ID_{RP}^{N_U N_{RP} ID_U} = g^{r N_U N_{RP} ID_U} \mod p$ . First, the discrete logarithm problem ensures that the RP cannot derive  $ID_U$  from  $PID_U$ .

Moreover,  $ID_{RP}$  is generated following Equation 1 to introduce a random  $r$  that is unknown to the RP, so that for a given  $ID_U$ ,  $PID_U$  is determined by  $r$ ,  $N_U$  and  $N_{RP}$  together. Otherwise, if two collusive RPs know  $r_1$  and  $r_2$  respectively, they can check if  $PID_{U_1}^{r_2 N_{U_2} N_{RP_2}} = PID_{U_2}^{r_1 N_{U_1} N_{RP_1}} \mod p$  holds, which means a same user logs into them in two SSO sessions (i.e.,  $ID_{U_1} = ID_{U_2}$ ).

**User Account Transformation.** The RP can derive a unique  $Account$  for each user following Equation 4.

$$\mathcal{F}_{PID_U \mapsto Account} : Account = PID_U^T \mod p \quad (4)$$

Here, we define  $T = (N_U N_{RP})^{-1} \mod q$  as the RP's trapdoor. As  $q$  is a prime number and  $1 < N_U, N_{RP} < q$ ,  $q$  is coprime to  $N_U N_{RP}$ . Also, there always exists a  $T$  that satisfies  $T(N_U N_{RP}) = 1 \mod q$ . Moreover, from Equations 2, 3 and 4, we have  $Account = ID_{RP}^{ID_U} \mod p$ , derived as below.

$$\begin{aligned} Account &= PID_U^T = (PID_{RP}^{ID_U})^{(N_U N_{RP})^{-1} \mod q} \\ &= ID_{RP}^{ID_U N_U N_{RP} T \mod q} = ID_{RP}^{ID_U} \mod p \end{aligned} \quad (5)$$

Therefore, when a user logs in at an RP multiple times, the RP can always derive the same  $Account$  to identify the user. Finally, the transformation function  $\mathcal{F}_{PID_U \mapsto Account}$  satisfies the following requirements: (a) due to the discrete logarithm problem, the RP cannot derive  $ID_U$  from  $Account$ , and (b) collusive RPs cannot link a user's  $Accounts$  at different RPs.

These three identifier-transformation functions enable *transformed RP designation* and *trapdoor user identification* to satisfy all the security and privacy requirements of an SSO.

**Transformed RP Designation.**  $\mathcal{F}_{ID_{RP} \mapsto PID_{RP}}$  ensures that the user and RP cooperatively generate a fresh  $PID_{RP}$  in each login, while  $\mathcal{F}_{ID_U \mapsto PID_U}$  ensures that the IdP generates the exact  $PID_U$  for the  $ID_U$  who logs in at  $PID_{RP}$ . The

IdP will bind  $PID_U$  with  $PID_{RP}$  in the identity proof, which designates this identity proof to  $PID_{RP}$ . Finally, the transformed RP designation is provided through two phases. The function  $\mathcal{F}_{ID_{RP} \rightarrow PID_{RP}}$  prevents the curious IdP from linking  $PID_{RPs}$  of different logins at an RP, and therefore avoids IdP-based login tracing.

**Trapdoor User Identification.** In a user's multiple logins, the RP expresses different  $PID_U$ s and has the corresponding  $T$ s, so that derives the identical  $Account$ . The comprehensive design of identifier-transformation functions prevents collusive RPs from linking a user's  $PID_U$ s and  $Accounts$  at different RPs, and therefore prevents RP-based identity linkage.

### B. UPPRESSO Overview

The UPPRESSO system has four procedures, namely system initialization, RP initial registration, user registration, and SSO login.

**System Initialization.** System initialization is conducted once by the IdP to establish the entire system. In particular, the IdP generates a large prime  $p$ , a prime factor  $q$  of  $p - 1$  and a generator  $g$  of order  $q$  as the parameters of the discrete logarithm problem. The IdP also generates one key pair  $(SK, PK)$  to sign identity proofs and RP certificates. The lengths of  $p$ ,  $q$  and  $(SK, PK)$  should satisfy the required security strength. Then, the IdP keeps  $SK$  secret, while announcing  $p$ ,  $q$ ,  $g$  and  $PK$  are public parameters.

**RP Initial Registration.** RP initial registration is launched by each RP to obtain the necessary configurations from the IdP, including a unique identifier  $ID_{RP}$  and its corresponding RP certificate  $Cert_{RP}$ . Each RP launches this procedure only once. In particular, an RP registers itself at the IdP and requests  $ID_{RP}$  and  $Cert_{RP}$  as follows:

- The RP sends a registration request to the IdP, including the RP endpoint (e.g., URL) to receive identity proofs.
- The IdP chooses a unique random number  $r$  ( $1 < r < q$ ), calculates  $ID_{RP} = g^r \mod p$ , signs  $[ID_{RP}, Endpoint_{RP}, *]$  using  $SK$ , where  $*$  denotes the supplementary information such as the RP's common name, and returns  $Cert_{RP} = [ID_{RP}, Endpoint_{RP}, *]_{SK}$  to the RP, where  $[\cdot]_{SK}$  means the message is signed using  $SK$ .
- The RP verifies  $Cert_{RP}$  using  $PK$  and accepts  $ID_{RP}$  and  $Cert_{RP}$  if they are valid.

Note that,  $ID_{RP}$  cannot be chosen by the RP. It must be chosen by the IdP with  $r$  unknown to the RP.

**User registration.** UPPRESSO takes the same user registration process as other SSO systems to set up a unique user identifier  $ID_U$  and the corresponding user credential. User registration is launched only once by each user.  $ID_U$  can be chosen by either the user or the IdP, as long as it is unique for each user.

**SSO Login.** Finally, an SSO login procedure will be launched when a user attempts to log into an RP. It is designed on top of the identifier-transformation functions. As shown in

Figure 3, the SSO login consists of four phases, namely, RP identifier transformation,  $PID_{RP}$  registration, identity proof generation and  $Account$  calculation. In RP identifier transformation, the user and the RP negotiate  $PID_{RP} = ID_{RP}^{N_U N_{RP}} \mod p$ . Next, the user registers  $PID_{RP}$  at the IdP. It is worth noting that this step has to be conducted by the user but not the RP. Otherwise, the IdP can associate  $PID_{RP}$  and  $ID_{RP}$ . To register  $PID_{RP}$ , the user needs to create a new endpoint and submit it with  $PID_{RP}$  to the IdP. Then, the RP requests the identity proof, and the IdP calculates  $PID_U = PID_{RP}^{ID_U} \mod p$  and signs the identity proof. Finally, in  $Account$  calculation, the RP derives  $Account = PID_U^{(N_U N_{RP})^{-1} \mod q} \mod p$  after verifying the identity proof and allows the user to log in under  $Account$ .

Moreover, as the IdP is unaware of the visited RP and also the RP's endpoint to receive the identity proof, this endpoint shall be queried by the user from the trusted IdP indirectly to ensure confidentiality; otherwise, an incorrect endpoint leaks the identity proofs. In UPPRESSO this is implemented as an RP certificate signed by the IdP, which is composed of  $ID_{RP}$ , the RP's endpoint and other supplementary information. Then, the user determines the correct endpoint by itself, while in commonly-used OIDC systems, the endpoint is configured by the IdP.

### C. SSO Login Flow of UPPRESSO

We illustrate the steps of the SSO login protocol of UPPRESSO in Figure 3, and describe the detailed processes as follows.

**RP Identifier Transformation.** In this phase, the user and the RP cooperate to generate  $PID_{RP}$  as follows:

- 1.1 The user sends a login request to trigger the negotiation of  $PID_{RP}$ .
- 1.2 The RP chooses a random number  $N_{RP}$  ( $1 < N_{RP} < q$ ), calculates  $Y_{RP} = ID_{RP}^{N_{RP}} \mod p$ , and sends  $Y_{RP}$  with  $Cert_{RP}$  to the user.
- 1.3 The user verifies  $Cert_{RP}$ , extracts  $ID_{RP}$  from the valid  $Cert_{RP}$ , chooses a random number  $N_U$  ( $1 < N_U < q$ ) to calculate  $PID_{RP} = Y_{RP}^{N_U} \mod p$ , and sends  $N_U$  to the RP.
- 1.4 The RP verifies  $N_U \neq 0 \mod q$ , calculates  $PID_{RP}$  with  $N_U$  and  $Y_{RP}$ , derives the trapdoor  $T = (N_U N_{RP})^{-1} \mod q$ ; and acknowledges the negotiation by responding with  $N_{RP}$ .
- 1.5 The user verifies that  $N_{RP} \neq 0 \mod q$  and  $Y_{RP} = ID_{RP}^{N_{RP}} \mod p$ .

The user halts the negotiation, if  $Cert_{RP}$  is invalid,  $N_{RP} = 0 \mod q$ , or  $Y_{RP} \neq ID_{RP}^{N_{RP}} \mod p$ . The verification of  $Y_{RP}$  and  $N_{RP}$  ensures the order of  $Y_{RP}$  (and also  $PID_{RP}$ ) is  $q$ , and prevents a malicious RP from choosing an arbitrary  $Y_{RP}$  (then  $PID_{RP}$ ) of order less than  $q$ , which makes it less difficult for the RP to derive  $ID_U$  from  $PID_U$ .

**$PID_{RP}$  Registration.** The user registers  $PID_{RP}$  at the IdP.






Fig. 3: The flow of a user login in UPPRESSO.

- 2.1 The user creates a one-time endpoint to hide the RP's endpoint from the IdP, and sends the  $PID_{RP}$  registration request  $[PID_{RP}, Hash(N_{RP}, N_U), Endpoint_U]$  to the IdP.
- 2.2 The IdP authenticates the user if she has not been authenticated yet. The IdP verifies that  $PID_{RP}$  is unique among unexpired  $PID_{RPs}$ , and then signs the response  $[PID_{RP}, Hash(N_{RP}, N_U), Validity]_{SK}$ , where  $Validity$  is the validity period. The IdP returns the signed response to the user.
- 2.3 The user forwards the registration result to the RP.
- 2.4 The RP verifies the IdP's signature, and accepts it only if  $PID_{RP}$  and  $Hash(N_{RP}, N_U)$  match those in the negotiation and it is in the validity period.

$Hash(N_{RP}, N_U)$  is attached as the nonce to avoid the registration result is accepted by two or more RPs, which have different  $ID_{RPs}$  but generate a same  $PID_{RP}$ . The IdP ensures  $PID_{RP}$  is unique among unexpired ones; otherwise, one identity proof for one  $PID_{RP}$  might be accepted by other RPs. More details are analyzed in Section ??.

**Id Proof Generation.** In this phase, the user login continues

and the IdP signs the identity proof.

- 3.1 The RP uses  $PID_{RP}$  and  $Endpoint_{RP}$  to construct an identity proof request for a set of user's attributes.
- 3.2 The user first confirms the scope of the requested attributes and verifies  $PID_{RP}$  with the negotiated one. The user replaces the endpoint with the registered one-time  $Endpoint_U$ , and sends the modified identity proof request to the IdP.
- 3.3 The IdP verifies whether  $PID_{RP}$  and  $Endpoint_U$  have been registered and unexpired, and calculates  $PID_U = PID_{RP}^{ID_U} \bmod p$  for the authenticated user.
- 3.4 The IdP constructs and signs the identity proof  $[PID_{RP}, PID_U, Iss, ValTime, Attr]_{SK}$ , where  $Iss$  is the identifier of the IdP,  $ValTime$  is the validity period,  $Attr$  contains the requested attributes. Then, the IdP sends the identity proof to the one-time endpoint at the user.
- 3.5 The user extracts the RP endpoint in  $Cert_{RP}$ , and forwards the identity proof to the RP through this endpoint.



The user halts the process if  $PID_{RP}$  in the identity proof request is inconsistent with the negotiated one. The IdP rejects the identity proof request, if the pair of  $PID_{RP}$  and  $Endpoint_U$  has not been registered.

**Account calculation.** Finally, RP derives the user's *Account* and completes the user login as follows.

- 4.1 The RP verifies the identity proof, including the signature, validity period, and the consistency between  $PID_{RP}$  and the negotiated one. If any fails, the RP rejects this login.
- 4.2 The RP extracts  $PID_U$ , calculates  $Account = PID_U^T \bmod p$ , and allows the user to log in.

#### D. Compatibility with OIDC

As described above, the SSO login protocol of UPPRESSO follows a same logic flow of OIDC login protocol with small modifications to transform the identifiers. Next, we will discuss these necessary modifications and demonstrate its compatibility with OIDC. This indicates that it can be easily integrated with other commonly adopted SSO systems.

First, UPPRESSO does not introduce any new role nor change the security assumptions for each role. Moreover, among the four phases of its SSO login flow, only the RP identifier transformation phase is newly introduced by UPPRESSO, while the other three ( $PID_{RP}$  registration, identity proof generation and *Account* calculation) adopt similar communication pattern as OIDC flows.

In particular, the  $PID_{RP}$  registration phase can be viewed as a variant of the RP dynamic registration flow of OIDC [?], where an entity registers its identity and endpoint at the IdP. Different from OIDC, in UPPRESSO, this process can be launched by any authenticated user who obtains an RP identifier, the registration response includes a signature by the IdP, and the registration will become invalid after a validity period. However, these changes only require small modifications to the RP dynamic registration flow of OIDC.

The identity proof generation and *Account* calculation phases adopt the same steps and functions as the implicit protocol flow of OIDC but calling a few different parameters. First, in identity proof generation,  $PID_U$  transformed from  $ID_U$  is used to replace  $ID_U$ , which is directly supported by OIDC, similar as in PPID approaches that also convert  $ID_U$  into  $PID_U$ . The calculation of *Account* from  $PID_U$  can be viewed as a customized step by the RP to derive its user account after the implicit protocol flow of OIDC ends. Another modification is the replacement of endpoint by the user for transmitting the identity proof to the RP. In fact, this message forwarding is common when an application-layer network proxy is deployed. So, the identity proof generation and *Account* calculation phases of UPPRESSO can be viewed as a particular but compatible implementation of the implicit protocol flow of OIDC.

It is worth noting that the identity proof generation and *Account* calculation phases of UPPRESSO can be also implemented as the authorization code flow of OIDC with small modifications, which will be discussed in Section VIII.

## VI. WEB MODEL

Our formal analysis of UPPRESSO is based on the Dolev-Yao style web model [?], which has been widely used in formal analysis of SSO protocol, e.g., OAuth 2.0 [?] and OIDC [?]. To make the description cleaner, we focus on our modification on OIDC, and assume DNS and HTTPS are secure, which has already been analyzed in [?].

### A. Communication Model

Here we give a brief presentation of generic Dolev-Yao-style communication model proposed by [?] on which our web model is based.

A *signature*  $\Sigma$  consists of a finite set of function symbols, such as *encrypt*, *decrypt*, and *pair*, each with an arity. A function symbol with arity 0 (with no arguments) is a constant symbol. The set of *terms* is defined over a signature  $\Sigma$ , an infinite set of names, and an infinite set of variables.

**Equational theory** is defined as usual in Dolev-Yao models which introduces the symbol  $\equiv$  representing the congruence relation on terms. For instance,  $dec(enc(m, k), k) \equiv m$

**Messages** are defined as formal terms without variables (called ground terms). The signature  $\Sigma$  for the messages in the model is considered containing constants (such as ASCII strings and nonce), sequence symbols (such as n-ary sequences  $\langle \rangle$ ,  $\langle . \rangle$ ,  $\langle ., . \rangle$  etc.) and further function symbols (such as encryption/decryption and digital signatures). An HTTP request is a common message in the web model, containing a type *HTTPReq*, a nonce  $n$ , a method GET or POST, a domain, a path, URL parameters, request headers, and the body over the  $\Sigma$  in the sequence symbol formate. Here is an example for an HTTP GET request for the domain *exa.com/path?para = 1* with the headers and body empty.

$$m := \langle \text{HTTPReq}, n, \text{GET}, \text{exa.com}, /path, \langle \langle para, 1 \rangle \rangle, \langle \rangle, \langle \rangle \rangle$$

**Events** are the basic communication elements in the model. An event is the term in the formate  $\langle a, f, m \rangle$ , where the  $a$  and  $f$  represent the address of sender and receiver, and  $m$  is the message transmitted.

**Atomic Processes.** An *atomic Dolev-Yao(DY) process* is constructed as the tuple  $p = (I^p, Z^p, R^p, s_0^p)$  representing the single node in the web model, such as the server and browser.  $I^p$  is the set of addresses a process listens to, and  $Z^p$  is the set of states (terms) which describes the process.  $R^p$  is the mapping between the pairs  $\langle s, e \rangle$  and  $\langle s', e' \rangle$  where  $s, s' \in Z^p$ . It's worth noting that for one process in a state only a finite set of events can be accepted by the process as the state and event are defined as the input of  $R^p$ .

**Scripting Processes.** The web model also contains the scripting process representing the client-side script loaded by browser such as JavaScript code. However, the *scripting process* must rely on an *atom process* such as browser and provide the relation  $R$  witch is called by this *atomic process*.

## B. Web System

The web system contains a set of processes (including atomic processes and scripting processes) and represents the web infrastructure. A web system is defined as a tuple  $(\mathcal{W}, \mathcal{S}, \text{script}, E^0)$ .  $\mathcal{W}$  is the set of atomic processes containing honest processes and malicious processes,  $\mathcal{S}$  is the set of scripting processes including honest scripts and malicious scripts,  $\text{script}$  is the set of concrete script code related with specific scripting process in  $\mathcal{S}$ , and  $E^0$  is the set of events which could be accepted by the processes in  $\mathcal{W}$ .

**Configuration.** We firstly define the set of states  $S$  of a system, consists of all the current states of processes in  $\mathcal{W}$ . And the set of events  $E$ , for each event  $e \in E$ , there is always a state  $s \in S$ ,  $e$  and  $s$  can be accepted by one of the processes as the input. A *configuration* of the system is defined as the tuple  $(S, E, N)$  where  $N$  is the mentioned sequence of unused nonces.

**Processing Steps.** A processing step is the system migrating from the configuration  $(S, E, N)$  to  $(S', E', N')$  by processing an event  $e \in E$ .

## C. Model Of UPPRESSO

The UPPRESSO model is a web system which is defined as

$$UWS = (\mathcal{W}, \mathcal{S}, \text{script}, E^0),$$

$\mathcal{W}$  is the finite set of atom processes in UPPRESSO system including a single IdP server process, multiple honest RP server processes, the browsers representing the users, and the attacker processes. We assume that all the honest RPs are implemented following the same rule so that the process are considered consistent besides of the addresses they listen to. The browsers controlled by user are considered honest. That is, the browser controlled by attackers can behave as an independent atomic process.  $\mathcal{S}$  is the finite set of scripting processes consists of *script\_rp*, *script\_idp* and *script\_attacker*. The *script\_rp* and *script\_idp* are downloaded from honest RP and IdP processes and the *script\_attacker* is downloaded from attacker process considered existing in all browser processes.

We now give a brief description about UPPRESSO model.

- The browser is responsible to send HTTP request, receive HTTP response, handle user behaviour and transmit message between scripting process. As the browser is honest, we only focus on the scripting process running on the browser. The detailed model of browser is shown in [?]
- IdP server process (defined as  $p^i$ ) only accepts the events whose messages are HTTP request and the  $path \in \{ /script, /dynamicRegistration, /login, /loginInfo, /authorize \}$ . The function of each path is shown in Section V. All the events are accepted by  $p^i$  in any state but the output may be different. The detailed  $R^i$  is shown in \*.
- RP server process (defined as  $p^r$ ) only accepts the events whose messages are HTTP request and the  $path \in \{ /script, /login, /startNegotiation, /registration, /uploadToken \}$ . The function of

each path is shown in Section V. The event with  $path \in \{ /script, /login, /startNegotiation \}$  are accepted in any state. However, the event with  $path \equiv /registration$  is accepted only when the state  $s$  is the output for event  $path \equiv /startNegotiation$ . In the same way the following accepted events must be arranged as  $path$  in the sequence */registration, /uploadToken*.

- IdP and RP scripting process accepts the events in the formate as HTTP response and postMessage. The details about accepted events are shown in ??.

## D. Security Of UPPRESSO

As we assume that the HTTP requests and responses are well protected by TLS, and the postMessage are securely implemented in browser, therefore, web attackers are not considered. In this section, we are going to prove the following theorem,

**Theorem 1.** Let  $UWS$  be a UPPRESSO web system, then  $UWS$  is secure.

Firstly, an SSO system is considered secure **iff** only the legitimate user can always log into an honest RP under her unique account. Based on the model of UPPRESSO, we found that an attacker can visit an honest RP as the honest user only when the attacker own the cookie which is bound to the honest user by RP. Therefore, the definition of a secure UPPRESSO system is,

**Definition 1.** Let  $UWS$  be a UPPRESSO web system,  $UWS$  is secure **iff** for any honest RP  $r \in \mathcal{W}$  and the authenticated cookie  $c$  for honest  $u$ ,  $c$  is unknown to the attacker  $a$ .

Therefore, to prove theorem 1, we are going to prove that an authenticate cookie  $c$  is unknown to attacker  $a$ . The proof can be separated as two parts, initially  $a$  does not know any authenticated cookie, and the following requirements must be met.

- If  $c$  is the authenticated cookie owned by  $u$ ,  $c$  cannot be obtained by  $a$ ;
- If  $c$  is an unauthenticated cookie owned by  $a$ ,  $c$  cannot be authenticated by  $r$  for  $u$ .

**Proof Outline.** Here we introduce the lemmas briefly to prove that  $UWS$  follows the requirements by Definition 1 so that  $UWS$  is secure. And the detailed proofs to these lemmas are in ??.

**Lemma 1.** The cookie owned by honest user will not be leaked to any attacker.

*Proof:* That is, due to the Same-Origin policy, the honest browser will not leak the cookies to any attacker. And based on the UPPRESSO model, it is to prove that RP server and RP script will not send any cookies to other processes either. Therefore, the attackers cannot obtain the  $u$ 's authenticated cookie. ■

Based on the model of UPPRESSO about RP server process, the procedure of the cookie being authenticated is described as follows.

**Definition 2.** In  $\mathcal{UWS}$ , the cookie  $c$  is to be set authenticated for user  $u$  only when RP  $r$  receives a valid  $u$ 's identity proof from the owner of  $c$ .

Then we are going to prove that  $\mathcal{UWS}$  follows the requirements that the cookie of the attacker cannot be set authenticated.

Here we propose the lemmas

**Lemma 2.** Attackers cannot obtain the user  $u$ 's password in  $\mathcal{UWS}$ .

**Lemma 3.** Attackers cannot forge the IdP issued proofs in  $\mathcal{UWS}$ .

*Proof:* Lemma 2 can be easily proved because the password is only sent by honest IdP scripting process to IdP server. Lemma 3 is proved as the IdP issued proofs are well signed and verified. Therefore, the following lemma can be proved base on Lemma 2 and Lemma 3. ■

**Lemma 4.** Attackers cannot obtain the  $u$ 's valid identity proof in  $\mathcal{UWS}$ .

*Proof:* We now give a brief proof about Lemma 4. As the attacker attempts to obtain a valid identity proof, he must receive the proof from one of following processes, IdP server process, RP server process, IdP scripting process and RP scripting process. That is, according to the model we find the honest RP scripting process only send identity proof to honest RP server and RP server will not send the proof to any process. It can be proved that only the process who holds  $u$ 's password can obtain the  $u$ 's identity proof from IdP server. As the attacker does not know  $u$ 's password so that he cannot obtain the identity proof from IdP server. To prove that attacker cannot obtain the identity from IdP scripting process is a little complicated so that we here only give a straightforward conclusion. That is when the honest user  $u$  sends the identity proof from the IdP scripting process, the receiver is restricted by the RP Certification  $cert_r$ . And the identity proof is valid in honest RP  $r$  only if the  $cert_r$  belongs to  $r$  (the full proof is in ??). ■

Therefore,  $\mathcal{UWS}$  satisfies the requirements in Definition ??, such that Theorem 1 is proved.

### E. Privacy Of UPPRESSO

Firstly we introduce the definition in [] about static equivalence.

**Definition 3.** Two messages  $t_1$  and  $t_2$  are statically equivalent, written  $t_1 \approx t_2$ , if and only if, for all terms such as  $M(x)$  and  $N(x)$  which only contain one variable  $x$  without nonces, it is true that  $M(t_1) \equiv N(t_1)$  **iff**  $M(t_2) \equiv N(t_2)$ . For instance, there are the messages  $m$  and  $m'$ , symmetric key  $k$ , such that  $enc(m, k) \approx enc(m', k)$  is always true to the attackers without the  $k$ .

Here we give the new definitions

**Definition 4.** For a large prime  $p$  (2048-bit length) and  $p-1$ 's prime factor  $q$  (256-bit length), there are two constants  $g_1, g_2$  as the generators of  $p$  and the constants  $n_1, n_2$  ( $n_1, n_2$

$< q$ ). We define the function symbol  $modpow(a, b, p) = a^b \mod p$ , there are  $modpow(g_1, n_1, p) \approx modpow(g_2, n_2, p)$  and  $modpow(g_1, n_1, p) \approx modpow(g_1, n_2, p)$  always true due to the discrete logarithm problem as the  $n_1$  and  $n_2$  are unknown.

**Definition 5. Equivalence of HTTP requests.** There are messages  $m_1$  and  $m_2$ , we say that  $m_1 \approx m_2$  **iff** the following conditions are met,

- If  $m_1$  and  $m_2$  are HTTPs requests, they are equivalent to the observers besides of the receiver.
- If  $m_1$  and  $m_2$  are HTTPs requests, they are equivalent for the receiver **iff** the value of the Host, Path, Origin and Referer headers in both requests are same, as well as the value of the Parameters and Body are statically equivalent.
- If  $m_1$  and  $m_2$  are HTTP requests, they are equivalent to all the observers as the equivalent HTTPS requests to receivers.

**Definition 6. Equivalence of events.** There are events  $e_1 := \langle a_1, f_1, m_1 \rangle$  and  $e_2 := \langle a_2, f_2, m_2 \rangle$ , we say that  $e_1 \approx e_2$  **iff**

- $a_1 \equiv a_2$  or  $a_1$  and  $a_2$  belong to random addresses.
- $f_1 \equiv f_2$  or  $f_1$  and  $f_2$  belong to random addresses.
- $m_1$  and  $m_2$  are equivalent.

Then we are going to prove the following theorem

**Theorem 2.** Let  $\mathcal{UWS}$  be a UPPRESSO web system, then  $\mathcal{UWS}$  is IdP-Privacy and RP-Privacy.

The definitions about IdP-Privacy and RP-Privacy are designed as follows.

**Definition 7. IdP-Privacy** Let  $\mathcal{UWS}$  be a UPPRESSO web system, there are honest RPs  $r_1, r_2 \in \mathcal{W}$ , IdP  $i \in \mathcal{W}$  and the honest user  $u$ , then  $\mathcal{UWS}$  is IdP-Privacy **iff** for every event  $e_1$  received by  $i$  during the  $u$  logging in to  $r_1$ , there is always an event  $e_2$  for the  $u$  logging in to  $r_2$ , and  $e_1$  and  $e_2$  are equivalent.

*Proof:* Here we only give a brief proof that  $\mathcal{UWS}$  meets the conditions defined in Definition 7. Firstly, it is assumed that the HTTPs transmissions well implemented such that all the events to IdP are regarded as equivalent to web attackers. As we consider IdP server is honest but curious,  $i$  can only hold the events to IdP server process and does not attempt to steal parameters from other processes or set any illegal parameters in the system.

Here we only focus on the same user's multiple requests to the IdP. IdP server only accepts the events whose messages are HTTP request and the *path*  $\in \{ /script, /dynamicRegistration, /login, /loginInfo, /authorize \}$ . All the path will be visited in each login procedure. It can be easily found that the visits to */script* and */loginInfo* carrying no parameters and bodies so that the events must be equivalent. The visits to */login* only carry  $u$ 's username and password so that the events are equivalent. Moreover

,the visits to */dynamicRegistration* and */authorize* carry the  $PID_{RP}$ s and *endpoints* where  $PID_{RP}$ s are statically equivalent because of Definition 4 and *endpoints* are unrelated random constants. Therefore,  $\mathcal{UWS}$  meets the conditions defined in Definition 1, so that theorem 1 is proved. ■

**Definition 8. RP-Privacy** Let  $\mathcal{UWS}$  be a UPPRESSO web system, there are honest RPs  $r_1, r_2 \in \mathcal{W}$  and the honest users  $u_1$  and  $u_2$ , then  $\mathcal{UWS}$  is RP-Privacy iff event through  $r_1$  and  $r_2$  share their states

- for every event  $e_1$  received by  $r_2$  during the  $u_1$  logging in to  $r_2$ , there is always an event  $e_2$  for the  $u_2$  logging in to  $r_2$ , and  $e_1$  and  $e_2$  are equivalent to  $r_1$ .
- for every events received by  $r_2$ , the event cannot be straightforward linked to the existing user's attributes at  $r_1$ .

RP server process only accepts the events whose messages are HTTP request and the  $path \in \{ /script, /login, /startNegotiation, /registration, /uploadToken \}$ . As the RPs may behave malicious so that the events received by RP scripting process should also be considered. However, all of the messages received by RP scripting process are transmitted to RP server. Therefore, we only need to focus on the events received by RP server.

Firstly, we assume that all the parameters are set legally. We give the brief proof. The events visiting to */script* and */login* carry no parameters and bodies so that the events must be equivalent. The visits to */startNegotiation* only carry the nonce so that the events are equivalent. The visits to */registration* carry the IdP signed registration result, however, the contents in the result contains the  $PID_{RP}$ ,  $N_U$  and *endpint*. The contents are all random constants ( $PID_{RP}$  is regarded as same as  $N_U$ ) so that the events are equivalent. The visits to */uploadToken* includes the identity proof containing the  $PID_{RP}$ ,  $PID_U$ . According to Definition 4, the  $PID_U$ s are statically equivalent to  $r_1$ . Moreover, with the  $r_2$  shared state,  $Account_{r_1}$ s are known to  $r_1$ . However,  $r_1$  is unable to transform  $Account_{r_1}$ s into the users' account  $Account_{r_2}$  at  $r_2$  so that the events cannot be linked to the existing user. Therefore, the requirements of Definition 8 are met.

However, as the RPs are considered maybe malicious, such that they will attempt to steal the data from other process or set the malicious parameters during the login procedure. That is, according to Definition 4, the  $PID_U$  the *Accounts* must be equivalent to the attacker as long as the attacker does not know the  $ID_U$ . Therefore the attacker may attempt to steal the  $ID_U$  from UPPRESSO system. But it is easy to be found that IdP will not send the plain  $ID_U$  to any process so that RPs cannot obtain the  $ID_U$ . Another way is that RPs may attempt to treat the *Account* or  $PID_U$  to be generated insecurely, but we are going to prove it is impossible.

- RP may lead the login using the forged  $ID_{RP}$  or  $PID_{RP}$  so that  $PID_U$ s and *Accounts* are no more equivalent. However,  $ID_{RP}$  are provided by the *Cert*, protected by the IdP's signature and verified by IdP script.  $PID_{RP}$  is generated by the  $ID_{RP}$  and the honest user generated nonce. Therefore, it is impossible

to lead the honest user to use the illegal  $ID_{RP}$  and  $PID_{RP}$ .

- RP may also lead the same user to upload the identity proof with same  $PID_U$  or *Account* so that the system is not RP-Privacy according to Definition 8. However, the  $PID_U$  is generated with the user's nonce  $N_U$  so that it is not controlled by the RP. *Account* is generated as the form  $ID_{RP}^{ID_U} \bmod p$ , while RPs may lead the user to use the same  $ID_{RP}$  to generate identity proof. However, the  $ID_{RP}$  is bound with *Cert* which is verified by the user and it is easy for user to find out the login RP does not coincide the RP name shown on her browser.

Therefore, we consider that  $\mathcal{W}$  meet all the requests defined in Definition 8 so that theorem 2 is proved.

## VII. IMPLEMENTATION AND PERFORMANCE EVALUATION

We have implemented the UPPRESSO prototype, and evaluated its performance by comparing with the original OIDC which only prevents RP-based identity linkage, and SPRESSO which only prevents IdP-based login tracing.

### A. Implementation

We adopt SHA-256 for digest generation, and RSA-2048 for signature generation. We randomly choose a 2048-bit prime as  $p$ , a 256-bit prime as  $q$ , and a  $q$ -order generator as  $g$ .  $N_U$ ,  $N_{RP}$  and  $ID_U$  are 256-bit random numbers. Then, the discrete logarithm problem provides equivalent security strength (i.e., 112 bits) as RSA-2048 [?]. UPPRESSO includes the processing at the IdP, users and the RPs. The implementations at each entity are as follows.

The implementation of the IdP only needs small modifications on the existing OIDC implementation. The UPPRESSO IdP is implemented based on MITREid Connect [?], an open-source OIDC Java implementation certificated by the OpenID Foundation [?]. We add 3 lines of Java code to calculate  $PID_U$ , 26 lines to the function of dynamic registration to support  $PID_{RP}$  registration, i.e., checking  $PID_{RP}$  and adding a signature and validity period in the response. The calculations of  $ID_{RP}$ ,  $PID_U$  and RSA signature are implemented based on Java built-in cryptographic libraries (e.g., BigInteger).

The user-side processing is implemented as a Chrome extension with about 330 lines of JavaScript code, to provide the functions in Steps 1.3, 1.5, 2.1, 3.2 and 3.5. The cryptographic computations, e.g., *Cert*<sub>RP</sub> verification and  $PID_{RP}$  negotiation, are implemented based on jsrsasn [?], an efficient JavaScript cryptographic library. This chrome extension requires permissions *chrome.tabs* and *chrome.windows* to obtain the RP's URL from the browser's tab, and *chrome.webRequest* to intercept, block, modify requests to the IdP or RP [?]. Here, the cross-origin HTTPS requests sent by this chrome extension to the RP and IdP, will be blocked by Chrome due to the default same-origin security policy. To avoid this block, UPPRESSO modifies the IdP and RP, and sets `chrome-extension://chrome-id` (`chrome-id` is uniquely assigned by Google) in

Access-Control-Allow-Origin header of the IdP's and RP's responses.

We provide a Java SDK for RPs to integrate UPPRESSO. The SDK provides 2 functions to encapsulate RP's processings: one for RP identifier transformation,  $PID_{RP}$  registration and identity proof request generation; while the other for identity proof verification and  $Account$  calculation. The SDK is implemented based on the Spring Boot framework with about 1100 lines code, and cryptographic computations are implemented based on Spring Security library. An RP only needs to invoke these two functions for the integration.

## B. Performance Evaluation

**Environment.** The evaluation was performed on 3 machines, one (3.4GHz CPU, 8GB RAM, 500GB SSD, Windows 10) as IdP, one (3.1GHz CPU, 8GB RAM, 128GB SSD, Windows 10) as an RP, and the last one (2.9GHz CPU, 8GB RAM, 128GB SSD, Windows 10) as a user. The user agent is Chrome v75.0.3770.100. And the machines are connected by an isolated 1Gbps network.

**Setting.** We compare UPPRESSO with MITREid Connect [?] and SPRESSO [?], where MITREid Connect provides open-source Java implementations [?] of IdP and RP's SDK, and SPRESSO provides the JavaScript implementations based on node.js for all entities [?]. We implemented a Java RP based on Spring Boot framework for UPPRESSO and MITREid Connect, by integrating the corresponding SDK respectively. The RPs in all the three schemes provide the same function, i.e., extracting the user's account from the identity proof. We have measured the time for a user's login at an RP, and calculated the average values of 1000 measurements. For better analysis, we divide a login into 4 phases according to the lifecycle of identity proof: **Identity proof requesting** (Steps 1.1-3.2 in Figure 3), the RP (and user) constructing and transmitting the request to IdP; **Identity proof generation** (Steps 3.3 and 3.4 in Figure 3), the IdP generating identity proof (no user authentication); **Identity proof extraction** (Steps 3.4 and 3.5 in Figure 3), the RP server extracts the identity proof from the IdP; and **Identity proof verification** (Steps 4.1 and 4.2 in Figure 3), the RP verifying and parsing the identity proof.

**Results.** The evaluation results are provided in Figure 4. The overall processing times are 113 ms, 308 ms and 254 ms for MITREid Connect, SPRESSO and UPPRESSO, respectively. The details are as follows.

In the requesting, UPPRESSO requires both the user and RP to perform 2 modular exponentiations for RP identifier transformation and complete  $PID_{RP}$  registration at the IdP, which totally need 144 ms; SPRESSO needs 19 ms for the RP to obtain IdP's public key and encrypt its domain; while MITREid Connect only needs 10 ms.

In the generation, UPPRESSO needs an extra 6 ms for computing  $PID_U$ , compared to MITREid Connect which only needs 32 ms. SPRESSO requires 71 ms, as it implements the IdP based on node.js and therefore can only adopt a JavaScript cryptographic library, while others adopt a more efficient Java library. As the processings in SPRESSO and MITREid Connect are the same, the processing time in SPRESSO may be reduced to 32 ms. And, then the overall time in SPRESSO will be 269 ms, still larger than 254 ms in UPPRESSO.




Fig. 4: The Evaluation.

In the identity proof extraction, UPPRESSO only needs 14 ms where the Chrome extension relays the identity proof to the RP server directly. MITREid Connect requires the IdP to send the identity proof to the RP's web page which then sends the proof to the RP server through a JavaScript function, and needs 57 ms. SPRESSO needs the longest time (193 ms) due to a complicated processing at the user's browser, which needs the browser to obtain identity proofs from the IdP, download the JavaScript program from a trusted entity (forwarder), execute the program to decrypt RP's endpoint, send identity proofs to this endpoint (an RP's web page) who finally transmits the proof to RP server. In the evaluation, the forwarder and IdP are deployed in one machine, which doesn't introduce performance degradation based on the observation.

In the verification, UPPRESSO needs an extra calculation for  $Account$ , which then requires 58 ms, compared to 14 ms in MITREid Connect and 17 ms in SPRESSO.

## VIII. DISCUSSIONS AND FUTURE WORK

In this section, we discuss some related issues and our future work.

**Scalability.** The adversary cannot exhaust  $ID_{RP}$  and  $PID_{RP}$ . For  $ID_{RP}$ , it is generated only in RP's initial registration. For  $PID_{RP}$ , in practice, we only need to ensure all  $PID_{RPs}$  are different among the unexpired identity proof (the number denoted as  $n$ ). We assume that IdP doesn't perform the uniqueness check, and then calculate the probability that at least two  $PID_{RPs}$  are equal in these  $n$  ones. The probability is  $1 - \prod_{i=0}^{n-1} (1 - i/q)$  which increases with  $n$ . For an IdP with throughput  $2 \times 10^8$  req/s, when the validity period of the identity proof ( $PID_{RP}$ ) is set as 5 minutes,  $n$  is less than  $2^{36}$ , then the probability is less than  $2^{-183}$  for 256-bit  $q$ . Moreover, as this probability is negligible, the uniqueness check of  $PID_{RP}$ , i.e., the  $PID_{RP}$  registration, could be removed in the SSO login process, and this optimization can be adopted when this negligible probability is acceptable by the users and RPs.

**Security against DoS attack.** The adversary may attempt to perform DoS attack on the IdP and RP. For example, the adversary may act as a user to invoke the  $PID_{RP}$  registration (Step 2.1) and identity proof generation (Step 3.2) at the IdP, which requires the IdP to perform two signature generations and one modular exponentiation. However, as the user has

already been authenticated at the IdP, the IdP could identify the malicious users based on audit, in addition to the existing DoS mitigation schemes. The adversary may act as a user requesting to log into an RP, and make the RP perform two modular exponentiations. The RP could previously calculated a set of  $Y_{RPS}$  to mitigate this attack.

**OIDC authorization code flow support.** The privacy-preserving functions  $\mathcal{F}_{ID_U \mapsto PID_U}$ ,  $\mathcal{F}_{ID_{RP} \mapsto PID_{RP}}$  and  $\mathcal{F}_{PID_U \mapsto Account}$  can be integrated into OIDC authorization code flow directly, therefore RP-based identity linkage and IdP-based login tracing are still prevented during the construction and parsing of identity proof. The only privacy leakage is introduced by the transmission, as RP servers obtain the identity proof directly from the IdP in this flow, which allows the IdP to obtain RP's network information (e.g., IP address). UPPRESSO needs to integrate existing anonymous networks (e.g., Tor) to prevent this leakage.

**Platform independent.** Our current implementation only requires the user to install a Chrome extension and doesn't need to store any persistent data at the user's machine. Moreover, the implementation could be further extended to remove the Chrome extension, whose JavaScript program is then fetched from the honest IdP. The processing is similar as SPRESSO. That is, 1) the RP's window (window A) opens a new iframe (window B) to visit the RP's web page, while the RP's web page redirects window B to the IdP; 2) window B downloads the JavaScript program from the IdP and performs the processing in Steps 1.3, 1.5, 2.1, 3.2 and 3.5; 3) then postMessages are adopted to exchange messages between window A and B for Steps 1.2, 1.3, 1.4, 2.3, 3.1 and 3.5. The opener handle of window B is preserved (i.e., window A) for the postMessage, as window A opens window B with a web page from the RP; and window B is redirected to the IdP with *noreferrer* attribute set, to prevent the browser from sending RP's URL in the Referrer header to the IdP.

**Malicious IdP mitigation.** The IdP is assumed to assign a unique  $ID_{RP}$  in  $Cert_{RP}$  for each RP and generate the correct  $PID_U$  for each login. The malicious IdP may attempt to provide the incorrect  $ID_{RP}$  and  $PID_U$ , which could be prevented by integrating certificate transparency [?] and user's identifier check [?]. With certificate transparency [?], the monitors check the uniqueness of  $ID_{RP}$  among all the certificates stored in the log server. To prevent the malicious IdP from injecting any incorrect  $PID_U$ , the user could provide a nickname to the RP for an extra check as in SPRESSO [?].

## IX. RELATED WORKS

Various SSO protocols have been proposed, such as, OIDC, OAuth 2.0, SAML, Central Authentication Service (CAS) [?] and Kerberos [?]. These protocols are widely adopted in Google, Facebook, Shibboleth project [?], Java applications and etc. And, plenty of works have been conducted on privacy protection and security analysis for SSO systems.

### A. Privacy protection for SSO systems.

**Privacy-preserving SSO systems.** As suggested by NIST [?], SSO systems should prevent both RP-based identity linkage and IdP-based login tracing. The pairwise user identifier is

adopted in SAML [?] and OIDC [?], and only prevents RP-based identity linkage; while SPRESSO [?] and BrowserID [?] only prevent IdP-based login tracing. BrowserID is adopted in Persona [?] and Firefox Accounts [?], however an analysis on Persona found IdP-based login tracing could still succeed [?], [?]. UPPRESSO prevents both the RP-based identity linkage and IdP-based login tracing, and could be integrated into OIDC which has been formally analyzed [?].

**Anonymous SSO systems.** Anonymous SSO schemes are designed to allow users to access a service (i.e. RP) protected by a verifier (i.e., IdP) without revealing their identities. One of the earliest anonymous SSO systems was proposed for Global System for Mobile (GSM) communication in 2008 [?]. The notion of anonymous SSO was formalized [?] in 2013. And, various cryptographic primitives, such as group signature, zero-knowledge proof and etc., were adopted to design anonymous SSO schemes [?], [?]. Anonymous SSO schemes are designed for the anonymous services, and not applicable to common services which need user identification.

### B. Security analysis of SSO systems.

**Formal analysis on SSO standards.** The SSO standards (e.g., SAML, OAuth and OIDC) have been formally analyzed. Fett et al. [?], [?] have conducted the formal analysis on OAuth 2.0 and OIDC standards based on an expressive Dolev-Yao style model [?], and proposed two new attacks, i.e., 307 redirect attack and IdP Mix-Up attack. When the IdP misuses HTTP 307 status code for redirection, the sensitive information (e.g., credentials) entered at the IdP will be leaked to the RP by the user's browser. While, IdP Mix-Up attack confuses the RP about which IdP is used and makes the victim RP send the identity proof to the malicious IdP, which breaks the confidentiality of the identity proof. Fett et al. [?], [?] have proved that OAuth 2.0 and OIDC are secure once these two attacks prevented. UPPRESSO could be integrated into OIDC, which simplifies its security analysis. [?] formally analyzed SAML and its variant proposed by Google, and found that Google's variant of SAML doesn't set RP's identifier in the identity proof, which breaks RP designation.

**Single sign-off.** In SSO systems, once a user's IdP account is compromised, the adversary could hijack all her RPs' accounts. A backwards-compatible extension, named single sign-off, is proposed for OIDC. The single sign-off allows the user to revoke all her identity proofs and notify all RPs to freeze her accounts [?]. The single sign-off could also be achieved in UPPRESSO, where the user needs to revoke the identity proofs at all RPs, as the IdP doesn't know which RPs the user visits.

**Analysis on SSO implementations.** Various vulnerabilities were found in SSO implementations, and then exploited for impersonation and identity injection attacks by breaking the confidentiality [?], [?], [?], [?], [?], integrity [?], [?], [?], [?], [?], [?] or RP designation [?], [?], [?], [?], [?] of identity proof. Wang et al. [?] analyzed the SSO implementations of Google and Facebook from the view of the browser relayed traffic, and found logic flaws in IdPs and RPs to break the confidentiality and integrity of identity proof. An authentication flaw was found in Google Apps [?], allowing a malicious RP to hijack a user's authentication attempt and inject the malicious code to steal the cookie (or identity proof) for the targeted RP,

breaking the confidentiality. The integrity has been tampered with in SAML, OAuth and OIDC systems [?], [?], [?], [?], [?], due to various vulnerabilities, such as XML Signature wrapping (XSW) [?], RP's incomplete verification [?], [?], [?], IdP spoofing [?], [?] and etc. And, a dedicated, bidirectional authenticated secure channel was proposed to improve the confidentiality and integrity of identity proof [?]. The vulnerabilities were also found to break the RP designation, such as the incorrect binding at IdPs [?], [?], insufficient verification at RPs [?], [?], [?]. Automatical tools, such as SSOScan [?], OAuthTester [?] and S3KVetter [?], have been designed to detect vulnerabilities for breaking the confidentiality, integrity or RP designation of identity proof.

**Analysis on mobile SSO systems.** In mobile SSO systems, the IdP App, IdP-provided SDK (e.g., an encapsulated WebView) or system browser are adopted to redirect identity proof from IdP App to RP App. However, none of them was trusted to ensure that the identity proof could be only sent to the designated RP [?], [?], as WebView and system browser cannot authenticate RP App while the IdP App may be repackaged. Moreover, the SSO protocols needed to be modified to provide SSO services for mobile Apps, however these modifications were not well understood by RP developers [?], [?]. The top Android applications have been analyzed [?], [?], [?], [?], [?], and vulnerabilities were found to break the confidentiality [?], [?], [?], [?], integrity [?], [?], and RP designation [?], [?] of identity proof.

## X. CONCLUSION

In this paper, we propose UPPRESSO, an unlinkable privacy-preserving single sign-on system, which protects a user's login activities at different RPs against both curious IdP and collusive RPs. To the best of our knowledge, UPPRESSO is the first approach that defend against both IdP-based login tracing and RP-based identity linkage privacy threats at the same time. To achieve these goals, we convert the privacy problem in SSO services into an identifier-transformation problem and design three transformation functions based on the discrete logarithm problem, where  $\mathcal{F}_{ID_{RP} \mapsto PID_{RP}}$  prevents curious IdP from knowing the identity of the RP,  $\mathcal{F}_{ID_U \mapsto PID_U}$  prevents collusive RPs from linking a user based on her identifier, and  $\mathcal{F}_{PID_U \mapsto Account}$  allows each RP to derive an identical account for a user in her multiple logins. The three functions could be integrated with existing SSO protocols, such as OIDC, to enhance the protection of user privacy, without breaking any security guarantee of SSO. Moreover, the evaluation on the prototype of UPPRESSO demonstrates that it supports an efficient SSO service, where a single login takes only 254 ms on average.

## REFERENCES

- [1] H. Kopka and P. W. Daly, *A Guide to L<sup>A</sup>T<sub>E</sub>X*, 3rd ed. Harlow, England: Addison-Wesley, 1999.



## APPENDIX A WEB MODEL

### A. Data Formate

Here we provide the details of formate of some messages we use to construct the UPPRESSO model.

**HTTP Messages.** An HTTP request message is the term of the form  $\langle \text{HTTPReq}, \text{nonce}, \text{method}, \text{host}, \text{path}, \text{parameters}, \text{headers}, \text{body} \rangle$ , and an HTTP response message is the term of the form  $\langle \text{HTTPResp}, \text{nonce}, \text{status}, \text{headers}, \text{body} \rangle$ . The details are dined as follows:

- $\text{HTTPReq}$  and  $\text{HTTPResp}$  are the type of messages.
- $\text{nonce}$  is the constant nonce mapping the response with the specific request.
- $\text{method}$  is the HTTP method, such as GET and POST.
- $\text{host}$  is the constant string domain of visited server.
- $\text{path}$  is the constant string representing the concrete resource of the server.
- $\text{parameters}$  contains the parameters carried by the url as the form  $\langle \langle \text{name}, \text{value} \rangle, \langle \text{name}, \text{value} \rangle, \dots \rangle$ , , for example the  $\text{parameters}$  HTTP request sent to the url  $\text{http} : // \text{www.example.com?type} = \text{confirm}$  is  $\langle \langle \text{type}, \text{confirm} \rangle \rangle$ .
- $\text{headers}$  is the header content of each HTTP messages as the form  $\langle \langle \text{name}, \text{value} \rangle, \langle \text{name}, \text{value} \rangle, \dots \rangle$ , such as  $\langle \langle \text{Referer}, \text{http} : // \text{www.example.com} \rangle, \langle \text{Cookies}, c \rangle \rangle$ .
- $\text{body}$  is the body content carried by HTTP POST request or HTTP response in the form  $\langle \langle \text{name}, \text{value} \rangle, \langle \text{name}, \text{value} \rangle, \dots \rangle$ .
- $\text{status}$  is the HTTP status code defined by HTTP standard.

**URL.** A URL is a term  $\langle \text{URL}, \text{protocol}, \text{host}, \text{path}, \text{parameters} \rangle$ , where URL is the type,  $\text{protocol}$  is chosen in S, P as S stands for HTTPS and P stands for HTTP. The  $\text{host}, \text{path}, \text{and parameters}$  are same as in HTTP message.

**Origin.** An Origin is a term  $\langle \text{host}, \text{protocol} \rangle$  that stands for the specific domain used by the HTTP CORS policy, where  $\text{host}$  and  $\text{protocol}$  are defined as same as in URL.

**POSTMESSAGE.** PostMessage is used in the browser for transmitting messages between scripts from different origins. We define the postMessage as the form  $\langle \text{POSTMESSAGE}, \text{target}, \text{Content}, \text{Origin} \rangle$ , where POSTMESSAGE is the type,  $\text{target}$  is the constant nonce which stands the for the receiver,  $\text{Content}$  is the message transmitted and Origin is restricts the receiver's origin.

**XMLHTTPREQUEST.** XMLHttpRequest is the HTTP message transmitted by scripts in the browser. That is the XMLHttpRequest is converted with the HTTP message by the browser. The XMLHttpRequest in the form  $\langle \text{XMLHTTPREQUEST}, \text{URL}, \text{methods}, \text{Body}, \text{nonce} \rangle$  can be converted into HTTP request message by the browser, and  $\langle \text{XMLHTTPREQUEST}, \text{Body}, \text{nonce} \rangle$  is converted from HTTP response message.

**Data Operation.** The data used in UPPRESSO are defined in the following forms:

- **Standardized Data** is the data in the fixed format, for instance the HTTP request is the standardized data in the form  $\langle \text{HTTPReq}, \text{nonce}, \text{method}, \text{host}, \text{path}, \text{parameters}, \text{headers}, \text{body} \rangle$ . We assume there is an HTTP request  $r := \langle \text{HTTPReq}, n, \text{GET}, \text{example.com}, / \text{path}, \langle \rangle, \langle \rangle, \langle \rangle \rangle$ , here we define the operation on the  $r$ . That is the elements in  $r$  can be accessed in the form  $r.\text{name}$ , such that  $r.\text{method} \equiv \text{GET}$ ,  $r.\text{path} \equiv / \text{path}$  and  $r.\text{body} \equiv \langle \rangle$ .
- **Dictionary Data** is the data in the form  $\langle \langle \text{name}, \text{value} \rangle, \langle \text{name}, \text{value} \rangle, \dots \rangle$ , for instance the  $\text{body}$  in HTTP request is dictionary data. We assume there is a  $\text{body} := \langle \langle \text{username}, \text{alice} \rangle, \langle \text{password}, 123 \rangle \rangle$ , here we define the operation on the  $\text{body}$ . That is we can access the elements in  $\text{body}$  in the form  $\text{body}[\text{name}]$ , such that  $\text{body}[\text{username}] \equiv \text{alice}$  and  $\text{body}[\text{password}] \equiv 123$ . We can also add the new attributes to the dictionary, for example after we set  $\text{body}[\text{age}] := 18$ , the  $\text{body}$  are changed into  $\langle \langle \text{username}, \text{alice} \rangle, \langle \text{password}, 123 \rangle, \langle \text{age}, 18 \rangle \rangle$ .

### B. Browser Model

As we consider that the browsers are honest in UPPRESSO model, therefore, we only focus on how the browsers interactive with the scripts.

### C. Model Of UPPRESSO

In this section, we will introduce the model of processes in UPPRESSO system, containing IdP server process, RP server process, IdP scripting process and RP scripting process.

#### D. IdP server process

The state

#### E. Analysis

---

##### Algorithm 1 $R^i$

---

**Input:**  $\langle a, f, m \rangle, s$

```
1: let  $s := s'$ 
2: let  $n, method, path, parameters, headers, body$  such that
    $\langle \text{HTTPReq}, n, method, path, parameters, headers, body \rangle \equiv m$ 
   if possible; otherwise stop  $\langle \rangle, s'$ 
3: if  $path \equiv /script$  then
4:   let  $m' := \langle \text{HTTPResp}, n, 200, \langle \rangle, s'.IdPScript \rangle$ 
5:   stop  $\langle f, a, m' \rangle, s'$ 
6: else if  $path \equiv /login$  then
7:   let  $cookie := headers[Cookie]$ 
8:   let  $session := s'.sessions[cookie]$ 
9:   let  $username := body[username]$ 
10:  let  $password := body[password]$ 
11:  if  $password \neq \text{SecretOfID}(username)$  then
12:    let  $m' := \langle \text{HTTPResp}, n, 200, \langle \rangle, \text{LoginFailure} \rangle$ 
13:    stop  $\langle f, a, m' \rangle, s'$ 
14:  end if
15:  let  $session[uid] := \text{UIDOfUser}(username)$ 
16:  let  $m' := \langle \text{HTTPResp}, n, 200, \langle \rangle, \text{LoginSuccess} \rangle$ 
17:  stop  $\langle f, a, m' \rangle, s'$ 
18: else if  $path \equiv /loginInfo$  then
19:   let  $cookie := headers[Cookie]$ 
20:   let  $session := s'.sessions[cookie]$ 
21:   let  $username := session[username]$ 
22:   if  $username \neq \text{null}$  then
23:     let  $m' := \langle \text{HTTPResp}, n, 200, \langle \rangle, \text{Logged} \rangle$ 
24:     stop  $\langle f, a, m' \rangle, s'$ 
25:   end if
26:   let  $m' := \langle \text{HTTPResp}, n, 200, \langle \rangle, \text{Unlogged} \rangle$ 
27:   stop  $\langle f, a, m' \rangle, s'$ 
28: else if  $path \equiv /dynamicRegistration$  then
29:   let  $PID_{RP} := body[PID_{RP}]$ 
30:   let  $Endpoint := body[Endpoint]$ 
31:   let  $Nonce := body[Nonce]$ 
32:   if  $PID_{RP} \in \text{ListOfPID}()$  then
33:     let  $Content := \langle \text{Fail}, PID_{RP}, Nonce \rangle$ 
34:     let  $Sig := \text{Sig}(Content, s'.SignKey)$ 
35:     let  $RegistrationResult := \langle Content, Sig \rangle$ 
36:     let  $m' := \langle \text{HTTPResp}, n, 200, \langle \rangle, RegistrationResult \rangle$ 
37:     stop  $\langle f, a, m' \rangle, s'$ 
38:   end if
39:   let  $Validity := \text{CurrentTime}() + s'.Validity$ 
40:   let  $s'.RPs := s'.RPs + \langle \rangle \langle PID_{RP}, Endpoint, Validity \rangle$ 
41:   let  $Content := \langle \text{OK}, PID_{RP}, Nonce, Validity \rangle$ 
42:   let  $Sig := \text{Sig}(Content, s'.SignKey)$ 
43:   let  $RegistrationResult := \langle Content, Sig \rangle$ 
44:   let  $m' := \langle \text{HTTPResp}, n, 200, \langle \rangle, RegistrationResult \rangle$ 
45:   stop  $\langle f, a, m' \rangle, s'$ 
46: else if  $path \equiv /authorize$  then
47:   let  $cookie := headers[Cookie]$ 
48:   let  $session := s'.sessions[cookie]$ 
49:   let  $username := session[username]$ 
50:   if  $username \equiv \text{null}$  then
51:     let  $m' := \langle \text{HTTPResp}, n, 200, \langle \rangle, \text{Fail} \rangle$ 
52:     stop  $\langle f, a, m' \rangle, s'$ 
```

```

53: end if
54: let  $PID_{RP} := parameters[PID_{RP}]$ 
55: let  $Endpoint := parameters[Endpoint]$ 
56: if  $PID_{RP} \notin ListOfPID() \vee Endpoint \notin EndpointsOFRP(PID)$  then
57:   let  $m' := \langle HTTPResp, n, 200, \langle \rangle, Fail \rangle$ 
58:   stop  $\langle f, a, m' \rangle, s'$ 
59: end if
60: let  $UID := session[uid]$ 
61: let  $PID_U := ModPow(PID_{RP}, UID, s'.p)$ 
62: let  $Validity := CurrentTime() + s'.Validity$ 
63: let  $Content := \langle PID_{RP}, PID_U, s'.ID, Validity \rangle$ 
64: let  $Sig := Sig(Content, s'.SignKey)$ 
65: let  $Token := \langle Content, Sig \rangle$ 
66: let  $s'.Tokens := s'.Tokens + \langle \rangle Token$ 
67: let  $m' := \langle HTTPResp, n, 200, \langle \rangle, \langle Token, Token \rangle \rangle$ 
68: stop  $\langle f, a, m' \rangle, s'$ 
69: end if
70: stop  $\langle \rangle, s'$ 

```

---

## Algorithm 2 $R^r$

---

**Input:**  $\langle a, f, m \rangle, s$

```

1: let  $s := s'$ 
2: let  $n, method, path, parameters, headers, body$  such that
    $\langle HTTPReq, n, method, path, parameters, headers, body \rangle \equiv m$ 
   if possible; otherwise stop  $\langle \rangle, s'$ 
3: if  $path \equiv /script$  then
4:   let  $m' := \langle HTTPResp, n, 200, \langle \rangle, s'.RPScript \rangle$ 
5:   stop  $\langle f, a, m' \rangle, s'$ 
6: else if  $path \equiv /login$  then
7:   let  $m' := \langle HTTPResp, n, 302, \langle \langle Location, s'.IdP.ScriptUrl \rangle \rangle, \langle \rangle \rangle$ 
8:   stop  $\langle f, a, m' \rangle, s'$ 
9: else if  $path \equiv /startNegotiation$  then
10:  let  $cookie := headers[Cookie]$ 
11:  let  $session := s'.sessions[cookie]$ 
12:  let  $N_U := parameters[N_U]$ 
13:  let  $PID_{RP} := ModPow(s'.ID_{RP}, N_U, s'.IdP.p)$ 
14:  let  $t := ExEU(N_U, s'.IdP.q)$ 
15:  let  $session[N_U] := N_U$ 
16:  let  $session[PID_{RP}] := PID_{RP}$ 
17:  let  $session[t] := t$ 
18:  let  $session[state] := expectRegistration$ 
19:  let  $m' := \langle HTTPResp, n, 200, \langle \rangle, \langle Cert, s'.Cert \rangle \rangle$ 
20:  stop  $\langle f, a, m' \rangle, s'$ 
21: else if  $path \equiv /registrationResult$  then
22:  let  $cookie := headers[Cookie]$ 
23:  let  $session := s'.sessions[cookie]$ 
24:  if  $session[state] \neq expectRegistration$  then
25:    let  $m' := \langle HTTPResp, n, 200, \langle \rangle, Fail \rangle$ 
26:    stop  $\langle f, a, m' \rangle, s'$ 
27:  end if
28:  let  $RegistrationResult := body[RegistrationResult]$ 
29:  let  $Content := RegistrationResult.Content$ 
30:  if  $checksig(Content, RegistrationResult.Sig, s'.IdP.PubKey) \equiv FALSE$  then
31:    let  $m' := \langle HTTPResp, n, 200, \langle \rangle, Fail \rangle$ 
32:    let  $session := null$ 
33:    stop  $\langle f, a, m' \rangle, s'$ 
34:  end if
35:  if  $Content.Result \neq OK$  then
36:    let  $m' := \langle HTTPResp, n, 200, \langle \rangle, Fail \rangle$ 
37:    let  $session := null$ 
38:    stop  $\langle f, a, m' \rangle, s'$ 

```

```

39: end if
40: let  $PID_{RP} := session[PID_{RP}]$ 
41: let  $N_U := session[N_U]$ 
42: let  $Nonce := Hash(N_U)$ 
43: let  $Time := CurrentTime()$ 
44: if  $PID_{RP} \neq Content.PID_{RP} \vee Nonce \neq Content.Nonce \vee Time > Content.Validity$  then
45:   let  $m' := \langle HTTPResp, n, 200, \langle \rangle, Fail \rangle$ 
46:   let  $session := null$ 
47:   stop  $\langle f, a, m' \rangle, s'$ 
48: end if
49: let  $session[PIDValidity] := Content.Validity$ 
50: let  $Endpoint \in s'.Endpoints$ 
51: let  $session[state] := expectToken$ 
52: let  $Nonce' := Random()$ 
53: let  $session[Nonce] := Nonce'$ 
54: let  $Body := \langle PID_{RP}, Endpoint, Nonce' \rangle$ 
55: let  $m' := \langle HTTPResp, n, 200, \langle \rangle, Body \rangle$ 
56: stop  $\langle f, a, m' \rangle, s'$ 
57: else if  $path \equiv /uploadToken$  then
58:   let  $cookie := headers[Cookie]$ 
59:   let  $session := s'.sessions[cookie]$ 
60:   if  $session[state] \neq expectToken$  then
61:     let  $m' := \langle HTTPResp, n, 200, \langle \rangle, Fail \rangle$ 
62:     stop  $\langle f, a, m' \rangle, s'$ 
63:   end if
64:   let  $Token := body[Token]$ 
65:   if  $checksig(Token.Content, Token.Sig, s'.IdP.PubKey) \equiv FALSE$  then
66:     let  $m' := \langle HTTPResp, n, 200, \langle \rangle, Fail \rangle$ 
67:     stop  $\langle f, a, m' \rangle, s'$ 
68:   end if
69:   let  $PID_{RP} := session[PID_{RP}]$ 
70:   let  $Time := CurrentTime()$ 
71:   let  $PIDValidity := session[PIDValidity]$ 
72:   let  $Content := Token.Content$ 
73:   if  $PID_{RP} \neq Content.PID_{RP} \vee Time > Content.Validity \vee Time > PIDValidity$  then
74:     let  $m' := \langle HTTPResp, n, 200, \langle \rangle, Fail \rangle$ 
75:     stop  $\langle f, a, m' \rangle, s'$ 
76:   end if
77:   let  $PID_U := Content.PID_U$ 
78:   let  $t := session[t]$ 
79:   let  $Account := ModPow(PID_U, t, s'.IdP.p)$ 
80:   if  $Account \in ListOfUser()$  then
81:     let  $RegisterUser(Account)$ 
82:   end if
83:   let  $session[user] := Account$ 
84:   let  $m' := \langle HTTPResp, n, 200, \langle \rangle, LoginSuccess \rangle$ 
85:   stop  $\langle f, a, m' \rangle, s'$ 
86: end if
87: stop  $\langle \rangle, s'$ 

```

---

### Algorithm 3 *script\_idp*

---

**Input:**  $\langle tree, docnonce, scriptstate, scriptinputs, cookies, localStorage, sessionStorage, ids, secret \rangle$

```

1: let  $s' := scriptstate$ 
2: let  $command := \langle \rangle$ 
3: let  $target := PARENTWINDOW(tree, docnonce)$ 
4: let  $IdPDomain := s'.Parameters[IdPDomain]$ 
5: switch  $s'.q$  do
6:   case start:
7:     let  $N_U := Random()$ 
8:     let  $command := \langle POSTMESSAGE, target, \langle \langle N_U, N_U \rangle \rangle, null \rangle$ 
9:     let  $s'.Parameters[N_U] := N_U$ 

```

```

10:   let  $s'.q := expectCert$ 
11: case  $expectCert$ :
12:   let  $pattern := \langle POSTMESSAGE, *, Content, * \rangle$ 
13:   let  $input := CHOOSEINPUT(scriptinputs, pattern)$ 
14:   if  $input \neq null$  then
15:     let  $Cert := input.Content[Cert]$ 
16:     let  $s'.Parameters[Cert] := Cert$ 
17:     if  $checksig(Cert.Content, Cert.Sig, s'.PubKey) \equiv null$  then
18:       let stop  $\langle \rangle$ 
19:     end if
20:     let  $N_U := s'.Parameters[N_U]$ 
21:     let  $PID_{RP} := ModPow(Cert.Content.ID_{RP}, N_U, s'.p)$ 
22:     let  $s'.Parameters[PID_{RP}] := PID_{RP}$ 
23:     let  $Endpoint := RandomUrl()$ 
24:     let  $s'.Parameters[Endpoint] := Endpoint$ 
25:     let  $Nonce := HashN_U$ 
26:     let  $Url := \langle URL, S, IdPDomain, /dynamicRegistration, \langle \rangle \rangle$ 
27:     let  $s'.refXHR := Random()$ 
28:     let  $command := \langle XMLHTTPREQUEST, Url, POST, \langle \langle PID_{RP}, PID_{RP} \rangle, \langle Nonce, Nonce \rangle, \langle Endpoint, Endpoint \rangle \rangle, s'.refXHR \rangle$ 
29:     let  $s'.q := expectRegistrationResult$ 
30:   end if
31: case  $expectRegistrationResult$ :
32:   let  $pattern := \langle XMLHTTPREQUEST, Body, s'.refXHR \rangle$ 
33:   let  $input := CHOOSEINPUT(scriptinputs, pattern)$ 
34:   if  $input \neq null$  then
35:     let  $RegistrationResult := input.Body[RegistrationResult]$ 
36:     if  $RegistrationResult.Content.Result \neq OK$  then
37:       let  $s'.q := stop$ 
38:       let stop  $\langle \rangle$ 
39:     end if
40:     let  $command := \langle POSTMESSAGE, target, \langle \langle RegistrationResult, RegistrationResult \rangle \rangle, null \rangle$ 
41:     let  $s'.q := expectProofRquest$ 
42:   end if
43: case  $expectProofRquest$ :
44:   let  $pattern := \langle POSTMESSAGE, *, Content, * \rangle$ 
45:   let  $input := CHOOSEINPUT(scriptinputs, pattern)$ 
46:   if  $input \neq null$  then
47:     let  $PID_{RP} := input.Content[PID_{RP}]$ 
48:     let  $Endpoint_{RP} := input.Content[Endpoint]$ 
49:     let  $s'.Parameters[Nonce] := input.Content[Nonce]$ 
50:     let  $Cert := s'.Parameters[Cert]$ 
51:     let  $s'.Parameters[Endpoint_{RP}] := Endpoint_{RP}$ 
52:     if  $Endpoint_{RP} \notin Cert.Content.Endpoints \vee PID_{RP} \neq s'.Parameters[PID_{RP}]$  then
53:       let  $s'.q := stop$ 
54:       let stop  $\langle \rangle$ 
55:     end if
56:     let  $Url := \langle URL, S, IdPDomain, /loginInfo, \langle \rangle \rangle$ 
57:     let  $s'.refXHR := Random()$ 
58:     let  $command := \langle XMLHTTPREQUEST, Url, GET, \langle \rangle, s'.refXHR \rangle$ 
59:     let  $s'.q := expectLoginState$ 
60:   end if
61: case  $expectLoginState$ :
62:   let  $pattern := \langle XMLHTTPREQUEST, Body, s'.refXHR \rangle$ 
63:   let  $input := CHOOSEINPUT(scriptinputs, pattern)$ 
64:   if  $input \neq null$  then
65:     if  $input.Body \equiv Logged$  then
66:       let  $username \in ids$ 
67:       let  $Url := \langle URL, S, IdPDomain, /login, \langle \rangle \rangle$   $mystates'.refXHR := Random()$ 
68:       let  $command := \langle XMLHTTPREQUEST, Url, POST, \langle \langle username, username \rangle, \langle password, secret \rangle \rangle, s'.refXHR \rangle$ 
69:       let  $s'.q := expectLoginResult$ 
70:     else if  $input.Body \equiv Unlogged$  then

```

```

71:     let  $PID_{RP} := s'.Parameters[PID_{RP}]$ 
72:     let  $Endpoint := s'.Parameters[Endpoint]$ 
73:     let  $Nonce := s'.Parameters[Nonce]$ 
74:     let  $Url := \langle URL, S, IdPDomain, /authorize,$ 
        $\langle \langle PID_{RP}, PID_{RP} \rangle, \langle Endpoint, Endpoint \rangle, \langle Nonce, Nonce \rangle \rangle \rangle$ 
75:     let  $s'.refXHR := Random()$ 
76:     let  $command := \langle XMLHTTPREQUEST, Url, GET, \langle \rangle, s'.refXHR \rangle$ 
77:     let  $s'.q := expectToken$ 
78:   end if
79: end if
80: case expectLoginResult:
81:   let  $pattern := \langle XMLHTTPREQUEST, Body, s'.refXHR \rangle$ 
82:   let  $input := CHOOSEINPUT(scriptinputs, pattern)$ 
83:   if  $input \neq null$  then
84:     if  $input.Body \neq LoginSuccess$  then
85:       let stop  $\langle \rangle$ 
86:     end if
87:     let  $PID_{RP} := s'.Parameters[PID_{RP}]$ 
88:     let  $Endpoint := s'.Parameters[Endpoint]$ 
89:     let  $Nonce := s'.Parameters[Nonce]$ 
90:     let  $Url := \langle URL, S, IdPDomain, /authorize,$ 
        $\langle \langle PID_{RP}, PID_{RP} \rangle, \langle Endpoint, Endpoint \rangle, \langle Nonce, Nonce \rangle \rangle \rangle$ 
91:     let  $s'.refXHR := Random()$ 
92:     let  $command := \langle XMLHTTPREQUEST, Url, GET, \langle \rangle, s'.refXHR \rangle$ 
93:     let  $s'.q := expectToken$ 
94:   end if
95: case expectToken:
96:   let  $pattern := \langle XMLHTTPREQUEST, Body, s'.refXHR \rangle$ 
97:   let  $input := CHOOSEINPUT(scriptinputs, pattern)$ 
98:   if  $input \neq null$  then
99:     let  $Token := input.Body[Token]$ 
100:    let  $RPOrigin := \langle s'.Parameters[Endpoint_{RP}], S \rangle$ 
101:    let  $command := \langle POSTMESSAGE, target, \langle Token, Token \rangle, RPOrigin \rangle$ 
102:    let  $s.q := stop$ 
103:   end if
104: end switch
105: let stop  $\langle s', cookies, localStorage, sessionStorage, command \rangle$ 

```

---

#### Algorithm 4 *script\_rp*

---

**Input:**  $\langle tree, docnonce, scriptstate, scriptinputs, cookies, localStorage, sessionStorage, ids, secret \rangle$

```

1: let  $s' := scriptstate$ 
2: let  $command := \langle \rangle$ 
3: let  $IdPWindow := SUBWINDOWS(tree, AUXWINDOW(tree, docnonce)).1.nonce$ 
4: let  $RPDomain := s'.Parameters[RPDomain]$ 
5: let  $IdPOrigin := \langle s'.Parameters[IdPDomain], S \rangle$ 
6: switch  $s'.q$  do
7:   case start:
8:     let  $Url := \langle URL, S, RPDomain, /login, \langle \rangle \rangle$ 
9:     let  $command := \langle IFRAME, Url, S ELF \rangle$ 
10:    let  $s'.q := expectN_U$ 
11:   case expect $N_U$ :
12:     let  $pattern := \langle POSTMESSAGE, *, Content, * \rangle$ 
13:     let  $input := CHOOSEINPUT(scriptinputs, pattern)$ 
14:     if  $input \neq null$  then
15:       let  $N_U := input.Content[N_U]$ 
16:       let  $Url := \langle URL, S, RPDomain, /startNegotiation, \langle \rangle \rangle$ 
17:       let  $s'.refXHR := Random()$ 
18:       let  $command := \langle XMLHTTPREQUEST, Url, POST, \langle \langle N_U, N_U \rangle \rangle, s'.refXHR \rangle$ 
19:       let  $s'.q := expectCert$ 
20:     end if
21:   case expectCert:

```

```

22:   let pattern := ⟨XMLHTTPREQUEST, Body, s'.refXHR⟩
23:   let input := CHOOSEINPUT(scriptinputs, pattern)
24:   if input ≠ null then
25:     let Cert := input.Content[Cert]
26:     let command := ⟨POSTMESSAGE, IdPWindow, ⟨⟨Cert, Cert⟩⟩, IdPOrigin⟩
27:     let s'.q := expectRegistrationResult
28:   end if
29: case expectRegistrationResult:
30:   let pattern := ⟨POSTMESSAGE, *, Content, *⟩
31:   let input := CHOOSEINPUT(scriptinputs, pattern)
32:   if input ≠ null then
33:     let RegistrationResult := input.Content[RegistrationResult]
34:     let Url := ⟨URL, S, RPDomain, /registrationResult, ⟨⟩⟩
35:     let s'.refXHR := Random()
36:     let command := ⟨XMLHTTPREQUEST, Url, POST, ⟨⟨RegistrationResult, RegistrationResult⟩⟩, s'.refXHR⟩
37:     let s'.q := expectTokenRequest
38:   end if
39: case expectTokenRequest:
40:   let pattern := ⟨XMLHTTPREQUEST, Body, s'.refXHR⟩
41:   let input := CHOOSEINPUT(scriptinputs, pattern)
42:   if input ≠ null then
43:     let PIDRP := input.Content.Body[PIDRP]
44:     let Endpoint := input.Content.Body[Endpoint]
45:     let Nonce := input.Content.Body[Nonce]
46:     let command := ⟨POSTMESSAGE, IdPWindow,
47:       ⟨⟨PIDRP, PIDRP⟩, ⟨Endpoint, Endpoint⟩, ⟨Nonce, Nonce⟩⟩, IdPOrigin⟩
48:     let s'.q := expectToken
49:   end if
50: case expectToken:
51:   let pattern := ⟨POSTMESSAGE, *, Content, *⟩
52:   let input := CHOOSEINPUT(scriptinputs, pattern)
53:   if input ≠ null then
54:     let Token := input.Content[Token]
55:     let Url := ⟨URL, S, RPDomain, /uploadToken, ⟨⟩⟩
56:     let s'.refXHR := Random()
57:     let command := ⟨XMLHTTPREQUEST, Url, POST, ⟨⟨Token, Token⟩⟩, s'.refXHR⟩
58:     let s'.q := expectLoginResult
59:   end if
60: case expectLoginResult:
61:   let pattern := ⟨XMLHTTPREQUEST, Body, s'.refXHR⟩
62:   let input := CHOOSEINPUT(scriptinputs, pattern)
63:   if input ≠ null then
64:     if input.Body ≡ LoginSuccess then
65:       let LoadHomepage()
66:     end if
67:   end if
68: end switch

```

---