



# PIZZA

## S A L E S   R E P O R T





# ABOUT PROJECT

The Pizza Sales Report project offers a comprehensive analysis of pizza sales data using SQL. Key features include calculating total orders, total revenue, and the contribution of each pizza type to overall sales. It identifies trends such as the most popular pizza size, top-selling pizza types, and the highest-priced pizza. Advanced insights include category-wise distribution, hourly order patterns, and cumulative revenue over time. The project also evaluates daily order averages and revenue-based rankings for pizza types within categories. This solution enables businesses to make data-driven decisions to optimize operations and maximize revenue.



RETRIEVE THE TOTAL NUMBER OF ORDERS PLACED

**SELECT**

`COUNT(order_id) AS total_orders`

**FROM**

`orders;`

Result Grid	
	<code>total_orders</code>
▶	21350

# CALCULATE THE TOTAL REVENUE GENERATED FROM PIZZA SALES.

```
SELECT  
    ROUND(SUM(order_details.quantity * pizzas.price),  
        2) AS total_revenue  
FROM  
    order_details  
    JOIN  
    pizzas ON pizzas.pizza_id = order_details.pizza_id
```

Result Grid	
	total_revenue
▶	817860.05





## IDENTIFY THE HIGHEST-PRICED PIZZA.

```
SELECT pizza_types.name, pizzas.price  
FROM pizza_types  
JOIN pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id  
ORDER BY pizzas.price DESC  
LIMIT 1;
```

Result Grid | Filter Row

	name	price
▶	The Greek Pizza	35.95

# IDENTIFY THE MOST COMMON PIZZA SIZE ORDERED.

```
SELECT
    pizzas.size,
    COUNT(order_details.order_details_id) AS order_count
FROM
    pizzas
    JOIN
        order_details ON pizzas.pizza_id = order_details.pizza_id
GROUP BY pizzas.size
ORDER BY order_count DESC;
```

	size	order_count
▶	L	18526
	M	15385
	S	14137
	XL	544
	XXL	28





# LIST THE TOP 5 MOST ORDERED PIZZA TYPES ALONG WITH THEIR QUANTITIES.

```
SELECT pizza_types.name, SUM(order_details.quantity) AS quantity
FROM pizza_types
JOIN pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
JOIN order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY quantity DESC
LIMIT 5;
```

Result Grid		
	name	quantity
▶	The Classic Deluxe Pizza	2453
	The Barbecue Chicken Pizza	2432
	The Hawaiian Pizza	2422
	The Pepperoni Pizza	2418
	The Thai Chicken Pizza	2371

JOIN THE NECESSARY TABLES TO FIND THE TOTAL QUANTITY OF EACH PIZZA CATEGORY ORDERED.

```
SELECT  
    pizza_types.category,  
    SUM(order_details.quantity) AS quantity  
FROM  
    pizza_types  
        JOIN  
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id  
        JOIN  
    order_details ON order_details.pizza_id = pizzas.pizza_id  
GROUP BY pizza_types.category  
ORDER BY quantity DESC;
```

	category	quantity
▶	Classic	14888
	Supreme	11987
	Veggie	11649
	Chicken	11050



# DETERMINE THE DISTRIBUTION OF ORDERS BY HOUR OF THE DAY.

SELECT

```
HOUR(order_time), COUNT(order_id) AS order_count
```

FROM

```
orders
```

```
GROUP BY HOUR(order_time);
```

Result Grid		Filter Rows:
	hour(order_time)	count(order_id)
▶	11	1231
	12	2520
	13	2455
	14	1472
	15	1468
	16	1920
	17	2336
	18	2399
	19	2009
	20	1642
	21	1198
	22	663
	23	28
	10	8
	9	1





JOIN RELEVANT TABLES TO FIND THE  
CATEGORY-WISE DISTRIBUTION OF PIZZAS.

```
SELECT  
    category, COUNT(name)  
FROM  
    pizza_types  
GROUP BY category;
```

Result Grid | Filter Rows

	category	count(name)
▶	Chicken	6
	Classic	8
	Supreme	9
	Veggie	9

GROUP THE ORDERS BY DATE AND CALCULATE THE AVERAGE NUMBER OF PIZZAS ORDERED PER DAY.

```
SELECT  
    ROUND(AVG(quantity), 0) as avg_pizza_ordered_per_day  
FROM  
(SELECT  
    orders.order_date, SUM(order_details.quantity) AS quantity  
FROM  
    orders  
JOIN order_details ON orders.order_id = order_details.order_id  
GROUP BY orders.order_date) AS order_quantity;
```

	Result Grid	 Filter Rows:
	avg_pizza_ordered_per_day	
▶	138	



# DETERMINE THE TOP 3 MOST ORDERED PIZZA TYPES BASED ON REVENUE.

```
SELECT
    pizza_types.name,
    SUM(order_details.quantity * pizzas.price) AS revenue
FROM
    pizza_types
        JOIN
    pizzas ON pizzas.pizza_type_id = pizza_types.pizza_type_id
        JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY revenue DESC
LIMIT 3;
```

	name	revenue
▶	The Thai Chicken Pizza	43434.25
	The Barbecue Chicken Pizza	42768
	The California Chicken Pizza	41409.5



# CALCULATE THE PERCENTAGE CONTRIBUTION OF EACH PIZZA TYPE TO TOTAL REVENUE.

```
SELECT
    pizza_types.category,
    ROUND(SUM(order_details.quantity * pizzas.price) / (SELECT
        ROUND(SUM(order_details.quantity * pizzas.price),
        2) AS total_revenue
    )
    FROM
        order_details
        JOIN
            pizzas ON pizzas.pizza_id = order_details.pizza_id) * 100,
    2) AS revenue
FROM
    pizza_types
    JOIN
        pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
        order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.category
ORDER BY revenue DESC;
```

	category	revenue
▶	Classic	26.91
	Supreme	25.46
	Chicken	23.96
	Veggie	23.68



# ANALYZE THE CUMULATIVE REVENUE GENERATED OVER TIME.

```
select order_date,  
sum(revenue) over(order by order_date) as cum_revenue  
from  
(select orders.order_date,  
sum(order_details.quantity * pizzas.price) as revenue  
from order_details join pizzas  
on order_details.pizza_id = pizzas.pizza_id  
join orders  
on orders.order_id = order_details.order_id  
group by orders.order_date) as sales;
```

	order_date	cum_revenue
▶	2015-01-01	2713.850000000004
	2015-01-02	5445.75
	2015-01-03	8108.15
	2015-01-04	9863.6
	2015-01-05	11929.55
	2015-01-06	14358.5
	2015-01-07	16560.7
	2015-01-08	19399.05
	2015-01-09	21526.4
	2015-01-10	23990.350000000002
	2015-01-11	25862.65



# DETERMINE THE TOP 3 MOST ORDERED PIZZA TYPES BASED ON REVENUE FOR EACH PIZZA CATEGORY.

```
select name, revenue from
(select category, name, revenue,
rank() over(partition by category order by revenue desc) as rn
from
(SELECT pizza_types.category, pizza_types.name,
sum((order_details.quantity)*pizzas.price) as revenue
from pizza_types join pizzas
on pizza_types.pizza_type_id = pizzas.pizza_type_id
join order_details
on order_details.pizza_id = pizzas.pizza_id
group by pizza_types.category, pizza_types.name) as a) as b
where rn <= 3;
```

	name	revenue
▶	The Thai Chicken Pizza	43434.25
	The Barbecue Chicken Pizza	42768
	The California Chicken Pizza	41409.5
	The Classic Deluxe Pizza	38180.5
	The Hawaiian Pizza	32273.25
	The Pepperoni Pizza	30161.75
	The Spicy Italian Pizza	34831.25
	The Italian Supreme Pizza	33476.75
	The Sicilian Pizza	30940.5
	The Four Cheese Pizza	32265.70000000065
	The Mexicana Pizza	26780.75



# PIZZA SALES REPORT

"Crafting efficient and scalable SQL solutions for data management."



MANU DEV CHHILLER

# THANK YOU

