

Anexo 4: Lista de los alias

Name	Definition
----	-----
%	ForEach-Object
?	Where-Object
ac	Add-Content
asnp	Add-PSSnapIn
cat	Get-Content
cd	Set-Location
chdir	Set-Location
clc	Clear-Content
clear	Clear-Host
clhy	Clear-History
cli	Clear-Item
clp	Clear-ItemProperty
cls	Clear-Host
clv	Clear-Variable
compare	Compare-Object
copy	Copy-Item
cp	Copy-Item
cpi	Copy-Item
cpp	Copy-ItemProperty
cvpa	Convert-Path
dbp	Disable-PSBreakpoint
del	Remove-Item
diff	Compare-Object
dir	Get-ChildItem
ebp	Enable-PSBreakpoint
echo	Write-Output
epal	Export-Alias
epcsv	Export-Csv
epsn	Export-PSSession
erase	Remove-Item
etsn	Enter-PSSession
exsn	Exit-PSSession
fc	Format-Custom
fl	Format-List
foreach	ForEach-Object
ft	Format-Table
fw	Format-Wide
gal	Get-Alias
gbp	Get-PSBreakpoint
gc	Get-Content
gci	Get-ChildItem
gcm	Get-Command
gcs	Get-PSCallStack
gdr	Get-PSDrive
ghy	Get-History
gi	Get-Item
gjb	Get-Job
gl	Get-Location
gm	Get-Member
gmo	Get-Module

gp	Get-ItemProperty
gps	Get-Process
group	Group-Object
gsn	Get-PSSession
gsnp	Get-PSSnapIn
gsv	Get-Service
gu	Get-Unique
gv	Get-Variable
gwmi	Get-WmiObject
h	Get-History
history	Get-History
icm	Invoke-Command
iex	Invoke-Expression
ihy	Invoke-History
ii	Invoke-Item
ipal	Import-Alias
ipcsv	Import-Csv
ipmo	Import-Module
ipsn	Import-PSSession
ise	powershell_ise.exe
iwmi	Invoke-WMIMethod
kill	Stop-Process
lp	Out-Printer
ls	Get-ChildItem
man	help
md	mkdir
measure	Measure-Object
mi	Move-Item
mount	New-PSDrive
move	Move-Item
mp	Move-ItemProperty
mv	Move-Item
nal	New-Alias
ndr	New-PSDrive
ni	New-Item
nmo	New-Module
nsn	New-PSSession
nv	New-Variable
ogv	Out-GridView
oh	Out-Host
popd	Pop-Location
ps	Get-Process
pushd	Push-Location
pwd	Get-Location
r	Invoke-History
rbp	Remove-PSBreakpoint
rcjb	Receive-Job
rd	Remove-Item
rdr	Remove-PSDrive
ren	Rename-Item
ri	Remove-Item
rjb	Remove-Job
rm	Remove-Item
rmdir	Remove-Item
rmo	Remove-Module

rni	Rename-Item
rn timer	Rename-ItemProperty
rp	Remove-ItemProperty
rsn	Remove-PSSession
rsnp	Remove-PSSnapin
rv	Remove-Variable
rvpa	Resolve-Path
rwmi	Remove-WMIObject
sajb	Start-Job
sal	Set-Alias
saps	Start-Process
sasv	Start-Service
sbp	Set-PSBreakpoint
sc	Set-Content
select	Select-Object
set	Set-Variable
si	Set-Item
sl	Set-Location
sleep	Start-Sleep
sort	Sort-Object
sp	Set-ItemProperty
spjb	Stop-Job
spps	Stop-Process
spsv	Stop-Service
start	Start-Process
sv	Set-Variable
swmi	Set-WMIInstance
tee	Tee-Object
type	Get-Content
where	Where-Object
wjb	Wait-Job
write	Write-Output