

The LWE problem from lattices to cryptography

Damien Stehlé

ENS de Lyon

Šibenik, June 2015



What is a good problem, for a cryptographer?

- Almost all of its instances must be **hard to solve**.
Attacks must be too expensive.
- Its instances must be **easy to sample**.
The algorithms run by honest users should be efficient.
- The problem must be (algebraically) **rich/expressive**.
So that interesting models of attacks can be handled,
even for advanced cryptographic functionalities.

What is a good problem, for a cryptographer?

- Almost all of its instances must be **hard to solve**.
Attacks must be too expensive.
- Its instances must be **easy to sample**.
The algorithms run by honest users should be efficient.
- The problem must be (algebraically) **rich/expressive**.
So that interesting models of attacks can be handled,
even for advanced cryptographic functionalities.

What is a good problem, for a cryptographer?

- Almost all of its instances must be **hard to solve**.
Attacks must be too expensive.
- Its instances must be **easy to sample**.
The algorithms run by honest users should be efficient.
- The problem must be (algebraically) **rich/expressive**.
So that interesting models of attacks can be handled,
even for advanced cryptographic functionalities.

What is a good problem, for a cryptographer?

- Almost all of its instances must be **hard to solve**.
Attacks must be too expensive.
- Its instances must be **easy to sample**.
The algorithms run by honest users should be efficient.
- The problem must be (algebraically) **rich/expressive**.
So that interesting models of attacks can be handled,
even for advanced cryptographic functionalities.

The Learning With Errors problem

Informal definition

Solve a random system of m noisy linear equations and n unknowns modulo an integer q , with $m \gg n$.

- The best known algorithms are exponential in $n \log q$.
- Sampling an instance costs $\mathcal{O}(mn \log q)$.
Very often, $m = \mathcal{O}(n \log q)$, so this is $\mathcal{O}((n \log q)^2)$.
- Very rich/expressive:
encryption [Re05], ID-based encr. [GePeVa08], fully homomorphic encr. [BrVa11], attribute-based encr. [GoVaWe13], etc.

The Learning With Errors problem

Informal definition

Solve a random system of m noisy linear equations and n unknowns modulo an integer q , with $m \gg n$.

- The best known algorithms are **exponential in $n \log q$** .
- Sampling an instance costs $\mathcal{O}(mn \log q)$.
Very often, $m = \mathcal{O}(n \log q)$, so this is $\mathcal{O}((n \log q)^2)$.
- Very rich/expressive:
encryption [Re05], ID-based encr. [GePeVa08], fully homomorphic encr. [BrVa11], attribute-based encr. [GoVaWe13], etc.

The Learning With Errors problem

Informal definition

Solve a random system of m noisy linear equations and n unknowns modulo an integer q , with $m \gg n$.

- The best known algorithms are **exponential in $n \log q$** .
- Sampling an instance costs $\mathcal{O}(mn \log q)$.
Very often, $m = \mathcal{O}(n \log q)$, so this is $\mathcal{O}((n \log q)^2)$.
- Very rich/expressive:
encryption [Re05], ID-based encr. [GePeVa08], fully homomorphic encr. [BrVa11], attribute-based encr. [GoVaWe13], etc.

Goals of this talk

- Introduce LWE.
- Show the relationship between LWE and lattices.
- Use LWE to design a public-key encryption scheme.
- Give some open problems.

Road-map

- Definition of the LWE problem
- Regev's encryption scheme
- Lattice problems
- Hardness of LWE
- Equivalent problems


Road-map

- **Definition of the LWE problem**
- Regev's encryption scheme
- Lattice problems
- Hardness of LWE
- Equivalent problems

Gaussian distributions

Continuous Gaussian of parameter s :


$$\left| \begin{array}{l} D_s(x) \sim \frac{1}{s} \exp\left(-\pi \frac{x^2}{s^2}\right) \\ \forall x \in \mathbb{R} \end{array} \right.$$



Gaussian distributions


Continuous Gaussian of parameter s :

$$\left| \begin{array}{l} D_s(x) \sim \frac{1}{s} \exp\left(-\pi \frac{x^2}{s^2}\right) \\ \forall x \in \mathbb{R} \end{array} \right.$$



Discrete Gaussian of support \mathbb{Z} and parameter s :


$$\left| \begin{array}{l} D_{\mathbb{Z},s}(x) \sim \frac{1}{s} \exp\left(-\pi \frac{x^2}{s^2}\right) \\ \forall x \in \mathbb{Z} \end{array} \right.$$



Gaussian distributions


Continuous Gaussian of parameter s :

$$\left| \begin{array}{l} D_s(x) \sim \frac{1}{s} \exp\left(-\pi \frac{x^2}{s^2}\right) \\ \forall x \in \mathbb{R} \end{array} \right.$$



Discrete Gaussian of support \mathbb{Z} and parameter s :

$$\left| \begin{array}{l} D_{\mathbb{Z},s}(x) \sim \frac{1}{s} \exp\left(-\pi \frac{x^2}{s^2}\right) \\ \forall x \in \mathbb{Z} \end{array} \right.$$



- That's not the rounding of a continuous Gaussian.
- One may efficiently sample from it.
- The usual tail bound holds.

The LWE problem [Re05]

Let $n \geq 1$, $q \geq 2$ and $\alpha \in (0, 1)$.

For all $\mathbf{s} \in \mathbb{Z}_q^n$, we define the distribution $D_{n,q,\alpha}(\mathbf{s})$:

$(\mathbf{a}, \langle \mathbf{a}, \mathbf{s} \rangle + e) \in \mathbb{Z}_q^n \times \mathbb{Z}_q$, with $\mathbf{a} \leftarrow U(\mathbb{Z}_q^n)$ and $e \leftarrow D_{\mathbb{Z},\alpha q}$.

Search LWE

For all \mathbf{s} : Given arbitrarily many samples from $D_{n,q,\alpha}(\mathbf{s})$, find \mathbf{s} .

(Information-theoretically, $\approx n \frac{\log q}{\log 1/\alpha}$ samples uniquely determine \mathbf{s} .)

Decision LWE

With non-negligible probability over $\mathbf{s} \leftarrow U(\mathbb{Z}_q^n)$:
distinguish between the distributions $D_{n,q,\alpha}(\mathbf{s})$ and $U(\mathbb{Z}_q^{n+1})$.

(Non-negligible: $1/(n \log q)^c$ for some constant $c > 0$.)

The LWE problem [Re05]

Let $n \geq 1$, $q \geq 2$ and $\alpha \in (0, 1)$.

For all $\mathbf{s} \in \mathbb{Z}_q^n$, we define the distribution $D_{n,q,\alpha}(\mathbf{s})$:

$(\mathbf{a}, \langle \mathbf{a}, \mathbf{s} \rangle + e) \in \mathbb{Z}_q^n \times \mathbb{Z}_q$, with $\mathbf{a} \leftarrow U(\mathbb{Z}_q^n)$ and $e \leftarrow D_{\mathbb{Z},\alpha q}$.

Search LWE

For all \mathbf{s} : Given arbitrarily many samples from $D_{n,q,\alpha}(\mathbf{s})$, find \mathbf{s} .

(Information-theoretically, $\approx n \frac{\log q}{\log 1/\alpha}$ samples uniquely determine \mathbf{s} .)

Decision LWE

With non-negligible probability over $\mathbf{s} \leftarrow U(\mathbb{Z}_q^n)$:
distinguish between the distributions $D_{n,q,\alpha}(\mathbf{s})$ and $U(\mathbb{Z}_q^{n+1})$.

(Non-negligible: $1/(n \log q)^c$ for some constant $c > 0$.)

The LWE problem [Re05]

Let $n \geq 1$, $q \geq 2$ and $\alpha \in (0, 1)$.

For all $\mathbf{s} \in \mathbb{Z}_q^n$, we define the distribution $D_{n,q,\alpha}(\mathbf{s})$:

$(\mathbf{a}, \langle \mathbf{a}, \mathbf{s} \rangle + e) \in \mathbb{Z}_q^n \times \mathbb{Z}_q$, with $\mathbf{a} \leftarrow U(\mathbb{Z}_q^n)$ and $e \leftarrow D_{\mathbb{Z},\alpha q}$.

Search LWE

For all \mathbf{s} : Given arbitrarily many samples from $D_{n,q,\alpha}(\mathbf{s})$, find \mathbf{s} .

(Information-theoretically, $\approx n \frac{\log q}{\log 1/\alpha}$ samples uniquely determine \mathbf{s} .)

Decision LWE

With non-negligible probability over $\mathbf{s} \leftarrow U(\mathbb{Z}_q^n)$:
distinguish between the distributions $D_{n,q,\alpha}(\mathbf{s})$ and $U(\mathbb{Z}_q^{n+1})$.

(Non-negligible: $1/(n \log q)^c$ for some constant $c > 0$.)

Decision LWE

Let $n \geq 1$, $q \geq 2$ and $\alpha \in (0, 1)$.

For all $\mathbf{s} \in \mathbb{Z}_q^n$, we define the distribution $D_{n,q,\alpha}(\mathbf{s})$:

$$(\mathbf{a}, \langle \mathbf{a}, \mathbf{s} \rangle + e), \text{ with } \mathbf{a} \leftarrow U(\mathbb{Z}_q^n) \text{ and } e \leftarrow D_{\mathbb{Z},\alpha q}.$$

Decision LWE

With non-negligible probability over $\mathbf{s} \leftarrow U(\mathbb{Z}_q^n)$:

distinguish between the distributions $D_{n,q,\alpha}(\mathbf{s})$ and $U(\mathbb{Z}_q^{n+1})$.

We are given an oracle \mathcal{O} that produces independent samples from always the same distribution, which is:

- either $D_{n,q,\alpha}(\mathbf{s})$ for a fixed \mathbf{s} ,
- or $U(\mathbb{Z}_q^{n+1})$.

We have to tell which, with probability $\geq \frac{1}{2} + \frac{1}{(n \log q)^{\Omega(1)}}$.


Search LWE \equiv solving noisy linear systems

Find $s_1, s_2, s_3, s_4, s_5 \in \mathbb{Z}_{23}$ such that:


$$\begin{array}{rcl} s_1 + 22s_2 + 17s_3 + 2s_4 + s_5 & \approx & 16 \pmod{23} \\ 3s_1 + 2s_2 + 11s_3 + 7s_4 + 8s_5 & \approx & 17 \pmod{23} \\ 15s_1 + 13s_2 + 10s_3 + s_4 + 22s_5 & \approx & 3 \pmod{23} \\ 17s_1 + 11s_2 + s_3 + 10s_4 + 3s_5 & \approx & 8 \pmod{23} \\ 2s_1 + s_2 + 13s_3 + 6s_4 + 2s_5 & \approx & 9 \pmod{23} \\ 4s_1 + 4s_2 + s_3 + 5s_4 + s_5 & \approx & 18 \pmod{23} \\ 11s_1 + 12s_2 + 5s_3 + s_4 + 9s_5 & \approx & 7 \pmod{23} \end{array}$$

We can even ask for arbitrarily many noisy equations.

Matrix version of LWE



- $A \leftarrow U(\mathbb{Z}_q^{m \times n})$,
- $s \leftarrow U(\mathbb{Z}_q^n)$,
- $e \leftarrow D_{\mathbb{Z}^m, \alpha q}$.



Discrete Gaussian error

Decision LWE:

Determine whether (A, b) is of the form above, or uniform.

Some simple remarks

- If $\alpha \approx 0$, LWE is easy to solve.
- If $\alpha \approx 1$, LWE is trivially hard.
- Very often, we are interested in

$$\alpha \approx \frac{1}{n^c}, \quad q \approx n^{c'}, \quad \text{for some constants } c' > c > 0.$$

- Why a discrete Gaussian noise?

Why is LWE interesting for crypto?

- LWE is just noisy linear algebra: Easy to use, expressive.
- LWE seems to be a (very) hard problem.

Two particularly useful properties:

- Unlimited number of samples.
- Random self-reducibility over \mathbf{s} .

If q is prime and $\leq n^{\mathcal{O}(1)}$, there are polynomial-time reductions between the Search and Decision versions of LWE [Re05].

(We may remove these assumptions, if we allow some polynomial blow-up on α .)

Why is LWE interesting for crypto?

- LWE is just noisy linear algebra: Easy to use, expressive.
- LWE seems to be a (very) hard problem.

Two particularly useful properties:

- Unlimited number of samples.
- Random self-reducibility over \mathbf{s} .

If q is prime and $\leq n^{\mathcal{O}(1)}$, there are polynomial-time reductions between the Search and Decision versions of LWE [Re05].

(We may remove these assumptions, if we allow some polynomial blow-up on α .)

Road-map

- Definition of the LWE problem
- **Regev's encryption scheme**
- Lattice problems
- Hardness of LWE
- Equivalent problems

Public-key encryption

A public-key encryption scheme over $\{0, 1\} \times \mathcal{C}$ consists in three algorithms:

- KEYGEN: Security parameter $\mapsto (pk, sk)$.
- ENC: $(pk, M) \mapsto C \in \mathcal{C}$.
- DEC: $(sk, C) \mapsto M' \in \{0, 1\}$.

Correctness

With probability ≈ 1 , $\forall M \in \{0, 1\} : \text{DEC}_{sk}(\text{ENC}_{pk}(M)) = M$.

Security (IND-CPA)

The distributions of $(pk, \text{ENC}_{pk}(0))$ and $(pk, \text{ENC}_{pk}(1))$ must be **computationally indistinguishable**.

Public-key encryption

A public-key encryption scheme over $\{0, 1\} \times \mathcal{C}$ consists in three algorithms:

- KEYGEN: Security parameter $\mapsto (pk, sk)$.
- ENC: $(pk, M) \mapsto C \in \mathcal{C}$.
- DEC: $(sk, C) \mapsto M' \in \{0, 1\}$.

Correctness

With probability ≈ 1 , $\forall M \in \{0, 1\} : \text{DEC}_{sk}(\text{ENC}_{pk}(M)) = M$.

Security (IND-CPA)

The distributions of $(pk, \text{ENC}_{pk}(0))$ and $(pk, \text{ENC}_{pk}(1))$ must be **computationally indistinguishable**.

Public-key encryption

A public-key encryption scheme over $\{0, 1\} \times \mathcal{C}$ consists in three algorithms:

- KEYGEN: Security parameter $\mapsto (pk, sk)$.
- ENC: $(pk, M) \mapsto C \in \mathcal{C}$.
- DEC: $(sk, C) \mapsto M' \in \{0, 1\}$.

Correctness

With probability ≈ 1 , $\forall M \in \{0, 1\} : \text{DEC}_{sk}(\text{ENC}_{pk}(M)) = M$.

Security (IND-CPA)

The distributions of $(pk, \text{ENC}_{pk}(0))$ and $(pk, \text{ENC}_{pk}(1))$ must be **computationally indistinguishable**.

Regev's encryption scheme

- **Parameters:** n, m, q, α .
- **Keys:** $sk = \mathbf{s}$ and $pk = (\mathbf{A}, \mathbf{b})$, with $\mathbf{b} = \mathbf{A}\mathbf{s} + \mathbf{e}$
- **ENC**($M \in \{0, 1\}$): Let $\mathbf{r} \leftarrow U(\{0, 1\}^m)$,

$$\mathbf{u}^T = \begin{matrix} \text{red box } \mathbf{r}^T \end{matrix} \begin{matrix} \text{blue box } \mathbf{A} \end{matrix}, \quad \mathbf{v} = \begin{matrix} \text{red box } \mathbf{r}^T \end{matrix} \begin{matrix} \text{blue box } \mathbf{b} \end{matrix} + \lfloor q/2 \rfloor \cdot M.$$

- **DEC**(\mathbf{u}, \mathbf{v}): Compute $\mathbf{v} - \mathbf{u}^T \mathbf{s}$ (modulo q).

$$\begin{matrix} \text{red box } \mathbf{r}^T \end{matrix} \left[\begin{matrix} \text{light blue box } \mathbf{A} \end{matrix} \begin{matrix} \text{green box } \mathbf{s} \end{matrix} + \begin{matrix} \text{red box } \mathbf{e} \end{matrix} \right] + \lfloor q/2 \rfloor \cdot M - \begin{matrix} \text{red box } \mathbf{r}^T \end{matrix} \begin{matrix} \text{light blue box } \mathbf{A} \end{matrix} \begin{matrix} \text{green box } \mathbf{s} \end{matrix} = \text{small} + \lfloor q/2 \rfloor \cdot M$$

If it's close to 0, output 0, else output 1.

Regev's encryption scheme

- **Parameters:** n, m, q, α .
- **Keys:** $sk = \mathbf{s}$ and $pk = (\mathbf{A}, \mathbf{b})$, with $\mathbf{b} = \mathbf{A} \mathbf{s} + \mathbf{e}$
- **ENC**($M \in \{0, 1\}$): Let $\mathbf{r} \leftarrow U(\{0, 1\}^m)$,

$$\mathbf{u}^T = \begin{matrix} \text{red box } \mathbf{r}^T \end{matrix} \begin{matrix} \text{blue box } \mathbf{A} \end{matrix}, \quad \mathbf{v} = \begin{matrix} \text{red box } \mathbf{r}^T \end{matrix} \begin{matrix} \text{blue box } \mathbf{b} \end{matrix} + \lfloor q/2 \rfloor \cdot M.$$

- **DEC**(\mathbf{u}, \mathbf{v}): Compute $\mathbf{v} - \mathbf{u}^T \mathbf{s}$ (modulo q).

$$\begin{matrix} \text{red box } \mathbf{r}^T \end{matrix} \left[\begin{matrix} \text{blue box } \mathbf{A} \end{matrix} \begin{matrix} \text{green box } \mathbf{s} \end{matrix} + \begin{matrix} \text{red box } \mathbf{e} \end{matrix} \right] + \lfloor q/2 \rfloor \cdot M - \begin{matrix} \text{red box } \mathbf{r}^T \end{matrix} \begin{matrix} \text{blue box } \mathbf{A} \end{matrix} \begin{matrix} \text{green box } \mathbf{s} \end{matrix} = \text{small} + \lfloor q/2 \rfloor \cdot M$$

If it's close to 0, output 0, else output 1.

Decryption correctness

Correctness

Assume that $\alpha \leq o(\frac{1}{\sqrt{m \log n}})$.

Then, with probability $\geq 1 - n^{-\omega(1)}$, it correctly decrypts.

We have

$$\mathbf{v} - \mathbf{u}^T \mathbf{s} = \mathbf{r}^T \mathbf{e} + \lfloor q/2 \rfloor M \pmod{q}.$$

As $\mathbf{e} \sim D_{\mathbb{Z}, \alpha q}^m$, we expect $\langle \mathbf{r}, \mathbf{e} \rangle$ to behave like $D_{\|\mathbf{r}\| \alpha q}$.

As $\|\mathbf{r}\| \leq \sqrt{m}$, we have $\|\mathbf{r}\| \alpha q \leq o(\frac{q}{\sqrt{\log n}})$, and
a sample from $D_{\|\mathbf{r}\| \alpha q}$ is $< q/8$ with probability $\geq 1 - n^{-\omega(1)}$.

Decryption correctness

Correctness

Assume that $\alpha \leq o(\frac{1}{\sqrt{m \log n}})$.

Then, with probability $\geq 1 - n^{-\omega(1)}$, it correctly decrypts.

We have

$$\mathbf{v} - \mathbf{u}^T \mathbf{s} = \mathbf{r}^T \mathbf{e} + \lfloor q/2 \rfloor M \pmod{q}.$$

As $\mathbf{e} \sim D_{\mathbb{Z}, \alpha q}^m$, we expect $\langle \mathbf{r}, \mathbf{e} \rangle$ to behave like $D_{\|\mathbf{r}\| \alpha q}$.

As $\|\mathbf{r}\| \leq \sqrt{m}$, we have $\|\mathbf{r}\| \alpha q \leq o(\frac{q}{\sqrt{\log n}})$, and
a sample from $D_{\|\mathbf{r}\| \alpha q}$ is $< q/8$ with probability $\geq 1 - n^{-\omega(1)}$.

\Rightarrow We know $\mathbf{r}^T \mathbf{e} + \lfloor q/2 \rfloor M$ over the integers.

Decryption correctness

Correctness

Assume that $\alpha \leq o(\frac{1}{\sqrt{m \log n}})$.

Then, with probability $\geq 1 - n^{-\omega(1)}$, it correctly decrypts.

We have

$$\mathbf{v} - \mathbf{u}^T \mathbf{s} = \mathbf{r}^T \mathbf{e} + \lfloor q/2 \rfloor M \pmod{q}.$$

As $\mathbf{e} \sim D_{\mathbb{Z}, \alpha q}^m$, we expect $\langle \mathbf{r}, \mathbf{e} \rangle$ to behave like $D_{\|\mathbf{r}\| \alpha q}$.

As $\|\mathbf{r}\| \leq \sqrt{m}$, we have $\|\mathbf{r}\| \alpha q \leq o(\frac{q}{\sqrt{\log n}})$, and
a sample from $D_{\|\mathbf{r}\| \alpha q}$ is $< q/8$ with probability $\geq 1 - n^{-\omega(1)}$.

\Rightarrow We know $\mathbf{r}^T \mathbf{e} + \lfloor q/2 \rfloor M$ over the integers.

Decryption correctness

Correctness

Assume that $\alpha \leq o(\frac{1}{\sqrt{m \log n}})$.

Then, with probability $\geq 1 - n^{-\omega(1)}$, it correctly decrypts.

We have

$$\mathbf{v} - \mathbf{u}^T \mathbf{s} = \mathbf{r}^T \mathbf{e} + \lfloor q/2 \rfloor M \pmod{q}.$$

As $\mathbf{e} \sim D_{\mathbb{Z}, \alpha q}^m$, we expect $\langle \mathbf{r}, \mathbf{e} \rangle$ to behave like $D_{\|\mathbf{r}\| \alpha q}$.

As $\|\mathbf{r}\| \leq \sqrt{m}$, we have $\|\mathbf{r}\| \alpha q \leq o(\frac{q}{\sqrt{\log n}})$, and
a sample from $D_{\|\mathbf{r}\| \alpha q}$ is $< q/8$ with probability $\geq 1 - n^{-\omega(1)}$.

\Rightarrow We know $\mathbf{r}^T \mathbf{e} + \lfloor q/2 \rfloor M$ over the integers.

IND-CPA Security

Security

Assume that $m = \Omega(n \log q)$. Then any (IND-CPA) attacker may be turned into an algorithm for $\text{LWE}_{n,q,\alpha}$.

Fake security experiment

Challenger uses and gives to the attacker a uniform pair (\mathbf{A}, \mathbf{b}) (instead of $\mathbf{b} = \mathbf{A} \cdot \mathbf{s} + \mathbf{e}$).

- ⊙ If attacker behaves differently than in real security experiment, it can be used to solve LWE.

Given this experiment, for any $\epsilon, \delta > 0$ there exists, under the LWE assumption, a challenger \mathcal{C} such that for any PPT attacker \mathcal{A} we have

IND-CPA Security

Security

Assume that $m = \Omega(n \log q)$. Then any (IND-CPA) attacker may be turned into an algorithm for $\text{LWE}_{n,q,\alpha}$.

Fake security experiment

Challenger uses and gives to the attacker a uniform pair (\mathbf{A}, \mathbf{b}) (instead of $\mathbf{b} = \mathbf{A} \cdot \mathbf{s} + \mathbf{e}$).

- 1 If attacker behaves differently than in real security experiment, it can be used to solve LWE.
- 2 In fake experiment, $(\mathbf{A}, \mathbf{b}, \mathbf{r}^T \mathbf{A}, \mathbf{r}^T \mathbf{b})$ is \approx uniform, hence $\text{ENC}(0)$ and $\text{ENC}(1)$ follow (\approx) the same distribution.

IND-CPA Security

Security

Assume that $m = \Omega(n \log q)$. Then any (IND-CPA) attacker may be turned into an algorithm for $\text{LWE}_{n,q,\alpha}$.

Fake security experiment

Challenger uses and gives to the attacker a uniform pair (\mathbf{A}, \mathbf{b}) (instead of $\mathbf{b} = \mathbf{A} \cdot \mathbf{s} + \mathbf{e}$).

- 1 If attacker behaves differently than in real security experiment, it can be used to solve LWE.
- 2 In fake experiment, $(\mathbf{A}, \mathbf{b}, \mathbf{r}^T \mathbf{A}, \mathbf{r}^T \mathbf{b})$ is \approx uniform, hence $\text{ENC}(0)$ and $\text{ENC}(1)$ follow (\approx) the same distribution.

IND-CPA Security

Security

Assume that $m = \Omega(n \log q)$. Then any (IND-CPA) attacker may be turned into an algorithm for $\text{LWE}_{n,q,\alpha}$.

Fake security experiment

Challenger uses and gives to the attacker a uniform pair (\mathbf{A}, \mathbf{b}) (instead of $\mathbf{b} = \mathbf{A} \cdot \mathbf{s} + \mathbf{e}$).

- 1 If attacker behaves differently than in real security experiment, it can be used to solve LWE.
- 2 In fake experiment, $(\mathbf{A}, \mathbf{b}, \mathbf{r}^T \mathbf{A}, \mathbf{r}^T \mathbf{b})$ is \approx uniform, hence $\text{ENC}(0)$ and $\text{ENC}(1)$ follow (\approx) the same distribution.

Setting the parameters: n, m, α, q

- Correctness: $\alpha \leq o\left(\frac{1}{\sqrt{m \log n}}\right)$
- Reducing LWE to IND-CPA security: $m \geq \Omega(n \log q)$
- ① Set α as large as possible (α impacts security)
- ② Set m as small as possible (m impacts efficiency)
- ③ Set n and q so that $\text{LWE}_{n,q,\alpha}$ is sufficiently hard to solve

Here: $\alpha = \tilde{\Theta}(\sqrt{n})$, $m = \tilde{\Theta}(n)$ and $q = \tilde{\Theta}(n)$.

This is not very practical... ciphertext expansion: $\tilde{\Theta}(n)$.

Setting the parameters: n, m, α, q

- Correctness: $\alpha \leq o\left(\frac{1}{\sqrt{m \log n}}\right)$
- Reducing LWE to IND-CPA security: $m \geq \Omega(n \log q)$
- ① Set α as large as possible (α impacts security)
- ② Set m as small as possible (m impacts efficiency)
- ③ Set n and q so that $\text{LWE}_{n,q,\alpha}$ is sufficiently hard to solve

Here: $\alpha = \tilde{\Theta}(\sqrt{n})$, $m = \tilde{\Theta}(n)$ and $q = \tilde{\Theta}(n)$.

This is not very practical... ciphertext expansion: $\tilde{\Theta}(n)$.

Setting the parameters: n, m, α, q

- Correctness: $\alpha \leq o\left(\frac{1}{\sqrt{m \log n}}\right)$
- Reducing LWE to IND-CPA security: $m \geq \Omega(n \log q)$
- ❶ Set α as large as possible (α impacts security)
- ❷ Set m as small as possible (m impacts efficiency)
- ❸ Set n and q so that $\text{LWE}_{n,q,\alpha}$ is sufficiently hard to solve

Here: $\alpha = \tilde{\Theta}(\sqrt{n})$, $m = \tilde{\Theta}(n)$ and $q = \tilde{\Theta}(n)$.

This is not very practical... ciphertext expansion: $\tilde{\Theta}(n)$.

Multi-bit Regev

- **Parameters:** n, m, q, α, ℓ .
- **Keys:** $\text{sk} = \mathbf{S} \in \mathbb{Z}_q^{n \times \ell}$ and $\text{pk} = (\mathbf{A}, \mathbf{B})$, with
 $\mathbf{B} = \mathbf{A}\mathbf{S} + \mathbf{E}$
- **ENC**($\mathbf{M} \in \{0, 1\}^\ell$): Let $\mathbf{r} \leftarrow U(\{0, 1\}^m)$,

$$\mathbf{u}^T = \overbrace{\mathbf{r}^T}^{\text{red box}}, \quad \mathbf{A} \quad \text{,} \quad \mathbf{v}^T = \overbrace{\mathbf{r}^T}^{\text{red box}}, \quad \mathbf{B} + \lfloor q/2 \rfloor \cdot \mathbf{M}^T.$$

- **DEC**(\mathbf{u}, \mathbf{v}): Compute $\mathbf{v}^T - \mathbf{u}^T \mathbf{S}$ (modulo q).

Asymptotic performance, for $\ell = n$

- Ciphertext expansion: $\tilde{\Theta}(1)$
- Processing time: $\tilde{\Theta}(n)$ per message bit
- Key size: $\tilde{\Theta}(n^2)$

Multi-bit Regev

- **Parameters:** n, m, q, α, ℓ .
- **Keys:** $\text{sk} = \mathbf{S} \in \mathbb{Z}_q^{n \times \ell}$ and $\text{pk} = (\mathbf{A}, \mathbf{B})$, with
 $\mathbf{B} = \mathbf{A}\mathbf{S} + \mathbf{E}$
- **ENC**($\mathbf{M} \in \{0, 1\}^\ell$): Let $\mathbf{r} \leftarrow U(\{0, 1\}^m)$,

$$\mathbf{u}^T = \overbrace{\mathbf{r}^T}^{\text{red box}}, \quad \mathbf{A} \quad \overbrace{\mathbf{r}^T}^{\text{red box}}, \quad \mathbf{B} + \lfloor q/2 \rfloor \cdot \mathbf{M}^T.$$

- **DEC**(\mathbf{u}, \mathbf{v}): Compute $\mathbf{v}^T - \mathbf{u}^T \mathbf{S}$ (modulo q).

Asymptotic performance, for $\ell = n$

- Ciphertext expansion: $\tilde{\Theta}(1)$
- Processing time: $\tilde{\Theta}(n)$ per message bit
- Key size: $\tilde{\Theta}(n^2)$

More on Regev's encryption

- This scheme is homomorphic for addition: add ciphertexts
- And also for multiplication: tensor ciphertexts

⇒ Can be turned into FHE [Br12]

- Enc and KeyGen may be swapped: dual-Regev [GePeVa08]

⇒ This allows ID-based encryption, and more

May be turned into a practical scheme [Pe14]

- Use Ring-LWE rather than LWE: more efficient
- Ciphertext expansion can be lowered to essentially 1
- IND-CCA security can be achieved efficiently in the ROM

More on Regev's encryption

- This scheme is homomorphic for addition: add ciphertexts
 - And also for multiplication: tensor ciphertexts
- ⇒ Can be turned into FHE [Br12]
- Enc and KeyGen may be swapped: dual-Regev [GePeVa08]
- ⇒ This allows ID-based encryption, and more
- May be turned into a practical scheme [Pe14]
- Use Ring-LWE rather than LWE: more efficient
 - Ciphertext expansion can be lowered to essentially 1
 - IND-CCA security can be achieved efficiently in the ROM

More on Regev's encryption

- This scheme is homomorphic for addition: add ciphertexts
- And also for multiplication: tensor ciphertexts

⇒ Can be turned into FHE [Br12]

- Enc and KeyGen may be swapped: dual-Regev [GePeVa08]

⇒ This allows ID-based encryption, and more

May be turned into a practical scheme [Pe14]

- Use Ring-LWE rather than LWE: more efficient
- Ciphertext expansion can be lowered to essentially 1
- IND-CCA security can be achieved efficiently in the ROM

Road-map

- Definition of the LWE problem
- Regev's encryption scheme
- **Lattice problems**
- Hardness of LWE
- Equivalent problems

Euclidean lattices


Lattice $L = \sum_{i=1}^n \mathbb{Z}\mathbf{b}_i \subset \mathbb{R}^n$,

for some linearly indep. \mathbf{b}_i 's.

Minimum $\lambda(L) = \min (\|\mathbf{b}\| : \mathbf{b} \in L \setminus \mathbf{0})$.

SVP_γ : Given as input a basis of L ,
find $\mathbf{b} \in L$ s.t. $0 < \|\mathbf{b}\| \leq \gamma \cdot \lambda(L)$.

BDD_γ : Given as input a basis of L , and
a vector \mathbf{t} s.t. $\text{dist}(\mathbf{t}, L) < \frac{1}{2\gamma} \cdot \lambda(L)$,
find $\mathbf{b} \in L$ minimizing $\|\mathbf{b} - \mathbf{t}\|$.



Euclidean lattices


Lattice $L = \sum_{i=1}^n \mathbb{Z}\mathbf{b}_i \subset \mathbb{R}^n$,

for some linearly indep. \mathbf{b}_i 's.

Minimum $\lambda(L) = \min (\|\mathbf{b}\| : \mathbf{b} \in L \setminus \mathbf{0})$.

SVP _{γ} : Given as input a basis of L ,
find $\mathbf{b} \in L$ s.t. $0 < \|\mathbf{b}\| \leq \gamma \cdot \lambda(L)$.

BDD _{γ} : Given as input a basis of L , and
a vector \mathbf{t} s.t. $\text{dist}(\mathbf{t}, L) < \frac{1}{2\gamma} \cdot \lambda(L)$,
find $\mathbf{b} \in L$ minimizing $\|\mathbf{b} - \mathbf{t}\|$.



Euclidean lattices


Lattice $L = \sum_{i=1}^n \mathbb{Z}\mathbf{b}_i \subset \mathbb{R}^n$,

for some linearly indep. \mathbf{b}_i 's.

Minimum $\lambda(L) = \min (\|\mathbf{b}\| : \mathbf{b} \in L \setminus \mathbf{0})$.

SVP _{γ} : Given as input a basis of L ,
find $\mathbf{b} \in L$ s.t. $0 < \|\mathbf{b}\| \leq \gamma \cdot \lambda(L)$.

BDD _{γ} : Given as input a basis of L , and
a vector \mathbf{t} s.t. $\text{dist}(\mathbf{t}, L) < \frac{1}{2\gamma} \cdot \lambda(L)$,
find $\mathbf{b} \in L$ minimizing $\|\mathbf{b} - \mathbf{t}\|$.



Best known (classical/quantum) algorithms

SVP $_{\gamma}$: Given L , find $\mathbf{b} \in L$ s.t. $0 < \|\mathbf{b}\| \leq \gamma \cdot \lambda(L)$.

BDD $_{\gamma}$: Given L and $\mathbf{t} \in \mathbb{R}^n$ s.t. $\text{dist}(\mathbf{t}, L) < \frac{1}{2\gamma} \cdot \lambda(L)$,
find $\mathbf{b} \in L$ minimizing $\|\mathbf{b} - \mathbf{t}\|$.

For small γ : [AgDaReSD15]

- Time $2^{n/2}$.
- In practice: up to $n \approx 120$ (with other algorithms).

For $\gamma = n^{\Omega(1)}$: BKZ [ScEu91, HaPuSt11]

- Time $(\frac{n}{\log \gamma})^{\mathcal{O}(\frac{n}{\log \gamma})}$.
- In practice, we can reach $\gamma \approx 1.01^n$ [ChNg11].

<https://github.com/dstehle/fplll>

Best known (classical/quantum) algorithms

SVP $_{\gamma}$: Given L , find $\mathbf{b} \in L$ s.t. $0 < \|\mathbf{b}\| \leq \gamma \cdot \lambda(L)$.

BDD $_{\gamma}$: Given L and $\mathbf{t} \in \mathbb{R}^n$ s.t. $\text{dist}(\mathbf{t}, L) < \frac{1}{2\gamma} \cdot \lambda(L)$,
find $\mathbf{b} \in L$ minimizing $\|\mathbf{b} - \mathbf{t}\|$.

For small γ : [AgDaReSD15]

- Time $2^{n/2}$.
- In practice: up to $n \approx 120$ (with other algorithms).

For $\gamma = n^{\Omega(1)}$: BKZ [ScEu91, HaPuSt11]

- Time $\left(\frac{n}{\log \gamma}\right)^{\mathcal{O}\left(\frac{n}{\log \gamma}\right)}$.
- In practice, we can reach $\gamma \approx 1.01^n$ [ChNg11].

<https://github.com/dstehle/fplll>

Best known (classical/quantum) algorithms

SVP $_{\gamma}$: Given L , find $\mathbf{b} \in L$ s.t. $0 < \|\mathbf{b}\| \leq \gamma \cdot \lambda(L)$.

BDD $_{\gamma}$: Given L and $\mathbf{t} \in \mathbb{R}^n$ s.t. $\text{dist}(\mathbf{t}, L) < \frac{1}{2\gamma} \cdot \lambda(L)$,
find $\mathbf{b} \in L$ minimizing $\|\mathbf{b} - \mathbf{t}\|$.

For small γ : [AgDaReSD15]

- Time $2^{n/2}$.
- In practice: up to $n \approx 120$ (with other algorithms).

For $\gamma = n^{\Omega(1)}$: BKZ [ScEu91, HaPuSt11]

- Time $(\frac{n}{\log \gamma})^{\mathcal{O}(\frac{n}{\log \gamma})}$.
- In practice, we can reach $\gamma \approx 1.01^n$ [ChNg11].

<https://github.com/dstehle/fplll>

Hardness of SVP

GapSVP $_{\gamma}$

Given a basis of a lattice L and $d > 0$, assess whether

$$\lambda(L) \leq d \quad \text{or} \quad \lambda(L) > \gamma \cdot d.$$

- **NP-hard** when $\gamma \leq \mathcal{O}(1)$ (random. red.) [Aj98, HaRe07]
- **In NP \cap coNP** when $\gamma \geq \sqrt{n}$ [GoGo98, AhRe04]
- **In P** when $\gamma \geq \exp\left(n \cdot \frac{\log \log n}{\log n}\right)$ (BKZ)

Hardness of SVP

GapSVP $_{\gamma}$

Given a basis of a lattice L and $d > 0$, assess whether

$$\lambda(L) \leq d \quad \text{or} \quad \lambda(L) > \gamma \cdot d.$$

- **NP-hard** when $\gamma \leq \mathcal{O}(1)$ (random. red.) [Aj98, HaRe07]
- **In NP \cap coNP** when $\gamma \geq \sqrt{n}$ [GoGo98, AhRe04]
- **In P** when $\gamma \geq \exp\left(n \cdot \frac{\log \log n}{\log n}\right)$ (BKZ)

Road-map

- Definition of the LWE problem
- Regev's encryption scheme
- Lattice problems
- **Hardness of LWE**
- Equivalent problems

Each LWE sample gives $\approx \log_2 \frac{1}{\alpha}$ bits of data on secret \mathbf{s} .

With a few samples, \mathbf{s} is uniquely specified. How to find it?

Exhaustive search

Assume we are given \mathbf{A} and $\mathbf{b} = \mathbf{A}\mathbf{s} + \mathbf{e}$, for some \mathbf{e} whose entries are $\approx \alpha q$.
We want to find \mathbf{s} .

1st variant:

- Try all the possible $\mathbf{s} \in \mathbb{Z}_q^n$.
 - Test if $\mathbf{b} - \mathbf{A} \cdot \mathbf{s}$ is small.
- \Rightarrow Cost $\approx q^n$.

2nd variant:

- Try all the possible n first error terms.
 - Recover the corresponding \mathbf{s} , by linear algebra.
 - Test if $\mathbf{b} - \mathbf{A} \cdot \mathbf{s}$ is small.
- \Rightarrow Cost $\approx (\alpha q \sqrt{\log n})^n$.

Exhaustive search

Assume we are given \mathbf{A} and $\mathbf{b} = \mathbf{A}\mathbf{s} + \mathbf{e}$, for some \mathbf{e} whose entries are $\approx \alpha q$.
We want to find \mathbf{s} .

1st variant:

- Try all the possible $\mathbf{s} \in \mathbb{Z}_q^n$.
- Test if $\mathbf{b} - \mathbf{A} \cdot \mathbf{s}$ is small.

\Rightarrow Cost $\approx q^n$.

2nd variant:

- Try all the possible n first error terms.
- Recover the corresponding \mathbf{s} , by linear algebra.
- Test if $\mathbf{b} - \mathbf{A} \cdot \mathbf{s}$ is small.

\Rightarrow Cost $\approx (\alpha q \sqrt{\log n})^n$.

Solving LWE with BKZ (1/2)

Assume we are given \mathbf{A} and $\mathbf{b} = \mathbf{A}\mathbf{s} + \mathbf{e}$, for some \mathbf{e} whose entries are $\approx \alpha q$.
We want to find \mathbf{s} .

Let $L_{\mathbf{A}} = \{\mathbf{x} \in \mathbb{Z}^m : \exists \mathbf{s} \in \mathbb{Z}^n, \mathbf{x} = \mathbf{A}\mathbf{s} [q]\} = \mathbf{A}\mathbb{Z}_q^n + q\mathbb{Z}^m$.

- $L_{\mathbf{A}}$ is a lattice of **dimension** m .
- Whp, its **minimum** satisfies $\lambda(L) \approx \sqrt{m} \cdot q^{1-\frac{n}{m}}$.
- We have $\text{dist}(\mathbf{b}, L) = \|\mathbf{e}\| \approx \sqrt{m}\alpha q$.

LWE reduces to BDD

This is a BDD instance in $\dim m$ with $\gamma \approx q^{-\frac{n}{m}}/\alpha$.

Solving LWE with BKZ (1/2)

Assume we are given \mathbf{A} and $\mathbf{b} = \mathbf{A}\mathbf{s} + \mathbf{e}$, for some \mathbf{e} whose entries are $\approx \alpha q$.
We want to find \mathbf{s} .

Let $L_{\mathbf{A}} = \{\mathbf{x} \in \mathbb{Z}^m : \exists \mathbf{s} \in \mathbb{Z}^n, \mathbf{x} = \mathbf{A}\mathbf{s} [q]\} = \mathbf{A}\mathbb{Z}_q^n + q\mathbb{Z}^m$.

- $L_{\mathbf{A}}$ is a lattice of **dimension** m .
- Whp, its **minimum** satisfies $\lambda(L) \approx \sqrt{m} \cdot q^{1-\frac{n}{m}}$.
- We have $\text{dist}(\mathbf{b}, L) = \|\mathbf{e}\| \approx \sqrt{m}\alpha q$.

LWE reduces to BDD

This is a BDD instance in $\dim m$ with $\gamma \approx q^{-\frac{n}{m}}/\alpha$.

Solving LWE with BKZ (1/2)

Assume we are given \mathbf{A} and $\mathbf{b} = \mathbf{A}\mathbf{s} + \mathbf{e}$, for some \mathbf{e} whose entries are $\approx \alpha q$.
We want to find \mathbf{s} .

Let $L_{\mathbf{A}} = \{\mathbf{x} \in \mathbb{Z}^m : \exists \mathbf{s} \in \mathbb{Z}^n, \mathbf{x} = \mathbf{A}\mathbf{s} [q]\} = \mathbf{A}\mathbb{Z}_q^n + q\mathbb{Z}^m$.

- $L_{\mathbf{A}}$ is a lattice of **dimension** m .
- Whp, its **minimum** satisfies $\lambda(L) \approx \sqrt{m} \cdot q^{1 - \frac{n}{m}}$.
- We have $\text{dist}(\mathbf{b}, L) = \|\mathbf{e}\| \approx \sqrt{m}\alpha q$.

LWE reduces to BDD

This is a BDD instance in $\dim m$ with $\gamma \approx q^{-\frac{n}{m}}/\alpha$.

Solving LWE with BKZ (1/2)

Assume we are given \mathbf{A} and $\mathbf{b} = \mathbf{A}\mathbf{s} + \mathbf{e}$, for some \mathbf{e} whose entries are $\approx \alpha q$.
We want to find \mathbf{s} .

Let $L_{\mathbf{A}} = \{\mathbf{x} \in \mathbb{Z}^m : \exists \mathbf{s} \in \mathbb{Z}^n, \mathbf{x} = \mathbf{A}\mathbf{s} [q]\} = \mathbf{A}\mathbb{Z}_q^n + q\mathbb{Z}^m$.

- $L_{\mathbf{A}}$ is a lattice of **dimension** m .
- Whp, its **minimum** satisfies $\lambda(L) \approx \sqrt{m} \cdot q^{1 - \frac{n}{m}}$.
- We have $\text{dist}(\mathbf{b}, L) = \|\mathbf{e}\| \approx \sqrt{m}\alpha q$.

LWE reduces to BDD

This is a BDD instance in $\dim m$ with $\gamma \approx q^{-\frac{n}{m}}/\alpha$.

Solving LWE with BKZ (2/2)

LWE reduces to BDD

This is a BDD instance in dim m with $\gamma \approx q^{-\frac{n}{m}}/\alpha$.

Cost of BKZ: $(\frac{m}{\log \gamma})^{\mathcal{O}(\frac{m}{\log \gamma})}$, with $\frac{\log \gamma}{m} = \frac{1}{m} \log \frac{1}{\alpha} - \frac{n \log q}{m^2}$.

Cost is minimized for $m \approx \frac{2n \log q}{\log \frac{1}{\alpha}}$.

Cost of BKZ to solve LWE

$$\text{Time: } \left(\frac{n \log q}{\log^2 \alpha} \right)^{\mathcal{O}\left(\frac{n \log q}{\log^2 \alpha}\right)}.$$

Solving LWE with BKZ (2/2)

LWE reduces to BDD

This is a BDD instance in dim m with $\gamma \approx q^{-\frac{n}{m}}/\alpha$.

Cost of BKZ: $(\frac{m}{\log \gamma})^{\mathcal{O}(\frac{m}{\log \gamma})}$, with $\frac{\log \gamma}{m} = \frac{1}{m} \log \frac{1}{\alpha} - \frac{n \log q}{m^2}$.

Cost is minimized for $m \approx \frac{2n \log q}{\log \frac{1}{\alpha}}$.

Cost of BKZ to solve LWE

$$\text{Time: } \left(\frac{n \log q}{\log^2 \alpha} \right)^{\mathcal{O}(\frac{n \log q}{\log^2 \alpha})}.$$

Hardness results on LWE

Assume that $\alpha q \geq 2\sqrt{n}$.

[Re05]

If q is prime and $\leq n^{\mathcal{O}(1)}$, then there exists a **quantum** polynomial-time reduction from **SVP** $_{\gamma}$ in **dim** n to $\text{LWE}_{n,q,\alpha}$, with $\gamma \approx n/\alpha$.

[BrLaPeReSt13]

If q is $\leq n^{\mathcal{O}(1)}$, then there exists a **classical** polynomial-time reduction from **GapSVP** $_{\gamma}$ in **dim** \sqrt{n} to $\text{LWE}_{n,q,\alpha}$, with $\gamma \approx n/\alpha$.

- The two results are incomparable.
- Best achievable γ here: n .
- In the case of Regev's encryption, we get $\gamma \approx n^{3/2}$.
- One can use BDD_{γ} instead (with a different γ).

Hardness results on LWE

Assume that $\alpha q \geq 2\sqrt{n}$.

[Re05]

If q is prime and $\leq n^{\mathcal{O}(1)}$, then there exists a **quantum** polynomial-time reduction from **SVP** $_{\gamma}$ in **dim** n to $\text{LWE}_{n,q,\alpha}$, with $\gamma \approx n/\alpha$.

[BrLaPeReSt13]

If q is $\leq n^{\mathcal{O}(1)}$, then there exists a **classical** polynomial-time reduction from **GapSVP** $_{\gamma}$ in **dim** \sqrt{n} to $\text{LWE}_{n,q,\alpha}$, with $\gamma \approx n/\alpha$.

- The two results are incomparable.
- Best achievable γ here: n .
- In the case of Regev's encryption, we get $\gamma \approx n^{3/2}$.
- One can use BDD_{γ} instead (with a different γ).

Hardness results on LWE

Assume that $\alpha q \geq 2\sqrt{n}$.

[Re05]

If q is prime and $\leq n^{\mathcal{O}(1)}$, then there exists a **quantum** polynomial-time reduction from **SVP** $_{\gamma}$ in **dim** n to $\text{LWE}_{n,q,\alpha}$, with $\gamma \approx n/\alpha$.

[BrLaPeReSt13]

If q is $\leq n^{\mathcal{O}(1)}$, then there exists a **classical** polynomial-time reduction from **GapSVP** $_{\gamma}$ in **dim** \sqrt{n} to $\text{LWE}_{n,q,\alpha}$, with $\gamma \approx n/\alpha$.

- The two results are incomparable.
- Best achievable γ here: n .
- In the case of Regev's encryption, we get $\gamma \approx n^{3/2}$.
- One can use BDD_{γ} instead (with a different γ).

Road-map

- Definition of the LWE problem
- Regev's encryption scheme
- Lattice problems
- Hardness of LWE
- **Equivalent problems**

LWE variants

Numerous variants have been showed to be at least as hard as LWE, up to polynomial factors in the noise rate α :

(Polynomial in n , $\log q$ and possibly in the number of samples m .)

- When \mathbf{s} is distributed from the error distribution.
- When \mathbf{s} is binary with sufficient entropy.
- When \mathbf{e} is uniform in a hypercube.
- When \mathbf{e} corresponds to a deterministic rounding of $\mathbf{A}\mathbf{s}$.
- When \mathbf{A} is binary (modulo q).
- When some extra information on \mathbf{e} is provided.
- When the first component of \mathbf{e} is zero.

LWE in dimension 1

1-dimensional LWE [BoVe96]

With non-negl. prob. over $s \leftarrow U(\mathbb{Z}_q)$: distinguish between

$$(a, a \cdot s + e) \text{ and } (a, b) \quad (\text{over } \mathbb{Z}_q^2),$$

where $a, b \leftarrow U(\mathbb{Z}_q)$, $e \leftarrow D_{\mathbb{Z}, \alpha q}$.

Hardness of 1-dim LWE [BrLaPeReSt13]

For any n, q, n', q' with $n \log q \leq n' \log q'$:
there exists a polynomial-time reduction from $\text{LWE}_{n,q,\alpha}$ to
 $\text{LWE}_{n',q',\alpha'}$ for some $\alpha' \leq \alpha \cdot (n \log q)^{O(1)}$.

$\Rightarrow \text{LWE}_{1,q^n}$ is no easier than $\text{LWE}_{n,q}$.

Approximate gcd

$\text{AGCD}_{\mathcal{D}, N, \alpha}$ [HG01]

With non-negl. prob. over $p \leftarrow \mathcal{D}$, distinguish between

$$u \text{ and } q \cdot p + r \quad (\text{over } \mathbb{Z}),$$

where $u \leftarrow U([0, N])$, $q \leftarrow U([0, \frac{N}{p}])$, $r \leftarrow [D_{\alpha p}]$.

Hardness of AD (Informal) [ChSt15]

$\text{AGCD}_{\mathcal{D}, N, \alpha}$ is computationally equivalent to $\text{LWE}_{n, q, \alpha}$, for some \mathcal{D} of mean $\approx q^n$ and some $N \approx q^{2n}$.

Conclusion

LWE:

- LWE is hard for almost all instances.
- It seems exponentially hard to solve, even quantumly.
- It is a rich/expressive problem, convenient for cryptographic design.

Lattices:

- LWE hardness comes from lattice problems.
- We can design lattice-based cryptosystems without knowing lattices!

Exciting topics I did not mention

- The Small Integer Solution problem (SIS)
⇒ Digital signatures.
- Ideal lattices, Ring-LWE, Ring-SIS, NTRU
⇒ Using polynomial rings (a.k.a. structured matrices) to get more efficient constructions.
- Implementation of lattice-based primitives.

These will be addressed in Léo's talk (Friday morning), my second talk (Friday afternoon) and Tim's talk (Friday afternoon).

Open problems: foundations

If q is prime and $\leq n^{\mathcal{O}(1)}$, then there exists a **quantum** polynomial-time reduction from **SVP $_{\gamma}$** in **dim** n to $\text{LWE}_{n,q,\alpha}$, with $\gamma \approx n/\alpha$.

If q is $\leq n^{\mathcal{O}(1)}$, then there exists a **classical** polynomial-time reduction from **GapSVP $_{\gamma}$** in **dim** \sqrt{n} to $\text{LWE}_{n,q,\alpha}$, with $\gamma \approx n/\alpha$.

- Does there exist a classical reduction from n -dimensional $\text{SVP}_{\gamma}/\text{BDD}_{\gamma}$ to $\text{LWE}_{n,q,\alpha}$?
- Does there exist a quantum algorithm for $\text{LWE}_{n,q,\alpha}$ that runs in time $2^{\sqrt{n}}$ (when $q \leq n^{\mathcal{O}(1)}$)?
- Is LWE easy for some $\alpha = 1 / n^{\mathcal{O}(1)}$?
- Can we reduce factoring/DL to LWE?

Open problems: foundations

If q is prime and $\leq n^{\mathcal{O}(1)}$, then there exists a **quantum** polynomial-time reduction from **SVP $_{\gamma}$** in **dim** n to $\text{LWE}_{n,q,\alpha}$, with $\gamma \approx n/\alpha$.

If q is $\leq n^{\mathcal{O}(1)}$, then there exists a **classical** polynomial-time reduction from **GapSVP $_{\gamma}$** in **dim** \sqrt{n} to $\text{LWE}_{n,q,\alpha}$, with $\gamma \approx n/\alpha$.

- Does there exist a classical reduction from n -dimensional $\text{SVP}_{\gamma}/\text{BDD}_{\gamma}$ to $\text{LWE}_{n,q,\alpha}$?
- Does there exist a quantum algorithm for $\text{LWE}_{n,q,\alpha}$ that runs in time $2^{\sqrt{n}}$ (when $q \leq n^{\mathcal{O}(1)}$)?
- Is LWE easy for some $\alpha = 1 / n^{\mathcal{O}(1)}$?
- Can we reduce factoring/DL to LWE?

Open problems: foundations

If q is prime and $\leq n^{\mathcal{O}(1)}$, then there exists a **quantum** polynomial-time reduction from **SVP $_{\gamma}$** in **dim** n to $\text{LWE}_{n,q,\alpha}$, with $\gamma \approx n/\alpha$.

If q is $\leq n^{\mathcal{O}(1)}$, then there exists a **classical** polynomial-time reduction from **GapSVP $_{\gamma}$** in **dim** \sqrt{n} to $\text{LWE}_{n,q,\alpha}$, with $\gamma \approx n/\alpha$.

- Does there exist a classical reduction from n -dimensional $\text{SVP}_{\gamma}/\text{BDD}_{\gamma}$ to $\text{LWE}_{n,q,\alpha}$?
- Does there exist a quantum algorithm for $\text{LWE}_{n,q,\alpha}$ that runs in time $2^{\sqrt{n}}$ (when $q \leq n^{\mathcal{O}(1)}$)?
- Is LWE easy for some $\alpha = 1 / n^{\mathcal{O}(1)}$?
- Can we reduce factoring/DL to LWE?

Open problems: foundations

If q is prime and $\leq n^{\mathcal{O}(1)}$, then there exists a **quantum** polynomial-time reduction from **SVP** $_{\gamma}$ in **dim** n to $\text{LWE}_{n,q,\alpha}$, with $\gamma \approx n/\alpha$.

If q is $\leq n^{\mathcal{O}(1)}$, then there exists a **classical** polynomial-time reduction from **GapSVP** $_{\gamma}$ in **dim** \sqrt{n} to $\text{LWE}_{n,q,\alpha}$, with $\gamma \approx n/\alpha$.

- Does there exist a classical reduction from n -dimensional $\text{SVP}_{\gamma}/\text{BDD}_{\gamma}$ to $\text{LWE}_{n,q,\alpha}$?
- Does there exist a quantum algorithm for $\text{LWE}_{n,q,\alpha}$ that runs in time $2^{\sqrt{n}}$ (when $q \leq n^{\mathcal{O}(1)}$)?
- Is LWE easy for some $\alpha = 1 / n^{\mathcal{O}(1)}$?
- Can we reduce factoring/DL to LWE?

Open problems: cryptanalysis

LWE-based cryptography is based on GapSVP_γ for $\gamma \geq n$.
No NP-hardness here...

- Can we solve SVP_γ in $\text{poly}(n)$ -time for some $\gamma = n^{\mathcal{O}(1)}$?
- And with a quantum computer?
- Can we do better than BKZ's $\left(\frac{n}{\log \gamma}\right)^{\mathcal{O}\left(\frac{n}{\log \gamma}\right)}$ run-time, for some γ ?
- What are the practical limits?

<http://www.latticechallenge.org>

Open problems: cryptanalysis

LWE-based cryptography is based on GapSVP_γ for $\gamma \geq n$.
No NP-hardness here...

- Can we solve SVP_γ in $\text{poly}(n)$ -time for some $\gamma = n^{\mathcal{O}(1)}$?
- And with a quantum computer?
- Can we do better than BKZ's $\left(\frac{n}{\log \gamma}\right)^{\mathcal{O}\left(\frac{n}{\log \gamma}\right)}$ run-time, for some γ ?
- What are the practical limits?

<http://www.latticechallenge.org>

Open problems: cryptanalysis

LWE-based cryptography is based on GapSVP_γ for $\gamma \geq n$.
No NP-hardness here...

- Can we solve SVP_γ in $\text{poly}(n)$ -time for some $\gamma = n^{\mathcal{O}(1)}$?
- And with a quantum computer?
- Can we do better than BKZ's $(\frac{n}{\log \gamma})^{\mathcal{O}(\frac{n}{\log \gamma})}$ run-time, for some γ ?
- What are the practical limits?

<http://www.latticechallenge.org>

Open problems: cryptanalysis

LWE-based cryptography is based on GapSVP_γ for $\gamma \geq n$.
No NP-hardness here...

- Can we solve SVP_γ in $\text{poly}(n)$ -time for some $\gamma = n^{\mathcal{O}(1)}$?
- And with a quantum computer?
- Can we do better than BKZ's $\left(\frac{n}{\log \gamma}\right)^{\mathcal{O}\left(\frac{n}{\log \gamma}\right)}$ run-time, for some γ ?
- What are the practical limits?

<http://www.latticechallenge.org>

Open problems: practice

There exist practical lattice-based signature and encryption schemes.

- Can lattice-based primitives outperform other approaches in some contexts?
- What about side-channel cryptanalysis?
- Can advanced lattice-based primitives be made practical? Attribute-based encryption? Homomorphic encryption?

Open problems: practice

There exist practical lattice-based signature and encryption schemes.

- Can lattice-based primitives outperform other approaches in some contexts?
- What about side-channel cryptanalysis?
- Can advanced lattice-based primitives be made practical? Attribute-based encryption? Homomorphic encryption?

Open problems: practice

There exist practical lattice-based signature and encryption schemes.

- Can lattice-based primitives outperform other approaches in some contexts?
- What about side-channel cryptanalysis?
- Can advanced lattice-based primitives be made practical?
Attribute-based encryption? Homomorphic encryption?

Open problems: practice

There exist practical lattice-based signature and encryption schemes.

- Can lattice-based primitives outperform other approaches in some contexts?
- What about side-channel cryptanalysis?
- Can advanced lattice-based primitives be made practical? Attribute-based encryption? Homomorphic encryption?

Bibliography

- AhRe04** D. Aharonov, O. Regev: Lattice problems in NP cap coNP. J. ACM 52(5): 749-765 (2005).
- AjDw97** M. Ajtai, C. Dwork: A Public-Key Cryptosystem with Worst-Case/Average-Case Equivalence. STOC 1997: 284-293.
- Aj98** M. Ajtai: The Shortest Vector Problem in L2 is NP-hard for Randomized Reductions (Extended Abstract). STOC 1998: 10-19.
- AgDaReSD15** D. Aggarwal, D. Dadush, O. Regev, N. Stephens-Davidowitz: Solving the Shortest Vector Problem in 2^n Time via Discrete Gaussian Sampling. Available on ARXIV.
- BoVe96** D. Boneh, R. Venkatesan: Hardness of Computing the Most Significant Bits of Secret Keys in Diffie-Hellman and Related Schemes. CRYPTO 1996: 129-142.
- Br12** Z. Brakerski: Fully Homomorphic Encryption without Modulus Switching from Classical GapSVP. CRYPTO 2012: 868-886.
- rLaPeReSt13** Z. Brakerski, A. Langlois, C. Peikert, O. Regev, D. Stehlé: Classical hardness of learning with errors. STOC 2013: 575-584.
- BrVa11** Z. Brakerski, V. Vaikuntanathan: Efficient Fully Homomorphic Encryption from (Standard) LWE. SIAM J. Comput. 43(2): 831-871 (2014).
- ChNg11** Y. Chen, P. Nguyen: BKZ 2.0: Better Lattice Security Estimates. ASIACRYPT 2011: 1-20.
- ChSt15** J. H. Cheon, D. Stehlé: Fully Homomorphic Encryption over the Integers Revisited. EUROCRYPT 2015.

Bibliography

- GePeVa08 C. Gentry, C. Peikert, V. Vaikuntanathan: Trapdoors for hard lattices and new cryptographic constructions. STOC 2008: 197-206.
- GoGo98 O. Goldreich, S. Goldwasser: On the Limits of Nonapproximability of Lattice Problems. J. Comput. Syst. Sci. 60(3): 540-563 (2000).
- GoVaWe13 S. Gorbunov, V. Vaikuntanathan, H. Wee: Attribute-based encryption for circuits. STOC 2013: 545-554.
- HaPuSt11 G. Hanrot, X. Pujol, D. Stehlé: Analyzing Blockwise Lattice Algorithms Using Dynamical Systems. CRYPTO 2011: 447-464.
- HaRe07 I. Haviv, O. Regev: Tensor-based Hardness of the Shortest Vector Problem to within Almost Polynomial Factors. Theory of Computing 8(1): 513-531 (2012).
- HG01 N. Howgrave-Graham: Approximate Integer Common Divisors. CaLC 2001: 51-66.
- Pe14 C. Peikert: Lattice Cryptography for the Internet. PQCrypto 2014: 197-219.
- Re03 O. Regev: New lattice-based cryptographic constructions. J. ACM 51(6): 899-942 (2004).
- Re05 O. Regev: On lattices, learning with errors, random linear codes, and cryptography. J. ACM 56(6) (2009).
- ScEu91 C.-P. Schnorr, M. Euchner: Lattice basis reduction: Improved practical algorithms and solving subset sum problems. Math. Program. 66: 181-199 (1994).