

**Manureet Kaur**

**CSE-A2**

**PPS COURSE 18105**

**C.R.No.1915050**

**University R.No** (<http://R.No>). **1905020**

## Programming for Problem Solving

### 1) Program to print message

```
#include<stdio.h>
void main()
{
    puts("Hi Budding Engineers");
}
```

OUTPUT:

```
Hi Budding Engineers
```

### 2) Program to print your address using puts

```
#include<stdio.h>
int main()
{
    puts("My address:");
    puts("H No. 121 Kehar Singh Nagar\nHaibowal,\nLudhiana,\n,\nPunjab,\nIndia.");
    return 0;
}
```

OUTPUT:

```
My address:
H No. 891-D Model Town Extension,
Libra Bus Service,
Ludhiana,
Punjab,
India.
```

### 3) Program to find sum of two numbers:

```
#include <stdio.h>
int num1, num2;

void main(){
printf("Welcome to the program to add to number\n");
printf("Write the numbers to be added:\n");
scanf("%d %d", &num1 ,&num2);
printf("The sum of two number is:");
printf("%d",num1 + num2);
}
```

#### OUTPUT:

```
Welcome to the program to add to number
Write the numbers to be added:
35
65
The sum of two number is:100
```

### 4)Program to convert temperature degree celcius to degree Farenheit

```
include<stdio.h>
float temp_in_c, temp_in_f;
int main(){
printf("Welcome to the temperature converter\n");
printf("Please Enter the temperature in degree celsius:\n");
scanf("%f",&temp_in_c);
temp_in_f = (temp_in_c * 9)/5 + 32;
printf("%f",temp_in_f);
}
```

#### OUTPUT:

```
Welcome to the temperature converter
Please Enter the temperature in degree celcius:
34
93.199997
```

### 5)Program to find area and perimeter of circle

```
#include <stdio.h>

#define PI 3.14f

int main()
{
    float rad,area, perm;

    printf("Enter radius of circle: ");
    scanf("%f",&rad);

    area=PI*rad*rad;
    perm=2*PI*rad;

    printf("Area of circle: %f \nPerimeter of circle: %f\n",area,perm);
    return 0;
}
```

**OUTPUT:**

```
Enter radius of circle: 2.34
Area of circle: 17.193384
Perimeter of circle: 14.695200
```

**6) Program to find factorial of a number**

```
#include <stdio.h>
int d;
int num = 1;
int main(){
printf("Enter the number whose factorial to be found:\n");
scanf(" %d",&d);
for(d; d>0; d--){
num = num *d ;
}
printf(" The factorial is %d",num);
return 0;

}
```

**OUTPUT:**

```
Enter the number whose factorial to be found:
8
The factorial is 40320
```

## 7)Program to swap a number without using two numbers:

```
#include <stdio.h>

int main()
{
    int a, b;

    printf("Input two integers (a & b) to swap\n");
    scanf("%d%d", &a, &b);

    a = a + b;
    b = a - b;
    a = a - b;

    printf("a = %d\nb = %d\n",a,b);
    return 0;
}
```

### OUTPUT:

```
Input two integers (a & b) to swap
4
6
a = 6
b = 4
```

## 8)Program to check if the Number is odd or even:

```
#include <stdio.h>
int num;
int main(){
    printf("Please enter the number to check if it's even or odd");
    scanf("%d",&num);
    if (num%2 == 0)
        printf("The number is Even:\n");
    else
        printf("The number id Odd");
}
```

### OUTPUT:

```
Please enter the number to check if it's even or odd:
56
The number is Even
```

## 9)Program to reverse a number

```
#include <stdio.h>
int x,num, rev = 0;
int main()
{
    printf("Enter the number to be reversed: \n");
    scanf("%d", &num);
    while(num > 1){
        x = num % 10;
        rev = rev * 10 + x;
        num = num / 10;
    }
    printf("The reversed number is : %d \n", rev);
    return 0;
}
```

OUTPUT:

```
Enter the number to be reversed:
789456
The reversed number is 654987
```

## 10)Program of FizzBuzz:

```
#include<stdio.h>
int num;
int main(){
    printf("Welcome to the Fizz Buzz Program");
    printf("Enter The number");
    scanf("%d",&num);
    if (num%3 == 0 && num%5 !=0)
        printf("Fizz");
    if (num%3 != 0 && num%5 == 0)
        printf("Buzz");
    if (num%3 == 0 && num%5 == 0)
        printf("FizzBuzz");
}
```

OUTPUT:

```
Welcome to the Fizz Buzz Program
Enter The number:45
FizzBuzz
```

## 11)Program to show days of week using Switch Case:

```
#include <stdio.h>

int main()
{
    int week;

    /* Input week number from user */
    printf("Enter week number(1-7): ");
    scanf("%d", &week);

    switch(week)
    {
        case 1:
            printf("Monday");
            break;
        case 2:
            printf("Tuesday");
            break;
        case 3:
            printf("Wednesday");
            break;
        case 4:
            printf("Thursday");
            break;
        case 5:
            printf("Friday");
            break;
        case 6:
            printf("Saturday");
            break;
        case 7:
            printf("Sunday");
            break;
        default:
            printf("Invalid input! Please enter week number between 1-7.");
    }

    return 0;
}
```

## OUTPUT:

```
Enter week number(1-7): 3
Wednesday
```

## 12) Program to Check if a number is Prime

```
#include<stdio.h>
void main()
{
int num,sum=0;
printf("enter the number which you want check to wheather prime or not\n");
scanf("%d",&num);
if(num==1)
printf("number is neither prime nor composite\n");
else if(num<1)
printf("enter number greater than 1\n");
else
{
for(int i=2;i<n;i++)
{
if(n%i==0)
sum++;
}
if(sum==0)
printf("The number is prime\n");
else
printf("The number is composite\n");
}
}
```

**OUTPUT:**

```
enter the number which you want check to wheather prime or not
71
The number is prime
```

**13)Program to check if a number is Palindrome**

```
#include<stdio.h>

int x,num, num_loop,rev= 0;
int main(){
printf("Welcome to the palindrome function\n");
printf("Enter the number:\n");
scanf("%d",&num);
num_loop = num;
while(num_loop > 1){
x = num_loop % 10;
rev = rev * 10 +x;
num_loop = num_loop/10;
}
if (rev == num)
printf("oh yes ! You wrote a palindrome number");
else
printf("sorry the number is not a palindrome");
}
```

**OUTPUT:**

```
Welcome to the palindrome function
Enter the number:
234565432
oh yes ! You wrote a palindrome number
```

**14)Program to check a palindrome of Word**



```
#include <stdio.h>
#include <string.h>

// A function to check if a string str is palindrome
void isPalindrome(char str[])
{
    // Start from leftmost and rightmost corners of str
    int l = 0;
    int h = strlen(str) - 1;

    // Keep comparing characters while they are same
    while (h > l)
    {
        if (str[l++] != str[h--])
        {
            printf("%s is Not Palindrome", str);
            return;
        }
    }
    printf("%s is palindrome", str);
}

// Driver program to test above function
int main()
{
    isPalindrome("abba");
    isPalindrome("abbccbba");
    isPalindrome("geeks");
    return 0;
}
```

## OUTPUT:

```
abba is palindrome
abbccbba is palindrome
geeks is Not Palindrome
```

## 15)Program to print fibonacci series

```
#include<stdio.h>
int a,b,c,i;
int main(){

printf("Enter the first number of the series");
scanf("%d",&a);
printf("Enter the second number");
scanf("%d",&b);
for(i=0;i<20;i++){
c = a+b;
printf("%d\n",c);
a = b;
b = c;
}
}
```

**OUTPUT:**

```
Enter the first number of the series5
Enter the second number6
11
17
28
45
73
118
191
309
500
809
1309
2118
3427
5545
8972
14517
23489
38006
61495
99501
```

## 16) Program to Enter and Display Elements of 1D Array:

```
#include <stdio.h>

int main()
{
    int array[100], position, c, n, value;

    printf("Enter number of elements in array\n");
    scanf("%d", &n);

    printf("Enter %d elements\n", n);

    for (c = 0; c < n; c++)
        scanf("%d", &array[c]);

    printf("Enter the location where you wish to insert an element\n");
    scanf("%d", &position);

    printf("Enter the value to insert\n");
    scanf("%d", &value);

    for (c = n - 1; c >= position - 1; c--)
        array[c+1] = array[c];

    array[position-1] = value;

    printf("Resultant array is\n");

    for (c = 0; c <= n; c++)
        printf("%d\n", array[c]);

    return 0;
}
```

### OUTPUT:

Input 10 elements in the array :

element - 0 : 1

element - 1 : 1

element - 2 : 2

element - 3 : 3

element - 4 : 4

element - 5 : 5

element - 6 : 6

element - 7 : 7

element - 8 : 8

element - 9 : 9

Elements in array are: 1 1 2 3 4 5 6 7 8 9

## 17)Program to Enter and Display Elements of 2D Array

```
#include<stdio.h>
int main(){
    /* 2D array declaration*/
    int disp[2][3];
    /*Counter variables for the loop*/
    int i, j;
    for(i=0; i<2; i++) {
        for(j=0;j<3;j++) {
            printf("Enter value for disp[%d][%d]:", i, j);
            scanf("%d", &disp[i][j]);
        }
    }
    //Displaying array elements
    printf("Two Dimensional array elements:\n");
    for(i=0; i<2; i++) {
        for(j=0;j<3;j++) {
            printf("%d ", disp[i][j]);
            if(j==2){
                printf("\n");
            }
        }
    }
    return 0;
}
```

## OUTPUT:

```
Enter value for disp[0][0]:1
Enter value for disp[0][1]:2
Enter value for disp[0][2]:3
Enter value for disp[1][0]:4
Enter value for disp[1][1]:5
Enter value for disp[1][2]:6
Two Dimensional array elements:
1 2 3
4 5 6
```

### 18) Program to add to Matrix:

```
#include<stdio.h>

int a[3][3], b[3][3],c[3][3], i ,j;
int main(){
printf("Welcome to the Matrix Program");

printf("Enter the value of matrix A");
for(i=0;i<3;i++){
for(j=0;j<3;j++){
scanf("%d",&a[i][j]);
}}

printf("Enter the value of matrix B");
for(i=0;i<3;i++){
for(j=0;j<3;j++){
scanf("%d",&b[i][j]);
}}

printf("You have entered all the values of the matrix\n");
printf("Now the program is displaying the addition of  matrix");

for(i=0;i<3;i++){
for(j=0;j<3;j++){
c[i][j] = b[i][j] + a[i][j];
}}

for(i=0;i<3;i++){
for(j=0;j<3;j++){

printf("%d\t",c[i][j]);
}
printf("\n");}

}
```

## OUTPUT:

```
Welcome to the Matrix ProgramEnter the value of matrix A
23
67
12
89
23
78
12
65
23
Enter the value of matrix B45
67
89
23
62
48
69
52
84
You have entered all the values of the matrix
Now the program is displaying the addition of matrix
68 134 101
112 85 126
81 117 107
```

### 19)Program to Display Transpose of Matrix:

```
#include<stdio.h>

int a[3][3],c[3][3], i ,j;
int main(){
printf("Welcome to the Matrix Transpose Program");

printf("Enter the value of matrix");
for(i=0;i<3;i++){
for(j=0;j<3;j++){
scanf("%d",&a[i][j]);
}}

for(i=0;i<3;i++){
for(j=0;j<3;j++){

printf("%d\t",a[i][j]);
}

printf("You have entered all the values of the matrix\n");
printf("Now the program is displaying the transpose of matrix\n");

for(i=0;i<3;i++){
for(j=0;j<3;j++){
c[j][i] = a[i][j];
}}

for(i=0;i<3;i++){
for(j=0;j<3;j++){

printf("%d\t",c[i][j]);
}
printf("\n");}

}
}
```

## OUTPUT:



Welcome to the Matrix Transpose ProgramEnter the value of matrix

34

56

625

536

75

68

97

07

You have entered all the values of the matrix

Now the program is displaying the transpose of matrix

34 625 68

34 536 97

56 75 7

## 20)Program for Subtraction of 2 Matrix:

```
#include<stdio.h>

int a[3][3], b[3][3],c[3][3], i ,j;
int main(){
printf("Welcome to the Matrix Program");

printf("Enter the value of matrix A");
for(i=0;i<3;i++){
for(j=0;j<3;j++){
scanf("%d",&a[i][j]);
}}

printf("Enter the value of matrix B");
for(i=0;i<3;i++){
for(j=0;j<3;j++){
scanf("%d",&b[i][j]);
}}

printf("You have entered all the values of the matrix\n");
printf("Now the program is displaying the addition of  matrix");

for(i=0;i<3;i++){
for(j=0;j<3;j++){
c[i][j] = b[i][j] - a[i][j];
}}

for(i=0;i<3;i++){
for(j=0;j<3;j++){

printf("%d\t",c[i][j]);
}
printf("\n");}

}
```

## OUTPUT:

Welcome to the Matrix ProgramEnter the value of matrix A

34

26

73

84

53

15

73

86

24

Enter the value of matrix B

1

57

43

57

33

10

24

46

13

You have entered all the values of the matrix

Now the program is displaying the addition of matrix-33 31 -30

-27 -20 -5

-49 -40 -11

## 21)Program to Find Multiplication of Matrix

```
#include <stdio.h>
int main()
{
    int a[10][10], b[10][10], result[10][10], r1, c1, r2, c2, i, j, k;
    printf("Enter rows and column for first matrix: ");
    scanf("%d %d", &r1, &c1);
    printf("Enter rows and column for second matrix: ");
    scanf("%d %d",&r2, &c2);
    // Column of first matrix should be equal to column of second matrix and
    while (c1 != r2)
    {
        printf("Error! column of first matrix not equal to row of second.\n\n");
        printf("Enter rows and column for first matrix: ");
        scanf("%d %d", &r1, &c1);
        printf("Enter rows and column for second matrix: ");
        scanf("%d %d",&r2, &c2);
    }
    // Storing elements of first matrix.
    printf("\nEnter elements of matrix 1:\n");
    for(i=0; i<r1; ++i)
        for(j=0; j<c1; ++j)
        {
            printf("Enter elements a%d%d: ",i+1, j+1);
            scanf("%d", &a[i][j]);
        }
    // Storing elements of second matrix.
    printf("\nEnter elements of matrix 2:\n");
    for(i=0; i<r2; ++i)
        for(j=0; j<c2; ++j)
        {
            printf("Enter elements b%d%d: ",i+1, j+1);
            scanf("%d",&b[i][j]);
        }
    // Initializing all elements of result matrix to 0
    for(i=0; i<r1; ++i)
        for(j=0; j<c2; ++j)
        {
            result[i][j] = 0;
        }
    // Multiplying matrices a and b and
    // storing result in result matrix
    for(i=0; i<r1; ++i)
        for(j=0; j<c2; ++j)
            for(k=0; k<c1; ++k)
            {
                result[i][j]+=a[i][k]*b[k][j];
            }
    // Displaying the result
    printf("\nOutput Matrix:\n");
    for(i=0; i<r1; ++i)
```

```
        for(j=0; j<c2; ++j)
        {
            printf("%d  ", result[i][j]);
            if(j == c2-1)
                printf("\n\n");
        }
    return 0;
}
```

## OUTPUT:

Enter rows and column for first matrix: 3

2

Enter rows and column for second matrix: 3

2

Error! column of first matrix not equal to row of second.

Enter rows and column for first matrix: 2

3

Enter rows and column for second matrix: 3

2

Enter elements of matrix 1:

Enter elements a11: 3

Enter elements a12: -2

Enter elements a13: 5

Enter elements a21: 3

Enter elements a22: 0

Enter elements a23: 4

Enter elements of matrix 2:

Enter elements b11: 2

Enter elements b12: 3

Enter elements b21: -9

Enter elements b22: 0

Enter elements b31: 0

Enter elements b32: 4

Output Matrix:

24 29

6 25

## 22) Program to find square of a number using function

```
#include <stdio.h>
int num,a;
int square(int num);

void main(){
printf("Welcome to the program to find the square of a number\n");
printf("Input the number you want to print:\n")
scanf("%d", &num);
square(num);
}

int square(int a)
{
printf("The Answer is :%d\n",a*a);
}
```

**OUTPUT:**

```
Welcome to the program to find the square of a number
Input the number you want to find square of:
3
The Answer is:9
```

**23)Program to swap two numbers by call by value**

```
#include<stdio.h>
void swap(int a,int b);
void main()
{
int x,y;
printf("\n Enter value for x:");
scanf("%d",&x);
printf("\n Enter value for y:");
scanf("%d",&y);
printf("\n Before calling swap functin\n");
printf("\n Value of x=%d,Value of y=%d\n",x,y);
swap(x,y);
printf("\n After returning from swap function");
printf("\n Value of x=%d,value of y=%d\n",x,y);
}
void swap(int a,int b)
{
int temp;
printf("\n Inside the function \n");
printf("\n Value of a=%d,Value of b=%d before swaping\n",a,b);
temp=a;
a=b;
b=temp;
printf("\n Value of a=%d,Value of b=%d after swaping\n",a,b);
}
```

## OUTPUT:

Enter value for x:45

Enter value for y:56

Before calling swap functin

Value of x=45,Value of y=56

Inside the function

Value of a=45,Value of b=56 before swaping

Value of a=56,Value of b=45 after swaping

After returning from swap function

Value of x=45,value of y=56

## 24)Program to swap two numbers by call by reference



```
#include<stdio.h>
void swap(int *,int *);
void main()
{
int x,y;
printf("\n Enter value for x:");
scanf("%d",&x);
printf("\n Enter value for y:");
scanf("%d",&y);
printf("\n Before calling swap functin\n");
printf("\n Value of x=%d,Value of y=%d\n",x,y);
swap(&x,&y);
printf("\n After returning from swap function");
printf("\n Value of x=%d,value of y=%d\n",x,y);
}
void swap(int *a,int *b)
{
int temp;
printf("\n Inside the function \n");
printf("\n Value of a=%d,Value of b=%d before swaping\n",*a,*b);
temp=*a;
*a=*b;
*b=temp;
printf("\n Value of a=%d,Value of b=%d after swaping\n",*a,*b);
}
```

## OUTPUT:

Enter value for x:23

Enter value for y:45

Before calling swap functin

Value of x=23,Value of y=45

Inside the function

Value of a=23,Value of b=45 before swaping

Value of a=45,Value of b=23 after swaping

After returning from swap function

Value of x=45,value of y=23

## 25)Program to Find factorial of a number using recursion:

```
#include <stdio.h>
int count = 1, num;
int multiply(int num);

int main(){
printf("Welcome to the program to find factorial by recursion");
printf("Write the number:\n");
scanf("%d",&num);
multiply(num);
printf("The facorial is %d",count);
}

int multiply(int num){
    count = count * num;
    if(num>1){
        multiply(num - 1);
    }
    return count;}
```

**OUTPUT:**

```
Welcome to the program to find factorial by recursionWrite the number:
8
The facorial is 40320
```

**26)Program to Find fibonacci series using recursion:**

```
#include <stdio.h>
int count, num1, num2, b;
int add(int num1,
```

**OUTPUT:**

Welcome to the program to write the fibonacci series by recursion

Write the first and second number of the series

2

3

How many terms you want in the fibonacci series

20

The fibonacci series is

2

3

5

8

13

21

34

55

89

144

233

377

610

987

1597

2584

4181

6765

10946

17711

## 27)Program to add elements to a structure and display them

```
#include <stdio.h>
struct student
{
    char name[50];
    int roll;
    float marks;
} s[10];
int main()
{
    int i;
    printf("Enter information of students:\n");
    // storing information
    for(i=0; i<10; ++i)
    {
        s[i].roll = i+1;
        printf("\nFor roll number%d,\n",s[i].roll);
        printf("Enter name: ");
        scanf("%s",s[i].name);
        printf("Enter marks: ");
        scanf("%f",&s[i].marks);
        printf("\n");
    }
    printf("Displaying Information:\n\n");
    // displaying information
    for(i=0; i<10; ++i)
    {
        printf("\nRoll number: %d\n",i+1);
        printf("Name: ");
        puts(s[i].name);
        printf("Marks: %.1f",s[i].marks);
        printf("\n");
    }
    return 0;
}
```

## OUTPUT:

Enter information of students:

For roll number1,

Enter name: Tom

Enter marks: 98

For roll number2,

Enter name: Jerry

Enter marks: 89

.  
. .  
.

Displaying Information:

Roll number: 1

Name: Tom

Marks: 98

.  
. .  
.

## 28)Pointer or variable

```
#include <stdio.h>

int main () {

    int  var = 20;    /* actual variable declaration */
    int  *ip;         /* pointer variable declaration */

    ip = &var; /* store address of var in pointer variable*/

    printf("Address of var variable: %x\n", &var );

    /* address stored in pointer variable */
    printf("Address stored in ip variable: %x\n", ip );

    /* access the value using the pointer */
    printf("Value of *ip variable: %d\n", *ip );

    return 0;
}
```

## OUTPUT

Address of var variable: bffd8b3c

Address stored in ip variable: bffd8b3c

Value of \*ip variable: 20