

Lab 9-1: Apache TSL Configuration
23002001-Hashini Gayathri Suraweera

```
hashinigayathri@hashinigayathri-VirtualBox:~$ cd Downloads
hashinigayathri@hashinigayathri-VirtualBox:~/Downloads$ cd opensslCA
hashinigayathri@hashinigayathri-VirtualBox:~/Downloads/opensslCA$ sudo nano /etc
/apache2/sites-available/default-ssl.conf
[sudo] password for hashinigayathri:
```

```
hashinigayathri@hashinigayathri-VirtualBox: ~/Downloads/opensslCA
GNU nano 7.2 /etc/apache2/sites-available/default-ssl.conf
<VirtualHost *:443>
    ServerAdmin webmaster@localhost
    ServerName 10.0.2.15:443
    DocumentRoot /var/www/html

    # Available loglevels: trace8, ..., trace1, debug, info, notice, warn,
    # error, crit, alert, emerg.
    # It is also possible to configure the loglevel for particular
    # modules, e.g.
    #LogLevel info ssl:warn

    ErrorLog ${APACHE_LOG_DIR}/error.log
    CustomLog ${APACHE_LOG_DIR}/access.log combined

    # For most configuration files from conf-available/, which are
    # enabled or disabled at a global level, it is possible to
    # include a line for only one particular virtual host. For example the
    # following line enables the CGI configuration for this host only
    # after it has been globally disabled with "a2disconf".
    #Include conf-available/serve-cgi-bin.conf

    # Enable/disable SSL for this virtual host.
    SSLEngine on

    # A self-signed (snakeoil) certificate can be created by installing
    # the ssl-cert package. See
    # /usr/share/doc/apache2/README.Debian.gz for more info.
    # If both key and certificate are stored in the same file, only the
    # SSLCertificateFile directive is needed.
    SSLCertificateFile /etc/apache2/ssl/hostcert.pem
    SSLCertificateKeyFile /etc/apache2/ssl/hostkey.pem

    # Server Certificate Chain:
```

```
div.validator {
}
</style>
</head>
<body>
  <h1>Name: Hashini gayathri</h1>
  <h2>Index: 23002001</h2>
```

Name: Hashini gayathri

Index: 23002001

Apache TLS Configuration Successful



ubuntu

Apache2 Ubuntu Default Page

It works!

This is the default welcome page used to test the correct operation of the Apache2 server after installation on Ubuntu systems. It is based on the equivalent page on Debian, from which the Ubuntu Apache packaging is derived. If you can read this page, it means that the Apache HTTP server installed at this site is working properly. You should **replace this file** (located at `/var/www/html/index.html`) before continuing to operate your HTTP server.

If you are a normal user of this web site and don't know what this page is about, this probably means that the site is currently unavailable due to maintenance. If the problem persists, please contact the site's administrator.

Configuration Overview

Ubuntu's Apache2 default configuration is different from the upstream default configuration, and split into several files optimized for interaction with Ubuntu tools. The configuration system is **fully documented in `/usr/share/doc/apache2/README.Debian.gz`**. Refer to this for the full documentation. Documentation for the web server itself can be found by accessing the **manual** if the `apache2-doc` package was installed on this server.

The configuration layout for an Apache2 web server installation on Ubuntu systems is as follows:

```
/etc/apache2/
|-- apache2.conf
|   |-- ports.conf
|-- mods-enabled
|   |-- *.load
|   |-- *.conf
|-- conf-enabled
|   |-- *.conf
|-- sites-enabled
|   |-- *.conf
```

- `apache2.conf` is the main configuration file. It puts the pieces together by including all remaining configuration files when starting up the web server.
- `ports.conf` is always included from the main configuration file. It is used to determine the listening ports for incoming connections, and this file can be customized anytime.
- Configuration files in the `mods-enabled/`, `conf-enabled/` and `sites-enabled/` directories contain particular configuration snippets which manage modules, global configuration fragments, or virtual host configurations, respectively.
- They are activated by symlinking available configuration files from their respective `*-available/` counterparts. These should be managed by using our helpers `a2enmod`, `a2dismod`, `a2ensite`,