Map::Tube

Mohammad S Anwar (@cpan_author)

PAUSE ID: manwar

German Perl Workshop 2018

Background

- First released in Oct 2010.
- So far 150+ public releases.
- Created around 36 maps of some of the most popular metros around the world.
- Currently 7 people associated with this project e.g. MANWAR, SKIM, GWS, SREZIC, ERRIETTA, MFONTANI and SLU.
- Formally introduced to Perl Community at LPW 2017.

Setup Environment

- \$ sudo cpanm -v Map::Tube
- \$ sudo cpanm -v Map::Tube::Plugin::Graph

Optional Plugins

- sudo cpanm -v Map::Tube::Plugin::FuzzyFind
- sudo cpanm -v Map::Tube::Plugin::Formatter

Let us create map for Madrid Metro

- Look for available map of Madrid Metro
- For this map, we would create JSON formatted source.

Skeleton of map data

```
"name": "Madrid Metro",
"lines": {
  "line": [
"stations": {
  "station": [
```

Line details

```
"id": "L3",
   "name": "L3",
   "color": "yellow"
}
```

Station details

```
"id": "L3-01",
   "name": "Villaverde Alto",
   "line": "L3:1",
   "link": "L3-02"
}
```

Map::Tube::Madrid

```
package Map::Tube::Madrid;
use File::Share ':all';
use Moo;
use namespace::autoclean;
has json => (is => 'lazy');
with 'Map::Tube';
sub _build_json { dist_file('Map-Tube-Madrid', 'madrid-map.json') }
1;
```

Shortest Route?

```
use strict; use warnings;
use Map::Tube::Madrid;
my $metro = Map::Tube::Madrid->new;
my $route = $metro->get_shortest_route('Sol', 'Delicias');
print "Route: $route\n";
```

Map Image?

```
use strict; use warnings;
use MIME::Base64;
use Map::Tube::Madrid;

my $metro = Map::Tube::Madrid->new;
my $map = $metro->name;
open(my $MAP_IMAGE, ">", "$map.png")
    or die "ERROR: Can't open [$map.png]: $!";
binmode($MAP_IMAGE);
print $MAP_IMAGE decode_base64($metro->as_image);
close($MAP_IMAGE);
```

Line Image?

```
use strict; use warnings;
use MIME::Base64;
use Map::Tube::Madrid;

my $metro = Map::Tube::Madrid->new;
my $line = 'L3';
open(my $LINE_IMAGE, ">", "$line.png")
   or die "ERROR: Can't open [$line.png]: $!";
binmode($LINE_IMAGE);
print $LINE_IMAGE decode_base64($metro->as_image($line));
close($LINE_IMAGE);
```

map-tube

- There is a very handy command line utility "map-tube" to play with installed maps.
- Just install Map::Tube::CLI to get the utility.

map-data-converter

- The distribution Map::Tube comes with a very useful tool "map-data-converter".
- With this tool, you can easily change the map source data format to XML or JSON.

More information?

- Please follow the documentation for Map::Tube::Cookbook.
- For object related details, please follow Map::Tube documentation.

Questions?

Thank You