ADVANCED DATABASE MANAGEMENT STYSTEM LAB

Name: Manya Madhu

Roll No:17

Batch: S2 RMCA B

Date: 06/05/2022

Experiment No: 6

<u>Aim</u>

To familiarize with join or cartesian product

Questions

- 1. Give name of customers having living city BOMBAY and branch city NAGPUR
- 2. Give names of customers having the same living city as their branch city
- 3. Give names of customers who are borrowers as well as depositors and having city NAGPUR.
- 4. Give names of borrowers having deposit amount greater than 1000 and loan amount greater than 2000.
- 5. Give names of depositors having the same branch as the branch of Sunil
- 6. Give names of borrowers having loan amount greater than the loan amount of Pramod
- 7. Give the name of the customer living in the city where branch of depositor Sunil is located.
- 8. Give branch city and living city of Pramod
- 9. Give branch city of Sunil and branch city of Anil
- 10. Give the living city of Anil and the living city of Sunil

Procedure

1.

SELECT D1.CNAME,D1.BNAME,C1.CNAME,C1.CITY,B1.CITY,B1.BNAME FROM DEPOSIT D1,CUSTOMER C1,BRANCH B1 WHERE C1.CITY = 'BOMBAY' AND B1.CITY = 'NAGPUR' AND D1.CNAME = C1.CNAME AND D1.BNAME = B1.BNAME;



2. SELECT distinct(customer.CNAME), BRANCH.CITY FROM BRANCH, customer WHERE BRANCH.city = customer.city;

	CNAME	CITY
•	KRANTI	BOMBAY
	MADHURI	NAGPUR
	NAREN	BOMBAY
	PRAMOD	NAGPUR
	SHIVANI	BOMBAY
	SUNIL	DELHI

3.

SELECT C1.CNAME FROM CUSTOMER C1,DEPOSIT D1,BORROW B1 WHERE C1.CITY='NAGPUR' AND C1.CNAME=D1.CNAME AND D1.CNAME = B1.CNAME;

	CNAME
•	MADHURI
	PRAMOD

4.

SELECT BR1.CNAME, BR1.AMOUNT, D1.CNAME, D1.AMOUNT FROM
BORROW BR1,DEPOSIT D1 WHERE D1.CNAME = BR1.CNAME AND
D1.AMOUNT > 1000 AND BR1.AMOUNT > 2000;

	CNAME	AMOUNT	CNAME	AMOUNT
▶	MEHUL	5000	MEHUL	3500
	PRAMOD	8000	PRAMOD	3000
	KRANTI	3000	KRANTI	5000

5.

SELECT D1.CNAME FROM DEPOSIT D1 WHERE D1.BNAME IN (SELECT D2.BNAME FROM DEPOSIT D2 WHERE D2.CNAME = 'SUNIL');

	CNAME
 -	SUNIL

6.

SELECT BR1.CNAME,BR1.AMOUNT FROM BORROW BR1 WHERE BR1.AMOUNT > ALL (SELECT BR2.AMOUNT FROM BORROW BR2 WHERE BR2.CNAME = 'PRAMOD');



7.
SELECT C.CNAME FROM CUSTOMER C WHERE C.CITY IN (SELECT B.CITY FROM BRANCH B WHERE B.BNAME IN (SELECT D.BNAME FROM DEPOSIT D WHERE D.CNAME='SUNIL'));




8.

SELECT B1.CITY, C1.CITY FROM BRANCH B1,CUSTOMER C1, DEPOSIT D1 WHERE C1.CNAME = 'PRAMOD' AND C1.CNAME = D1.CNAME AND D1.BNAME = B1.BNAME;



9.

SELECT B1.CITY FROM DEPOSIT D1, BRANCH B1 WHERE D1.BNAME = B1.BNAME AND D1.CNAME IN ('SUNIL','ANIL');



10.

SELECT C1.CNAME, C1.CITY FROM CUSTOMER C1 WHERE C1.CNAME ='ANIL' OR C1.CNAME = 'SUNIL';

