

Digital Signal Processing

Practical File



Session: 2022-23

Name: Kartavya Gupta

Course: B.Sc.(Hons) Electronics

Semester: V

Roll No. 1620016

INDEX

<u>S. No.</u>	<u>Title</u>
1	Generating some basic signals (Unit Sequence, Impulse Sequence, Ramp Sequence, Exponential & Real Sinusoidal Signal.)
2	Write a program to generate 50 Hz continuous time sinusoidal signal and its sampled version and plot the signal.
3	Generating of Shifting scaling and reversal.
4	Generating Even and Odd Signals.
5	Time Scaling (Up Sampling and Down Sampling)
6	Generating and plot the discrete time sequences in a given interval.
7	Convolution of Discrete Time Sequence.
8	To find the solution of the given Difference Equation.
9	To find the Z Transform of the given Signal.
10	To find the Inverse Z Transform.
11	Obtain the partial fraction and plot zero pole diagram.
12	To find the Discrete Time Fourier Transform of a given sequence
13	To find the Discrete Fourier Transform of the given sequence.
14	To find the Inverse Discrete Fourier Transform of given sequence.
15	To find the Circular Convolution of given sequence.
16	Implementation of Fast Fourier Transform and Comparison with Discrete Fourier Transform.

Experiment no. 1

Aim:

Program for generating some basic signals (Unit Sequence, Impulse Sequence, Ramp Sequence, Exponential & Real Sinusoidal Signal.)

Input (a):

```
%Program for generating some basic signals (Unit Sequence, Impulse Sequence, Ramp Sequence)
function[x,n]=basicsignal(n0,n1,n2)
n=[n1:n2];
%Impulse Sequence
x1=[n-n0==0];
subplot(3,1,1);
stem(n,x1,'o k')
title("Unit Impulse Sequence")
%Unit sequence
x2=[n-n0>=0];
subplot(3,1,2);
stem(n,x2)
title('Unit Step sequence')
%Ramp sequence
R=n.*x2;
subplot(3,1,3);
stem(n,R,'o b')
title('Ramp Sequence')
end
```

Input (b):


```
%Program to generate basic signals like exponential and real sinusoidal
%signals
%Real Sinusoidal Signals
n1=-2*pi;
n2=2*pi;
n=[n1:n2];
x=sin(n);
subplot(3,2,1)
stem(n,x)
title('Sine Function')
y=cos(n);
subplot(3,2,2)
stem(n,y)
title('Cosine Function')
%Exponential Signals
n1=0;
n2=10;
n=[n1:n2]
a=10;
x1=exp(-a.*n);
subplot(3,2,3)
stem(n,x1)
```

```


title('Exponential signals for a > 1:')
a=0.5;
x2=exp(-a.*n);
subplot(3,2,4)
stem(n,x2)
title('Exponential signals for 0<a<1 :')
a=-0.5;
x3=exp(-a.*n)
subplot(3,2,5)
stem(n,x3)
title('Exponential signals for -1 < a < 0 :')
a=-10;
x4=exp(-a.*n);
subplot(3,2,6)
stem(n,x4)
title('Exponential signals for a<-1 :')

```

Output (a):



Output (b):



Experiment no. 2

Aim:


Write a program to generate 50 Hz continuous time sinusoidal signal and its sampled version and plot the signal.

Input:

%Program to generate 50 Hz continuous time sinusoidal signal and its sampled version and plot %the signal.

```
t=[0:0.2:40]
x1=sin(2*3.14*50.*t);
subplot(2,1,1)
plot(t,x1)
title('Sine Wave with frequency 50 Hz:')
x2=sin(2*pi*50*t/100)
subplot(2,1,2)
stem(t,x2)
title('Sampled Version of Sine Wave:')
```

Output:



Experiment no. 3

Aim:

Program for Time Shifting, and reversal of signals.

Input (a):


%Program to shift the signal by a given factor

```
function[y,n]=SignalShift(x,m,k)
%y(n)=x(n-k)
k=[0:6];
x=[1,2,3,4,5,6,7];
subplot(3,1,1)
stem(k,x)
title('Original Signal')
m=5;
n=k-m;
y=x;
subplot(3,1,2)
stem(n,y)
title('Shifted Signal to Negative side')
m=-5;
n=k-m;
y=x;
subplot(3,1,3)
stem(n,y)
title('Shifted Signal to Positive side')
end
```


Input (b):

```
%Program for finding time reversal of a signal
n1=-10;
n2=10;
n0=0;
N=[n1:n2];
% Reversal function needs only X(output) & N(Range)
x=unitstep(n0,n1,n2);
subplot(2,1,1)
stem(N,x)
title('Original Signal:')
X2=flip1r(x);
N2=-flip1r(N);
subplot(2,1,2)
stem(N2,X2,'o r')
title('Reversed Signal:')
```

Output (a):



Output (b):



Experiment no. 4


Aim:

Generating Even and Odd Signals

Input:

```
%PROGRAM TO FIND THE ODD AND EVEN COMPONENT OF A SIGNAL
x=[1,2,3,4,5,6]
n=[-1:4];
subplot(2,2,1)
stem(n,x)
title('Original Signal:')
n1=-fliplr(n)
x1=fliplr(x)
subplot(2,2,2)
stem(n1,x1)
title('Reversed Signal:')
xe=0.5.*SignalAdd(x,x1,n,n1)
rf=[min(min(n1),min(n)):max(max(n1),max(n))]
subplot(2,2,3)
stem(rf,xe)
title('Even Signal of x:')
xo=0.5.*SignalAdd(x,-x1,n,n1)
subplot(2,2,4)
stem(rf,xo)
title('Odd Signal of x:')
```

Output:



Experiment no. 5


Aim:

Program to do Time Scaling (Up Sampling and Down Sampling)

Input:

```
%Program to do Time Scaling (Up Sampling and Down Sampling)
x=[1,2,3,4,5,6]
n=[0:5]
subplot(2,2,1)
stem(n,x)
title('Original Signal:')
nxf=9;
nxl=0
nx=[nxl:nxf];
y2=zeros(1,10)
y2(find((nx>=min(n))&(nx<=max(n))==1))=x
subplot(2,2,2)
stem(nx,y2)
title('Up-Sampling')
new=mod(n,3)
new=(new==0)
y3=x(find(new==1))
n1=0:length(y3)-1;
subplot(2,2,3)
stem(n1,y3)
title('Down Sampling')
```

Output:



Experiment no. 6


Aim:

Generating and plot the discrete time sequences in a given interval.

Input:

```
%Program to plot the function %  $x(n) = 10*[u(n)-u(n-10)]$   $0 \leq n \leq 20$   
function[y,n]=arbitrary(n1,n2)  
n=[n1:n2]  
y=10*[unitstep(0,n1,n2) - unitstep(10,n1,n2)]  
stem(n,y,'b')  
end
```

Output:



Experiment no. 7


Aim:

Program for Convolution of Discrete Time Sequence.

Input:

```
%Program To find the convolution of the given x and h
x=[3,11,7,0,-1,4,2]
rx=[-3:3]
subplot(2,2,1)
stem(rx,x,'c')
title('Input Function:')
rh=[-2:3]
h=[2,3,0,-5,2,1]
subplot(2,2,2)
stem(rh,h,'b')
title('Impulse Response:')
nzl=rx(1)+rh(1)
nzh=rx(length(x))+ rh(length(h));
nz=nzl:nzh;
z=conv(x,h);
subplot(2,2,3)
stem(nz,z,'k')
title('Output:')
```

Output:



Experiment no. 8

Aim:


To find the solution of the given Difference Equation.

Input:

```
%y(n)-0.5y(n-1)+0.25y(n-2)=x(n)+2x(n-1)+x(n-3)
% n=[0:100];
% Compute and Plot the impulse response of a system over range 0<n<100
% Determine the Stability of the system from this impulse response.
b=[1,2,1];
a=[1,-0.5,0.25];
n=[0:100];
h=impz(b,a,101);
subplot(2,1,1);
stem(n,h)
title('Impulse Response:')
x=unitimpulse(0,0,100);
s=filter(b,a,x);
subplot(2,1,2)
stem(n,s);
title('Step Impulse :')
z=sum(abs(h));
fprintf('\n The Sum of Impulse Response:%f',z)
```

Output:

```
>>>soldiffeq
The Sum of Impulse Response:6.571429
```



Experiment no. 9

Aim:

To find the Z Transform of the given Signal.

Input:

```
%Program to find the Z-transform for sequence x=0.25^n
% Use ztrans form z transform
% use residuez for getting coefficients of partial fraction
syms z n
x=(1/4)^n;
y=ztrans(x)
pretty(y)
```


Output:

ztransform

y =

$z/(z - 1/4)$

$$\frac{z}{z - \frac{1}{4}}$$



```
ztransform.m x +
1 %Program to find the Z-transform for sequence x=0.25^n
2 % Use ztrans form z transform
3 % use residuez for getting coefficients of partial fraction
4 syms z n
5 x=(1/4)^n;
6 y=ztrans(x)
7 pretty(y)
8

Command Window
>> ztransform

y =
z/(z - 1/4)
|
z
-----
1
z - -
4

>>
```

Experiment no. 10

Aim:

To find the inverse Z Transform of the given Signal.

Input:

```
%Program to find the Z-transform for sequence x=0.25^n
% Use ztrans form z transform
% use residues for getting coefficients of partial fraction
syms z n
x=(1/4)^n;
y=ztrans(x)
pretty(y)
```


Output:

```
>> inverseztrans
```

```
t =
```

```
(1/2)^n
```

```
/ 1 \n
| - |
\ 2 /
```



The image shows a MATLAB script editor window titled 'inverseztrans.m' with the following code:

```
1 %Program to find the inverse Z-transform of y=2z/2z-1
2 % use iztrans for inverse z transform
3 syms z
4 y1=(2*z/(2*z-1));
5 t=iztrans(y1)
6 pretty(t)
7
```

Below the script editor is the Command Window, which displays the output of the script:

```
4
>> inverseztrans
t =
(1/2)^n
/ 1 \n
| - |
\ 2 /
>>
```

Experiment no. 11

Aim:

Program to Obtain the partial fraction and plot zero pole diagram.

Input:

```
% Program to plot the pole zero diagram
% using residuez for getting coefficients of partial fraction.
b=[4,4];
a=[4,-8,5,-1];
[R,p,c]=residuez(b,a)
% plot the Zplane
zplane(b,a)
```

Output:

```
>>>Polezero
R =


    8.0000 + 0.0000i
   -4.0000 - 0.0000i
   -3.0000 + 0.0000i

p =

    1.0000 + 0.0000i
    0.5000 + 0.0000i
    0.5000 - 0.0000i

c =

[]
```



Experiment no. 12

Aim:

To find the Discrete Time Fourier Transform of a given sequence.

Input:

```
% Program to find the DTFT of a sequence
```

```
syms w
x=[1,1,1,1,1];
n=[0,1,2,3,4];
subplot(3,2,1)
stem(n,x,'r')
xlabel(' n -> ')
ylabel(' x(n) ')
title('Discrete Signal')
t=x.*exp(-i*n*w)
t2(w)=sum(t)
%t2(0)
w1=[0:0.1:pi];
t3=t2(w1)
subplot(3,2,2)
plot(w1,t3)
xlabel(' w -> ')
ylabel(' X(e^jw) ')
title('DTFT for 0<=w<=pi')
w2=[0:0.1:2*pi];
t3=t2(w2)
subplot(3,2,3)
plot(w2,t3)
xlabel(' w -> ')
ylabel(' X(e^jw) ')
title('DTFT for 0<=w<=2pi')
w3=[-pi:0.1:pi];
t3=t2(w3)
subplot(3,2,4)
plot(w3,t3)
xlabel(' w -> ')
ylabel(' X(e^jw) ')
title('DTFT for -pi<=w<=pi')
w4=[-2*pi:0.1:2*pi];
t3=t2(w4)
subplot(3,2,5)
plot(w4,t3)
xlabel(' w -> ')
ylabel(' X(e^jw) ')
title('DTFT for 2pi<=w<=2pi')
```







Output:

```
CURRENT WORKSPACE
>> DTFT
t =
[1, exp(-w*1i), exp(-w*2i), exp(-w*3i), exp(-w*4i)]

t2(w) =
exp(-w*1i) + exp(-w*2i) + exp(-w*3i) + exp(-w*4i) + 1

t3 =
[5, exp(-1i/5) + exp(-2i/5) + exp(-1i/10) + exp(-3i/10) + 1, exp(-1i/5) + exp(-2i/5) + exp(-3i/5) + exp(-4i/5) + 1, exp(-3i/5) + exp(-6i/5) +
Warning: Imaginary parts of complex X and/or Y arguments ignored.
> In DTFT (line 16)

t3 =
[5, exp(-1i/5) + exp(-2i/5) + exp(-1i/10) + exp(-3i/10) + 1, exp(-1i/5) + exp(-2i/5) + exp(-3i/5) + exp(-4i/5) + 1, exp(-3i/5) + exp(-6i/5) +
Warning: Imaginary parts of complex X and/or Y arguments ignored.
```



Experiment no. 13

Aim:

To find the Discrete Fourier Transform of the given sequence.

Input:

```
%User defined function for finding the discrete fourier transform of a
%sequence
function[Xk]=dft(xn ,N)
n=[0:1:N-1];
k=[0:1:N-1];
WN=exp(-j*2*pi/N);
nk=n'*k;
WNnk=WN.^nk;
Xk=xn*WNnk
end
```

Output:


```
>> dft([1,2,3,4,5,6],6)
```

Xk =

```
21.0000 + 0.0000i    -3.0000 + 5.1962i    -3.0000 + 1.7321i    -3.0000 - 0.0000i
-3.0000 - 1.7321i    -3.0000-5.1962i
```

ans =

```
21.0000 + 0.0000i    -3.0000 + 5.1962i    -3.0000 + 1.7321i    -3.0000 - 0.0000i
-3.0000 - 1.7321i    -3.0000 - 5.1962i
```

A screenshot of the MATLAB environment. The top part shows the MATLAB Editor with a script named 'dft.m' containing a user-defined function for the Discrete Fourier Transform (DFT). The function takes an input sequence 'xn' and its length 'N', and returns the DFT coefficients 'Xk'. The function uses a twiddle factor 'WN' and a matrix 'WNnk' to compute the DFT. The bottom part shows the MATLAB Command Window where the function is called with the sequence [1, 2, 3, 4, 5, 6] and N=6. The output 'Xk' is displayed as a 1x4 matrix of complex numbers, and 'ans' is also shown with the same values.

```
dft.m x DTFT.m x +
1 %User defined function for finding the discrete fourier transform of a
2 %sequence
3 function[Xk]=dft(xn ,N)
4 n=[0:1:N-1];
5 k=[0:1:N-1];
6 WN=exp(-j*2*pi/N);
7 nk=n'*k;
8 WNnk=WN.^nk;
9 Xk=xn*WNnk
10 end
11

Command Window

>> dft([1,2,3,4,5,6],6)

Xk =

21.0000 + 0.0000i    -3.0000 + 5.1962i    -3.0000 + 1.7321i    -3.0000 - 0.0000i    -3.0000 - 1.7321i    -3.0000 - 5.1962i

ans =

21.0000 + 0.0000i    -3.0000 + 5.1962i    -3.0000 + 1.7321i    -3.0000 - 0.0000i    -3.0000 - 1.7321i    -3.0000 - 5.1962i

>>
```

Experiment no. 14

Aim:

To find the Inverse Discrete Fourier Transform of the given sequence.

Input:


```
%Program to find inverse dft of a given sequence
%function[xn]=idft( Xk,N)
Xk=[10.0000+0.0000i , -2.0000+2.0000i, -2.0000-0.0000i , -2.0000-2.0000i];
N=4;
n=[0:1:N-1];
k=[0:1:N-1];
WN=exp(-j*2*pi/N);
nk=n'*k;
WNnk=WN.^(-nk);
xn=(Xk*WNnk)/N
%end
```

Output:

```
>>>idft
```

```
xn =
```

```
1.0000 + 0.0000i    2.0000 + 0.0000i    3.0000 - 0.0000i    4.0000 - 0.0000i
```



The image shows a MATLAB script editor with a file named 'idft.m' and a command window. The script defines a function 'idft' that takes a frequency domain sequence 'Xk' and the number of points 'N' as input and returns the time domain sequence 'xn'. The script uses the inverse DFT formula with a twiddle factor 'WN'. The command window shows the execution of the 'idft' function, displaying the resulting sequence 'xn' as a row vector of four complex numbers.

```
1 %Program to find inverse dft of a given sequence
2 %function[xn]=idft( Xk,N)
3 Xk=[10.0000+0.0000i , -2.0000+2.0000i, -2.0000-0.0000i , -2.0000-2.0000i];
4 N=4;
5 n=[0:1:N-1];
6 k=[0:1:N-1];
7 WN=exp(-j*2*pi/N);
8 nk=n'*k;
9 WNnk=WN.^(-nk);
10 xn=(Xk*WNnk)/N
11 %end
12
```

```
>> idft

xn =

    1.0000 + 0.0000i    2.0000 + 0.0000i    3.0000 - 0.0000i    4.0000 - 0.0000i

>> idft

xn =

    1.0000 + 0.0000i    2.0000 + 0.0000i    3.0000 - 0.0000i    4.0000 - 0.0000i

>>
```

Experiment no. 15

Aim:

To find the Circular Convolution of given sequence

Input:


```
% Program for finding out circular Convolution of given x[n] and h[n].
n=[0:3];
x=[1,2,3,4];
subplot(2,2,1)
stem(n,x,'r')
title('Input Signal')
h=[0,1,1,3];
subplot(2,2,2)
stem(n,h,'b')
title('Impulse Response:')
y=cconv(x,h,4)
subplot(2,2,3)
stem(n,y,'k')
title('Output Signal:')
```

Output:

```
>> CircConv
```

```
y =
```

```
13    14    15     8
```



Experiment no. 16


Aim:

Implementation of Fast Fourier Transform and Comparison with Discrete Fourier Transform.

Input:

```
%Program for implementing fast fourier transform (fft)
x=[0:1:1023]
n=[0:1:1023]
N=1024;
clock
%etime(t1,t2)
t3=clock
WN=exp(-j*2*pi/N);
nk=n'*n;
WNnk=WN.^nk;
Xk=x*WNnk;
stem(n,Xk)
title('Using DFT')
t4=timeit(@() Xk)
```

Output:



```
Command Window
ans =
1.0e+03 *
2.0220 0.0110 0.0130 0.0160 0.0020 0.0369

t3 =
1.0e+03 *
2.0220 0.0110 0.0130 0.0160 0.0020 0.0369

Warning: Using only the real component of complex data.
> In matlab.graphics.chart.internal.getRealData (line 52)
In stem (line 95)
In fft (line 12)
Warning: The measured time for F may be inaccurate because it is running
> In timeit (line 158)
In fft (line 14)

t4 =
2.5121e-09

>>
```

