VAR4°W

BEARINGS ARE MAGNETIC ALTITUDES, ELEVATIONS AND HEIGHTS IN METERS DME DISTANCES IN NAUTICAL MILES DISTANCES IN KM TL 3600 TA 3000 3300(QNH>1031HPA) 2700(QNH<979HPA) 1. RNAV 2. GNSS REQUIRED 3. RADAR REQUIRED \odot TAMIX A Ν WEIXIAN CH 104X N36 21.8E114 55.0 NOT TO SCALE NOPIN 4 **LEKUB** DUBAG Altimeter setting may be required by ATC CC201 CC124 (A) MAX 380KmH 2400 MAX 380KmH CC121 MAX 380KmH IAF CC122*296* CC202 CC123 <u>900</u> MAX 380KmH MAX 380KmH **XINZHENG** 114.5 CGO CH 92X CC103 N34 31.1E113 50.6 CC104 1200 MAX 380KmH CC102 2400 or by ATC MAX 380KmH D 3000 *296* **,** cc200 (B) Holding MAX IAS 460KmH • Holding MAX IAS 380KmH • Holding MAX IAS 350KmH CC101 1100 **ARP ZHOUKOU** 115.5 ZHO CH 102X N33 39.9E114 39.3 MSA 46km Changes: APP FREQ,MSA,XINZHENG 'VOR'