

```
##### 0 - safe choice A, 1 - risky choice B #####
library(rstan); rstan_options(javascript=FALSE)
```

```
## Loading required package: StanHeaders
```

```
## Loading required package: ggplot2
```

```
## rstan (Version 2.21.8, GitRev: 2elf913d3ca3)
```

```
## For execution on a local, multicore CPU with excess RAM we recommend calling
## options(mc.cores = parallel::detectCores()).
## To avoid recompilation of unchanged Stan programs, we recommend calling
## rstan_options(auto_write = TRUE)
```

```
library(bayesplot)
```

```
## This is bayesplot version 1.10.0
```

```
## - Online documentation and vignettes at mc-stan.org/bayesplot
```

```
## - bayesplot theme set to bayesplot::theme_default()
```

```
## * Does _not_ affect other ggplot2 plots
```

```
## * See ?bayesplot_theme_set for details on theme setting
```

```
options(mc.cores = parallel::detectCores())
rstan_options(auto_write = T)

# Get list of files in 'data_2' folder with the pattern "riskytimed"
files <- dir(path = "data_2", pattern="riskytimed")

# Read all csv files in the list
data_list <- lapply(paste0("data_2/", files), read.table, header = TRUE, skip = 0,
fill = TRUE, sep= ";")

# Concatenate rows of all items in the list into a data frame
dat <- do.call("rbind", data_list)
```

```

# gamble characteristics
dat$eva = dat$oa1*dat$pa1+dat$oa2*dat$pa2 + dat$oa3*dat$pa3+dat$oa4*dat$pa4
dat$evb = dat$ob1*dat$pb1+dat$ob2*dat$pb2 + dat$ob3*dat$pb3+dat$ob4*dat$pb4
dat$evd = dat$evb - dat$eva
dat$sda = sqrt((dat$oa1-dat$eva)^2*dat$pa1 + (dat$oa2-dat$eva)^2*dat$pa2 + (dat$oa
3-dat$eva)^2*dat$pa3 + (dat$oa4-dat$eva)^2*dat$pa4)
dat$sdb = sqrt((dat$ob1-dat$evb)^2*dat$pb1 + (dat$ob2-dat$evb)^2*dat$pb2 + (dat$ob
3-dat$evb)^2*dat$pb3 + (dat$ob4-dat$evb)^2*dat$pb4)
dat$sdd = dat$sdb - dat$sda
dat$evdummy = ifelse(dat$evd>0,1,0)

```

```

# transform to +/- 1; safe - 1, risky +1
dat$cho <- ifelse(dat$choice==0,-1,ifelse(dat$choice==1,1,NA))
ids <- unique(dat$id)
for(j in 1:length(ids)){
  dat$tid[dat$id==ids[j]] <- j
}
tids <- unique(dat$tid)
# only control data
control_dat <- dat[dat$cond=="control",]
# remove fast RTs
rcontrol_dat <- control_dat[control_dat$rt>1,]
# only condition no time pressure
dataList = list(cho = rcontrol_dat$cho, rt = rcontrol_dat$rt, participant = rcont
rol_dat$tid, N=nrow(rcontrol_dat), L = length(tids), starting_point=0.5, evd = rc
ontrol_dat$evd, sdd = rcontrol_dat$sdd)

```

```

parameters = c("transf_mu_alpha","transf_mu_threshold","transf_mu_ndt", "transf_mu_
_theta", 'sd_threshold',"sd_alpha","sd_ndt", 'sd_theta', "alpha_sbj","threshold_s
bj","ndt_sbj",'theta_sbj', "log_lik")

initFunc <-function (i) {
  initList=list()
  for (ll in 1:i){
    initList[[ll]] = list(mu_alpha = runif(1, -5, 5),
                          sd_alpha = runif(1,0,1),
                          mu_threshold = runif(1,-0.5, 5),
                          sd_threshold = runif(1, 0, 1),
                          mu_ndt = runif(1, -1.5, 0),
                          sd_ndt = runif(1, 0, 1),
                          mu_theta = runif(1,-20, 1),
                          sd_theta = runif(1,0,1),
                          z_alpha = runif(length(tids),-0.1,0.1),
                          z_theta = runif(length(tids),-0.1,0.1),
                          z_threshold = runif(length(tids),-0.1,0.1),
                          z_ndt = runif(length(tids),-0.1,0.1)

    )
  }

  return(initList)
}

```

```

m <- stan_model("MV_Baseline.stan")
dsamples <- sampling(m,
  data=dataList,
  pars=parameters,
  iter=2000,
  chains=4,#If not specified, gives random inits
  init = initFunc(4),
  warmup = 1000, # Stands for burn-in; Default = iter/2
  seed = 12, # Setting seed; Default is random seed
  refresh = 0
)


```

```


#parameters = c("transf_mu_alpha","transf_mu_threshold","transf_mu_ndt", "transf_m
u_theta",'sd_threshold',"sd_alpha","sd_ndt", 'sd_theta', "alpha_sbj","threshold_sb
j","ndt_sbj",'theta_sbj',"log_lik")

rstan::traceplot(dsamples, pars=c("transf_mu_alpha","transf_mu_theta", "transf_mu_
_threshold","transf_mu_ndt", 'sd_threshold',"sd_alpha","sd_ndt", 'sd_theta', "lp_
_"), inc_warmup = TRUE, nrow = 3)

```



```
pairs(dsamples, pars = c("transf_mu_alpha", "transf_mu_theta", "transf_mu_threshold", "transf_mu_ndt", "sd_threshold", "sd_alpha", "sd_ndt", "sd_theta", "lp_"))
```




```
print(dsamples, pars = c("transf_mu_alpha", "transf_mu_theta", "transf_mu_threshold",
"transf_mu_ndt", 'sd_threshold',"sd_alpha","sd_ndt", 'sd_theta', "lp_"))
```

```
## Inference for Stan model: MV_Baseline.
## 4 chains, each with iter=2000; warmup=1000; thin=1;
## post-warmup draws per chain=1000, total post-warmup draws=4000.
##
##               mean se_mean    sd      2.5%      25%      50%
## transf_mu_alpha    -0.59    0.00  0.09    -0.77    -0.65    -0.59
## transf_mu_theta     0.01    0.00  0.00     0.01     0.01     0.01
## transf_mu_threshold  4.52    0.01  0.14     4.26     4.42     4.51
## transf_mu_ndt       1.09    0.00  0.05     0.99     1.06     1.09
## sd_threshold        1.15    0.00  0.11     0.95     1.07     1.14
## sd_alpha            0.67    0.00  0.07     0.54     0.62     0.66
## sd_ndt              0.57    0.00  0.06     0.46     0.53     0.57
## sd_theta            0.23    0.00  0.04     0.17     0.21     0.23
## lp__               -23454.46  0.53 15.68 -23485.40 -23465.11 -23454.08
##               75%      97.5% n_eff Rhat
## transf_mu_alpha    -0.53    -0.41   583 1.01
## transf_mu_theta     0.01     0.01  2722 1.00
## transf_mu_threshold  4.61     4.80   349 1.02
## transf_mu_ndt       1.13     1.19   444 1.00
## sd_threshold        1.22     1.40   775 1.00
## sd_alpha            0.71     0.82  1072 1.00
## sd_ndt              0.61     0.70  1309 1.00
## sd_theta            0.25     0.31  1927 1.00
## lp__               -23443.55 -23424.64   886 1.00
##
## Samples were drawn using NUTS(diag_e) at Sun Oct 15 23:35:06 2023.
## For each parameter, n_eff is a crude measure of effective sample size,
## and Rhat is the potential scale reduction factor on split chains (at
## convergence, Rhat=1).
```

```
parameters = c("transf_mu_alpha","transf_mu_theta", "transf_mu_threshold","transf_mu_ndt", 'sd_threshold',"sd_alpha","sd_ndt", 'sd_theta')
ratios_cp <- neff_ratio(dsamples, pars = c("transf_mu_alpha","transf_mu_theta", "transf_mu_threshold","transf_mu_ndt", 'sd_threshold',"sd_alpha","sd_ndt", 'sd_theta'))
df_ratios_cp <- as.data.frame(ratios_cp)
print(df_ratios_cp)
```

```
##               ratios_cp
## transf_mu_alpha    0.14577766
## transf_mu_theta    0.68043159
## transf_mu_threshold 0.08723854
## transf_mu_ndt      0.11103014
## sd_threshold       0.19368357
## sd_alpha           0.26804279
## sd_ndt             0.32721784
## sd_theta           0.48173670
```

```
mcmc_neff(ratios_cp, size = 2)
```



```
library(ggplot2)
library(tidyverse) # for the gather function
```

```
## — Attaching core tidyverse packages ————— tidyverse 2.0.0 —
—
## ✓ dplyr      1.1.0      ✓ readr      2.1.4
## ✓ forcats   1.0.0      ✓ stringr    1.5.0
## ✓ lubridate 1.9.2      ✓ tibble     3.1.8
## ✓ purrr     1.0.1      ✓ tidyr      1.3.0
## — Conflicts ————— tidyverse_conflicts() —
—
## ✖ tidyr::extract() masks rstan::extract()
## ✖ dplyr::filter()  masks stats::filter()
## ✖ dplyr::lag()     masks stats::lag()
## i Use the [ ]8;;http://conflicted.r-lib.org/[ ]conflicted package[ ]8;;[ ] to force a
ll conflicts to become errors
```

```
samples_matrix <- as.matrix(dsamples)
means <- colMeans(samples_matrix)
hpd_interval <- t(apply(samples_matrix, 2, function(x) quantile(x, probs=c(0.025,
0.975))))

parameters <- c("transf_mu_alpha", "transf_mu_theta", "transf_mu_threshold",
                "transf_mu_ndt")

# Reshape data to a long format
df_long <- as.data.frame(samples_matrix) %>%
  gather(key = "parameter", value = "value", parameters)
```

```
## Warning: Using an external vector in selections was deprecated in tidyselect 1.
1.0.
## i Please use `all_of()` or `any_of()` instead.
##   # Was:
##   data %>% select(parameters)
##
##   # Now:
##   data %>% select(all_of(parameters))
##
## See <https://tidyselect.r-lib.org/reference/faq-external-vector.html>.
## This warning is displayed once every 8 hours.
## Call `lifecycle::last_lifecycle_warnings()` to see where this warning was
## generated.
```



```

# Convert hpd_interval to a data frame and name the columns
hpd_interval_sub <- hpd_interval[parameters, ]
hpd_df <- as.data.frame(hpd_interval_sub)
colnames(hpd_df) <- c("lower", "upper")
rownames(hpd_df) <- parameters
hpd_df$parameter <- rownames(hpd_df)

# Aesthetic enhancements
theme_set(theme_minimal(base_size = 14)) # Set the default theme

custom_palette <- c("density_fill" = "lightgray",
                    "mean_line" = "blue",
                    "hpd_line" = "darkgreen")

# Add text labels for mean, lower, and upper HPD values
df_long <- df_long %>%
  group_by(parameter) %>%
  mutate(mean = means[parameter])

hpd_df <- hpd_df %>%
  mutate(mid = (lower + upper) / 2)

p <- ggplot(df_long, aes(x = value)) +
  geom_density(aes(fill = "density_fill")) +
  scale_fill_manual(values = custom_palette, guide = FALSE) +
  geom_vline(aes(xintercept = mean, color = "mean_line"), linetype = "dashed", size = 1, alpha = 0.7) +
  geom_text(data = df_long, aes(x = mean, y = 0, label = round(mean, 2)), vjust = -0.5, hjust = 0.5, size = 4, color = custom_palette["mean_line"]) +
  geom_vline(data = hpd_df, aes(xintercept = lower, color = "hpd_line"), linetype = "solid", size = 1, alpha = 0.5) +
  geom_text(data = hpd_df, aes(x = lower, y = 0, label = round(lower, 2)), vjust = -0.5, hjust = -0.5, size = 4, color = custom_palette["hpd_line"]) +
  geom_vline(data = hpd_df, aes(xintercept = upper, color = "hpd_line"), linetype = "solid", size = 1, alpha = 0.5) +
  geom_text(data = hpd_df, aes(x = upper, y = 0, label = round(upper, 2)), vjust = -0.5, hjust = 1.5, size = 4, color = custom_palette["hpd_line"]) +
  facet_wrap(~ parameter, scales = "free", ncol = 2) +
  scale_color_manual(values = custom_palette, guide = FALSE) +
  labs(title = "Posterior distributions")

```

```


## Warning: Using `size` aesthetic for lines was deprecated in ggplot2 3.4.0.
## i Please use `linewidth` instead.
## This warning is displayed once every 8 hours.
## Call `lifecycle::last_lifecycle_warnings()` to see where this warning was
## generated.

```

```
print(p)
```

```
## Warning: The `guide` argument in `scale_*()` cannot be `FALSE`. This was deprecated in
## ggplot2 3.3.4.
## i Please use "none" instead.
## This warning is displayed once every 8 hours.
## Call `lifecycle::last_lifecycle_warnings()` to see where this warning was
## generated.
```

Posterior distributions



```


library(RWiener)
library(purrr) # if not already loaded
rcontrol_dat <- rcontrol_dat %>%
  mutate(drift = (means["transf_mu_theta"] * (evd + means["transf_mu_alpha"] * sd
d))*cho)

simulated_data <- rcontrol_dat %>%
  rowwise() %>%
  mutate(simulated = list(rep(drift, 10))) %>%
  ungroup() %>%
  mutate(simulated = map(simulated, ~ rwiener(10,
                                              means["transf_mu_threshold"],
                                              means["transf_mu_ndt"],
                                              0.5,
                                              .)))

# If you want to get a long format data frame with one row for each simulated valu
e:
simulated_long <- simulated_data %>%
  unnest(cols = c(simulated))
hist(simulated_long$q, xlim=c(0, 30))

```

Histogram of simulated_long\$q



```
hist(rcontrol_dat$rt, xlim=c(0,30))
```

Histogram of rcontrol_dat\$rt

