

```
library(htmltools)
```

```
##### 0 - safe choice A, 1 - risky choice B #####  
library(rstan); rstan_options(javascript=FALSE)
```

```
## Loading required package: StanHeaders
```

```
## Loading required package: ggplot2
```

```
## rstan (Version 2.21.8, GitRev: 2elf913d3ca3)
```

```
## For execution on a local, multicore CPU with excess RAM we recommend calling  
## options(mc.cores = parallel::detectCores()).  
## To avoid recompilation of unchanged Stan programs, we recommend calling  
## rstan_options(auto_write = TRUE)
```

```
options(mc.cores = parallel::detectCores())  
rstan_options(auto_write = T)
```

```
# Get list of files in 'data_2' folder with the pattern "riskytimed"  
files <- dir(path = "data_2", pattern="riskytimed")
```

```
# Read all csv files in the list  
data_list <- lapply(paste0("data_2/", files), read.table, header = TRUE, skip = 0,  
fill = TRUE, sep = ";")
```

```
# Concatenate rows of all items in the list into a data frame  
dat <- do.call("rbind", data_list)
```

```
# gamble characteristics  
dat$eva = dat$oa1*dat$pa1+dat$oa2*dat$pa2 + dat$oa3*dat$pa3+dat$oa4*dat$pa4  
dat$evb = dat$ob1*dat$pb1+dat$ob2*dat$pb2 + dat$ob3*dat$pb3+dat$ob4*dat$pb4  
dat$evd = dat$evb - dat$eva  
dat$sda = sqrt((dat$oa1-dat$eva)^2*dat$pa1 + (dat$oa2-dat$eva)^2*dat$pa2 + (dat$oa  
3-dat$eva)^2*dat$pa3 + (dat$oa4-dat$eva)^2*dat$pa4)  
dat$sdb = sqrt((dat$ob1-dat$evb)^2*dat$pb1 + (dat$ob2-dat$evb)^2*dat$pb2 + (dat$ob  
3-dat$evb)^2*dat$pb3 + (dat$ob4-dat$evb)^2*dat$pb4)  
dat$sdd = dat$sdb - dat$sda  
dat$evdummy = ifelse(dat$evd>0,1,0)
```

```

# transform to +/- 1; safe - 1, risky +1
dat$cho <- ifelse(dat$choice==0,-1,ifelse(dat$choice==1,1,NA))

ids <- unique(dat$id)
for(j in 1:length(ids)){
  dat$tid[dat$id==ids[j]] <- j
}
tids <- unique(dat$tid)
# only control data
control_dat <- dat[dat$cond=="control",]
# remove fast RTs
rcontrol_dat <- control_dat[control_dat$rt>1,]

# only condition no time pressure
dataList = list(cho = rcontrol_dat$cho,rt = rcontrol_dat$rt, participant = rcontrol_dat$tid,N=nrow(rcontrol_dat), L = length(tids),starting_point=0.5, evd = rcontrol_dat$evd, sdd = rcontrol_dat$sdd)

```

```

oa = as.matrix(rcontrol_dat[, c("oa1", "oa2", "oa3", "oa4")])
ob = as.matrix(rcontrol_dat[, c("ob1", "ob2", "ob3", "ob4")])
pa = as.matrix(rcontrol_dat[, c("pa1", "pa2", "pa3", "pa4")])
pb = as.matrix(rcontrol_dat[, c("pb1", "pb2", "pb3", "pb4")])

```

```

dataList = list(cho = rcontrol_dat$cho,rt = rcontrol_dat$rt, participant = rcontrol_dat$tid,N=nrow(rcontrol_dat), L = length(tids),starting_point=0.5,
  oa = as.matrix(rcontrol_dat[, c("oa1", "oa2", "oa3", "oa4")]),
  ob = as.matrix(rcontrol_dat[, c("ob1", "ob2", "ob3", "ob4")]),
  pa = as.matrix(rcontrol_dat[, c("pa1", "pa2", "pa3", "pa4")]),
  pb = as.matrix(rcontrol_dat[, c("pb1", "pb2", "pb3", "pb4")])
)

parameters = c("transf_mu_alpha","transf_mu_threshold","transf_mu_ndt", "transf_mu_theta",'sd_threshold',"sd_alpha","sd_ndt", 'sd_theta', "alpha_sbj","threshold_sbj","ndt_sbj",'theta_sbj',"log_lik")

```

```

initFunc <-function (i) {
  initList=list()
  for (ll in 1:i){
    initList[[ll]] = list(mu_alpha = runif(1,-1.4578,2.5413),
                          sd_alpha = runif(1,0,1),
                          mu_threshold = runif(1,-0.5, 2.5),
                          sd_threshold = runif(1,0,1),
                          mu_ndt = runif(1, -1.5, 0),
                          sd_ndt = runif(1, 0, 1),
                          mu_theta = runif(1,0,6),
                          sd_theta = runif(1,0,1),
                          z_alpha = runif(length(tids),-0.1,0.1),
                          z_theta = runif(length(tids),-0.1,0.1),
                          z_threshold = runif(length(tids),-0.1,0.1),
                          z_ndt = runif(length(tids),-0.1,0.1)

    )
  }

  return(initList)
}

```

```

m <- stan_model("EU_Baseline.stan")
dsamples <- sampling(m,
  data=dataList,
  pars=parameters,
  iter=3000,
  chains=4,#If not specified, gives random inits
  init = initFunc(4),
  warmup = 1500, # Stands for burn-in; Default = iter/2
  seed = 12, # Setting seed; Default is random seed
  refresh = 0
)

```

```

## Warning: There were 19 transitions after warmup that exceeded the maximum treed
epth. Increase max_treedepth above 10. See
## https://mc-stan.org/misc/warnings.html#maximum-treedepth-exceeded

```

```


## Warning: Examine the pairs() plot to diagnose sampling problems

```

```


rstan::traceplot(dsamples, pars=c("transf_mu_alpha","transf_mu_threshold","transf_
mu_ndt","transf_mu_theta", "sd_alpha","sd_threshold","sd_ndt",'sd_theta', "lp__"),
inc_warmup = TRUE, nrow = 3)

```



```
pairs(dsamples, pars = c( "transf_mu_alpha","transf_mu_threshold","transf_mu_ndt",
"transf_mu_theta", "sd_alpha","sd_threshold","sd_ndt",'sd_theta', "lp__"))
```

```
## Warning in par(usr): argument 1 does not name a graphical parameter
## Warning in par(usr): argument 1 does not name a graphical parameter
## Warning in par(usr): argument 1 does not name a graphical parameter
## Warning in par(usr): argument 1 does not name a graphical parameter
## Warning in par(usr): argument 1 does not name a graphical parameter
## Warning in par(usr): argument 1 does not name a graphical parameter
## Warning in par(usr): argument 1 does not name a graphical parameter
## Warning in par(usr): argument 1 does not name a graphical parameter
## Warning in par(usr): argument 1 does not name a graphical parameter
```



```
print(dsamples, pars = c("transf_mu_alpha", "transf_mu_threshold", "transf_mu_ndt", "
transf_mu_theta", "sd_alpha", "sd_threshold", "sd_ndt", "sd_theta", "lp"))
```

```
## Inference for Stan model: EU_Baseline.
## 4 chains, each with iter=3000; warmup=1500; thin=1;
## post-warmup draws per chain=1500, total post-warmup draws=6000.
##
##               mean se_mean    sd      2.5%      25%      50%
## transf_mu_alpha      0.23    0.00  0.06      0.13      0.19      0.22
## transf_mu_threshold    4.50    0.01  0.15      4.21      4.41      4.50
## transf_mu_ndt         1.10    0.00  0.05      1.00      1.06      1.10
## transf_mu_theta       3.07    0.04  1.29      0.94      2.13      2.95
## sd_alpha              2.02    0.01  0.22      1.64      1.87      2.01
## sd_threshold          1.15    0.00  0.12      0.95      1.06      1.14
## sd_ndt                0.56    0.00  0.06      0.46      0.52      0.56
## sd_theta              8.80    0.03  1.30      6.55      7.90      8.69
## lp__                 -23467.93    0.49 15.68 -23500.04 -23478.41 -23467.37
##               75%      97.5% n_eff Rhat
## transf_mu_alpha      0.26      0.35   715 1.01
## transf_mu_threshold    4.60      4.80   554 1.00
## transf_mu_ndt         1.13      1.20   575 1.00
## transf_mu_theta       3.87      5.95   955 1.00
## sd_alpha              2.16      2.50 1111 1.00
## sd_threshold          1.22      1.40 1014 1.00
## sd_ndt                0.60      0.69 1357 1.01
## sd_theta              9.61     11.60 1925 1.00
## lp__                 -23457.32 -23438.00 1010 1.00
##
## Samples were drawn using NUTS(diag_e) at Tue Oct 17 04:39:25 2023.
## For each parameter, n_eff is a crude measure of effective sample size,
## and Rhat is the potential scale reduction factor on split chains (at
## convergence, Rhat=1).
```

```
library(bayesplot)
```

```
## This is bayesplot version 1.10.0
```

```
## - Online documentation and vignettes at mc-stan.org/bayesplot
```

```
## - bayesplot theme set to bayesplot::theme_default()
```


```
## * Does _not_ affect other ggplot2 plots
```

```
## * See ?bayesplot_theme_set for details on theme setting
```

```
ratios_cp <- neff_ratio(dsamples, pars = c("transf_mu_alpha", "transf_mu_theta", "transf_mu_threshold", "transf_mu_ndt", 'sd_threshold', "sd_alpha", "sd_ndt", 'sd_theta', "lp__"))
df_ratios_cp <- as.data.frame(ratios_cp)
print(df_ratios_cp)
```

```
##              ratios_cp
## transf_mu_alpha    0.11918999
## transf_mu_theta    0.15917447
## transf_mu_threshold 0.09238789
## transf_mu_ndt      0.09581390
## sd_threshold       0.16900667
## sd_alpha           0.18508883
## sd_ndt             0.22617162
## sd_theta           0.32084126
## lp__               0.16829710
```

```
mcmc_neff(ratios_cp, size = 2)
```



```
library(ggplot2)
library(tidyverse) # for the gather function
```

```
## — Attaching core tidyverse packages ————— tidyverse 2.0.0 —
—
## ✓ dplyr      1.1.1      ✓ readr      2.1.4
## ✓ forcats    1.0.0      ✓ stringr    1.5.0
## ✓ lubridate  1.9.2      ✓ tibble     3.2.1
## ✓ purrr      1.0.1      ✓ tidyr      1.3.0
## — Conflicts ————— tidyverse_conflicts() —
—
## ✖ tidyr::extract() masks rstan::extract()
## ✖ dplyr::filter()  masks stats::filter()
## ✖ dplyr::lag()     masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
samples_matrix <- as.matrix(dsamples)
means <- colMeans(samples_matrix)
hpd_interval <- t(apply(samples_matrix, 2, function(x) quantile(x, probs=c(0.025,
0.975))))
```

```
parameters <- c("transf_mu_alpha", "transf_mu_theta", "transf_mu_threshold",
"transf_mu_ndt")
```

```
# Reshape data to a long format
df_long <- as.data.frame(samples_matrix) %>%
  gather(key = "parameter", value = "value", parameters)
```

```
## Warning: Using an external vector in selections was deprecated in tidysselect 1.
1.0.
## i Please use `all_of()` or `any_of()` instead.
## # Was:
## data %>% select(parameters)
##
## # Now:
## data %>% select(all_of(parameters))
##
## See <https://tidysselect.r-lib.org/reference/faq-external-vector.html>.
## This warning is displayed once every 8 hours.
## Call `lifecycle::last_lifecycle_warnings()` to see where this warning was
## generated.
```



```

# Convert hpd_interval to a data frame and name the columns
hpd_interval_sub <- hpd_interval[parameters, ]
hpd_df <- as.data.frame(hpd_interval_sub)
colnames(hpd_df) <- c("lower", "upper")
rownames(hpd_df) <- parameters
hpd_df$parameter <- rownames(hpd_df)

# Aesthetic enhancements
theme_set(theme_minimal(base_size = 14)) # Set the default theme

custom_palette <- c("density_fill" = "lightgray",
                    "mean_line" = "blue",
                    "hpd_line" = "darkgreen")

# Add text labels for mean, lower, and upper HPD values
df_long <- df_long %>%
  group_by(parameter) %>%
  mutate(mean = means[parameter])

hpd_df <- hpd_df %>%
  mutate(mid = (lower + upper) / 2)

p <- ggplot(df_long, aes(x = value)) +
  geom_density(aes(fill = "density_fill")) +
  scale_fill_manual(values = custom_palette, guide = FALSE) +
  geom_vline(aes(xintercept = mean, color = "mean_line"), linetype = "dashed", size = 1, alpha = 0.7) +
  geom_text(data = df_long, aes(x = mean, y = 0, label = round(mean, 2)), vjust = -0.5, hjust = 0.5, size = 4, color = custom_palette["mean_line"]) +
  geom_vline(data = hpd_df, aes(xintercept = lower, color = "hpd_line"), linetype = "solid", size = 1, alpha = 0.5) +
  geom_text(data = hpd_df, aes(x = lower, y = 0, label = round(lower, 2)), vjust = -0.5, hjust = -0.5, size = 4, color = custom_palette["hpd_line"]) +
  geom_vline(data = hpd_df, aes(xintercept = upper, color = "hpd_line"), linetype = "solid", size = 1, alpha = 0.5) +
  geom_text(data = hpd_df, aes(x = upper, y = 0, label = round(upper, 2)), vjust = -0.5, hjust = 1.5, size = 4, color = custom_palette["hpd_line"]) +
  facet_wrap(~ parameter, scales = "free", ncol = 2) +
  scale_color_manual(values = custom_palette, guide = FALSE) +
  labs(title = "Posterior distributions")

```

```

## Warning: Using `size` aesthetic for lines was deprecated in ggplot2 3.4.0.
## i Please use `linewidth` instead.
## This warning is displayed once every 8 hours.
## Call `lifecycle::last_lifecycle_warnings()` to see where this warning was
## generated.

```

```
print(p)
```

```
## Warning: The `guide` argument in `scale_*()` cannot be `FALSE`. This was deprecated in
## ggplot2 3.3.4.
## i Please use "none" instead.
## This warning is displayed once every 8 hours.
## Call `lifecycle::last_lifecycle_warnings()` to see where this warning was
## generated.
```

Posterior distributions

