

How to use fonts in typst-api

There are 4 ways in which you can use fonts in this library.

1. Using the default fonts

The docker image comes with a set of default fonts that you can use without any additional configuration. These are:

- New Computer Modern
- New Computer Modern Math
- Libertinus Serif
- Dejavu Sans Mono
- Inter
- IBM Plex Sans

The first 4 are the default fonts used in the typst library, while the last 2 are additional fonts I've added because I really like them and I think it's nice to have at least one built-in font that looks nice or modern.

The default font for regular text is 'New Computer Modern', which looks like the text you are seeing right now. Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magnam aliquam quaerat voluptatem. Ut enim aequaleamus animo, cum corpore dolemus, fieri tamen permagna accessio potest, si aliquod aeternum et infinitum impendere..

For using a custom font, you just need to specify the font name in your document. Like this:
`#set text(font: "Inter").`

Notice how the font has changed from the default 'New Computer Modern' to 'Inter'. Let's add some dummy text to see how it looks: Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magnam aliquam quaerat voluptatem. Ut enim aequaleamus animo, cum corpore dolemus, fieri tamen permagna accessio potest, si aliquod aeternum et infinitum impendere..

2. Using system fonts

As we are running typst inside docker, it will only have access to the fonts installed inside the Linux container (which are very few by default). If you want the Docker container to access your host OS's system fonts, you must mount your font directory into the container's `/usr/share/fonts` directory (which is where the API automatically searches for system fonts).

You can do this by adding a volume to your `docker-compose.yml`:

For Linux:

```
volumes:  
  - /usr/share/fonts:/usr/share/fonts/host:ro
```

For Windows:

```
volumes:  
  - C:\Windows\Fonts:/usr/share/fonts/windows:ro
```

For macOS:

volumes:

- /Library/Fonts:/usr/share/fonts/mac:ro

However, if instead of docker you are running the API natively using `cargo run`, it will automatically detect and load all the system fonts installed on your host OS (Windows, macOS, or Linux).

3. Using a custom fonts/ directory (recommended)

This API is designed so that you can put a set of .ttf or .otf files in a `fonts/` directory next to your `docker-compose.yml` and `.env` files. And all those fonts will be available by default there.

If you add new fonts to the `fonts/` directory while the container is running, you don't need to restart it! You can just send a POST request to `/fonts/refresh` to hot-reload the font cache, or send a GET request to `/fonts` to see all available fonts.

4. Dynamic custom fonts, passing the font files in the HTTP request (not recommended)

If you really need to, you can also pass fonts in the HTTP request. This is not recommended because it will make your requests much larger and slower, but it is possible.

Just add your .ttf, .otf, or .ttc files as part of the `multipart/form-data` payload when hitting the `/compile` endpoint. The API will load these fonts ephemerally just for that specific compilation, without polluting the global font cache.