Farbkalibrierung – Ausstreichblatt

Malen nach Zahlen · 48 Felder · Marker in den Ecken nicht bemalen oder abdecken

01 Code: _____	**02** Code: _____	**03** Code: _____	**04** Code: _____	**05** Code: _____	**06** Code: _____
07 Code: _____	**08** Code: _____	**09** Code: _____	**10** Code: _____	**11** Code: _____	**12** Code: _____
13 Code: _____	**14** Code: _____	**15** Code: _____	**16** Code: _____	**17** Code: _____	**18** Code: _____
19 Code: _____	**20** Code: _____	**21** Code: _____	**22** Code: _____	**23** Code: _____	**24** Code: _____
25 Code: _____	**26** Code: _____	**27** Code: _____	**28** Code: _____	**29** Code: _____	**30** Code: _____
31 Code: _____	**32** Code: _____	**33** Code: _____	**34** Code: _____	**35** Code: _____	**36** Code: _____
37 Code: _____	**38** Code: _____	**39** Code: _____	**40** Code: _____	**41** Code: _____	**42** Code: _____
43 Code: _____	**44** Code: _____	**45** Code: _____	**46** Code: _____	**47** Code: _____	**48** Code: _____

Referenzen

Papierweiß
NICHT bemalen

Graukarte hier auflegen (optional)
z. B. 18 %-Graukarte

1. Auf mattem, weißem Papier (≥ 160 g) drucken, Skalierung 100 %.
2. Jede Farbe deckend in 2 Schichten, ruhig etwas über den Rand malen.
3. Tubencode notieren, mind. 24 h trocknen.
4. Bei Tageslicht von oben fotografieren, ohne Blitz, Schatten und Spiegelung.

Metallic-/Perlfarben weglassen.