




# Q200


## 2GB RAM | 16GB FLASH



Allwinner H313 Quad Core  
ARM Cortex A53



G31 OPenGL3.2  
GPU processor



10/100 M  
Ethernet port



4K\*2K UHD Output  
HDMI 2.0A



480i/576i  
standard definition output



Android 10.0



IEEE 802.11 b/g/n/ac  
2.4Gh/5Gh



2\* USB Host Port



Support  
4GB/8GB/16GB/32GB/64GB

MARAM TECHNOLOGIES PVT LTD

Plot No: 564-A/17, 3rd Floor, Road No. 92, near Lotus Pond, Jubilee Hills, Hyderabad - 500033

✉ info@maramtechnologies.in ☎ +91 8125 703 703 🌐 www.maramtechnologies.in

## **SPECIFICATIONS**

### **Bluetooth**

- Yes(Optional)

### **Moudle**

- Plastic : Black Color

### **1\*Optical**

- Digital Audio Output

### **Power**

- DC 5V/2A

### **Real-Time Clock (RTC)**

- YES(Optional)

## **VIDEO**

- Video Engine (AVE) with dedicated hardware decoders and encoders
- Support multi-video decoder up to 4Kx2K@60fps+1x1080P@60fps
- Supports multiple "secured" video decoding sessions and simultaneous decoding and encoding

### **Video Decoding**

- Vp9 Profile 2 up to 4Kx2K@60fps
- H.265 Main10@L5.1 up to 4Kx2K@60fps, or 6K@30fps
- AVS2-P2 Profile up to 4Kx2K@60fps
- H.264 BP/MP/HP@L4.2 up to 4Kx2K@30fps
- MPEG-4 SP/ASP@L5 up to 1080P@60fps(ISO-14496)
- MPEG-2 MP/HL up to 1080P@60fps(ISO-13818)
- MPEG-1 MP/HL up to 1080P@60fps(ISO-11172)
- Xvid up to 1080P@60fps
- Sorenson Spark up to 1080P@60fps
- Vp8 up to 1080P@60fps
- AVS/AVS+ JiZhun Profile up to 1080P@60fps
- WMV9/VC1 SP/MP/AP up to 1080P@60fps
- JPEG HFIF file format up to 45MPPS
- Multiple language and multiple format sub-title video support
- MJPEG and JPEG unlimited pixel resolution decoding(ISO/IEC-10918)
- Supports JPEG thumbnail, scaling, rotation and transition effects
- Supports \*.mkv, \*.wmv, \*.mpg, \*.mpeg, \*.dat, \*.avi, \*.mov, \*.iso, \*.mp4, \*.rm and \*.jpg file formats

## **AUDIO**

- Supports MP3, AAC, WMA, RM, FLAC, Ogg and programmable with 7.1/5.1 down-mixing Audio Codec
- Two audio digital-to-analog(DAC) channels
- Support 16-bit and 20-bit sample rate
- 8kHz to 192kHz DAC sample rate
- 95+/-2dB SNR@A-weight, -80+/-dB THD+N, output Level more than 0.55Vrms
- One 128\*24-bits FIFO for DAC data transmit
- Built-in TDM/PCM/I2S ports with TDM/PCM mode up to 384kHz x 32bits x 8ch or 96kHz x 32bits x 32ch and I2S mode up to 384kHz x 32bits x 8ch
- Digital microphone PDM input with programmable CIC, LPF & HPF, support up to 8 DMICs
- Built-in stereo audio DAC
- Supports concurrent dual audio stereo channel output with combination of analog+PCM or I2S+PCM